

## Scikit Data Access

Generated by Doxygen 1.8.13



# Contents

<b>1</b>	<b>Namespace Index</b>	<b>1</b>
1.1	Packages . . . . .	1
<b>2</b>	<b>Hierarchical Index</b>	<b>3</b>
2.1	Class Hierarchy . . . . .	3
<b>3</b>	<b>Class Index</b>	<b>5</b>
3.1	Class List . . . . .	5
<b>4</b>	<b>File Index</b>	<b>7</b>
4.1	File List . . . . .	7
<b>5</b>	<b>Namespace Documentation</b>	<b>9</b>
5.1	skdaccess Namespace Reference . . . . .	9
5.2	skdaccess.astro Namespace Reference . . . . .	9
5.3	skdaccess.astro.kepler Namespace Reference . . . . .	9
5.4	skdaccess.astro.kepler.data_fetcher Namespace Reference . . . . .	9
5.5	skdaccess.bin Namespace Reference . . . . .	10
5.6	skdaccess.bin.skdaccess Namespace Reference . . . . .	10
5.6.1	Function Documentation . . . . .	10
5.6.1.1	skdaccess_script() . . . . .	10
5.7	skdaccess.framework Namespace Reference . . . . .	10
5.8	skdaccess.framework.data_class Namespace Reference . . . . .	11

5.9	<a href="#">skdaccess.framework.param_class Namespace Reference</a>	11
5.10	<a href="#">skdaccess.geo Namespace Reference</a>	12
5.11	<a href="#">skdaccess.geo.gldas Namespace Reference</a>	12
5.12	<a href="#">skdaccess.geo.gldas.data_fetcher Namespace Reference</a>	12
5.13	<a href="#">skdaccess.geo.grace Namespace Reference</a>	12
5.14	<a href="#">skdaccess.geo.grace.data_fetcher Namespace Reference</a>	12
5.15	<a href="#">skdaccess.geo.groundwater Namespace Reference</a>	12
5.16	<a href="#">skdaccess.geo.groundwater.data_fetcher Namespace Reference</a>	13
5.17	<a href="#">skdaccess.geo.modis Namespace Reference</a>	13
5.18	<a href="#">skdaccess.geo.modis.cache Namespace Reference</a>	13
5.19	<a href="#">skdaccess.geo.modis.cache.cloud_mask Namespace Reference</a>	13
5.20	<a href="#">skdaccess.geo.modis.cache.cloud_mask.data_fetcher Namespace Reference</a>	13
5.21	<a href="#">skdaccess.geo.modis.cache.cloud_opacity Namespace Reference</a>	13
5.22	<a href="#">skdaccess.geo.modis.cache.cloud_opacity.data_fetcher Namespace Reference</a>	14
5.23	<a href="#">skdaccess.geo.modis.cache.data_fetcher Namespace Reference</a>	14
5.24	<a href="#">skdaccess.geo.modis.cache.reflectance Namespace Reference</a>	14
5.25	<a href="#">skdaccess.geo.modis.cache.reflectance.data_fetcher Namespace Reference</a>	14
5.26	<a href="#">skdaccess.geo.modis.stream Namespace Reference</a>	14
5.27	<a href="#">skdaccess.geo.modis.stream.cloud_mask Namespace Reference</a>	14
5.28	<a href="#">skdaccess.geo.modis.stream.cloud_mask.data_fetcher Namespace Reference</a>	15
5.29	<a href="#">skdaccess.geo.modis.stream.cloud_opacity Namespace Reference</a>	15
5.30	<a href="#">skdaccess.geo.modis.stream.cloud_opacity.data_fetcher Namespace Reference</a>	15
5.31	<a href="#">skdaccess.geo.modis.stream.data_fetcher Namespace Reference</a>	15
5.32	<a href="#">skdaccess.geo.modis.stream.reflectance Namespace Reference</a>	15
5.33	<a href="#">skdaccess.geo.modis.stream.reflectance.data_fetcher Namespace Reference</a>	15
5.34	<a href="#">skdaccess.geo.pbo Namespace Reference</a>	16
5.35	<a href="#">skdaccess.geo.pbo.data_fetcher Namespace Reference</a>	16
5.36	<a href="#">skdaccess.utilities Namespace Reference</a>	16

5.37 skdaccess.utilities.grace_util Namespace Reference	16
5.37.1 Function Documentation	16
5.37.1.1 averageDates()	17
5.37.1.2 computeEWD()	18
5.37.1.3 dateMismatch()	18
5.37.1.4 getStartEndDate()	19
5.37.1.5 readTellusData()	19
5.38 skdaccess.utilities.gw_util Namespace Reference	20
5.38.1 Function Documentation	20
5.38.1.1 combine_water_heights()	20
5.39 skdaccess.utilities.kepler_util Namespace Reference	20
5.39.1 Function Documentation	20
5.39.1.1 normalize()	20
5.40 skdaccess.utilities.modis_util Namespace Reference	21
5.40.1 Function Documentation	21
5.40.1.1 calibrateModis()	21
5.40.1.2 checkBit()	22
5.40.1.3 createGrid()	22
5.40.1.4 getFileIDs()	23
5.40.1.5 getFileURLs()	24
5.40.1.6 getImageType()	24
5.40.1.7 getModisData()	24
5.40.1.8 readMODISData()	25
5.40.1.9 rescale()	25
5.41 skdaccess.utilities.pbo_util Namespace Reference	26
5.41.1 Function Documentation	26
5.41.1.1 getLatLonRange()	26
5.41.1.2 getROIstations()	27
5.41.1.3 getStationCoords()	27
5.41.1.4 nostab_sys()	28
5.41.1.5 propagateErrors()	28
5.41.1.6 removeAntennaOffset()	30
5.41.1.7 stab_sys()	30

<b>6</b>	<b>Class Documentation</b>	<b>33</b>
6.1	skdaccess.framework.param_class.AutoList Class Reference	33
6.1.1	Detailed Description	34
6.1.2	Constructor & Destructor Documentation	34
6.1.2.1	__init__()	34
6.1.3	Member Function Documentation	34
6.1.3.1	__call__()	34
6.1.3.2	__getitem__()	35
6.1.3.3	__len__()	35
6.1.3.4	__setitem__()	35
6.1.3.5	__str__()	36
6.1.3.6	getAllOptions()	36
6.1.3.7	perturb()	36
6.1.3.8	reset()	36
6.1.3.9	val()	37
6.1.4	Member Data Documentation	37
6.1.4.1	val_init	37
6.1.4.2	val_list	37
6.2	skdaccess.framework.param_class.AutoListCycle Class Reference	37
6.2.1	Detailed Description	38
6.2.2	Constructor & Destructor Documentation	38
6.2.2.1	__init__()	38
6.2.3	Member Function Documentation	39
6.2.3.1	__call__()	39
6.2.3.2	__getitem__()	39
6.2.3.3	__len__()	39
6.2.3.4	__setitem__()	40
6.2.3.5	__str__()	40

6.2.3.6	<a href="#">getAllOptions()</a>	40
6.2.3.7	<a href="#">perturb()</a>	41
6.2.3.8	<a href="#">reset()</a>	41
6.2.3.9	<a href="#">val()</a>	41
6.2.4	<a href="#">Member Data Documentation</a>	41
6.2.4.1	<a href="#">index</a>	41
6.2.4.2	<a href="#">list_val_list</a>	41
6.2.4.3	<a href="#">val_init</a>	42
6.2.4.4	<a href="#">val_list</a>	42
6.3	<a href="#">skdaccess.framework.param_class.AutoListPermute Class Reference</a>	42
6.3.1	<a href="#">Detailed Description</a>	43
6.3.2	<a href="#">Member Function Documentation</a>	43
6.3.2.1	<a href="#">__call__()</a>	43
6.3.2.2	<a href="#">__getitem__()</a>	43
6.3.2.3	<a href="#">__len__()</a>	44
6.3.2.4	<a href="#">__setitem__()</a>	44
6.3.2.5	<a href="#">__str__()</a>	44
6.3.2.6	<a href="#">getAllOptions()</a>	45
6.3.2.7	<a href="#">perturb()</a>	45
6.3.2.8	<a href="#">reset()</a>	45
6.3.2.9	<a href="#">val()</a>	45
6.3.3	<a href="#">Member Data Documentation</a>	45
6.3.3.1	<a href="#">val_init</a>	46
6.3.3.2	<a href="#">val_list</a>	46
6.4	<a href="#">skdaccess.framework.param_class.AutoListRemove Class Reference</a>	46
6.4.1	<a href="#">Detailed Description</a>	47
6.4.2	<a href="#">Constructor &amp; Destructor Documentation</a>	47
6.4.2.1	<a href="#">__init__()</a>	47

6.4.3	Member Function Documentation	47
6.4.3.1	__call__()	47
6.4.3.2	__getitem__()	48
6.4.3.3	__len__()	48
6.4.3.4	__setitem__()	48
6.4.3.5	__str__()	49
6.4.3.6	getAllOptions()	49
6.4.3.7	perturb()	49
6.4.3.8	reset()	49
6.4.3.9	val()	50
6.4.4	Member Data Documentation	50
6.4.4.1	n	50
6.4.4.2	val_init	50
6.4.4.3	val_list	50
6.5	skdaccess.framework.param_class.AutoListSubset Class Reference	50
6.5.1	Detailed Description	51
6.5.2	Member Function Documentation	51
6.5.2.1	__call__()	51
6.5.2.2	__getitem__()	52
6.5.2.3	__len__()	52
6.5.2.4	__setitem__()	52
6.5.2.5	__str__()	53
6.5.2.6	getAllOptions()	53
6.5.2.7	perturb()	53
6.5.2.8	reset()	53
6.5.2.9	val()	54
6.5.3	Member Data Documentation	54
6.5.3.1	val_init	54



6.5.3.2	<a href="#">val_list</a>	54
6.6	<a href="#">skdaccess.framework.param_class.AutoParam Class Reference</a>	54
6.6.1	<a href="#">Detailed Description</a>	55
6.6.2	<a href="#">Constructor &amp; Destructor Documentation</a>	55
6.6.2.1	<a href="#">__init__()</a>	55
6.6.3	<a href="#">Member Function Documentation</a>	56
6.6.3.1	<a href="#">__call__()</a>	56
6.6.3.2	<a href="#">__str__()</a>	56
6.6.3.3	<a href="#">perturb()</a>	56
6.6.3.4	<a href="#">reset()</a>	56
6.6.4	<a href="#">Member Data Documentation</a>	57
6.6.4.1	<a href="#">val</a>	57
6.6.4.2	<a href="#">val_init</a>	57
6.7	<a href="#">skdaccess.framework.param_class.AutoParamList Class Reference</a>	57
6.7.1	<a href="#">Detailed Description</a>	58
6.7.2	<a href="#">Constructor &amp; Destructor Documentation</a>	58
6.7.2.1	<a href="#">__init__()</a>	58
6.7.3	<a href="#">Member Function Documentation</a>	58
6.7.3.1	<a href="#">__call__()</a>	58
6.7.3.2	<a href="#">__str__()</a>	59
6.7.3.3	<a href="#">perturb()</a>	59
6.7.3.4	<a href="#">reset()</a>	59
6.7.4	<a href="#">Member Data Documentation</a>	59
6.7.4.1	<a href="#">val</a>	59
6.7.4.2	<a href="#">val_init</a>	59
6.7.4.3	<a href="#">val_list</a>	60
6.8	<a href="#">skdaccess.framework.param_class.AutoParamListCycle Class Reference</a>	60
6.8.1	<a href="#">Detailed Description</a>	60

6.8.2	Constructor & Destructor Documentation	61
6.8.2.1	__init__()	61
6.8.3	Member Function Documentation	61
6.8.3.1	__call__()	61
6.8.3.2	__str__()	61
6.8.3.3	perturb()	62
6.8.3.4	reset()	62
6.8.4	Member Data Documentation	62
6.8.4.1	current_index	62
6.8.4.2	val	62
6.8.4.3	val_init	62
6.8.4.4	val_list	62
6.9	skdaccess.framework.param_class.AutoParamMinMax Class Reference	63
6.9.1	Detailed Description	63
6.9.2	Constructor & Destructor Documentation	63
6.9.2.1	__init__()	64
6.9.3	Member Function Documentation	64
6.9.3.1	__call__()	64
6.9.3.2	__str__()	64
6.9.3.3	perturb()	65
6.9.3.4	reset()	65
6.9.4	Member Data Documentation	65
6.9.4.1	decimals	65
6.9.4.2	n	65
6.9.4.3	n_max	65
6.9.4.4	val	65
6.9.4.5	val_init	66
6.9.4.6	val_max	66

6.9.4.7	<a href="#">val_min</a>	66
6.10	<a href="#">skdaccess.geo.modis.stream.cloud_opacity.DataFetcher Class Reference</a>	66
6.10.1	<a href="#">Detailed Description</a>	66
6.10.2	<a href="#">Constructor &amp; Destructor Documentation</a>	67
6.10.2.1	<a href="#">__init__()</a>	67
6.11	<a href="#">skdaccess.geo.modis.cache.DataFetcher Class Reference</a>	67
6.11.1	<a href="#">Detailed Description</a>	69
6.11.2	<a href="#">Constructor &amp; Destructor Documentation</a>	69
6.11.2.1	<a href="#">__init__()</a>	69
6.11.3	<a href="#">Member Function Documentation</a>	70
6.11.3.1	<a href="#">__str__()</a>	70
6.11.3.2	<a href="#">cacheData()</a> [1/2]	70
6.11.3.3	<a href="#">cacheData()</a> [2/2]	70
6.11.3.4	<a href="#">find_data()</a>	71
6.11.3.5	<a href="#">getConfig()</a>	71
6.11.3.6	<a href="#">getDataLocation()</a>	72
6.11.3.7	<a href="#">getHDFStorage()</a>	72
6.11.3.8	<a href="#">getMetadata()</a>	72
6.11.3.9	<a href="#">multirun_enabled()</a>	72
6.11.3.10	<a href="#">output()</a>	73
6.11.3.11	<a href="#">perturb()</a>	73
6.11.3.12	<a href="#">reset()</a>	73
6.11.3.13	<a href="#">setDataLocation()</a>	73
6.11.3.14	<a href="#">verbose_print()</a>	74
6.11.3.15	<a href="#">writeConfig()</a>	74
6.11.4	<a href="#">Member Data Documentation</a>	74
6.11.4.1	<a href="#">ap_paramList</a>	74
6.11.4.2	<a href="#">daynightboth</a>	74

6.11.4.3	<a href="#">end_date</a>	74
6.11.4.4	<a href="#">grid</a>	75
6.11.4.5	<a href="#">grid_fill</a>	75
6.11.4.6	<a href="#">modis_id</a>	75
6.11.4.7	<a href="#">modis_identifier</a>	75
6.11.4.8	<a href="#">modis_platform</a>	75
6.11.4.9	<a href="#">start_date</a>	75
6.11.4.10	<a href="#">use_long_name</a>	75
6.11.4.11	<a href="#">variable_list</a>	76
6.11.4.12	<a href="#">verbose</a>	76
6.12	<a href="#">skdaccess.geo.modis.stream.reflectance.DataFetcher Class Reference</a>	76
6.12.1	<a href="#">Detailed Description</a>	76
6.12.2	<a href="#">Constructor &amp; Destructor Documentation</a>	76
6.12.2.1	<a href="#">__init__()</a>	77
6.13	<a href="#">skdaccess.geo.pbo.DataFetcher Class Reference</a>	77
6.13.1	<a href="#">Detailed Description</a>	79
6.13.2	<a href="#">Constructor &amp; Destructor Documentation</a>	79
6.13.2.1	<a href="#">__init__()</a>	79
6.13.3	<a href="#">Member Function Documentation</a>	79
6.13.3.1	<a href="#">__str__()</a>	80
6.13.3.2	<a href="#">downloadFullDataset()</a>	80
6.13.3.3	<a href="#">getAntennaLogs()</a>	80
6.13.3.4	<a href="#">getConfig()</a>	81
6.13.3.5	<a href="#">getDataLocation()</a>	81
6.13.3.6	<a href="#">getInfo()</a>	81
6.13.3.7	<a href="#">getMetadata()</a>	82
6.13.3.8	<a href="#">getStationMetadata()</a>	82
6.13.3.9	<a href="#">multirun_enabled()</a>	82

6.13.3.10 output()	82
6.13.3.11 perturb()	83
6.13.3.12 reset()	83
6.13.3.13 setDataLocation()	83
6.13.3.14 setStationList()	83
6.13.3.15 verbose_print()	84
6.13.3.16 writeConfig()	84
6.13.4 Member Data Documentation	84
6.13.4.1 antenna_info	84
6.13.4.2 ap_paramList	84
6.13.4.3 default_columns	84
6.13.4.4 default_error_columns	85
6.13.4.5 index_date_only	85
6.13.4.6 meta_data	85
6.13.4.7 station_list	85
6.13.4.8 use_progress_bar	85
6.13.4.9 verbose	85
6.14 skdaccess.geo.gldas.DataFetcher Class Reference	86
6.14.1 Detailed Description	87
6.14.2 Constructor & Destructor Documentation	87
6.14.2.1 __init__()	87
6.14.3 Member Function Documentation	87
6.14.3.1 __str__()	87
6.14.3.2 downloadFullDataset()	88
6.14.3.3 getConfig()	88
6.14.3.4 getDataLocation()	88
6.14.3.5 getMetadata()	89
6.14.3.6 multirun_enabled()	89

6.14.3.7	<code>output()</code>	89
6.14.3.8	<code>perturb()</code>	90
6.14.3.9	<code>reset()</code>	90
6.14.3.10	<code>setDataLocation()</code>	90
6.14.3.11	<code>verbose_print()</code>	90
6.14.3.12	<code>writeConfig()</code>	91
6.14.4	Member Data Documentation	91
6.14.4.1	<code>ap_paramList</code>	91
6.14.4.2	<code>end_date</code>	91
6.14.4.3	<code>resample</code>	91
6.14.4.4	<code>start_date</code>	91
6.14.4.5	<code>verbose</code>	92
6.15	<code>skdaccess.geo.grace.DataFetcher</code> Class Reference	92
6.15.1	Detailed Description	93
6.15.2	Constructor & Destructor Documentation	93
6.15.2.1	<code>__init__()</code>	93
6.15.3	Member Function Documentation	93
6.15.3.1	<code>__str__()</code>	94
6.15.3.2	<code>downloadFullDataset()</code>	94
6.15.3.3	<code>getConfig()</code>	94
6.15.3.4	<code>getDataLocation()</code>	94
6.15.3.5	<code>getMetadata()</code>	95
6.15.3.6	<code>multirun_enabled()</code>	95
6.15.3.7	<code>output()</code>	95
6.15.3.8	<code>perturb()</code>	96
6.15.3.9	<code>reset()</code>	96
6.15.3.10	<code>setDataLocation()</code>	96
6.15.3.11	<code>verbose_print()</code>	96

6.15.3.12 writeConfig()	97
6.15.4 Member Data Documentation	97
6.15.4.1 ap_paramList	97
6.15.4.2 end_date	97
6.15.4.3 start_date	97
6.15.4.4 verbose	97
6.16 skdaccess.geo.modis.stream.cloud_mask.DataFetcher Class Reference	98
6.16.1 Detailed Description	98
6.16.2 Constructor & Destructor Documentation	98
6.16.2.1 __init__()	98
6.17 skdaccess.geo.groundwater.DataFetcher Class Reference	99
6.17.1 Detailed Description	100
6.17.2 Constructor & Destructor Documentation	100
6.17.2.1 __init__()	100
6.17.3 Member Function Documentation	101
6.17.3.1 __str__()	101
6.17.3.2 downloadFullDataset()	101
6.17.3.3 getConfig()	101
6.17.3.4 getDataLocation()	102
6.17.3.5 getMetadata()	102
6.17.3.6 getStationMetadata()	102
6.17.3.7 multirun_enabled()	103
6.17.3.8 output()	103
6.17.3.9 perturb()	103
6.17.3.10 reset()	103
6.17.3.11 setDataLocation()	103
6.17.3.12 verbose_print()	104
6.17.3.13 writeConfig()	104

6.17.4	Member Data Documentation	104
6.17.4.1	ap_paramList	104
6.17.4.2	cutoff	104
6.17.4.3	end_date	105
6.17.4.4	start_date	105
6.17.4.5	verbose	105
6.18	skdaccess.geo.modis.cache.cloud_mask.DataFetcher Class Reference	105
6.18.1	Detailed Description	105
6.18.2	Constructor & Destructor Documentation	106
6.18.2.1	__init__()	106
6.19	skdaccess.geo.modis.cache.cloud_opacity.DataFetcher Class Reference	106
6.19.1	Detailed Description	107
6.19.2	Constructor & Destructor Documentation	107
6.19.2.1	__init__()	107
6.20	skdaccess.geo.modis.stream.DataFetcher Class Reference	107
6.20.1	Detailed Description	109
6.20.2	Constructor & Destructor Documentation	109
6.20.2.1	__init__()	109
6.20.3	Member Function Documentation	109
6.20.3.1	__str__()	110
6.20.3.2	getConfig()	110
6.20.3.3	getMetadata()	110
6.20.3.4	multirun_enabled()	110
6.20.3.5	output()	111
6.20.3.6	perturb()	111
6.20.3.7	reset()	111
6.20.3.8	retrieveOnlineData()	111
6.20.3.9	verbose_print()	112



6.20.3.10 writeConfig()	112
6.20.4 Member Data Documentation	112
6.20.4.1 ap_paramList	112
6.20.4.2 daynightboth	112
6.20.4.3 end_date	113
6.20.4.4 grid	113
6.20.4.5 grid_fill	113
6.20.4.6 modis_id	113
6.20.4.7 modis_identifier	113
6.20.4.8 modis_platform	113
6.20.4.9 start_date	113
6.20.4.10 use_long_name	114
6.20.4.11 variable_list	114
6.20.4.12 verbose	114
6.21 skdaccess.geo.modis.cache.reflectance.DataFetcher Class Reference	114
6.21.1 Detailed Description	114
6.21.2 Constructor & Destructor Documentation	115
6.21.2.1 __init__()	115
6.22 skdaccess.astro.kepler.DataFetcher Class Reference	115
6.22.1 Detailed Description	117
6.22.2 Constructor & Destructor Documentation	117
6.22.2.1 __init__()	117
6.22.3 Member Function Documentation	117
6.22.3.1 __str__()	117
6.22.3.2 cacheData() [1/2]	118
6.22.3.3 cacheData() [2/2]	118
6.22.3.4 downloadKeplerData()	118
6.22.3.5 getConfig()	119

6.22.3.6	<a href="#">getDataLocation()</a>	119
6.22.3.7	<a href="#">getHDFSStorage()</a>	119
6.22.3.8	<a href="#">getMetadata()</a>	120
6.22.3.9	<a href="#">multirun_enabled()</a>	120
6.22.3.10	<a href="#">output()</a>	120
6.22.3.11	<a href="#">perturb()</a>	120
6.22.3.12	<a href="#">reset()</a>	121
6.22.3.13	<a href="#">setDataLocation()</a>	121
6.22.3.14	<a href="#">verbose_print()</a>	121
6.22.3.15	<a href="#">writeConfig()</a>	121
6.22.4	<a href="#">Member Data Documentation</a>	122
6.22.4.1	<a href="#">ap_paramList</a>	122
6.22.4.2	<a href="#">quarter_list</a>	122
6.22.4.3	<a href="#">verbose</a>	122
6.23	<a href="#">skdaccess.framework.data_class.DataFetcherBase Class Reference</a>	122
6.23.1	<a href="#">Detailed Description</a>	123
6.23.2	<a href="#">Constructor &amp; Destructor Documentation</a>	123
6.23.2.1	<a href="#">__init__()</a>	123
6.23.3	<a href="#">Member Function Documentation</a>	124
6.23.3.1	<a href="#">__str__()</a>	124
6.23.3.2	<a href="#">getConfig()</a>	124
6.23.3.3	<a href="#">getMetadata()</a>	124
6.23.3.4	<a href="#">multirun_enabled()</a>	125
6.23.3.5	<a href="#">output()</a>	125
6.23.3.6	<a href="#">perturb()</a>	125
6.23.3.7	<a href="#">reset()</a>	125
6.23.3.8	<a href="#">verbose_print()</a>	126
6.23.3.9	<a href="#">writeConfig()</a>	126

6.23.4	Member Data Documentation	127
6.23.4.1	ap_paramList	127
6.23.4.2	verbose	127
6.24	skdaccess.framework.data_class.DataFetcherCache Class Reference	127
6.24.1	Detailed Description	128
6.24.2	Member Function Documentation	128
6.24.2.1	__str__()	129
6.24.2.2	cacheData()	129
6.24.2.3	getConfig()	129
6.24.2.4	getDataLocation()	129
6.24.2.5	getHDFSStorage()	130
6.24.2.6	getMetadata()	130
6.24.2.7	multirun_enabled()	130
6.24.2.8	output()	131
6.24.2.9	perturb()	131
6.24.2.10	reset()	131
6.24.2.11	setDataLocation()	131
6.24.2.12	verbose_print()	132
6.24.2.13	writeConfig()	132
6.24.3	Member Data Documentation	132
6.24.3.1	ap_paramList	132
6.24.3.2	verbose	132
6.25	skdaccess.framework.data_class.DataFetcherLocal Class Reference	133
6.25.1	Detailed Description	133
6.25.2	Member Function Documentation	134
6.25.2.1	__str__()	134
6.25.2.2	getConfig()	134
6.25.2.3	getDataLocation()	134

6.25.2.4	<a href="#">getMetadata()</a>	135
6.25.2.5	<a href="#">multirun_enabled()</a>	135
6.25.2.6	<a href="#">output()</a>	135
6.25.2.7	<a href="#">perturb()</a>	135
6.25.2.8	<a href="#">reset()</a>	136
6.25.2.9	<a href="#">setDataLocation()</a>	136
6.25.2.10	<a href="#">verbose_print()</a>	136
6.25.2.11	<a href="#">writeConfig()</a>	136
6.25.3	<a href="#">Member Data Documentation</a>	137
6.25.3.1	<a href="#">ap_paramList</a>	137
6.25.3.2	<a href="#">verbose</a>	137
6.26	<a href="#">skdaccess.framework.data_class.DataFetcherStorage Class Reference</a>	137
6.26.1	<a href="#">Detailed Description</a>	138
6.26.2	<a href="#">Member Function Documentation</a>	138
6.26.2.1	<a href="#">__str__()</a>	138
6.26.2.2	<a href="#">downloadFullDataset()</a>	138
6.26.2.3	<a href="#">getConfig()</a>	139
6.26.2.4	<a href="#">getDataLocation()</a>	139
6.26.2.5	<a href="#">getMetadata()</a>	139
6.26.2.6	<a href="#">multirun_enabled()</a>	140
6.26.2.7	<a href="#">output()</a>	140
6.26.2.8	<a href="#">perturb()</a>	140
6.26.2.9	<a href="#">reset()</a>	140
6.26.2.10	<a href="#">setDataLocation()</a>	140
6.26.2.11	<a href="#">verbose_print()</a>	141
6.26.2.12	<a href="#">writeConfig()</a>	141
6.26.3	<a href="#">Member Data Documentation</a>	141
6.26.3.1	<a href="#">ap_paramList</a>	141

6.26.3.2	verbose	141
6.27	skdaccess.framework.data_class.DataFetcherStream Class Reference	142
6.27.1	Detailed Description	142
6.27.2	Member Function Documentation	143
6.27.2.1	__str__()	143
6.27.2.2	getConfig()	143
6.27.2.3	getMetadata()	143
6.27.2.4	multirun_enabled()	143
6.27.2.5	output()	144
6.27.2.6	perturb()	144
6.27.2.7	reset()	144
6.27.2.8	retrieveOnlineData()	144
6.27.2.9	verbose_print()	145
6.27.2.10	writeConfig()	145
6.27.3	Member Data Documentation	145
6.27.3.1	ap_paramList	145
6.27.3.2	verbose	145
6.28	skdaccess.framework.data_class.DataWrapperBase Class Reference	146
6.28.1	Detailed Description	146
6.28.2	Constructor & Destructor Documentation	147
6.28.2.1	__init__()	147
6.28.3	Member Function Documentation	147
6.28.3.1	__len__()	147
6.28.3.2	addResult()	147
6.28.3.3	get()	148
6.28.3.4	getIterator()	148
6.28.3.5	getResults()	148
6.28.3.6	info()	149

6.28.3.7	reset()	149
6.28.3.8	update()	149
6.28.4	Member Data Documentation	149
6.28.4.1	constants	149
6.28.4.2	data	150
6.28.4.3	meta_data	150
6.28.4.4	results	150
6.28.4.5	run_id	150
6.29	skdaccess.framework.data_class.ImageWrapper Class Reference	150
6.29.1	Detailed Description	151
6.29.2	Member Function Documentation	151
6.29.2.1	__len__()	152
6.29.2.2	addResult()	152
6.29.2.3	deleteData()	152
6.29.2.4	get()	152
6.29.2.5	getIterator()	153
6.29.2.6	getResults()	153
6.29.2.7	info()	153
6.29.2.8	reset()	154
6.29.2.9	update()	154
6.29.2.10	updateData()	154
6.29.3	Member Data Documentation	154
6.29.3.1	constants	154
6.29.3.2	data	155
6.29.3.3	meta_data	155
6.29.3.4	results	155
6.29.3.5	run_id	155
6.30	skdaccess.utilities.modis_util.LatLon Class Reference	155

6.30.1 Detailed Description	156
6.30.2 Constructor & Destructor Documentation	156
6.30.2.1 <code>__init__()</code>	156
6.30.3 Member Function Documentation	156
6.30.3.1 <code>__call__()</code>	156
6.30.4 Member Data Documentation	158
6.30.4.1 <code>alat</code>	158
6.30.4.2 <code>alon</code>	158
6.30.4.3 <code>lat_data</code>	158
6.30.4.4 <code>lon_data</code>	158
6.30.4.5 <code>x_offset</code>	158
6.30.4.6 <code>y_offset</code>	159
6.31 <code>skdaccess.framework.data_class.SeriesDictionaryWrapper</code> Class Reference	159
6.31.1 Detailed Description	160
6.31.2 Member Function Documentation	160
6.31.2.1 <code>__len__()</code>	160
6.31.2.2 <code>addResult()</code>	160
6.31.2.3 <code>get()</code>	161
6.31.2.4 <code>getIndices()</code>	161
6.31.2.5 <code>getIterator()</code>	161
6.31.2.6 <code>getLength()</code>	162
6.31.2.7 <code>getResults()</code>	162
6.31.2.8 <code>info()</code>	162
6.31.2.9 <code>reset()</code>	162
6.31.2.10 <code>update()</code>	162
6.31.3 Member Data Documentation	163
6.31.3.1 <code>constants</code>	163
6.31.3.2 <code>data</code>	163

6.31.3.3	<a href="#">data_names</a>	163
6.31.3.4	<a href="#">error_names</a>	163
6.31.3.5	<a href="#">meta_data</a>	163
6.31.3.6	<a href="#">results</a>	164
6.31.3.7	<a href="#">run_id</a>	164
6.32	<a href="#">skdaccess.framework.data_class.SeriesWrapper Class Reference</a>	164
6.32.1	<a href="#">Detailed Description</a>	165
6.32.2	<a href="#">Constructor &amp; Destructor Documentation</a>	165
6.32.2.1	<a href="#">__init__()</a>	165
6.32.3	<a href="#">Member Function Documentation</a>	166
6.32.3.1	<a href="#">__len__()</a>	166
6.32.3.2	<a href="#">addResult()</a>	166
6.32.3.3	<a href="#">get()</a>	166
6.32.3.4	<a href="#">getIndices()</a>	167
6.32.3.5	<a href="#">getIterator()</a>	167
6.32.3.6	<a href="#">getLength()</a>	167
6.32.3.7	<a href="#">getResults()</a>	167
6.32.3.8	<a href="#">info()</a>	168
6.32.3.9	<a href="#">reset()</a>	168
6.32.3.10	<a href="#">update()</a>	168
6.32.4	<a href="#">Member Data Documentation</a>	168
6.32.4.1	<a href="#">constants</a>	168
6.32.4.2	<a href="#">data</a>	169
6.32.4.3	<a href="#">data_names</a>	169
6.32.4.4	<a href="#">error_names</a>	169
6.32.4.5	<a href="#">meta_data</a>	169
6.32.4.6	<a href="#">results</a>	169
6.32.4.7	<a href="#">run_id</a>	169



6.33 skdaccess.framework.data_class.TableWrapper Class Reference . . . . .	170
6.33.1 Detailed Description . . . . .	171
6.33.2 Constructor & Destructor Documentation . . . . .	171
6.33.2.1 __init__() . . . . .	171
6.33.3 Member Function Documentation . . . . .	171
6.33.3.1 __len__() . . . . .	172
6.33.3.2 addColumn() . . . . .	172
6.33.3.3 addResult() . . . . .	172
6.33.3.4 get() . . . . .	173
6.33.3.5 getDefaultColumns() . . . . .	173
6.33.3.6 getDefaultErrorColumns() . . . . .	173
6.33.3.7 getIterator() . . . . .	173
6.33.3.8 getLength() . . . . .	174
6.33.3.9 getResults() . . . . .	174
6.33.3.10 info() . . . . .	174
6.33.3.11 removeFrames() . . . . .	174
6.33.3.12 reset() . . . . .	175
6.33.3.13 update() . . . . .	175
6.33.3.14 updateData() . . . . .	175
6.33.3.15 updateFrames() . . . . .	176
6.33.4 Member Data Documentation . . . . .	176
6.33.4.1 constants . . . . .	176
6.33.4.2 data . . . . .	176
6.33.4.3 default_columns . . . . .	176
6.33.4.4 default_error_columns . . . . .	176
6.33.4.5 meta_data . . . . .	177
6.33.4.6 results . . . . .	177
6.33.4.7 run_id . . . . .	177

6.34	skdaccess.framework.data_class.XArrayWrapper Class Reference	177
6.34.1	Detailed Description	178
6.34.2	Constructor & Destructor Documentation	178
6.34.2.1	__init__()	178
6.34.3	Member Function Documentation	179
6.34.3.1	__len__()	179
6.34.3.2	addResult()	179
6.34.3.3	get()	179
6.34.3.4	getIterator()	180
6.34.3.5	getResults()	180
6.34.3.6	info()	180
6.34.3.7	reset()	180
6.34.3.8	update()	180
6.34.4	Member Data Documentation	181
6.34.4.1	constants	181
6.34.4.2	data	181
6.34.4.3	index_list	181
6.34.4.4	meta_data	181
6.34.4.5	results	181
6.34.4.6	run_id	181

<b>7 File Documentation</b>	<b>183</b>
7.1 astro/kepler/data_fetcher.py File Reference . . . . .	183
7.2 geo/gldas/data_fetcher.py File Reference . . . . .	183
7.3 geo/grace/data_fetcher.py File Reference . . . . .	183
7.4 geo/groundwater/data_fetcher.py File Reference . . . . .	184
7.5 geo/modis/cache/cloud_mask/data_fetcher.py File Reference . . . . .	184
7.6 geo/modis/cache/cloud_opacity/data_fetcher.py File Reference . . . . .	184
7.7 geo/modis/cache/data_fetcher.py File Reference . . . . .	185
7.8 geo/modis/cache/reflectance/data_fetcher.py File Reference . . . . .	185
7.9 geo/modis/stream/cloud_mask/data_fetcher.py File Reference . . . . .	185
7.10 geo/modis/stream/cloud_opacity/data_fetcher.py File Reference . . . . .	185
7.11 geo/modis/stream/data_fetcher.py File Reference . . . . .	186
7.12 geo/modis/stream/reflectance/data_fetcher.py File Reference . . . . .	186
7.13 geo/pbo/data_fetcher.py File Reference . . . . .	186
7.14 bin/skdaccess.py File Reference . . . . .	187
7.15 framework/data_class.py File Reference . . . . .	187
7.16 framework/param_class.py File Reference . . . . .	188
7.17 utilities/grace_util.py File Reference . . . . .	188
7.18 utilities/gw_util.py File Reference . . . . .	189
7.19 utilities/kepler_util.py File Reference . . . . .	189
7.20 utilities/modis_util.py File Reference . . . . .	189
7.21 utilities/pbo_util.py File Reference . . . . .	190
 <b>Index</b>	 <b>191</b>



# Chapter 1

## Namespace Index

### 1.1 Packages

Here are the packages with brief descriptions (if available):

<a href="#">skdaccess</a>	9
<a href="#">skdaccess.astro</a>	9
<a href="#">skdaccess.astro.kepler</a>	9
<a href="#">skdaccess.astro.kepler.data_fetcher</a>	9
<a href="#">skdaccess.bin</a>	10
<a href="#">skdaccess.bin.skdaccess</a>	10
<a href="#">skdaccess.framework</a>	10
<a href="#">skdaccess.framework.data_class</a>	11
<a href="#">skdaccess.framework.param_class</a>	11
<a href="#">skdaccess.geo</a>	12
<a href="#">skdaccess.geo.gldas</a>	12
<a href="#">skdaccess.geo.gldas.data_fetcher</a>	12
<a href="#">skdaccess.geo.grace</a>	12
<a href="#">skdaccess.geo.grace.data_fetcher</a>	12
<a href="#">skdaccess.geo.groundwater</a>	12
<a href="#">skdaccess.geo.groundwater.data_fetcher</a>	13
<a href="#">skdaccess.geo.modis</a>	13
<a href="#">skdaccess.geo.modis.cache</a>	13
<a href="#">skdaccess.geo.modis.cache.cloud_mask</a>	13
<a href="#">skdaccess.geo.modis.cache.cloud_mask.data_fetcher</a>	13
<a href="#">skdaccess.geo.modis.cache.cloud_opacity</a>	13
<a href="#">skdaccess.geo.modis.cache.cloud_opacity.data_fetcher</a>	14
<a href="#">skdaccess.geo.modis.cache.data_fetcher</a>	14
<a href="#">skdaccess.geo.modis.cache.reflectance</a>	14
<a href="#">skdaccess.geo.modis.cache.reflectance.data_fetcher</a>	14
<a href="#">skdaccess.geo.modis.stream</a>	14
<a href="#">skdaccess.geo.modis.stream.cloud_mask</a>	14
<a href="#">skdaccess.geo.modis.stream.cloud_mask.data_fetcher</a>	15
<a href="#">skdaccess.geo.modis.stream.cloud_opacity</a>	15
<a href="#">skdaccess.geo.modis.stream.cloud_opacity.data_fetcher</a>	15
<a href="#">skdaccess.geo.modis.stream.data_fetcher</a>	15

<a href="#">skdaccess.geo.modis.stream.reflectance</a>	15
<a href="#">skdaccess.geo.modis.stream.reflectance.data_fetcher</a>	15
<a href="#">skdaccess.geo.pbo</a>	16
<a href="#">skdaccess.geo.pbo.data_fetcher</a>	16
<a href="#">skdaccess.utilities</a>	16
<a href="#">skdaccess.utilities.grace_util</a>	16
<a href="#">skdaccess.utilities.gw_util</a>	20
<a href="#">skdaccess.utilities.kepler_util</a>	20
<a href="#">skdaccess.utilities.modis_util</a>	21
<a href="#">skdaccess.utilities.pbo_util</a>	26

## Chapter 2

# Hierarchical Index

### 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

skdaccess.framework.param_class.AutoParam . . . . .	54
skdaccess.framework.param_class.AutoParamList . . . . .	57
skdaccess.framework.param_class.AutoParamListCycle . . . . .	60
skdaccess.framework.param_class.AutoParamMinMax . . . . .	63
MDF	
skdaccess.geo.modis.cache.cloud_mask.DataFetcher . . . . .	105
skdaccess.geo.modis.cache.cloud_opacity.DataFetcher . . . . .	106
skdaccess.geo.modis.cache.reflectance.DataFetcher . . . . .	114
skdaccess.geo.modis.stream.cloud_mask.DataFetcher . . . . .	98
skdaccess.geo.modis.stream.cloud_opacity.DataFetcher . . . . .	66
skdaccess.geo.modis.stream.reflectance.DataFetcher . . . . .	76
object	
skdaccess.framework.data_class.DataFetcherBase . . . . .	122
skdaccess.framework.data_class.DataFetcherLocal . . . . .	133
skdaccess.framework.data_class.DataFetcherCache . . . . .	127
skdaccess.astro.kepler.DataFetcher . . . . .	115
skdaccess.geo.modis.cache.DataFetcher . . . . .	67
skdaccess.framework.data_class.DataFetcherStorage . . . . .	137
skdaccess.geo.gldas.DataFetcher . . . . .	86
skdaccess.geo.grace.DataFetcher . . . . .	92
skdaccess.geo.groundwater.DataFetcher . . . . .	99
skdaccess.geo.pbo.DataFetcher . . . . .	77
skdaccess.framework.data_class.DataFetcherStream . . . . .	142
skdaccess.geo.modis.stream.DataFetcher . . . . .	107
skdaccess.framework.data_class.DataWrapperBase . . . . .	146
skdaccess.framework.data_class.ImageWrapper . . . . .	150
skdaccess.framework.data_class.SeriesWrapper . . . . .	164
skdaccess.framework.data_class.SeriesDictionaryWrapper . . . . .	159
skdaccess.framework.data_class.TableWrapper . . . . .	170
skdaccess.framework.data_class.XArrayWrapper . . . . .	177

skdaccess.framework.param_class.AutoList . . . . .	33
skdaccess.framework.param_class.AutoListCycle . . . . .	37
skdaccess.framework.param_class.AutoListPermute . . . . .	42
skdaccess.framework.param_class.AutoListRemove . . . . .	46
skdaccess.framework.param_class.AutoListSubset . . . . .	50
skdaccess.utilities.modis_util.LatLon . . . . .	155



## Chapter 3

# Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

<a href="#">skdaccess.framework.param_class.AutoList</a>	
Specifies a list for returning selections of lists, as opposed to a single element . . . . .	33
<a href="#">skdaccess.framework.param_class.AutoListCycle</a>	
An Autolist that cycles through different lists . . . . .	37
<a href="#">skdaccess.framework.param_class.AutoListPermute</a>	
A perturber that permutes a list . . . . .	42
<a href="#">skdaccess.framework.param_class.AutoListRemove</a>	
Removes a different single element from the initial list at each perturb call . . . . .	46
<a href="#">skdaccess.framework.param_class.AutoListSubset</a>	
An <a href="#">AutoList</a> perturber that creates random subsets of a list . . . . .	50
<a href="#">skdaccess.framework.param_class.AutoParam</a>	
Defines a tunable parameter class inherited by specific subclasses . . . . .	54
<a href="#">skdaccess.framework.param_class.AutoParamList</a>	
A tunable parameter with a specified list of choices that can be randomly selected via perturb . . . . .	57
<a href="#">skdaccess.framework.param_class.AutoParamListCycle</a>	
Cycles through a list of paramters . . . . .	60
<a href="#">skdaccess.framework.param_class.AutoParamMinMax</a>	
A tunable parameter with min and max ranges, perturbs to a random value in range . . . . .	63
<a href="#">skdaccess.geo.modis.stream.cloud_opacity.DataFetcher</a>	
Data Fetcher for MODIS Cloud Opacity . . . . .	66
<a href="#">skdaccess.geo.modis.cache.DataFetcher</a>	
Data Fetcher for MODIS data . . . . .	67
<a href="#">skdaccess.geo.modis.stream.reflectance.DataFetcher</a>	
Data fetcher for the modis surface reflectance product ('09', 1 km resolution) . . . . .	76
<a href="#">skdaccess.geo.pbo.DataFetcher</a>	
Data fetcher for PBO GPS data . . . . .	77
<a href="#">skdaccess.geo.gldas.DataFetcher</a>	
Data Fetcher for GLDAS data . . . . .	86
<a href="#">skdaccess.geo.grace.DataFetcher</a>	
Data Fetcher for GRACE data . . . . .	92
<a href="#">skdaccess.geo.modis.stream.cloud_mask.DataFetcher</a>	
Data Fetcher for MODIS Cloud Mask . . . . .	98

<a href="#">skdaccess.geo.groundwater.DataFetcher</a>	
Generates Data Wrappers of groundwater measurements taken in the US . . . . .	99
<a href="#">skdaccess.geo.modis.cache.cloud_mask.DataFetcher</a>	
Data Fetcher for MODIS Cloud Mask . . . . .	105
<a href="#">skdaccess.geo.modis.cache.cloud_opacity.DataFetcher</a>	
Data Fetcher for MODIS Cloud Opacity . . . . .	106
<a href="#">skdaccess.geo.modis.stream.DataFetcher</a>	
Data Fetcher for MODIS data . . . . .	107
<a href="#">skdaccess.geo.modis.cache.reflectance.DataFetcher</a>	
Data fetcher for the modis surface reflectance product ('09', 1 km resolution) . . . . .	114
<a href="#">skdaccess.astro.kepler.DataFetcher</a>	
Data Fetcher for Kepler light curve data . . . . .	115
<a href="#">skdaccess.framework.data_class.DataFetcherBase</a>	
Base class for all data fetchers . . . . .	122
<a href="#">skdaccess.framework.data_class.DataFetcherCache</a>	
Data fetcher base class for downloading data and caching results on hard disk . . . . .	127
<a href="#">skdaccess.framework.data_class.DataFetcherLocal</a>	
Data fetcher base class for use when storing data locally . . . . .	133
<a href="#">skdaccess.framework.data_class.DataFetcherStorage</a>	
Data fetcher base class for use when entire data set is downloaded . . . . .	137
<a href="#">skdaccess.framework.data_class.DataFetcherStream</a>	
Data fetcher base class for downloading data into memory . . . . .	142
<a href="#">skdaccess.framework.data_class.DataWrapperBase</a>	
Base class for wrapping data for use in DiscoveryPipeline . . . . .	146
<a href="#">skdaccess.framework.data_class.ImageWrapper</a>	
Wrapper for image data . . . . .	150
<a href="#">skdaccess.utilities.modis_util.LatLon</a>	
Calculates Lat/Lon position from y,x pixel coordinate . . . . .	155
<a href="#">skdaccess.framework.data_class.SeriesDictionaryWrapper</a>	
Data wrapper for series data using a dictionary of data frames . . . . .	159
<a href="#">skdaccess.framework.data_class.SeriesWrapper</a>	
Data wrapper for series data using a data panel . . . . .	164
<a href="#">skdaccess.framework.data_class.TableWrapper</a>	
Data wrapper for table data using an ordered dictionary . . . . .	170
<a href="#">skdaccess.framework.data_class.XArrayWrapper</a>	
Wrapper for xarrays . . . . .	177

## Chapter 4

# File Index

### 4.1 File List

Here is a list of all files with brief descriptions:

astro/kepler/ <a href="#">data_fetcher.py</a>	183
bin/ <a href="#">skdaccess.py</a>	187
framework/ <a href="#">data_class.py</a>	187
framework/ <a href="#">param_class.py</a>	188
geo/gldas/ <a href="#">data_fetcher.py</a>	183
geo/grace/ <a href="#">data_fetcher.py</a>	183
geo/groundwater/ <a href="#">data_fetcher.py</a>	184
geo/modis/cache/ <a href="#">data_fetcher.py</a>	185
geo/modis/cache/cloud_mask/ <a href="#">data_fetcher.py</a>	184
geo/modis/cache/cloud_opacity/ <a href="#">data_fetcher.py</a>	184
geo/modis/cache/reflectance/ <a href="#">data_fetcher.py</a>	185
geo/modis/stream/ <a href="#">data_fetcher.py</a>	186
geo/modis/stream/cloud_mask/ <a href="#">data_fetcher.py</a>	185
geo/modis/stream/cloud_opacity/ <a href="#">data_fetcher.py</a>	185
geo/modis/stream/reflectance/ <a href="#">data_fetcher.py</a>	186
geo/pbo/ <a href="#">data_fetcher.py</a>	186
utilities/ <a href="#">grace_util.py</a>	188
utilities/ <a href="#">gw_util.py</a>	189
utilities/ <a href="#">kepler_util.py</a>	189
utilities/ <a href="#">modis_util.py</a>	189
utilities/ <a href="#">pbo_util.py</a>	190



## Chapter 5

# Namespace Documentation

### 5.1 skdaccess Namespace Reference

#### Namespaces

- [astro](#)
- [bin](#)
- [framework](#)
- [geo](#)
- [utilities](#)

### 5.2 skdaccess.astro Namespace Reference

#### Namespaces

- [kepler](#)

### 5.3 skdaccess.astro.kepler Namespace Reference

#### Namespaces

- [data\\_fetcher](#)

### 5.4 skdaccess.astro.kepler.data\_fetcher Namespace Reference

#### Classes

- class [DataFetcher](#)

*Data Fetcher for Kepler light curve data.*

## 5.5 skdaccess.bin Namespace Reference

### Namespaces

- [skdaccess](#)

## 5.6 skdaccess.bin.skdaccess Namespace Reference

### Functions

- def [skdaccess\\_script](#) ()  
*This function defines a script for downloading data.*

### 5.6.1 Function Documentation

#### 5.6.1.1 skdaccess\_script()

```
def skdaccess.bin.skdaccess.skdaccess_script ( )
```

This function defines a script for downloading data.

## 5.7 skdaccess.framework Namespace Reference

### Namespaces

- [data\\_class](#)
- [param\\_class](#)

## 5.8 skdaccess.framework.data\_class Namespace Reference

### Classes

- class [DataFetcherBase](#)  
*Base class for all data fetchers.*
- class [DataFetcherCache](#)  
*Data fetcher base class for downloading data and caching results on hard disk.*
- class [DataFetcherLocal](#)  
*Data fetcher base class for use when storing data locally.*
- class [DataFetcherStorage](#)  
*Data fetcher base class for use when entire data set is downloaded.*
- class [DataFetcherStream](#)  
*Data fetcher base class for downloading data into memory.*
- class [DataWrapperBase](#)  
*Base class for wrapping data for use in DiscoveryPipeline.*
- class [ImageWrapper](#)  
*Wrapper for image data.*
- class [SeriesDictionaryWrapper](#)  
*Data wrapper for series data using a dictionary of data frames.*
- class [SeriesWrapper](#)  
*Data wrapper for series data using a data panel.*
- class [TableWrapper](#)  
*Data wrapper for table data using an ordered dictionary.*
- class [XArrayWrapper](#)  
*Wrapper for xarrays.*

## 5.9 skdaccess.framework.param\_class Namespace Reference

### Classes

- class [AutoList](#)  
*Specifies a list for returning selections of lists, as opposed to a single element.*
- class [AutoListCycle](#)  
*An Autolist that cycles through different lists.*
- class [AutoListPermute](#)  
*A perturber that permutes a list.*
- class [AutoListRemove](#)  
*Removes a different single element from the initial list at each perturb call.*
- class [AutoListSubset](#)  
*An [AutoList](#) perturber that creates random subsets of a list.*
- class [AutoParam](#)  
*Defines a tunable parameter class inherited by specific subclasses.*
- class [AutoParamList](#)  
*A tunable parameter with a specified list of choices that can be randomly selected via perturb.*
- class [AutoParamListCycle](#)  
*Cycles through a list of paramters.*
- class [AutoParamMinMax](#)  
*A tunable parameter with min and max ranges, perturbs to a random value in range.*

## 5.10 skdaccess.geo Namespace Reference

### Namespaces

- [gldas](#)
- [grace](#)
- [groundwater](#)
- [modis](#)
- [pbo](#)

## 5.11 skdaccess.geo.gldas Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.12 skdaccess.geo.gldas.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for GLDAS data.*

## 5.13 skdaccess.geo.grace Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.14 skdaccess.geo.grace.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for GRACE data.*

## 5.15 skdaccess.geo.groundwater Namespace Reference

### Namespaces

- [data\\_fetcher](#)



## 5.16 skdaccess.geo.groundwater.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Generates Data Wrappers of groundwater measurements taken in the US.*

## 5.17 skdaccess.geo.modis Namespace Reference

### Namespaces

- [cache](#)
- [stream](#)

## 5.18 skdaccess.geo.modis.cache Namespace Reference

### Namespaces

- [cloud\\_mask](#)
- [cloud\\_opacity](#)
- [data\\_fetcher](#)
- [reflectance](#)

## 5.19 skdaccess.geo.modis.cache.cloud\_mask Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.20 skdaccess.geo.modis.cache.cloud\_mask.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS Cloud Mask.*

## 5.21 skdaccess.geo.modis.cache.cloud\_opacity Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.22 skdaccess.geo.modis.cache.cloud\_opacity.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS Cloud Opacity.*

## 5.23 skdaccess.geo.modis.cache.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS data.*

## 5.24 skdaccess.geo.modis.cache.reflectance Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.25 skdaccess.geo.modis.cache.reflectance.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data fetcher for the modis surface reflectance product ('09', 1 km resolution)*

## 5.26 skdaccess.geo.modis.stream Namespace Reference

### Namespaces

- [cloud\\_mask](#)
- [cloud\\_opacity](#)
- [data\\_fetcher](#)
- [reflectance](#)

## 5.27 skdaccess.geo.modis.stream.cloud\_mask Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.28 skdaccess.geo.modis.stream.cloud\_mask.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS Cloud Mask.*

## 5.29 skdaccess.geo.modis.stream.cloud\_opacity Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.30 skdaccess.geo.modis.stream.cloud\_opacity.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS Cloud Opacity.*

## 5.31 skdaccess.geo.modis.stream.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data Fetcher for MODIS data.*

## 5.32 skdaccess.geo.modis.stream.reflectance Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.33 skdaccess.geo.modis.stream.reflectance.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data fetcher for the modis surface reflectance product ('09', 1 km resolution)*

## 5.34 skdaccess.geo.pbo Namespace Reference

### Namespaces

- [data\\_fetcher](#)

## 5.35 skdaccess.geo.pbo.data\_fetcher Namespace Reference

### Classes

- class [DataFetcher](#)  
*Data fetcher for PBO GPS data.*

## 5.36 skdaccess.utilities Namespace Reference

### Namespaces

- [grace\\_util](#)
- [gw\\_util](#)
- [kepler\\_util](#)
- [modis\\_util](#)
- [pbo\\_util](#)

## 5.37 skdaccess.utilities.grace\_util Namespace Reference

### Functions

- def [averageDates](#) (dates, round\_nearest\_day=False)  
*Compute the average of a pandas series of timestamps.*
- def [dateMismatch](#) (dates, days=10)  
*Check if dates are not within a certain number of days of each other.*
- def [computeEWD](#) (grace\_data, scale\_factor, round\_nearest\_day=False)  
*Compute scale corrected equivalent water depth.*
- def [readTellusData](#) (filename, lat\_lon\_list, lat\_name, lon\_name, data\_name, data\_label=None, time\_name=None, lat\_bounds\_name=None, lon\_bounds\_name=None, uncertainty\_name=None, lat\_bounds=None, lon\_bounds=None)  
*This function reads in netcdf data provided by GRACE Tellus.*
- def [getStartEndDate](#) (in\_data)

### 5.37.1 Function Documentation

#### 5.37.1.1 averageDates()

```
def skdaccess.utilities.grace_util.averageDates (
    dates,
    round_nearest_day = False )
```

Compute the average of a pandas series of timestamps.

**Parameters**

<i>dates</i>	Pandas series of pandas datetime objects
<i>round_nearest_day</i>	Round to the nearest day

**Returns**

Average of dates

**5.37.1.2 computeEWD()**

```
def skdaccess.utilities.grace_util.computeEWD (
    grace_data,
    scale_factor,
    round_nearest_day = False )
```

Compute scale corrected equivalent water depth.

Equivalent water depth by averaging results from GFZ, CSR, and JPL, and then applying the scale factor

**Parameters**

<i>grace_data</i>	Data frame containing grace data
<i>scale_factor</i>	Scale factor to apply
<i>round_nearest_day</i>	Round dates to nearest day

**Returns**

Equivalent water depth determined by applying the scale factor to the average GFZ, JPL and CSR.

**5.37.1.3 dateMismatch()**

```
def skdaccess.utilities.grace_util.dateMismatch (
    dates,
    days = 10 )
```

Check if dates are not within a certain number of days of each other.

**Parameters**

<i>dates</i>	Iterable container of pandas timestamps
<i>days</i>	Number of days

**Returns**

true if they are not with 10 days, false otherwise

**5.37.1.4 getStartEndDate()**

```
def skdaccess.utilities.grace_util.getStartEndDate (
    in_data )
```

**5.37.1.5 readTellusData()**

```
def skdaccess.utilities.grace_util.readTellusData (
    filename,
    lat_lon_list,
    lat_name,
    lon_name,
    data_name,
    data_label = None,
    time_name = None,
    lat_bounds_name = None,
    lon_bounds_name = None,
    uncertainty_name = None,
    lat_bounds = None,
    lon_bounds = None )
```

This function reads in netcdf data provided by GRACE Tellus.

**Parameters**

<i>filename</i>	Name of file to read in
<i>lat_name</i>	Name of latitude data
<i>lon_name</i>	Name of longitude data
<i>data_name</i>	Name of data product
<i>time_name</i>	Name of time data
<i>lat_bounds_name</i>	Name of latitude boundaries
<i>lon_bounds_name</i>	Name of longitude boundaries
<i>uncertainty_name</i>	Name of uncertainty in data set
<i>lat_bounds</i>	Latitude bounds
<i>lon_bounds</i>	Longitude bounds

**Returns**

dictionary containing data and dictionary containing latitude and longitude

## 5.38 skdaccess.utilities.gw\_util Namespace Reference

### Functions

- def [combine\\_water\\_heights](#) (in\_data)  
*Combine median and average water heights.*

### 5.38.1 Function Documentation

#### 5.38.1.1 combine\_water\_heights()

```
def skdaccess.utilities.gw_util.combine_water_heights (
    in_data )
```

Combine median and average water heights.

Create a column of water heights in input data frame using Median Water Depth by default, but fills in missing data using average values

#### Parameters

<i>in_data</i>	Input water heights data
----------------	--------------------------

## 5.39 skdaccess.utilities.kepler\_util Namespace Reference

### Functions

- def [normalize](#) (in\_data, column='PDCSAP\_FLUX', group\_column='QUARTER')  
*This function normalizes PDCSAP\_FLUX data by quarter by dividing the flux by the median for the quarter.*

### 5.39.1 Function Documentation

#### 5.39.1.1 normalize()

```
def skdaccess.utilities.kepler_util.normalize (
    in_data,
    column = 'PDCSAP_FLUX',
    group_column = 'QUARTER' )
```

This function normalizes PDCSAP\_FLUX data by quarter by dividing the flux by the median for the quarter.



## Parameters

<i>in_data</i>	Data to be normalized
<i>column</i>	Name of column to be normalized
<i>group_column</i>	Name of column used to group data

## 5.40 skdaccess.utilities.modis\_util Namespace Reference

## Classes

- class [LatLon](#)  
*Calculates Lat/Lon position from y,x pixel coordinate.*

## Functions

- def [getImageType](#) (in\_data)  
*Determine what type of modis data is being processed.*
- def [calibrateModis](#) (data, metadata)  
*This function calibrates input modis data.*
- def [rescale](#) (in\_array, max\_val=0.9, min\_val=-0.01)  
*This function rescales an image to fall between 0 and 1.*
- def [checkBit](#) (data, bit)  
*Get the bit value from a bit flag.*
- def [createGrid](#) (data, y\_start, y\_end, x\_start, x\_end, y\_grid, x\_grid, dtype, grid\_fill=np.nan)  
*Subsets image data into a smaller image.*
- def [getFileIDs](#) (modis\_identifier, start\_date, end\_date, lat, lon, daynightboth)  
*Retrieve file IDs for images matching search parameters.*
- def [getFileURLs](#) (file\_ids)  
*Retrieve the ftp location for a list of file IDs.*
- def [getModisData](#) (dataset, variable\_name)  
*Loads modis data.*
- def [readMODISData](#) (modis\_list, variables, grid, grid\_fill, use\_long\_name, platform, product\_id)  
*Retrieve a list of modis data.*

## 5.40.1 Function Documentation

5.40.1.1 [calibrateModis\(\)](#)

```
def skdaccess.utilities.modis_util.calibrateModis (
    data,
    metadata )
```

This function calibrates input modis data.

**Parameters**

<i>data</i>	Input modis data
<i>metadata</i>	Metadata associated with modis input data

**Returns**

calibrated modis data

**5.40.1.2 checkBit()**

```
def skdaccess.utilities.modis_util.checkBit (
    data,
    bit )
```

Get the bit value from a bit flag.

**Parameters**

<i>data</i>	Integer bit flag
<i>bit</i>	Which bit to select (start indexing at 0)

**Returns**

value of chosen bit in bit flag

**5.40.1.3 createGrid()**

```
def skdaccess.utilities.modis_util.createGrid (
    data,
    y_start,
    y_end,
    x_start,
    x_end,
    y_grid,
    x_grid,
    dtype,
    grid_fill = np.nan )
```

Subsets image data into a smaller image.

Takes care to make sure the resulting subsection has the expected size by filling in missing data

## Parameters

<i>data</i>	Input data
<i>y_start</i>	Starting pixel for y
<i>y_end</i>	Ending pixel for y
<i>x_start</i>	Starting pixel x
<i>x_end</i>	Ending pixel for x
<i>y_grid</i>	Grid size for y
<i>x_grid</i>	Grid size for x
<i>dtype</i>	The dtype of the new grid data
<i>grid_fill</i>	Fill value to use when there is no data

## Returns

image subsection, fraction of valid data

## 5.40.1.4 getFileIDs()

```
def skdaccess.utilities.modis_util.getFileIDs (
    modis_identifier,
    start_date,
    end_date,
    lat,
    lon,
    daynightboth )
```

Retrieve file IDs for images matching search parameters.

## Parameters

<i>modis_identifier</i>	Product identifier (e.g. MOD09)
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>lat</i>	Latitude
<i>lon</i>	Longitude
<i>daynightboth</i>	Get daytime images ('D'), nighttime images ('N') or both ('B')

## Returns

list of file IDs

#### 5.40.1.5 getFileURLs()

```
def skdaccess.utilities.modis_util.getFileURLs (
    file_ids )
```

Retrieve the ftp location for a list of file IDs.

##### Parameters

<i>file_ids</i>	List of file IDs
-----------------	------------------

##### Returns

List of ftp locations

#### 5.40.1.6 getImageType()

```
def skdaccess.utilities.modis_util.getImageType (
    in_data )
```

Determine what type of modis data is being processed.

There are 3 array shapes we deal with:

```
mode 1 -> (y, x, z)
mode 2 -> (y, x)
mode 3 -> (z, y, x)
```

where z axis represents different data products and y and x correspond to the y and x image coordinates from the modis instrument

##### Parameters

<i>in_data</i>	Input modis data
----------------	------------------

##### Returns

type of modis data

#### 5.40.1.7 getModisData()

```
def skdaccess.utilities.modis_util.getModisData (
    dataset,
    variable_name )
```

Loads modis data.

#### Parameters

<i>dataset</i>	netCDF4 dataset
<i>variable_name</i>	Name of variable to extract from dataset

#### Returns

(modis\_data, metadata)

#### 5.40.1.8 readMODISData()

```
def skdaccess.utilities.modis_util.readMODISData (
    modis_list,
    variables,
    grid,
    grid_fill,
    use_long_name,
    platform,
    product_id )
```

Retrieve a list of modis data.

#### Parameters

<i>modis_list</i>	List of MODIS data to load
<i>variables</i>	List of variables in the MODIS data to load
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)
<i>grid_fill</i>	Fill value to use when creating gridded data
<i>use_long_name</i>	Use long names for metadata instead of variable name
<i>platform</i>	Which satellite to use, either MOD or MYD.
<i>product_id</i>	Product string (e.g. '06_L2')

#### 5.40.1.9 rescale()

```
def skdaccess.utilities.modis_util.rescale (
    in_array,
    max_val = 0.9,
    min_val = -0.01 )
```

This function rescales an image to fall between 0 and 1.

## Parameters

<i>in_array</i>	Data to be rescaled
<i>max_val</i>	Values greater than or equal to max_val will become 1
<i>min_val</i>	Values less than or equal to min_val will become 0

## Returns

scaled data

## 5.41 skdaccess.utilities.pbo\_util Namespace Reference

## Functions

- def [getStationCoords](#) (pbo\_info, station\_list)  
*Get the station coordinates for a list of stations.*
- def [getLatLonRange](#) (pbo\_info, station\_list)  
*Retrive the range of latitude and longitude occupied by a set of stations.*
- def [getROIstations](#) (geo\_point, radiusParam, data, header)  
*This function returns the 4ID station codes for the stations in a region.*
- def [stab\\_sys](#) (data\_iterator, metadata, stab\_min\_NE=.0005, stab\_min\_U=.005, sigsc=2, errProp=1)  
*Stabilize GPS data to a region.*
- def [propagateErrors](#) (R, sc, stationCovs)  
*Propagate GPS errors.*
- def [nostab\\_sys](#) (allH, allD, timerng, indx=1, mdyratio=.7, use\_progress\_bar=True, index\_date\_only=False)  
*Do not apply stabilization and simply returns stations after checking for sufficient amount of data.*
- def [removeAntennaOffset](#) (antenna\_offsets, data, window\_start=pd.to\_timedelta('4D'), window\_end=pd.to\_←timedelta('4D'), min\_diff=0.005, debug=False)  
*Remove offsets caused by changes in antennas.*

### 5.41.1 Function Documentation

#### 5.41.1.1 [getLatLonRange\(\)](#)

```
def skdaccess.utilities.pbo_util.getLatLonRange (
    pbo_info,
    station_list )
```

Retrive the range of latitude and longitude occupied by a set of stations.

## Parameters

<i>pbo_info</i>	PBO Metadata
<i>station_list</i>	List of stations

## Returns

list containing two tuples, lat\_range and lon\_range

## 5.41.1.2 getROIstations()

```
def skdaccess.utilities.pbo_util.getROIstations (
    geo_point,
    radiusParam,
    data,
    header )
```

This function returns the 4ID station codes for the stations in a region.

The region of interest is defined by the geographic coordinate and a window size

## Parameters

<i>geo_point</i>	The geographic (lat,lon) coordinate of interest
<i>radiusParam</i>	An overloaded radius of interest [km] or latitude and longitude window [deg] around the geo_point
<i>data</i>	Stabilized (or unstabilized) data generated from the data fetcher or out of stab_sys
<i>header</i>	Header dictionary with stations metadata keyed by their 4ID code. This is output with the data.

## Returns

station\_list, list of site 4ID codes in the specified geographic region

## 5.41.1.3 getStationCoords()

```
def skdaccess.utilities.pbo_util.getStationCoords (
    pbo_info,
    station_list )
```

Get the station coordinates for a list of stations.

**Parameters**

<i>pbo_info</i>	PBO Metadata
<i>station_list</i>	List of stations

**Returns**

list of tuples containing lat, lon coordinates of stations

**5.41.1.4 nostab\_sys()**

```
def skdaccess.utilities.pbo_util.nostab_sys (
    allH,
    allD,
    timerng,
    indx = 1,
    mdyratio = .7,
    use_progress_bar = True,
    index_date_only = False )
```

Do not apply stabilization and simply returns stations after checking for sufficient amount of data.

**Parameters**

<i>allH</i>	a dictionary of all of the headers of all sites loaded from the data directory
<i>allD</i>	a dictionary of all of the panda format data of all of the corresponding sites
<i>timerng</i>	an array with two string elements, describing the starting and ending dates
<i>indx</i>	a list of site 4ID's indicating stations in the relevant geographic location, or 1 for all sites
<i>mdyratio</i>	optional parameter for the minimum required ratio of data to determine if a site is kept for further analysis

**Returns**

smSet, a reduced size dictionary of the data (in meters) for the sites in the specified geographic region and smHdr, a reduced size dictionary of the headers for the sites in the region

**5.41.1.5 propagateErrors()**

```
def skdaccess.utilities.pbo_util.propagateErrors (
    R,
    SC,
    stationCovs )
```



Propagate GPS errors.

By writing out the  $R \cdot E \cdot R^T$  equations... to calculate the new covariance matrix without needing to form the matrix first as an intermediate step. Modifies covariance matrix in place

## Parameters

<i>R</i>	Rotation matrix
<i>sc</i>	Scaling value
<i>stationCovs</i>	Station Covariances

## 5.41.1.6 removeAntennaOffset()

```
def skdaccess.utilities.pbo_util.removeAntennaOffset (
    antenna_offsets,
    data,
    window_start = pd.to_timedelta('4D'),
    window_end = pd.to_timedelta('4D'),
    min_diff = 0.005,
    debug = False )
```

Remove offsets caused by changes in antennas.

## Parameters

<i>antenna_offsets</i>	Pandas series of dates describing when the antenna changes were made
<i>data</i>	Input GPS data
<i>window_start</i>	Starting time before and after event to use for calculating offset
<i>window_end</i>	Ending time before and after event to use before calculating offset
<i>min_diff</i>	Minimum difference before and after offset to for applying correction
<i>debug</i>	Enable debug output

## Returns

GPS data with the offsets removed

## 5.41.1.7 stab\_sys()

```
def skdaccess.utilities.pbo_util.stab_sys (
    data_iterator,
    metadata,
    stab_min_NE = .0005,
    stab_min_U = .005,
    sigsc = 2,
    errProp = 1 )
```

Stabilize GPS data to a region.

The `stab_sys` function is a Python implementation of the Helmert 7-parameter transformation, used to correct for common mode error. This builds on Prof Herring's `stab_sys` function in his `tscon` Fortran code. It uses a SVD approach to estimating the rotation matrix gathered from 'Computing Helmert Transformations' by G.A. Watson as well as its references. Note that units should be in meters, that is in the format from the level 2 processed UNAVCO pos files

#### Parameters

<i>data_iterator</i>	Expects an iterator that returns label, pandas dataframe
<i>metadata</i>	Metadata that contains 'refXYZ' and 'refNEU'
<i>stab_min_NE</i>	Optional minimum horizontal covariance parameter
<i>stab_min_U</i>	Optional minimum vertical covariance parameter
<i>sigsc</i>	Optional scaling factor for determining cutoff bounds for non stable sites
<i>errProp</i>	Propagate errors through the transformation

#### Returns

`smSet`, a reduced size dictionary of the data (in mm) for the sites in the specified geographic region, `smHdr`, a reduced size dictionary of the headers for the sites in the region




## Chapter 6

# Class Documentation

### 6.1 skdaccess.framework.param\_class.AutoList Class Reference

Specifies a list for returning selections of lists, as opposed to a single element.

Inheritance diagram for skdaccess.framework.param\_class.AutoList:



#### Public Member Functions

- def `__init__` (self, `val_list`)  
*Construct a `AutoList` object.*
- def `val` (self)  
*Retrieves current list of parameters.*
- def `perturb` (self)  
*This class doesn't change the list when being perturbed.*
- def `reset` (self)  
*Reset current list to initial list.*
- def `getAllOptions` (self)  
*Get all possible options.*
- def `__str__` (self)  
*String representation of class.*
- def `__len__` (self)  
*Retrieves the length of parameters contained in the list.*
- def `__getitem__` (self, ii)  
*Retrieves item from list.*
- def `__setitem__` (self, ii, `val`)  
*Set a value in the list.*
- def `__call__` (self)  
*Retrieve current list.*

## Public Attributes

- [val\\_init](#)
- [val\\_list](#)

### 6.1.1 Detailed Description

Specifies a list for returning selections of lists, as opposed to a single element.

### 6.1.2 Constructor & Destructor Documentation

#### 6.1.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoList.__init__ (
    self,
    val_list )
```

Construct a [AutoList](#) object.

#### Parameters

<i>val_list</i>	List of parameters
-----------------	--------------------

### 6.1.3 Member Function Documentation

#### 6.1.3.1 `__call__()`

```
def skdaccess.framework.param_class.AutoList.__call__ (
    self )
```

Retrieve current list.

#### Returns

Current list

### 6.1.3.2 `__getitem__()`

```
def skdaccess.framework.param_class.AutoList.__getitem__ (
    self,
    ii )
```

Retrieves item from list.

#### Parameters

<i>ii</i>	Index of item to be retrieved
-----------	-------------------------------

#### Returns

Item at index ii

### 6.1.3.3 `__len__()`

```
def skdaccess.framework.param_class.AutoList.__len__ (
    self )
```

Retrieves the length of parameters contained in the list.

#### Returns

Number of elements in the list

### 6.1.3.4 `__setitem__()`

```
def skdaccess.framework.param_class.AutoList.__setitem__ (
    self,
    ii,
    val )
```

Set a value in the list.

#### Parameters

<i>ii</i>	Index of list to be set
<i>val</i>	Input value

#### 6.1.3.5 `__str__()`

```
def skdaccess.framework.param_class.AutoList.__str__ (
    self )
```

String representation of class.

##### Returns

String containing all parameters in list

#### 6.1.3.6 `getAllOptions()`

```
def skdaccess.framework.param_class.AutoList.getAllOptions (
    self )
```

Get all possible options.

##### Returns

List that contains every option that could possibly be selected

#### 6.1.3.7 `perturb()`

```
def skdaccess.framework.param_class.AutoList.perturb (
    self )
```

This class doesn't change the list when being perturbed.

#### 6.1.3.8 `reset()`

```
def skdaccess.framework.param_class.AutoList.reset (
    self )
```

Reset current list to initial list.



### 6.1.3.9 val()

```
def skdaccess.framework.param_class.AutoList.val (
    self )
```

Retrieves current list of parameters.

#### Returns

List of current parameters

## 6.1.4 Member Data Documentation

### 6.1.4.1 val\_init

```
skdaccess.framework.param_class.AutoList.val_init
```

### 6.1.4.2 val\_list

```
skdaccess.framework.param_class.AutoList.val_list
```


The documentation for this class was generated from the following file:

- framework/[param\\_class.py](#)

## 6.2 skdaccess.framework.param\_class.AutoListCycle Class Reference

An Autolist that cycles through different lists.

Inheritance diagram for skdaccess.framework.param\_class.AutoListCycle:



## Public Member Functions

- def `__init__` (self, `list_val_list`)  
*Construct a `AutoList_Cycle` object.*
- def `perturb` (self)  
*Select next list from list of lists.*
- def `reset` (self)  
*Resets to the first list in the list of lists.*
- def `getAllOptions` (self)  
*Get elements that could possibly be called.*
- def `val` (self)  
*Retrieves current list of parameters.*
- def `__str__` (self)  
*String representation of class.*
- def `__len__` (self)  
*Retrieves the length of parameters contained in the list.*
- def `__getitem__` (self, ii)  
*Retrieves item from list.*
- def `__setitem__` (self, ii, `val`)  
*Set a value in the list.*
- def `__call__` (self)  
*Retrieve current list.*

## Public Attributes

- `list_val_list`
- `val_list`
- `index`
- `val_init`

### 6.2.1 Detailed Description

An Autolist that cycles through different lists.

### 6.2.2 Constructor & Destructor Documentation

#### 6.2.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoListCycle.__init__ (
    self,
    list_val_list )
```

Construct a `AutoList_Cycle` object.

#### Parameters

<i>list_val_list</i>	List of different lists to cycle through
----------------------	--

### 6.2.3 Member Function Documentation

#### 6.2.3.1 \_\_call\_\_()

```
def skdaccess.framework.param_class.AutoList.__call__ (
    self ) [inherited]
```

Retrieve current list.

#### Returns

Current list

#### 6.2.3.2 \_\_getitem\_\_()

```
def skdaccess.framework.param_class.AutoList.__getitem__ (
    self,
    ii ) [inherited]
```

Retrieves item from list.

#### Parameters

<i>ii</i>	Index of item to be retrieved
-----------	-------------------------------

#### Returns

Item at index ii

#### 6.2.3.3 \_\_len\_\_()

```
def skdaccess.framework.param_class.AutoList.__len__ (
    self ) [inherited]
```

Retrieves the length of parameters contained in the list.

**Returns**

Number of elements in the list

**6.2.3.4 \_\_setitem\_\_()**

```
def skdaccess.framework.param_class.AutoList.__setitem__ (
    self,
    ii,
    val ) [inherited]
```

Set a value in the list.

**Parameters**

<i>ii</i>	Index of list to be set
<i>val</i>	Input value

**6.2.3.5 \_\_str\_\_()**

```
def skdaccess.framework.param_class.AutoList.__str__ (
    self ) [inherited]
```

String representation of class.

**Returns**

String containing all parmaters in list

**6.2.3.6 getAllOptions()**

```
def skdaccess.framework.param_class.AutoListCycle.getAllOptions (
    self )
```

Get elements that could possibly be called.

**Returns**

List of all possible elements

### 6.2.3.7 perturb()

```
def skdaccess.framework.param_class.AutoListCycle.perturb (  
    self )
```

Select next list from list of lists.

### 6.2.3.8 reset()

```
def skdaccess.framework.param_class.AutoListCycle.reset (  
    self )
```

Resets to the first list in the list of lists.

### 6.2.3.9 val()

```
def skdaccess.framework.param_class.AutoList.val (  
    self ) [inherited]
```

Retrieves current list of parameters.

#### Returns

List of current parameters

## 6.2.4 Member Data Documentation

### 6.2.4.1 index

```
skdaccess.framework.param_class.AutoListCycle.index
```

### 6.2.4.2 list\_val\_list

```
skdaccess.framework.param_class.AutoListCycle.list_val_list
```

#### 6.2.4.3 val\_init

`skdaccess.framework.param_class.AutoList.val_init` [inherited]

#### 6.2.4.4 val\_list

`skdaccess.framework.param_class.AutoListCycle.val_list`


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.3 skdaccess.framework.param\_class.AutoListPermute Class Reference

A perturber that permutes a list.

Inheritance diagram for `skdaccess.framework.param_class.AutoListPermute`:



### Public Member Functions

- `def perturb (self)`  
*Randomly permutes the initial list.*
- `def val (self)`  
*Retrieves current list of parameters.*
- `def reset (self)`  
*Reset current list to initial list.*
- `def getAllOptions (self)`  
*Get all possible options.*
- `def __str__ (self)`  
*String representation of class.*
- `def __len__ (self)`  
*Retrieves the length of parameters contained in the list.*
- `def __getitem__ (self, ii)`  
*Retrieves item from list.*
- `def __setitem__ (self, ii, val)`  
*Set a value in the list.*
- `def __call__ (self)`  
*Retrieve current list.*

## Public Attributes

- [val\\_init](#)
- [val\\_list](#)

### 6.3.1 Detailed Description

A perturber that permutes a list.

### 6.3.2 Member Function Documentation

#### 6.3.2.1 `__call__()`

```
def skdaccess.framework.param_class.AutoList.__call__ (
    self ) [inherited]
```

Retrieve current list.

#### Returns

Current list

#### 6.3.2.2 `__getitem__()`

```
def skdaccess.framework.param_class.AutoList.__getitem__ (
    self,
    ii ) [inherited]
```

Retrieves item from list.

#### Parameters

<i>ii</i>	Index of item to be retrieved
-----------	-------------------------------

#### Returns

Item at index ii

#### 6.3.2.3 `__len__()`

```
def skdaccess.framework.param_class.AutoList.__len__ (
    self ) [inherited]
```

Retrieves the length of parameters contained in the list.

##### Returns

Number of elements in the list

#### 6.3.2.4 `__setitem__()`

```
def skdaccess.framework.param_class.AutoList.__setitem__ (
    self,
    ii,
    val ) [inherited]
```

Set a value in the list.

##### Parameters

<i>ii</i>	Index of list to be set
<i>val</i>	Input value

#### 6.3.2.5 `__str__()`

```
def skdaccess.framework.param_class.AutoList.__str__ (
    self ) [inherited]
```

String representation of class.

##### Returns

String containing all parmaters in list



#### 6.3.2.6 getAllOptions()

```
def skdaccess.framework.param_class.AutoList.getAllOptions (
    self ) [inherited]
```

Get all possible options.

##### Returns

List that contains every option that could possibly be selected

#### 6.3.2.7 perturb()

```
def skdaccess.framework.param_class.AutoListPermute.perturb (
    self )
```

Randomly permutes the initial list.

#### 6.3.2.8 reset()

```
def skdaccess.framework.param_class.AutoList.reset (
    self ) [inherited]
```

Reset current list to initial list.

#### 6.3.2.9 val()

```
def skdaccess.framework.param_class.AutoList.val (
    self ) [inherited]
```

Retrieves current list of parameters.

##### Returns

List of current parameters

### 6.3.3 Member Data Documentation

### 6.3.3.1 val\_init

`skdaccess.framework.param_class.AutoList.val_init` [inherited]

### 6.3.3.2 val\_list

`skdaccess.framework.param_class.AutoList.val_list` [inherited]


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.4 skdaccess.framework.param\_class.AutoListRemove Class Reference

Removes a different single element from the initial list at each perturb call.

Inheritance diagram for `skdaccess.framework.param_class.AutoListRemove`:



### Public Member Functions

- `def __init__ (self, val_list)`  
*Construct a AutoList\_Cycle object.*
- `def perturb (self)`  
*Systematically change which item is absent from the list.*
- `def reset (self)`  
*Reset the list to its initial value.*
- `def val (self)`  
*Retrieves current list of parameters.*
- `def getAllOptions (self)`  
*Get all possible options.*
- `def __str__ (self)`  
*String representation of class.*
- `def __len__ (self)`  
*Retrieves the length of parameters contained in the list.*
- `def __getitem__ (self, ii)`  
*Retrieves item from list.*
- `def __setitem__ (self, ii, val)`  
*Set a value in the list.*
- `def __call__ (self)`  
*Retrieve current list.*

## Public Attributes

- `n`
- `val_list`
- `val_init`

### 6.4.1 Detailed Description

Removes a different single element from the initial list at each perturb call.

### 6.4.2 Constructor & Destructor Documentation

#### 6.4.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoListRemove.__init__ (
    self,
    val_list )
```

Construct a AutoList\_Cycle object.

#### Parameters

<code>val_list</code>	Initial list of parameters.
-----------------------	-----------------------------

### 6.4.3 Member Function Documentation

#### 6.4.3.1 `__call__()`

```
def skdaccess.framework.param_class.AutoList.__call__ (
    self ) [inherited]
```

Retrieve current list.

#### Returns

Current list

#### 6.4.3.2 `__getitem__()`

```
def skdaccess.framework.param_class.AutoList.__getitem__ (
    self,
    ii ) [inherited]
```

Retrieves item from list.

##### Parameters

<i>ii</i>	Index of item to be retrieved
-----------	-------------------------------

##### Returns

Item at index *ii*

#### 6.4.3.3 `__len__()`

```
def skdaccess.framework.param_class.AutoList.__len__ (
    self ) [inherited]
```

Retrieves the length of parameters contained in the list.

##### Returns

Number of elements in the list

#### 6.4.3.4 `__setitem__()`

```
def skdaccess.framework.param_class.AutoList.__setitem__ (
    self,
    ii,
    val ) [inherited]
```

Set a value in the list.

##### Parameters

<i>ii</i>	Index of list to be set
<i>val</i>	Input value

#### 6.4.3.5 \_\_str\_\_()

```
def skdaccess.framework.param_class.AutoList.__str__ (
    self ) [inherited]
```

String representation of class.

##### Returns

String containing all parmaters in list

#### 6.4.3.6 getAllOptions()

```
def skdaccess.framework.param_class.AutoList.getAllOptions (
    self ) [inherited]
```

Get all possible options.

##### Returns

List that contains every option that could possibly be selected

#### 6.4.3.7 perturb()

```
def skdaccess.framework.param_class.AutoListRemove.perturb (
    self )
```

Systematically change which item is absent from the list.

#### 6.4.3.8 reset()

```
def skdaccess.framework.param_class.AutoListRemove.reset (
    self )
```

Reset the list to its initial value.

#### 6.4.3.9 val()

```
def skdaccess.framework.param_class.AutoList.val (
    self ) [inherited]
```

Retrieves current list of parameters.

#### Returns

List of current parameters

### 6.4.4 Member Data Documentation

#### 6.4.4.1 n

```
skdaccess.framework.param_class.AutoListRemove.n
```

#### 6.4.4.2 val\_init

```
skdaccess.framework.param_class.AutoList.val_init [inherited]
```

#### 6.4.4.3 val\_list

```
skdaccess.framework.param_class.AutoListRemove.val_list
```


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.5 skdaccess.framework.param\_class.AutoListSubset Class Reference

An [AutoList](#) perturber that creates random subsets of a list.

Inheritance diagram for skdaccess.framework.param\_class.AutoListSubset:



## Public Member Functions

- def [perturb](#) (self)  
*Perturb the list by selecting a random subset of the initial list.*
- def [val](#) (self)  
*Retrieves current list of parameters.*
- def [reset](#) (self)  
*Reset current list to initial list.*
- def [getAllOptions](#) (self)  
*Get all possible options.*
- def [\\_\\_str\\_\\_](#) (self)  
*String representation of class.*
- def [\\_\\_len\\_\\_](#) (self)  
*Retrieves the length of parameters contained in the list.*
- def [\\_\\_getitem\\_\\_](#) (self, ii)  
*Retrieves item from list.*
- def [\\_\\_setitem\\_\\_](#) (self, ii, [val](#))  
*Set a value in the list.*
- def [\\_\\_call\\_\\_](#) (self)  
*Retrieve current list.*

## Public Attributes

- [val\\_list](#)
- [val\\_init](#)

### 6.5.1 Detailed Description

An [AutoList](#) perturber that creates random subsets of a list.

List can be empty

### 6.5.2 Member Function Documentation

#### 6.5.2.1 [\\_\\_call\\_\\_](#)()

```
def skdaccess.framework.param_class.AutoList.__call__ (
    self ) [inherited]
```

Retrieve current list.

#### Returns

Current list

### 6.5.2.2 `__getitem__()`

```
def skdaccess.framework.param_class.AutoList.__getitem__ (
    self,
    ii ) [inherited]
```

Retrieves item from list.

#### Parameters

<i>ii</i>	Index of item to be retrieved
-----------	-------------------------------

#### Returns

Item at index *ii*

### 6.5.2.3 `__len__()`

```
def skdaccess.framework.param_class.AutoList.__len__ (
    self ) [inherited]
```

Retrieves the length of parameters contained in the list.

#### Returns

Number of elements in the list

### 6.5.2.4 `__setitem__()`

```
def skdaccess.framework.param_class.AutoList.__setitem__ (
    self,
    ii,
    val ) [inherited]
```

Set a value in the list.

#### Parameters

<i>ii</i>	Index of list to be set
<i>val</i>	Input value



#### 6.5.2.5 `__str__()`

```
def skdaccess.framework.param_class.AutoList.__str__ (
    self ) [inherited]
```

String representation of class.

##### Returns

String containing all parameters in list

#### 6.5.2.6 `getAllOptions()`

```
def skdaccess.framework.param_class.AutoList.getAllOptions (
    self ) [inherited]
```

Get all possible options.

##### Returns

List that contains every option that could possibly be selected

#### 6.5.2.7 `perturb()`

```
def skdaccess.framework.param_class.AutoListSubset.perturb (
    self )
```

Perturb the list by selecting a random subset of the initial list.

#### 6.5.2.8 `reset()`

```
def skdaccess.framework.param_class.AutoList.reset (
    self ) [inherited]
```

Reset current list to initial list.

### 6.5.2.9 val()

```
def skdaccess.framework.param_class.AutoList.val (
    self ) [inherited]
```

Retrieves current list of parameters.

#### Returns

List of current parameters

## 6.5.3 Member Data Documentation

### 6.5.3.1 val\_init

```
skdaccess.framework.param_class.AutoList.val_init [inherited]
```

### 6.5.3.2 val\_list

```
skdaccess.framework.param_class.AutoListSubset.val_list
```


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.6 skdaccess.framework.param\_class.AutoParam Class Reference

Defines a tunable parameter class inherited by specific subclasses.

Inheritance diagram for skdaccess.framework.param\_class.AutoParam:



## Public Member Functions

- def `__init__` (self, `val_init`)  
*Initialize an [AutoParam](#) object.*
- def `perturb` (self)  
*Perturb paramter.*
- def `reset` (self)  
*Reset value to initial value.*
- def `__str__` (self)  
*String representation of class.*
- def `__call__` (self)  
*Retrieves current value of the parameter.*

## Public Attributes

- `val`
- `val_init`

### 6.6.1 Detailed Description

Defines a tunable parameter class inherited by specific subclasses.

[AutoParam](#) class and subclass work on a single value. functions perturb value and reset to initial value

### 6.6.2 Constructor & Destructor Documentation

#### 6.6.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoParam.__init__ (
    self,
    val_init )
```

Initialize an [AutoParam](#) object.

#### Parameters

<code>val_init</code>	Value for parameter
-----------------------	---------------------

### 6.6.3 Member Function Documentation

#### 6.6.3.1 `__call__()`

```
def skdaccess.framework.param_class.AutoParam.__call__ (
    self )
```

Retrieves current value of the parameter.

##### Returns

Current value of the parameter

#### 6.6.3.2 `__str__()`

```
def skdaccess.framework.param_class.AutoParam.__str__ (
    self )
```

String representation of class.

##### Returns

String of current value

#### 6.6.3.3 `perturb()`

```
def skdaccess.framework.param_class.AutoParam.perturb (
    self )
```

Perturb paramter.

This class doesn't change the value.

#### 6.6.3.4 `reset()`

```
def skdaccess.framework.param_class.AutoParam.reset (
    self )
```

Reset value to initial value.

## 6.6.4 Member Data Documentation

### 6.6.4.1 val

`skdaccess.framework.param_class.AutoParam.val`

### 6.6.4.2 val\_init

`skdaccess.framework.param_class.AutoParam.val_init`


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.7 skdaccess.framework.param\_class.AutoParamList Class Reference

A tunable parameter with a specified list of choices that can be randomly selected via perturb.

Inheritance diagram for `skdaccess.framework.param_class.AutoParamList`:



### Public Member Functions

- `def __init__(self, val_init, val_list)`  
*Construct an [AutoParamList](#) object.*
- `def perturb(self)`  
*Randomly select a value from `val_list`.*
- `def reset(self)`  
*Reset the list to the default value.*
- `def __str__(self)`  
*String representation of class.*
- `def __call__(self)`  
*Retrieves current value of the parameter.*

## Public Attributes

- [val](#)
- [val\\_init](#)
- [val\\_list](#)

### 6.7.1 Detailed Description

A tunable parameter with a specified list of choices that can be randomly selected via perturb.

### 6.7.2 Constructor & Destructor Documentation

#### 6.7.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoParamList.__init__ (
    self,
    val_init,
    val_list )
```

Construct an [AutoParamList](#) object.

#### Parameters

<i>val_init</i>	initial value for the parameter
<i>val_list</i>	List of possible variants for the parameter

### 6.7.3 Member Function Documentation

#### 6.7.3.1 `__call__()`

```
def skdaccess.framework.param_class.AutoParam.__call__ (
    self ) [inherited]
```

Retrieves current value of the parameter.

#### Returns

Current value of the parameter

### 6.7.3.2 \_\_str\_\_()

```
def skdaccess.framework.param_class.AutoParam.__str__ (
    self ) [inherited]
```

String representation of class.

#### Returns

String of current value

### 6.7.3.3 perturb()

```
def skdaccess.framework.param_class.AutoParamList.perturb (
    self )
```

Randomly select a value from val\_list.

### 6.7.3.4 reset()

```
def skdaccess.framework.param_class.AutoParamList.reset (
    self )
```

Reset the list to the default value.

## 6.7.4 Member Data Documentation

### 6.7.4.1 val

```
skdaccess.framework.param_class.AutoParamList.val
```

### 6.7.4.2 val\_init

```
skdaccess.framework.param_class.AutoParamList.val_init
```

### 6.7.4.3 val\_list

`skdaccess.framework.param_class.AutoParamList.val_list`


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.8 skdaccess.framework.param\_class.AutoParamListCycle Class Reference

Cycles through a list of paramters.

Inheritance diagram for `skdaccess.framework.param_class.AutoParamListCycle`:



### Public Member Functions

- `def __init__(self, val_list)`  
*Construct an [AutoParamListCycle](#).*
- `def perturb(self)`  
*Select the next value from the list of parameters.*
- `def reset(self)`  
*Reset the list to the default values.*
- `def __str__(self)`  
*String representation of class.*
- `def __call__(self)`  
*Retrieves current value of the parameter.*

### Public Attributes

- `val`
- `val_list`
- `current_index`
- `val_init`

### 6.8.1 Detailed Description

Cycles through a list of paramters.



## 6.8.2 Constructor & Destructor Documentation

### 6.8.2.1 \_\_init\_\_()

```
def skdaccess.framework.param_class.AutoParamListCycle.__init__ (
    self,
    val_list )
```

Construct an [AutoParamListCycle](#).

#### Parameters

<i>val_list</i>	List of possible variants for the parameter
-----------------	---

## 6.8.3 Member Function Documentation

### 6.8.3.1 \_\_call\_\_()

```
def skdaccess.framework.param_class.AutoParam.__call__ (
    self ) [inherited]
```

Retrieves current value of the parameter.

#### Returns

Current value of the parameter

### 6.8.3.2 \_\_str\_\_()

```
def skdaccess.framework.param_class.AutoParam.__str__ (
    self ) [inherited]
```

String representation of class.

#### Returns

String of current value

#### 6.8.3.3 perturb()

```
def skdaccess.framework.param_class.AutoParamListCycle.perturb (  
    self )
```

Select the next value from the list of parameters.

#### 6.8.3.4 reset()

```
def skdaccess.framework.param_class.AutoParamListCycle.reset (  
    self )
```

Reset the list to the default values.

### 6.8.4 Member Data Documentation

#### 6.8.4.1 current\_index

```
skdaccess.framework.param_class.AutoParamListCycle.current_index
```

#### 6.8.4.2 val

```
skdaccess.framework.param_class.AutoParamListCycle.val
```

#### 6.8.4.3 val\_init

```
skdaccess.framework.param_class.AutoParam.val_init [inherited]
```

#### 6.8.4.4 val\_list

```
skdaccess.framework.param_class.AutoParamListCycle.val_list
```


The documentation for this class was generated from the following file:

- framework/[param\\_class.py](#)

## 6.9 skdaccess.framework.param\_class.AutoParamMinMax Class Reference

A tunable parameter with min and max ranges, perturbs to a random value in range.

Inheritance diagram for skdaccess.framework.param\_class.AutoParamMinMax:



### Public Member Functions

- def `__init__` (self, `val_init`, `val_min`, `val_max`, `decimals`=0, `extreme`=0)  
*Construct `AutoParamMinMax` object.*
- def `perturb` (self)  
*Perturb the parameter by choosing a random value between `val_min` and `val_max`.*
- def `reset` (self)  
*Reset to initial value.*
- def `__str__` (self)  
*String representation of class.*
- def `__call__` (self)  
*Retrieves current value of the parameter.*

### Public Attributes

- `val`
- `val_init`
- `val_min`
- `val_max`
- `n`
- `n_max`
- `decimals`

#### 6.9.1 Detailed Description

A tunable parameter with min and max ranges, perturbs to a random value in range.

It can optionally choose either the min or the max after `n` perturbs

#### 6.9.2 Constructor & Destructor Documentation

### 6.9.2.1 `__init__()`

```
def skdaccess.framework.param_class.AutoParamMinMax.__init__ (
    self,
    val_init,
    val_min,
    val_max,
    decimals = 0,
    extreme = 0 )
```

Construct [AutoParamMinMax](#) object.

#### Parameters

<i>val_init</i>	Initial value for parameter
<i>val_min</i>	Minimum value for param
<i>val_max</i>	Maximum value for parameter
<i>decimals</i>	Number of decimals to include in the random number
<i>extreme</i>	Either the maximum or minimum is chosen every extreme number of iterations. Using a value of one will be an extreme value every time. Using a value of zero will always choose a random value.

## 6.9.3 Member Function Documentation

### 6.9.3.1 `__call__()`

```
def skdaccess.framework.param_class.AutoParam.__call__ (
    self ) [inherited]
```

Retrieves current value of the parameter.

#### Returns

Current value of the parameter

### 6.9.3.2 `__str__()`

```
def skdaccess.framework.param_class.AutoParam.__str__ (
    self ) [inherited]
```

String representation of class.

#### Returns

String of current value

### 6.9.3.3 perturb()

```
def skdaccess.framework.param_class.AutoParamMinMax.perturb (
    self )
```

Perturb the parameter by choosing a random value between val\_min and val\_max.

Will choose a random number with precision specified by decimals. Will optionally pick the min or the max value after a specified number of perturb calls

### 6.9.3.4 reset()

```
def skdaccess.framework.param_class.AutoParamMinMax.reset (
    self )
```

Reset to initial value.

## 6.9.4 Member Data Documentation

### 6.9.4.1 decimals

```
skdaccess.framework.param_class.AutoParamMinMax.decimals
```

### 6.9.4.2 n

```
skdaccess.framework.param_class.AutoParamMinMax.n
```

### 6.9.4.3 n\_max

```
skdaccess.framework.param_class.AutoParamMinMax.n_max
```

### 6.9.4.4 val

```
skdaccess.framework.param_class.AutoParamMinMax.val
```

#### 6.9.4.5 val\_init

`skdaccess.framework.param_class.AutoParamMinMax.val_init`

#### 6.9.4.6 val\_max

`skdaccess.framework.param_class.AutoParamMinMax.val_max`

#### 6.9.4.7 val\_min

`skdaccess.framework.param_class.AutoParamMinMax.val_min`


The documentation for this class was generated from the following file:

- [framework/param\\_class.py](#)

## 6.10 skdaccess.geo.modis.stream.cloud\_opacity.DataFetcher Class Reference

Data Fetcher for MODIS Cloud Opacity.

Inheritance diagram for `skdaccess.geo.modis.stream.cloud_opacity.DataFetcher`:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date, end_date, modis_platform='Terra', daynightboth='D', grid=None)`  
*Construct Data Fetcher object for MODIS cloud Opacity data.*

#### 6.10.1 Detailed Description

Data Fetcher for MODIS Cloud Opacity.

## 6.10.2 Constructor & Destructor Documentation

### 6.10.2.1 `__init__()`

```
def skdaccess.geo.modis.stream.cloud_opacity.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None )
```

Construct Data Fetcher object for MODIS cloud Opacity data.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)


The documentation for this class was generated from the following file:

- [geo/modis/stream/cloud\\_opacity/data\\_fetcher.py](#)

## 6.11 skdaccess.geo.modis.cache.DataFetcher Class Reference

Data Fetcher for MODIS data.

Inheritance diagram for skdaccess.geo.modis.cache.DataFetcher:



## Public Member Functions

- `def __init__ (self, ap_paramList, modis_platform, modis_id, variable_list, start_date, end_date, daynightboth='D', grid=None, grid_fill=np.nan, use_long_name=False)`  
*Construct Data Fetcher object.*
- `def find_data (self, fileid_list)`  
*Finds files previously downloaded files associated with fileids.*
- `def cacheData (self, data_specification)`  
*Download MODIS data.*
- `def output (self)`  
*Generate data wrapper.*
- `def cacheData (self, keyname, online_path_list, username=None, password=None, authentication_url=None, cookiejar=None, use_requests=False, use_progress_bar=True)`  
*Download and store specified data to local disk.*
- `def multirun_enabled (self)`  
*Returns whether or not this data fetcher is multirun enabled.*
- `def getHDFSStorage (self, keyname)`
- `def getDataLocation (data_name)`  
*Get the location of data set.*
- `def setDataLocation (data_name, location, key='data_location')`  
*Set the location of a data set.*
- `def perturb (self)`  
*Perturb parameters.*
- `def reset (self)`  
*Set all parameters to initial value.*
- `def __str__ (self)`  
*Generate string description.*
- `def getMetadata (self)`  
*Return metadata about Data Fetcher.*
- `def getConfig ()`  
*Retrieve skdaccess configuration.*
- `def writeConfig (conf)`  
*Write config to disk.*
- `def verbose_print (self, args, kwargs)`



## Public Attributes

- [modis\\_id](#)
- [variable\\_list](#)
- [start\\_date](#)
- [end\\_date](#)
- [daynightboth](#)
- [grid](#)
- [grid\\_fill](#)
- [use\\_long\\_name](#)
- [modis\\_platform](#)
- [modis\\_identifier](#)
- [ap\\_paramList](#)
- [verbose](#)

### 6.11.1 Detailed Description

Data Fetcher for MODIS data.

### 6.11.2 Constructor & Destructor Documentation

#### 6.11.2.1 `__init__()`

```
def skdaccess.geo.modis.cache.DataFetcher.__init__ (
    self,
    ap_paramList,
    modis_platform,
    modis_id,
    variable_list,
    start_date,
    end_date,
    daynightboth = 'D',
    grid = None,
    grid_fill = np.nan,
    use_long_name = False )
```

Construct Data Fetcher object.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>modis_id</i>	Product string (e.g. '06_L2')
<i>variable_list</i>	List of variables to fetch

## Parameters

<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)
<i>grid_fill</i>	Fill value to use when creating gridded data
<i>use_long_name</i>	Use long names for metadata instead of variable name

## 6.11.3 Member Function Documentation

6.11.3.1 `__str__()`

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

6.11.3.2 `cacheData()` [1/2]

```
def skdaccess.geo.modis.cache.DataFetcher.cacheData (
    self,
    data_specification )
```

Download MODIS data.

## Parameters

<i>data_specification</i>	List of file IDs to cache
---------------------------	---------------------------

6.11.3.3 `cacheData()` [2/2]

```
def skdaccess.framework.data_class.DataFetcherCache.cacheData (
    self,
    keyname,
    online_path_list,
```

```

    username = None,
    password = None,
    authentication_url = None,
    cookiejar = None,
    use_requests = False,
    use_progress_bar = True ) [inherited]

```

Download and store specified data to local disk.

#### Parameters

<i>data_specification</i>	Specification of data to be retrieved
---------------------------	---------------------------------------

#### Returns

List of downloaded file locations

#### 6.11.3.4 find\_data()

```

def skdaccess.geo.modis.cache.DataFetcher.find_data (
    self,
    fileid_list )

```

Finds files previously downloaded files associated with fileids.

#### Parameters

<i>fileid_list</i>	List of file id's
--------------------	-------------------

#### Returns

Pandas series of file locaitons indexed by file id

#### 6.11.3.5 getConfig()

```

def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]

```

Retrieve skdaccess configuration.

#### Returns

configParser.ConfigParser object of configuration

#### 6.11.3.6 `getDataLocation()`

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

##### Parameters

<i>data_name</i>	Name of data set
------------------	------------------

##### Returns

string of data location, None if not found

#### 6.11.3.7 `getHDFSStorage()`

```
def skdaccess.framework.data_class.DataFetcherCache.getHDFSStorage (
    self,
    keyname ) [inherited]
```

#### 6.11.3.8 `getMetadata()`

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.11.3.9 `multirun_enabled()`

```
def skdaccess.framework.data_class.DataFetcherCache.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.11.3.10 output()

```
def skdaccess.geo.modis.cache.DataFetcher.output (
    self )
```

Generate data wrapper.

##### Returns

data wrapper of MODIS data

#### 6.11.3.11 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.11.3.12 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.11.3.13 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.11.3.14 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.11.3.15 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.11.4 Member Data Documentation

#### 6.11.4.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.11.4.2 daynightboth

```
skdaccess.geo.modis.cache.DataFetcher.daynightboth
```

#### 6.11.4.3 end\_date

```
skdaccess.geo.modis.cache.DataFetcher.end_date
```

#### 6.11.4.4 grid

skdaccess.geo.modis.cache.DataFetcher.grid

#### 6.11.4.5 grid\_fill

skdaccess.geo.modis.cache.DataFetcher.grid\_fill

#### 6.11.4.6 modis\_id

skdaccess.geo.modis.cache.DataFetcher.modis\_id

#### 6.11.4.7 modis\_identifier

skdaccess.geo.modis.cache.DataFetcher.modis\_identifier

#### 6.11.4.8 modis\_platform

skdaccess.geo.modis.cache.DataFetcher.modis\_platform

#### 6.11.4.9 start\_date

skdaccess.geo.modis.cache.DataFetcher.start\_date

#### 6.11.4.10 use\_long\_name

skdaccess.geo.modis.cache.DataFetcher.use\_long\_name

#### 6.11.4.11 variable\_list

`skdaccess.geo.modis.cache.DataFetcher.variable_list`

#### 6.11.4.12 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [geo/modis/cache/data\\_fetcher.py](#)

## 6.12 skdaccess.geo.modis.stream.reflectance.DataFetcher Class Reference

Data fetcher for the modis surface reflectance product ('09', 1 km resolution)

Inheritance diagram for `skdaccess.geo.modis.stream.reflectance.DataFetcher`:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date, end_date, modis_platform='Terra', daynightboth='D', grid=None, bands=[1])`  
*Construct Data Fetcher for MODIS 1km surface reflectance.*

#### 6.12.1 Detailed Description

Data fetcher for the modis surface reflectance product ('09', 1 km resolution)

#### 6.12.2 Constructor & Destructor Documentation



6.12.2.1 `__init__()`

```
def skdaccess.geo.modis.stream.reflectance.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None,
    bands = [1 ]
)
```

Construct Data Fetcher for MODIS 1km surface reflectance.

## Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)
<i>bands</i>	List of modis bands to retrieve


The documentation for this class was generated from the following file:

- [geo/modis/stream/reflectance/data\\_fetcher.py](#)

## 6.13 skdaccess.geo.pbo.DataFetcher Class Reference

Data fetcher for PBO GPS data.

Inheritance diagram for skdaccess.geo.pbo.DataFetcher:



## Public Member Functions

- def `__init__` (self, start\_time, end\_time, `ap_paramList`, mdyratio=.5, `default_columns`=['dN', dE, dU, `default_error_columns`=['Sn', Se, Su, `use_progress_bar`=True, `index_date_only`=True)  
*Initialize a `DataFetcher`.*
- def `setStationList` (self, `station_list`)  
*Set the list of stations to use.*
- def `getInfo` (self)  
*Get information about the stations and geo\_point.*
- def `output` (self)  
*Generate PBO Data Wrapper.*
- def `__str__` (self)  
*print the parameter values*
- def `getStationMetadata` (data\_frame=False)  
*Read in the metadata and convert to dictionary.*
- def `getAntennaLogs` ()  
*Get antenna logs.*
- def `downloadFullDataset` (cls, out\_file='pbo\_data.h5', use\_file=None)  
*Download and parse data from the Plate Boundary Observatory.*
- def `multirun_enabled` (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def `getDataLocation` (data\_name)  
*Get the location of data set.*
- def `setDataLocation` (data\_name, location, key='data\_location')  
*Set the location of a data set.*
- def `perturb` (self)  
*Perturb parameters.*
- def `reset` (self)  
*Set all parameters to initial value.*
- def `getMetadata` (self)  
*Return metadata about Data Fetcher.*
- def `getConfig` ()  
*Retrieve skdaccess configuration.*
- def `writeConfig` (conf)  
*Write config to disk.*
- def `verbose_print` (self, args, kwargs)

## Public Attributes

- `station_list`
- `default_columns`
- `default_error_columns`
- `use_progress_bar`
- `index_date_only`
- `antenna_info`
- `meta_data`
- `ap_paramList`
- `verbose`

### 6.13.1 Detailed Description

Data fetcher for PBO GPS data.

### 6.13.2 Constructor & Destructor Documentation

#### 6.13.2.1 \_\_init\_\_()

```
def skdaccess.geo.pbo.DataFetcher.__init__ (
    self,
    start_time,
    end_time,
    ap_paramList,
    mdyratio = .5,
    default_columns = ['dN',
    dE,
    dU,
    default_error_columns = ['Sn',
    Se,
    Su,
    use_progress_bar = True,
    index_date_only = True )
```

Initialize a [DataFetcher](#).

#### Parameters

<i>start_time</i>	String of starting date in the form of "2005-01-01"
<i>end_time</i>	String of ending date in the form of "2014-12-31"
<i>ap_paramList[lat_range]</i>	AutoList, Latitude range used to select stabilization sites
<i>ap_paramList[lon_range]</i>	AutoList, Longitude range used to select stabilization sites
<i>mdyratio</i>	Only keep stations that have mdyratio of data in the specified time range
<i>default_columns</i>	Default columns to process
<i>default_error_columns</i>	Default error columns to process
<i>use_progress_bar</i>	Use a progress bar when loading data
<i>index_date_only</i>	Create a index using date only (no hour information)

### 6.13.3 Member Function Documentation

#### 6.13.3.1 `__str__()`

```
def skdaccess.geo.pbo.DataFetcher.__str__ (
    self )
```

print the parameter values

##### Returns

String representation of Data Fetcher

#### 6.13.3.2 `downloadFullDataset()`

```
def skdaccess.geo.pbo.DataFetcher.downloadFullDataset (
    cls,
    out_file = 'pbo_data.h5',
    use_file = None )
```

Download and parse data from the Plate Boundary Observatory.

##### Parameters

<i>out_file</i>	Output filename for parsed data
<i>use_file</i>	Use already downloaded data. If None, data will be downloaded.

##### Returns

Absolute path of parsed data

#### 6.13.3.3 `getAntennaLogs()`

```
def skdaccess.geo.pbo.DataFetcher.getAntennaLogs ( )
```

Get antenna logs.

##### Returns

dictionary of data frames containing antenna logs

#### 6.13.3.4 getConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

##### Returns

configParser.ConfigParser object of configuration

#### 6.13.3.5 getDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

##### Parameters

<i>data_name</i>	Name of data set
------------------	------------------

##### Returns

string of data location, None if not found

#### 6.13.3.6 getInfo()

```
def skdaccess.geo.pbo.DataFetcher.getInfo (
    self )
```

Get information about the stations and geo\_point.

##### Returns

tuple containing station list and geo\_point

#### 6.13.3.7 getMetadata()

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.13.3.8 getStationMetadata()

```
def skdaccess.geo.pbo.DataFetcher.getStationMetadata (
    data_frame = False )
```

Read in the metadata and convert to dictionary.

##### Returns

dictionary of PBO metadata

#### 6.13.3.9 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherStorage.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.13.3.10 output()

```
def skdaccess.geo.pbo.DataFetcher.output (
    self )
```

Generate PBO Data Wrapper.

##### Returns

PBO Data Wrapper

#### 6.13.3.11 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.13.3.12 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.13.3.13 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.13.3.14 setStationList()

```
def skdaccess.geo.pbo.DataFetcher.setStationList (
    self,
    station_list )
```

Set the list of stations to use.

##### Parameters

<i>station_list</i>	List of stations to fetch
---------------------	---------------------------

#### 6.13.3.15 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.13.3.16 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.13.4 Member Data Documentation

#### 6.13.4.1 antenna\_info

```
skdaccess.geo.pbo.DataFetcher.antenna_info
```

#### 6.13.4.2 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.13.4.3 default\_columns

```
skdaccess.geo.pbo.DataFetcher.default_columns
```



#### 6.13.4.4 default\_error\_columns

`skdaccess.geo.pbo.DataFetcher.default_error_columns`

#### 6.13.4.5 index\_date\_only

`skdaccess.geo.pbo.DataFetcher.index_date_only`

#### 6.13.4.6 meta\_data

`skdaccess.geo.pbo.DataFetcher.meta_data`

#### 6.13.4.7 station\_list

`skdaccess.geo.pbo.DataFetcher.station_list`

#### 6.13.4.8 use\_progress\_bar

`skdaccess.geo.pbo.DataFetcher.use_progress_bar`

#### 6.13.4.9 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [geo/pbo/data\\_fetcher.py](#)

## 6.14 skdaccess.geo.gldas.DataFetcher Class Reference

Data Fetcher for GLDAS data.

Inheritance diagram for skdaccess.geo.gldas.DataFetcher:



### Public Member Functions

- def `__init__` (self, `ap_paramList`, `start_date`=None, `end_date`=None, `resample`=False)  
*Construct a GLDAS Data Fetcher.*
- def `output` (self)  
*Create data wrapper of GLDAS data for specified geopoint.*
- def `downloadFullDataset` (cls, `out_file`=None, `use_file`=None)  
*Download GLDAS data.*
- def `__str__` (self)  
*String representation of data fetcher.*
- def `multirun_enabled` (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def `getDataLocation` (data\_name)  
*Get the location of data set.*
- def `setDataLocation` (data\_name, location, key='data\_location')  
*Set the location of a data set.*
- def `perturb` (self)  
*Perturb parameters.*
- def `reset` (self)  
*Set all parameters to initial value.*
- def `getMetadata` (self)  
*Return metadata about Data Fetcher.*
- def `getConfig` ()  
*Retrieve skdaccess configuration.*
- def `writeConfig` (conf)  
*Write config to disk.*
- def `verbose_print` (self, args, kwargs)

## Public Attributes

- [start\\_date](#)
- [end\\_date](#)
- [resample](#)
- [ap\\_paramList](#)
- [verbose](#)

### 6.14.1 Detailed Description

Data Fetcher for GLDAS data.

### 6.14.2 Constructor & Destructor Documentation

#### 6.14.2.1 `__init__()`

```
def skdaccess.geo.gldas.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date = None,
    end_date = None,
    resample = False )
```

Construct a GLDAS Data Fetcher.

#### Parameters

<i>ap_paramList</i> [ <i>geo_point</i> ]	Autolist of Geographic location tuples
<i>start_date</i>	Beginning date
<i>end_date</i>	Ending date
<i>resample</i>	Resample the data to daily resolution, leaving NaN's in days without data (Default True)

### 6.14.3 Member Function Documentation

#### 6.14.3.1 `__str__()`

```
def skdaccess.geo.gldas.DataFetcher.__str__ (
    self )
```

String representation of data fetcher.

**Returns**

String listing the name and geopoint of data fetcher

**6.14.3.2 downloadFullDataset()**

```
def skdaccess.geo.gldas.DataFetcher.downloadFullDataset (
    cls,
    out_file = None,
    use_file = None )
```

Download GLDAS data.

**Parameters**

<i>out_file</i>	Output filename for parsed data
<i>use_file</i>	Directory of downloaded data. If None, data will be downloaded.

**Returns**

Absolute path of parsed data

**6.14.3.3 getConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

**Returns**

configParser.ConfigParser object of configuration

**6.14.3.4 getDataLocation()**

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

**Parameters**

<i>data_name</i>	Name of data set
------------------	------------------

**Returns**

string of data location, None if not found

**6.14.3.5 getMetadata()**

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

**Returns**

metadata of object.

**6.14.3.6 multirun\_enabled()**

```
def skdaccess.framework.data_class.DataFetcherStorage.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

**Returns**

Boolean indicating whether or not this data fetcher is multirun enabled

**6.14.3.7 output()**

```
def skdaccess.geo.gldas.DataFetcher.output (
    self )
```

Create data wrapper of GLDAS data for specified geopoint.

**Returns**

GLDAS Data Wrapper

#### 6.14.3.8 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (  
    self ) [inherited]
```

Perturb parameters.

#### 6.14.3.9 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (  
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.14.3.10 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (  
    data_name,  
    location,  
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.14.3.11 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (  
    self,  
    args,  
    kwargs ) [inherited]
```

#### 6.14.3.12 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (  
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.14.4 Member Data Documentation

#### 6.14.4.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.14.4.2 end\_date

```
skdaccess.geo.gldas.DataFetcher.end_date
```

#### 6.14.4.3 resample

```
skdaccess.geo.gldas.DataFetcher.resample
```

#### 6.14.4.4 start\_date

```
skdaccess.geo.gldas.DataFetcher.start_date
```

#### 6.14.4.5 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [geo/gldas/data\\_fetcher.py](#)

## 6.15 skdaccess.geo.grace.DataFetcher Class Reference

Data Fetcher for GRACE data.

Inheritance diagram for `skdaccess.geo.grace.DataFetcher`:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date=None, end_date=None)`  
*Construct a Grace Data Fetcher.*
- `def output(self)`  
*Create data wrapper of grace data for specified geopoints.*
- `def __str__(self)`  
*String representation of data fetcher.*
- `def downloadFullDataset(cls, out_file='grace.h5', use_file=None)`  
*Download and parse data from the Gravity Recovery and Climate Experiment.*
- `def multirun_enabled(self)`  
*Returns whether or not this data fetcher is multirun enabled.*
- `def getDataLocation(data_name)`  
*Get the location of data set.*
- `def setDataLocation(data_name, location, key='data_location')`  
*Set the location of a data set.*
- `def perturb(self)`  
*Perturb parameters.*
- `def reset(self)`



- *Set all parameters to initial value.*
- def [getMetadata](#) (self)  
*Return metadata about Data Fetcher.*
- def [getConfig](#) ()  
*Retrieve skdaccess configuration.*
- def [writeConfig](#) (conf)  
*Write config to disk.*
- def [verbose\\_print](#) (self, args, kwargs)

## Public Attributes

- [start\\_date](#)
- [end\\_date](#)
- [ap\\_paramList](#)
- [verbose](#)

### 6.15.1 Detailed Description

Data Fetcher for GRACE data.

### 6.15.2 Constructor & Destructor Documentation

#### 6.15.2.1 `__init__()`

```
def skdaccess.geo.grace.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date = None,
    end_date = None )
```

Construct a Grace Data Fetcher.

#### Parameters

<i>ap_paramList[geo_point]</i>	AutoList of geographic location tuples (lat,lon)
<i>start_date</i>	Beginning date
<i>end_date</i>	Ending date

### 6.15.3 Member Function Documentation

**6.15.3.1 \_\_str\_\_()**

```
def skdaccess.geo.grace.DataFetcher.__str__ (
    self )
```

String representation of data fetcher.

**Returns**

String listing the name and geopoint of data fetcher

**6.15.3.2 downloadFullDataset()**

```
def skdaccess.geo.grace.DataFetcher.downloadFullDataset (
    cls,
    out_file = 'grace.h5',
    use_file = None )
```

Download and parse data from the Gravity Recovery and Climate Experiment.

**Parameters**

<i>out_file</i>	Output filename for parsed data
<i>use_file</i>	Directory of already downloaded data. If None, data will be downloaded.

**Returns**

Absolute path of parsed data

**6.15.3.3 getConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

**Returns**

configParser.ConfigParser object of configuration

**6.15.3.4 getDataLocation()**

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

**Parameters**

<i>data_name</i>	Name of data set
------------------	------------------

**Returns**

string of data location, None if not found

**6.15.3.5 getMetadata()**

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

**Returns**

metadata of object.

**6.15.3.6 multirun\_enabled()**

```
def skdaccess.framework.data_class.DataFetcherStorage.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

**Returns**

Boolean indicating whether or not this data fetcher is multirun enabled

**6.15.3.7 output()**

```
def skdaccess.geo.grace.DataFetcher.output (
    self )
```

Create data wrapper of grace data for specified geopoints.

**Returns**

Grace Data Wrapper

#### 6.15.3.8 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.15.3.9 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.15.3.10 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.15.3.11 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.15.3.12 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (  
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.15.4 Member Data Documentation

#### 6.15.4.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.15.4.2 end\_date

```
skdaccess.geo.grace.DataFetcher.end_date
```

#### 6.15.4.3 start\_date

```
skdaccess.geo.grace.DataFetcher.start_date
```

#### 6.15.4.4 verbose

```
skdaccess.framework.data_class.DataFetcherBase.verbose [inherited]
```


The documentation for this class was generated from the following file:

- [geo/grace/data\\_fetcher.py](#)

## 6.16 skdaccess.geo.modis.stream.cloud\_mask.DataFetcher Class Reference

Data Fetcher for MODIS Cloud Mask.

Inheritance diagram for skdaccess.geo.modis.stream.cloud\_mask.DataFetcher:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date, end_date, modis_platform='Terra', daynightboth='D', grid=None)`  
*Construct Data Fetcher for MODIS cloud mask data.*

### 6.16.1 Detailed Description

Data Fetcher for MODIS Cloud Mask.

### 6.16.2 Constructor & Destructor Documentation

#### 6.16.2.1 \_\_init\_\_()

```

def skdaccess.geo.modis.stream.cloud_mask.DataFetcher.__init__(
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None )
  
```

Construct Data Fetcher for MODIS cloud mask data.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)


The documentation for this class was generated from the following file:

- [geo/modis/stream/cloud\\_mask/data\\_fetcher.py](#)

## 6.17 skdaccess.geo.groundwater.DataFetcher Class Reference

Generates Data Wrappers of groundwater measurements taken in the US.

Inheritance diagram for skdaccess.geo.groundwater.DataFetcher:



### Public Member Functions

- `def __init__(self, ap_paramList=[], start_date=None, end_date=None, cutoff=0.75)`  
*Construct a Groundwater Data Fetcher.*
- `def output(self)`  
*Fetch Groundwater Data Wrapper.*
- `def __str__(self)`  
*String representation of data fetcher.*
- `def getStationMetadata()`  
*Retrieve metadata on groundwater wells.*
- `def downloadFullDataset(cls, out_file='gw.h5', use_file=None)`  
*Download and parse US groundwater data provided by USGS.*
- `def multirun_enabled(self)`  
*Returns whether or not this data fetcher is multirun enabled.*
- `def getDataLocation(data_name)`  
*Get the location of data set.*
- `def setDataLocation(data_name, location, key='data_location')`  
*Set the location of a data set.*
- `def perturb(self)`  
*Perturb parameters.*
- `def reset(self)`  
*Set all parameters to initial value.*
- `def getMetadata(self)`

*Return metadata about Data Fetcher.*

- def [getConfig](#) ()  
*Retrieve skdaccess configuration.*
- def [writeConfig](#) (conf)  
*Write config to disk.*
- def [verbose\\_print](#) (self, args, kwargs)

## Public Attributes

- [start\\_date](#)
- [end\\_date](#)
- [ap\\_paramList](#)
- [cutoff](#)
- [verbose](#)

## 6.17.1 Detailed Description

Generates Data Wrappers of groundwater measurements taken in the US.

## 6.17.2 Constructor & Destructor Documentation

### 6.17.2.1 `__init__()`

```
def skdaccess.geo.groundwater.DataFetcher.__init__ (
    self,
    ap_paramList = [],
    start_date = None,
    end_date = None,
    cutoff = 0.75 )
```

Construct a Groundwater Data Fetcher.

#### Parameters

<i>ap_paramList[LowerLat]</i>	Autoparam Lower latitude
<i>ap_paramList[UpperLat]</i>	Autoparam Upper latitude
<i>ap_paramList[LeftLon]</i>	Autoparam Left longitude
<i>ap_paramList[RightLon]</i>	Autoparam Right longitude
<i>start_date</i>	Starting date (default: None)
<i>end_date</i>	Ending date (default: None)
<i>cutoff</i>	Required amount of data for each station



### 6.17.3 Member Function Documentation

#### 6.17.3.1 `__str__()`

```
def skdaccess.geo.groundwater.DataFetcher.__str__ (
    self )
```

String representation of data fetcher.

##### Returns

string describing data fetcher

#### 6.17.3.2 `downloadFullDataset()`

```
def skdaccess.geo.groundwater.DataFetcher.downloadFullDataset (
    cls,
    out_file = 'gw.h5',
    use_file = None )
```

Download and parse US groundwater data provided by USGS.

##### Parameters

<i>out_file</i>	Output filename for parsed data
<i>use_file</i>	Specify the directory where the data is. If None, the function will download the data

##### Returns

Absolute path of parsed data

#### 6.17.3.3 `getConfig()`

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

##### Returns

configParser.ConfigParser object of configuration

#### 6.17.3.4 `getDataLocation()`

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

##### Parameters

<i>data_name</i>	Name of data set
------------------	------------------

##### Returns

string of data location, None if not found

#### 6.17.3.5 `getMetadata()`

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.17.3.6 `getStationMetadata()`

```
def skdaccess.geo.groundwater.DataFetcher.getStationMetadata ( )
```

Retrieve metadata on groundwater wells.

##### Returns

pandas dataframe with groundwater well information

### 6.17.3.7 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherStorage.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

#### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

### 6.17.3.8 output()

```
def skdaccess.geo.groundwater.DataFetcher.output (
    self )
```

Fetch Groundwater Data Wrapper.

#### Returns

Groundwater Data Wrapper

### 6.17.3.9 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

### 6.17.3.10 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

### 6.17.3.11 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

**Parameters**

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

**6.17.3.12 verbose\_print()**

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

**6.17.3.13 writeConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

**Parameters**

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

**6.17.4 Member Data Documentation****6.17.4.1 ap\_paramList**

```
skdaccess.geo.groundwater.DataFetcher.ap_paramList
```

**6.17.4.2 cutoff**

```
skdaccess.geo.groundwater.DataFetcher.cutoff
```

## 6.17.4.3 end\_date

```
skdaccess.geo.groundwater.DataFetcher.end_date
```

## 6.17.4.4 start\_date

```
skdaccess.geo.groundwater.DataFetcher.start_date
```

## 6.17.4.5 verbose

```
skdaccess.framework.data_class.DataFetcherBase.verbose [inherited]
```


The documentation for this class was generated from the following file:

- [geo/groundwater/data\\_fetcher.py](#)

## 6.18 skdaccess.geo.modis.cache.cloud\_mask.DataFetcher Class Reference

Data Fetcher for MODIS Cloud Mask.

Inheritance diagram for skdaccess.geo.modis.cache.cloud\_mask.DataFetcher:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date, end_date, modis_platform='Terra', daynightboth='D', grid=None)`  
*Construct Data Fetcher for MODIS cloud mask data.*

### 6.18.1 Detailed Description

Data Fetcher for MODIS Cloud Mask.

## 6.18.2 Constructor & Destructor Documentation

### 6.18.2.1 `__init__()`

```
def skdaccess.geo.modis.cache.cloud_mask.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None )
```

Construct Data Fetcher for MODIS cloud mask data.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)


The documentation for this class was generated from the following file:

- [geo/modis/cache/cloud\\_mask/data\\_fetcher.py](#)

## 6.19 `skdaccess.geo.modis.cache.cloud_opacity.DataFetcher` Class Reference

Data Fetcher for MODIS Cloud Opacity.

Inheritance diagram for `skdaccess.geo.modis.cache.cloud_opacity.DataFetcher`:



## Public Member Functions

- def `__init__` (self, ap\_paramList, start\_date, end\_date, modis\_platform='Terra', daynightboth='D', grid=None)  
*Construct Data Fetcher object for MODIS cloud Opacity data.*

### 6.19.1 Detailed Description

Data Fetcher for MODIS Cloud Opacity.

### 6.19.2 Constructor & Destructor Documentation

#### 6.19.2.1 `__init__`()

```
def skdaccess.geo.modis.cache.cloud_opacity.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None )
```

Construct Data Fetcher object for MODIS cloud Opacity data.

#### Parameters

<code>ap_paramList[lat]</code>	Search latitude
<code>ap_paramList[lon]</code>	Search longitude
<code>start_date</code>	Starting date
<code>end_date</code>	Ending date
<code>modis_platform</code>	Platform (Either "Terra" or "Aqua")
<code>daynightboth</code>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<code>grid</code>	Further divide each image into a multiple grids of size (y,x)


The documentation for this class was generated from the following file:

- [geo/modis/cache/cloud\\_opacity/data\\_fetcher.py](#)

## 6.20 skdaccess.geo.modis.stream.DataFetcher Class Reference

Data Fetcher for MODIS data.

Inheritance diagram for `skdaccess.geo.modis.stream.DataFetcher`:



### Public Member Functions

- `def __init__ (self, ap_paramList, modis_platform, modis_id, variable_list, start_date, end_date, daynightboth='D', grid=None, grid_fill=np.nan, use_long_name=False)`  
Construct Data Fetcher object.
- `def output (self)`  
Generate data wrapper.
- `def retrieveOnlineData (self, data_specification)`  
Method for downloading data into memory.
- `def multirun_enabled (self)`  
Returns whether or not this data fetcher is multirun enabled.
- `def perturb (self)`  
Perturb parameters.
- `def reset (self)`  
Set all parameters to initial value.
- `def __str__ (self)`  
Generate string description.
- `def getMetadata (self)`  
Return metadata about Data Fetcher.
- `def getConfig ()`  
Retrieve skdaccess configuration.
- `def writeConfig (conf)`  
Write config to disk.
- `def verbose_print (self, args, kwargs)`

### Public Attributes

- `modis_id`
- `variable_list`
- `start_date`
- `end_date`
- `daynightboth`
- `grid`
- `grid_fill`
- `use_long_name`
- `modis_platform`
- `modis_identifier`
- `ap_paramList`
- `verbose`



### 6.20.1 Detailed Description

Data Fetcher for MODIS data.

### 6.20.2 Constructor & Destructor Documentation

#### 6.20.2.1 `__init__()`

```
def skdaccess.geo.modis.stream.DataFetcher.__init__ (
    self,
    ap_paramList,
    modis_platform,
    modis_id,
    variable_list,
    start_date,
    end_date,
    daynightboth = 'D',
    grid = None,
    grid_fill = np.nan,
    use_long_name = False )
```

Construct Data Fetcher object.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>modis_id</i>	Product string (e.g. '06_L2')
<i>variable_list</i>	List of variables to fetch
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)
<i>grid_fill</i>	Fill value to use when creating gridded data
<i>use_long_name</i>	Use long names for metadata instead of variable name

### 6.20.3 Member Function Documentation

#### 6.20.3.1 `__str__()`

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

#### 6.20.3.2 `getConfig()`

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

##### Returns

configParser.ConfigParser object of configuration

#### 6.20.3.3 `getMetadata()`

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.20.3.4 `multirun_enabled()`

```
def skdaccess.framework.data_class.DataFetcherStream.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

### 6.20.3.5 output()

```
def skdaccess.geo.modis.stream.DataFetcher.output (
    self )
```

Generate data wrapper.

#### Returns

data wrapper of MODIS data

### 6.20.3.6 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

### 6.20.3.7 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

### 6.20.3.8 retrieveOnlineData()

```
def skdaccess.framework.data_class.DataFetcherStream.retrieveOnlineData (
    self,
    data_specification ) [inherited]
```

Method for downloading data into memory.

#### Parameters

<i>data_specification</i>	Url list of data to be retrieved
---------------------------	----------------------------------

**Returns**

Retrieved data

**6.20.3.9 verbose\_print()**

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

**6.20.3.10 writeConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

**Parameters**

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

**6.20.4 Member Data Documentation****6.20.4.1 ap\_paramList**

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

**6.20.4.2 daynightboth**

```
skdaccess.geo.modis.stream.DataFetcher.daynightboth
```

#### 6.20.4.3 end\_date

skdaccess.geo.modis.stream.DataFetcher.end\_date

#### 6.20.4.4 grid

skdaccess.geo.modis.stream.DataFetcher.grid

#### 6.20.4.5 grid\_fill

skdaccess.geo.modis.stream.DataFetcher.grid\_fill

#### 6.20.4.6 modis\_id

skdaccess.geo.modis.stream.DataFetcher.modis\_id

#### 6.20.4.7 modis\_identifier

skdaccess.geo.modis.stream.DataFetcher.modis\_identifier

#### 6.20.4.8 modis\_platform

skdaccess.geo.modis.stream.DataFetcher.modis\_platform

#### 6.20.4.9 start\_date

skdaccess.geo.modis.stream.DataFetcher.start\_date

#### 6.20.4.10 use\_long\_name

`skdaccess.geo.modis.stream.DataFetcher.use_long_name`

#### 6.20.4.11 variable\_list

`skdaccess.geo.modis.stream.DataFetcher.variable_list`

#### 6.20.4.12 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [geo/modis/stream/data\\_fetcher.py](#)

## 6.21 skdaccess.geo.modis.cache.reflectance.DataFetcher Class Reference

Data fetcher for the modis surface reflectance product ('09', 1 km resolution)

Inheritance diagram for `skdaccess.geo.modis.cache.reflectance.DataFetcher`:



### Public Member Functions

- `def __init__(self, ap_paramList, start_date, end_date, modis_platform='Terra', daynightboth='D', grid=None, bands=[1])`  
*Construct Data Fetcher for MODIS 1km surface reflectance.*

#### 6.21.1 Detailed Description

Data fetcher for the modis surface reflectance product ('09', 1 km resolution)

### 6.21.2 Constructor & Destructor Documentation

#### 6.21.2.1 \_\_init\_\_()

```
def skdaccess.geo.modis.cache.reflectance.DataFetcher.__init__ (
    self,
    ap_paramList,
    start_date,
    end_date,
    modis_platform = 'Terra',
    daynightboth = 'D',
    grid = None,
    bands = [1 ]
```

Construct Data Fetcher for MODIS 1km surface reflectance.

#### Parameters

<i>ap_paramList[lat]</i>	Search latitude
<i>ap_paramList[lon]</i>	Search longitude
<i>start_date</i>	Starting date
<i>end_date</i>	Ending date
<i>modis_platform</i>	Platform (Either "Terra" or "Aqua")
<i>daynightboth</i>	Use daytime data ('D'), nighttime data ('N') or both ('B')
<i>grid</i>	Further divide each image into a multiple grids of size (y,x)
<i>bands</i>	List of modis bands to retrieve


The documentation for this class was generated from the following file:

- [geo/modis/cache/reflectance/data\\_fetcher.py](#)

## 6.22 skdaccess.astro.kepler.DataFetcher Class Reference

Data Fetcher for Kepler light curve data.

Inheritance diagram for skdaccess.astro.kepler.DataFetcher:



## Public Member Functions

- def `__init__` (self, ap\_paramList, quarter\_list=None)  
Initialize Kepler Data Fetcher.
- def `downloadKeplerData` (self, kid\_list)  
Download and parse Kepler data for a list of kepler id's.
- def `cacheData` (self, data\_specification)  
Cache Kepler data locally.
- def `output` (self)  
Output kepler data wrapper.
- def `cacheData` (self, keyname, online\_path\_list, username=None, password=None, authentication\_url=None, cookiejar=None, use\_requests=False, use\_progress\_bar=True)  
Download and store specified data to local disk.
- def `multirun_enabled` (self)  
Returns whether or not this data fetcher is multirun enabled.
- def `getHDFSStorage` (self, keyname)
- def `getDataLocation` (data\_name)  
Get the location of data set.
- def `setDataLocation` (data\_name, location, key='data\_location')  
Set the location of a data set.
- def `perturb` (self)  
Perturb parameters.
- def `reset` (self)  
Set all parameters to initial value.
- def `__str__` (self)  
Generate string description.
- def `getMetadata` (self)  
Return metadata about Data Fetcher.
- def `getConfig` ()  
Retrieve skdaccess configuration.
- def `writeConfig` (conf)  
Write config to disk.
- def `verbose_print` (self, args, kwargs)



## Public Attributes

- [quarter\\_list](#)
- [ap\\_paramList](#)
- [verbose](#)

### 6.22.1 Detailed Description

Data Fetcher for Kepler light curve data.

### 6.22.2 Constructor & Destructor Documentation

#### 6.22.2.1 \_\_init\_\_()

```
def skdaccess.astro.kepler.DataFetcher.__init__ (
    self,
    ap_paramList,
    quarter_list = None )
```

Initialize Kepler Data Fetcher.

#### Parameters

<i>ap_paramList[kepler_id_list]</i>	List of kepler id's
<i>quarter_list</i>	List of quarters (0-17) (default: all quarters)

### 6.22.3 Member Function Documentation

#### 6.22.3.1 \_\_str\_\_()

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

### 6.22.3.2 cacheData() [1/2]

```
def skdaccess.astro.kepler.DataFetcher.cacheData (
    self,
    data_specification )
```

Cache Kepler data locally.

#### Parameters

<i>data_specification</i>	List of kepler IDs
---------------------------	--------------------

### 6.22.3.3 cacheData() [2/2]

```
def skdaccess.framework.data_class.DataFetcherCache.cacheData (
    self,
    keyname,
    online_path_list,
    username = None,
    password = None,
    authentication_url = None,
    cookiejar = None,
    use_requests = False,
    use_progress_bar = True ) [inherited]
```

Download and store specified data to local disk.

#### Parameters

<i>data_specification</i>	Specification of data to be retrieved
---------------------------	---------------------------------------

#### Returns

List of downloaded file locations

### 6.22.3.4 downloadKeplerData()

```
def skdaccess.astro.kepler.DataFetcher.downloadKeplerData (
    self,
    kid_list )
```

Download and parse Kepler data for a list of kepler id's.

**Parameters**

<i>kid_list</i>	List of Kepler ID's to download
-----------------	---------------------------------

**Returns**

dictionary of kepler data

**6.22.3.5 getConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

**Returns**

configParser.ConfigParser object of configuration

**6.22.3.6 getDataLocation()**

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

**Parameters**

<i>data_name</i>	Name of data set
------------------	------------------

**Returns**

string of data location, None if not found

**6.22.3.7 getHDFStorage()**

```
def skdaccess.framework.data_class.DataFetcherCache.getHDFStorage (
    self,
    keyname ) [inherited]
```

#### 6.22.3.8 getMetadata()

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.22.3.9 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherCache.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.22.3.10 output()

```
def skdaccess.astro.kepler.DataFetcher.output (
    self )
```

Output kepler data wrapper.

##### Returns

DataWrapper

#### 6.22.3.11 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

### 6.22.3.12 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

### 6.22.3.13 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

#### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

### 6.22.3.14 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

### 6.22.3.15 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

#### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

## 6.22.4 Member Data Documentation

### 6.22.4.1 `ap_paramList`

`skdaccess.framework.data_class.DataFetcherBase.ap_paramList` [inherited]

### 6.22.4.2 `quarter_list`

`skdaccess.astro.kepler.DataFetcher.quarter_list`

### 6.22.4.3 `verbose`

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [astro/kepler/data\\_fetcher.py](#)

## 6.23 `skdaccess.framework.data_class.DataFetcherBase` Class Reference

Base class for all data fetchers.

Inheritance diagram for `skdaccess.framework.data_class.DataFetcherBase`:



## Public Member Functions

- def `__init__` (self, `ap_paramList`=[], `verbose`=False)  
*Initialize data fetcher with parameter list.*
- def `output` (self)  
*Output data wrapper.*
- def `perturb` (self)  
*Perturb parameters.*
- def `reset` (self)  
*Set all parameters to initial value.*
- def `__str__` (self)  
*Generate string description.*
- def `getMetadata` (self)  
*Return metadata about Data Fetcher.*
- def `getConfig` ()  
*Retrieve skdaccess configuration.*
- def `writeConfig` (conf)  
*Write config to disk.*
- def `multirun_enabled` (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def `verbose_print` (self, args, kwargs)

## Public Attributes

- `ap_paramList`
- `verbose`

### 6.23.1 Detailed Description

Base class for all data fetchers.

### 6.23.2 Constructor & Destructor Documentation

#### 6.23.2.1 `__init__`()

```
def skdaccess.framework.data_class.DataFetcherBase.__init__ (
    self,
    ap_paramList = [],
    verbose = False )
```

Initialize data fetcher with parameter list.

**Parameters**

<i>ap_paramList</i>	List of parameters
---------------------	--------------------

**6.23.3 Member Function Documentation****6.23.3.1 \_\_str\_\_()**

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self )
```

Generate string description.

**6.23.3.2 getConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( )
```

Retrieve skdaccess configuration.

**Returns**

configParser.ConfigParser object of configuration

**6.23.3.3 getMetadata()**

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self )
```

Return metadata about Data Fetcher.

**Returns**

metadata of object.



#### 6.23.3.4 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherBase.multirun_enabled (
    self )
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.23.3.5 output()

```
def skdaccess.framework.data_class.DataFetcherBase.output (
    self )
```

Output data wrapper.

##### Returns

Datawrapper

#### 6.23.3.6 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self )
```

Perturb parameters.

#### 6.23.3.7 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self )
```

Set all parameters to initial value.

#### 6.23.3.8 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs )
```

#### 6.23.3.9 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf )
```

Write config to disk.

## Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.23.4 Member Data Documentation

#### 6.23.4.1 ap\_paramList

`skdaccess.framework.data_class.DataFetcherBase.ap_paramList`

#### 6.23.4.2 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose`


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.24 skdaccess.framework.data\_class.DataFetcherCache Class Reference

Data fetcher base class for downloading data and caching results on hard disk.

Inheritance diagram for `skdaccess.framework.data_class.DataFetcherCache`:



## Public Member Functions

- def [cacheData](#) (self, keyname, online\_path\_list, username=None, password=None, authentication\_url=None, cookiejar=None, use\_requests=False, use\_progress\_bar=True)  
*Download and store specified data to local disk.*
- def [multirun\\_enabled](#) (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def [getHDFSStorage](#) (self, keyname)
- def [getDataLocation](#) (data\_name)  
*Get the location of data set.*
- def [setDataLocation](#) (data\_name, location, key='data\_location')  
*Set the location of a data set.*
- def [output](#) (self)  
*Output data wrapper.*
- def [perturb](#) (self)  
*Perturb parameters.*
- def [reset](#) (self)  
*Set all parameters to initial value.*
- def [\\_\\_str\\_\\_](#) (self)  
*Generate string description.*
- def [getMetadata](#) (self)  
*Return metadata about Data Fetcher.*
- def [getConfig](#) ()  
*Retrieve skdaccess configuration.*
- def [writeConfig](#) (conf)  
*Write config to disk.*
- def [verbose\\_print](#) (self, args, kwargs)

## Public Attributes

- [ap\\_paramList](#)
- [verbose](#)

### 6.24.1 Detailed Description

Data fetcher base class for downloading data and caching results on hard disk.

### 6.24.2 Member Function Documentation

#### 6.24.2.1 `__str__()`

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

#### 6.24.2.2 `cacheData()`

```
def skdaccess.framework.data_class.DataFetcherCache.cacheData (
    self,
    keyname,
    online_path_list,
    username = None,
    password = None,
    authentication_url = None,
    cookiejar = None,
    use_requests = False,
    use_progress_bar = True )
```

Download and store specified data to local disk.

##### Parameters

<i>data_specification</i>	Specification of data to be retrieved
---------------------------	---------------------------------------

##### Returns

List of downloaded file locations

#### 6.24.2.3 `getConfig()`

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

##### Returns

configParser.ConfigParser object of configuration

#### 6.24.2.4 `getDataLocation()`

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

**Parameters**

<i>data_name</i>	Name of data set
------------------	------------------

**Returns**

string of data location, None if not found

**6.24.2.5 getHDFSStorage()**

```
def skdaccess.framework.data_class.DataFetcherCache.getHDFSStorage (
    self,
    keyname )
```

**6.24.2.6 getMetadata()**

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

**Returns**

metadata of object.

**6.24.2.7 multirun\_enabled()**

```
def skdaccess.framework.data_class.DataFetcherCache.multirun_enabled (
    self )
```

Returns whether or not this data fetcher is multirun enabled.

**Returns**

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.24.2.8 output()

```
def skdaccess.framework.data_class.DataFetcherBase.output (
    self ) [inherited]
```

Output data wrapper.

##### Returns

Datawrapper

#### 6.24.2.9 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.24.2.10 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.24.2.11 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.24.2.12 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.24.2.13 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.24.3 Member Data Documentation

#### 6.24.3.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.24.3.2 verbose

```
skdaccess.framework.data_class.DataFetcherBase.verbose [inherited]
```

The documentation for this class was generated from the following file:


- framework/[data\\_class.py](#)



## 6.25 skdaccess.framework.data\_class.DataFetcherLocal Class Reference

Data fetcher base class for use when storing data locally.

Inheritance diagram for skdaccess.framework.data\_class.DataFetcherLocal:



### Public Member Functions

- def [getDataLocation](#) (data\_name)  
*Get the location of data set.*
- def [setDataLocation](#) (data\_name, location, key='data\_location')  
*Set the location of a data set.*
- def [output](#) (self)  
*Output data wrapper.*
- def [perturb](#) (self)  
*Perturb parameters.*
- def [reset](#) (self)  
*Set all parameters to initial value.*
- def [\\_\\_str\\_\\_](#) (self)  
*Generate string description.*
- def [getMetadata](#) (self)  
*Return metadata about Data Fetcher.*
- def [getConfig](#) ()  
*Retrieve skdaccess configuration.*
- def [writeConfig](#) (conf)  
*Write config to disk.*
- def [multirun\\_enabled](#) (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def [verbose\\_print](#) (self, args, kwargs)

### Public Attributes

- [ap\\_paramList](#)
- [verbose](#)

#### 6.25.1 Detailed Description

Data fetcher base class for use when storing data locally.

## 6.25.2 Member Function Documentation

### 6.25.2.1 \_\_str\_\_()

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

### 6.25.2.2 getConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

#### Returns

configParser.ConfigParser object of configuration

### 6.25.2.3 getDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name )
```

Get the location of data set.

#### Parameters

<i>data_name</i>	Name of data set
------------------	------------------

#### Returns

string of data location, None if not found

#### 6.25.2.4 getMetadata()

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

##### Returns

metadata of object.

#### 6.25.2.5 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherBase.multirun_enabled (
    self ) [inherited]
```

Returns whether or not this data fetcher is multirun enabled.

##### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.25.2.6 output()

```
def skdaccess.framework.data_class.DataFetcherBase.output (
    self ) [inherited]
```

Output data wrapper.

##### Returns

Datawrapper

#### 6.25.2.7 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.25.2.8 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.25.2.9 setDataLocation()

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' )
```

Set the location of a data set.

##### Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

#### 6.25.2.10 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.25.2.11 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

##### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

### 6.25.3 Member Data Documentation

#### 6.25.3.1 ap\_paramList

`skdaccess.framework.data_class.DataFetcherBase.ap_paramList` [inherited]

#### 6.25.3.2 verbose

`skdaccess.framework.data_class.DataFetcherBase.verbose` [inherited]


The documentation for this class was generated from the following file:

- [framework/data\\_class.py](#)

## 6.26 skdaccess.framework.data\_class.DataFetcherStorage Class Reference

Data fetcher base class for use when entire data set is downloaded.

Inheritance diagram for `skdaccess.framework.data_class.DataFetcherStorage`:



### Public Member Functions

- def [downloadFullDataset](#) (cls, out\_file, use\_file=None)  
*Abstract function used to download full data set.*
- def [multirun\\_enabled](#) (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def [getDataLocation](#) (data\_name)  
*Get the location of data set.*
- def [setDataLocation](#) (data\_name, location, key='data\_location')  
*Set the location of a data set.*
- def [output](#) (self)  
*Output data wrapper.*
- def [perturb](#) (self)

- Perturb parameters.*
  - def `reset` (self)
  - Set all parameters to initial value.*
- def `__str__` (self)
  - Generate string description.*
- def `getMetadata` (self)
  - Return metadata about Data Fetcher.*
- def `getConfig` ()
  - Retrieve skdaccess configuration.*
- def `writeConfig` (conf)
  - Write config to disk.*
- def `verbose_print` (self, args, kwargs)

## Public Attributes

- `ap_paramList`
- `verbose`

### 6.26.1 Detailed Description

Data fetcher base class for use when entire data set is downloaded.

### 6.26.2 Member Function Documentation

#### 6.26.2.1 `__str__()`

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

#### 6.26.2.2 `downloadFullDataset()`

```
def skdaccess.framework.data_class.DataFetcherStorage.downloadFullDataset (
    cls,
    out_file,
    use_file = None )
```

Abstract function used to download full data set.

**Parameters**

<i>out_file</i>	output file name
<i>use_file</i>	Use previously downloaded data

**Returns**

Absolute path of parsed data

**6.26.2.3 getConfig()**

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

**Returns**

configParser.ConfigParser object of configuration

**6.26.2.4 getDataLocation()**

```
def skdaccess.framework.data_class.DataFetcherLocal.getDataLocation (
    data_name ) [inherited]
```

Get the location of data set.

**Parameters**

<i>data_name</i>	Name of data set
------------------	------------------

**Returns**

string of data location, None if not found

**6.26.2.5 getMetadata()**

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

**Returns**

metadata of object.

**6.26.2.6 multirun\_enabled()**

```
def skdaccess.framework.data_class.DataFetcherStorage.multirun_enabled (
    self )
```

Returns whether or not this data fetcher is multirun enabled.

**Returns**

Boolean indicating whether or not this data fetcher is multirun enabled

**6.26.2.7 output()**

```
def skdaccess.framework.data_class.DataFetcherBase.output (
    self ) [inherited]
```

Output data wrapper.

**Returns**

Datawrapper

**6.26.2.8 perturb()**

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

**6.26.2.9 reset()**

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

**6.26.2.10 setDataLocation()**

```
def skdaccess.framework.data_class.DataFetcherLocal.setDataLocation (
    data_name,
    location,
    key = 'data_location' ) [inherited]
```

Set the location of a data set.



## Parameters

<i>data_name</i>	Name of data set
<i>location</i>	Location of data set
<i>key</i>	Key of configuration option

## 6.26.2.11 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

## 6.26.2.12 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

## Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

## 6.26.3 Member Data Documentation

## 6.26.3.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

## 6.26.3.2 verbose

```
skdaccess.framework.data_class.DataFetcherBase.verbose [inherited]
```


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.27 skdaccess.framework.data\_class.DataFetcherStream Class Reference

Data fetcher base class for downloading data into memory.

Inheritance diagram for skdaccess.framework.data\_class.DataFetcherStream:



### Public Member Functions

- def [retrieveOnlineData](#) (self, data\_specification)  
*Method for downloading data into memory.*
- def [multirun\\_enabled](#) (self)  
*Returns whether or not this data fetcher is multirun enabled.*
- def [output](#) (self)  
*Output data wrapper.*
- def [perturb](#) (self)  
*Perturb parameters.*
- def [reset](#) (self)  
*Set all parameters to initial value.*
- def [\\_\\_str\\_\\_](#) (self)  
*Generate string description.*
- def [getMetadata](#) (self)  
*Return metadata about Data Fetcher.*
- def [getConfig](#) ()  
*Retrieve skdaccess configuration.*
- def [writeConfig](#) (conf)  
*Write config to disk.*
- def [verbose\\_print](#) (self, args, kwargs)

### Public Attributes

- [ap\\_paramList](#)
- [verbose](#)

#### 6.27.1 Detailed Description

Data fetcher base class for downloading data into memory.

## 6.27.2 Member Function Documentation

### 6.27.2.1 \_\_str\_\_()

```
def skdaccess.framework.data_class.DataFetcherBase.__str__ (
    self ) [inherited]
```

Generate string description.

### 6.27.2.2 getConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.getConfig ( ) [inherited]
```

Retrieve skdaccess configuration.

#### Returns

configParser.ConfigParser object of configuration

### 6.27.2.3 getMetadata()

```
def skdaccess.framework.data_class.DataFetcherBase.getMetadata (
    self ) [inherited]
```

Return metadata about Data Fetcher.

#### Returns

metadata of object.

### 6.27.2.4 multirun\_enabled()

```
def skdaccess.framework.data_class.DataFetcherStream.multirun_enabled (
    self )
```

Returns whether or not this data fetcher is multirun enabled.

#### Returns

Boolean indicating whether or not this data fetcher is multirun enabled

#### 6.27.2.5 output()

```
def skdaccess.framework.data_class.DataFetcherBase.output (
    self ) [inherited]
```

Output data wrapper.

##### Returns

Datawrapper

#### 6.27.2.6 perturb()

```
def skdaccess.framework.data_class.DataFetcherBase.perturb (
    self ) [inherited]
```

Perturb parameters.

#### 6.27.2.7 reset()

```
def skdaccess.framework.data_class.DataFetcherBase.reset (
    self ) [inherited]
```

Set all parameters to initial value.

#### 6.27.2.8 retrieveOnlineData()

```
def skdaccess.framework.data_class.DataFetcherStream.retrieveOnlineData (
    self,
    data_specification )
```

Method for downloading data into memory.

##### Parameters

<i>data_specification</i>	Url list of data to be retrieved
---------------------------	----------------------------------

### Returns

Retrieved data

#### 6.27.2.9 verbose\_print()

```
def skdaccess.framework.data_class.DataFetcherBase.verbose_print (
    self,
    args,
    kwargs ) [inherited]
```

#### 6.27.2.10 writeConfig()

```
def skdaccess.framework.data_class.DataFetcherBase.writeConfig (
    conf ) [inherited]
```

Write config to disk.

### Parameters

<i>conf</i>	configparser.ConfigParser object
-------------	----------------------------------

## 6.27.3 Member Data Documentation

#### 6.27.3.1 ap\_paramList

```
skdaccess.framework.data_class.DataFetcherBase.ap_paramList [inherited]
```

#### 6.27.3.2 verbose

```
skdaccess.framework.data_class.DataFetcherBase.verbose [inherited]
```


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.28 skdaccess.framework.data\_class.DataWrapperBase Class Reference

Base class for wrapping data for use in DiscoveryPipeline.

Inheritance diagram for skdaccess.framework.data\_class.DataWrapperBase:



### Public Member Functions

- `def __init__ (self, obj_wrap, run_id=-1, meta_data=None)`  
Construct wrapper from input data.
- `def update (self, obj)`  
Updated wrapped data.
- `def get (self)`  
Retrieve stored data.
- `def getResults (self)`  
Retrieve accumulated results, if any.
- `def addResult (self, rkey, rres)`  
Add a result to the data wrapper.
- `def reset (self)`  
Reset data back to original state.
- `def info (self, key=None)`  
Get information about data wrapper.
- `def getIterator (self)`  
Get an iterator to the data.
- `def __len__ (self)`  
Get length of wrapped data.

### Public Attributes

- `data`
- `results`
- `constants`
- `run_id`
- `meta_data`

### 6.28.1 Detailed Description

Base class for wrapping data for use in DiscoveryPipeline.

## 6.28.2 Constructor & Destructor Documentation

### 6.28.2.1 \_\_init\_\_()

```
def skdaccess.framework.data_class.DataWrapperBase.__init__ (
    self,
    obj_wrap,
    run_id = -1,
    meta_data = None )
```

Construct wrapper from input data.

#### Parameters

<i>obj_wrap</i>	Data to be wrapped
<i>run_id</i>	ID of the run
<i>meta_data</i>	Metadata to store with data

## 6.28.3 Member Function Documentation

### 6.28.3.1 \_\_len\_\_()

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self )
```

Get length of wrapped data.

#### Returns

length of wrapped data

### 6.28.3.2 addResult()

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres )
```

Add a result to the data wrapper.

**Parameters**

<i>rkey</i>	Result key
<i>rres</i>	Result

**6.28.3.3 get()**

```
def skdaccess.framework.data_class.DataWrapperBase.get (
    self )
```

Retrieve stored data.

**Returns**

Stored data

**6.28.3.4 getIterator()**

```
def skdaccess.framework.data_class.DataWrapperBase.getIterator (
    self )
```

Get an iterator to the data.

**Returns**

iterator to data

**6.28.3.5 getResults()**

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self )
```

Retrieve accumulated results, if any.

**Returns**

store results



### 6.28.3.6 info()

```
def skdaccess.framework.data_class.DataWrapperBase.info (
    self,
    key = None )
```

Get information about data wrapper.

#### Returns

The stored metadata

### 6.28.3.7 reset()

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self )
```

Reset data back to original state.

### 6.28.3.8 update()

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj )
```

Updated wrapped data.

#### Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

## 6.28.4 Member Data Documentation

### 6.28.4.1 constants

```
skdaccess.framework.data_class.DataWrapperBase.constants
```

#### 6.28.4.2 data

```
skdaccess.framework.data_class.DataWrapperBase.data
```

#### 6.28.4.3 meta\_data

```
skdaccess.framework.data_class.DataWrapperBase.meta_data
```

#### 6.28.4.4 results

```
skdaccess.framework.data_class.DataWrapperBase.results
```

#### 6.28.4.5 run\_id

```
skdaccess.framework.data_class.DataWrapperBase.run_id
```


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.29 skdaccess.framework.data\_class.ImageWrapper Class Reference

Wrapper for image data.

Inheritance diagram for skdaccess.framework.data\_class.ImageWrapper:



## Public Member Functions

- def [getIterator](#) (self)  
*Get an iterator to the data.*
- def [updateData](#) (self, label, new\_data)  
*Change image.*
- def [deleteData](#) (self, label)  
*Delete image.*
- def [update](#) (self, obj)  
*Updated wrapped data.*
- def [get](#) (self)  
*Retrieve stored data.*
- def [getResults](#) (self)  
*Retrieve accumulated results, if any.*
- def [addResult](#) (self, rkey, rres)  
*Add a result to the data wrapper.*
- def [reset](#) (self)  
*Reset data back to original state.*
- def [info](#) (self, key=None)  
*Get information about data wrapper.*
- def [\\_\\_len\\_\\_](#) (self)  
*Get length of wrapped data.*

## Public Attributes

- [data](#)
- [results](#)
- [constants](#)
- [run\\_id](#)
- [meta\\_data](#)

### 6.29.1 Detailed Description

Wrapper for image data.

### 6.29.2 Member Function Documentation

#### 6.29.2.1 `__len__()`

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self ) [inherited]
```

Get length of wrapped data.

##### Returns

length of wrapped data

#### 6.29.2.2 `addResult()`

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres ) [inherited]
```

Add a result to the data wrapper.

##### Parameters

<i>rkey</i>	Result key
<i>rres</i>	Result

#### 6.29.2.3 `deleteData()`

```
def skdaccess.framework.data_class.ImageWrapper.deleteData (
    self,
    label )
```

Delete image.

##### Parameters

<i>label</i>	Delete image with label
--------------	-------------------------

#### 6.29.2.4 `get()`

```
def skdaccess.framework.data_class.DataWrapperBase.get (
```

```
self ) [inherited]
```

Retrieve stored data.

#### Returns

Stored data

#### 6.29.2.5 `getIterator()`

```
def skdaccess.framework.data_class.ImageWrapper.getIterator (
    self )
```

Get an iterator to the data.

#### Returns

Iterator yielding (label, image\_data)

#### 6.29.2.6 `getResults()`

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self ) [inherited]
```

Retrieve accumulated results, if any.

#### Returns

store results

#### 6.29.2.7 `info()`

```
def skdaccess.framework.data_class.DataWrapperBase.info (
    self,
    key = None ) [inherited]
```

Get information about data wrapper.

#### Returns

The stored metadata

#### 6.29.2.8 reset()

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self ) [inherited]
```

Reset data back to original state.

#### 6.29.2.9 update()

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj ) [inherited]
```

Updated wrapped data.

##### Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

#### 6.29.2.10 updateData()

```
def skdaccess.framework.data_class.ImageWrapper.updateData (
    self,
    label,
    new_data )
```

Change image.

##### Parameters

<i>label</i>	Label of data to be changed
<i>new_data</i>	New data to replace old data

### 6.29.3 Member Data Documentation

#### 6.29.3.1 constants

```
skdaccess.framework.data_class.DataWrapperBase.constants [inherited]
```

### 6.29.3.2 data

`skdaccess.framework.data_class.DataWrapperBase.data` [inherited]

### 6.29.3.3 meta\_data

`skdaccess.framework.data_class.DataWrapperBase.meta_data` [inherited]

### 6.29.3.4 results

`skdaccess.framework.data_class.DataWrapperBase.results` [inherited]

### 6.29.3.5 run\_id

`skdaccess.framework.data_class.DataWrapperBase.run_id` [inherited]


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.30 skdaccess.utilities.modis\_util.LatLon Class Reference

Calculates Lat/Lon position from y,x pixel coordinate.

Inheritance diagram for `skdaccess.utilities.modis_util.LatLon`:



### Public Member Functions

- `def __init__(self, metadata, x\_offset=0, y\_offset=0)`  
*Initialize getLatLon object.*
- `def \_\_call\_\_(self, y, x)`  
*Convert pixel coordinates to lat/lon.*

## Public Attributes

- [x\\_offset](#)
- [y\\_offset](#)
- [lat\\_data](#)
- [lon\\_data](#)
- [alat](#)
- [alon](#)

### 6.30.1 Detailed Description

Calculates Lat/Lon position from y,x pixel coordinate.

### 6.30.2 Constructor & Destructor Documentation

#### 6.30.2.1 `__init__()`

```
def skdaccess.utilities.modis_util.LatLon.__init__ (
    self,
    metadata,
    x_offset = 0,
    y_offset = 0 )
```

Initialize getLatLon object.

#### Parameters

<i>metadata</i>	Image metadata
<i>x_offset</i>	Pixel offset (used when gridding data)
<i>y_offset</i>	Pixel offset (used when gridding data)

### 6.30.3 Member Function Documentation

#### 6.30.3.1 `__call__()`

```
def skdaccess.utilities.modis_util.LatLon.__call__ (
    self,
```



$y,$   
 $x$  )

Convert pixel coordinates to lat/lon.

**Parameters**

<i>y</i>	y coordinate
<i>x</i>	x coordinate

**Returns**

(lat, lon)

**6.30.4 Member Data Documentation****6.30.4.1 alat**

`skdaccess.utilities.modis_util.LatLon.alat`

**6.30.4.2 alon**

`skdaccess.utilities.modis_util.LatLon.alon`

**6.30.4.3 lat\_data**

`skdaccess.utilities.modis_util.LatLon.lat_data`

**6.30.4.4 lon\_data**

`skdaccess.utilities.modis_util.LatLon.lon_data`

**6.30.4.5 x\_offset**

`skdaccess.utilities.modis_util.LatLon.x_offset`

## 6.30.4.6 y\_offset

```
skdaccess.utilities.modis_util.LatLon.y_offset
```


The documentation for this class was generated from the following file:

- [utilities/modis\\_util.py](#)

## 6.31 skdaccess.framework.data\_class.SeriesDictionaryWrapper Class Reference

Data wrapper for series data using a dictionary of data frames.

Inheritance diagram for skdaccess.framework.data\_class.SeriesDictionaryWrapper:



## Public Member Functions

- def [getIterator](#) (self)  
Get an iterator to the data.
- def [getIndices](#) (self)  
Get the indices of the data.
- def [getLength](#) (self)  
Get total number of series that the iterate will loop over.
- def [update](#) (self, obj)  
Updated wrapped data.
- def [get](#) (self)  
Retrieve stored data.
- def [getResults](#) (self)  
Retrieve accumulated results, if any.
- def [addResult](#) (self, rkey, rres)  
Add a result to the data wrapper.
- def [reset](#) (self)  
Reset data back to original state.
- def [info](#) (self, key=None)  
Get information about data wrapper.
- def [\\_\\_len\\_\\_](#) (self)  
Get length of wrapped data.

## Public Attributes

- [data\\_names](#)
- [error\\_names](#)
- [data](#)
- [results](#)
- [constants](#)
- [run\\_id](#)
- [meta\\_data](#)

### 6.31.1 Detailed Description

Data wrapper for series data using a dictionary of data frames.

### 6.31.2 Member Function Documentation

#### 6.31.2.1 `__len__()`

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self ) [inherited]
```

Get length of wrapped data.

#### Returns

length of wrapped data

#### 6.31.2.2 `addResult()`

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres ) [inherited]
```

Add a result to the data wrapper.

#### Parameters

<i>rkey</i>	Result key
<i>rres</i>	Result

### 6.31.2.3 get()

```
def skdaccess.framework.data_class.DataWrapperBase.get (
    self ) [inherited]
```

Retrieve stored data.

#### Returns

Stored data

### 6.31.2.4 getIndices()

```
def skdaccess.framework.data_class.SeriesDictionaryWrapper.getIndices (
    self )
```

Get the indices of the data.

#### Returns

index of data

### 6.31.2.5 getIterator()

```
def skdaccess.framework.data_class.SeriesDictionaryWrapper.getIterator (
    self )
```

Get an iterator to the data.

#### Returns

Iterator (label, data, errors) that will cycle over data and error names

#### 6.31.2.6 `getLength()`

```
def skdaccess.framework.data_class.SeriesDictionaryWrapper.getLength (
    self )
```

Get total number of series that the iterate will loop over.

##### Returns

Number of series iterator will traverse over

#### 6.31.2.7 `getResults()`

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self ) [inherited]
```

Retrieve accumulated results, if any.

##### Returns

store results

#### 6.31.2.8 `info()`

```
def skdaccess.framework.data_class.DataWrapperBase.info (
    self,
    key = None ) [inherited]
```

Get information about data wrapper.

##### Returns

The stored metadata

#### 6.31.2.9 `reset()`

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self ) [inherited]
```

Reset data back to original state.

#### 6.31.2.10 `update()`

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj ) [inherited]
```

Updated wrapped data.

#### Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

### 6.31.3 Member Data Documentation

#### 6.31.3.1 constants

`skdaccess.framework.data_class.DataWrapperBase.constants` [inherited]

#### 6.31.3.2 data

`skdaccess.framework.data_class.DataWrapperBase.data` [inherited]

#### 6.31.3.3 data\_names

`skdaccess.framework.data_class.SeriesWrapper.data_names` [inherited]

#### 6.31.3.4 error\_names

`skdaccess.framework.data_class.SeriesWrapper.error_names` [inherited]

#### 6.31.3.5 meta\_data

`skdaccess.framework.data_class.DataWrapperBase.meta_data` [inherited]

### 6.31.3.6 results

`skdaccess.framework.data_class.DataWrapperBase.results` [inherited]

### 6.31.3.7 run\_id

`skdaccess.framework.data_class.DataWrapperBase.run_id` [inherited]


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

## 6.32 skdaccess.framework.data\_class.SeriesWrapper Class Reference

Data wrapper for series data using a data panel.

Inheritance diagram for `skdaccess.framework.data_class.SeriesWrapper`:



### Public Member Functions

- `def __init__ (self, obj_wrap, data\_names, error\_names=None, meta\_data=None, run\_id=-1)`  
*Initialize Series Wrapper.*
- `def getIterator (self)`  
*Get an iterator to the data.*
- `def getIndices (self)`  
*Get the indices of the data.*
- `def getLength (self)`  
*Get total number of series that the iterate will loop over.*
- `def update (self, obj)`  
*Updated wrapped data.*
- `def get (self)`  
*Retrieve stored data.*



- def [getResults](#) (self)  
*Retrieve accumulated results, if any.*
- def [addResult](#) (self, rkey, rres)  
*Add a result to the data wrapper.*
- def [reset](#) (self)  
*Reset data back to original state.*
- def [info](#) (self, key=None)  
*Get information about data wrapper.*
- def [\\_\\_len\\_\\_](#) (self)  
*Get length of wrapped data.*

## Public Attributes

- [data\\_names](#)
- [error\\_names](#)
- [data](#)
- [results](#)
- [constants](#)
- [run\\_id](#)
- [meta\\_data](#)

### 6.32.1 Detailed Description

Data wrapper for series data using a data panel.

### 6.32.2 Constructor & Destructor Documentation

#### 6.32.2.1 `__init__()`

```
def skdaccess.framework.data_class.SeriesWrapper.__init__ (
    self,
    obj_wrap,
    data_names,
    error_names = None,
    meta_data = None,
    run_id = -1 )
```

Initialize Series Wrapper.

#### Parameters

<i>obj_wrap</i>	Pandas data panel to wrap
<i>data_names</i>	List of data column names
<i>error_names</i>	List of error column names
<i>meta_data</i>	Metadata
<i>run_id</i>	ID of run

### 6.32.3 Member Function Documentation

#### 6.32.3.1 `__len__()`

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self ) [inherited]
```

Get length of wrapped data.

##### Returns

length of wrapped data

#### 6.32.3.2 `addResult()`

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres ) [inherited]
```

Add a result to the data wrapper.

##### Parameters

<i>rkey</i>	Result key
<i>rres</i>	Result

#### 6.32.3.3 `get()`

```
def skdaccess.framework.data_class.DataWrapperBase.get (
    self ) [inherited]
```

Retrieve stored data.

##### Returns

Stored data

#### 6.32.3.4 getIndices()

```
def skdaccess.framework.data_class.SeriesWrapper.getIndices (
    self )
```

Get the indices of the data.

##### Returns

index of data

#### 6.32.3.5 getIterator()

```
def skdaccess.framework.data_class.SeriesWrapper.getIterator (
    self )
```

Get an iterator to the data.

##### Returns

Iterator (label, data, errors) that will cycle over data and error names

#### 6.32.3.6 getLength()

```
def skdaccess.framework.data_class.SeriesWrapper.getLength (
    self )
```

Get total number of series that the iterate will loop over.

##### Returns

Number of series iterator will traverse over

#### 6.32.3.7 getResults()

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self ) [inherited]
```

Retrieve accumulated results, if any.

##### Returns

store results

#### 6.32.3.8 info()

```
def skdaccess.framework.data_class.DataWrapperBase.info (
    self,
    key = None ) [inherited]
```

Get information about data wrapper.

##### Returns

The stored metadata

#### 6.32.3.9 reset()

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self ) [inherited]
```

Reset data back to original state.

#### 6.32.3.10 update()

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj ) [inherited]
```

Updated wrapped data.

##### Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

### 6.32.4 Member Data Documentation

#### 6.32.4.1 constants

```
skdaccess.framework.data_class.DataWrapperBase.constants [inherited]
```

#### 6.32.4.2 data

`skdaccess.framework.data_class.DataWrapperBase.data` [inherited]

#### 6.32.4.3 data\_names

`skdaccess.framework.data_class.SeriesWrapper.data_names`

#### 6.32.4.4 error\_names

`skdaccess.framework.data_class.SeriesWrapper.error_names`

#### 6.32.4.5 meta\_data

`skdaccess.framework.data_class.DataWrapperBase.meta_data` [inherited]

#### 6.32.4.6 results

`skdaccess.framework.data_class.DataWrapperBase.results` [inherited]

#### 6.32.4.7 run\_id

`skdaccess.framework.data_class.DataWrapperBase.run_id` [inherited]


The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)

### 6.33 skdaccess.framework.data\_class.TableWrapper Class Reference

Data wrapper for table data using an ordered dictionary.

Inheritance diagram for skdaccess.framework.data\_class.TableWrapper:



#### Public Member Functions

- def `__init__` (self, obj\_wrap, run\_id=-1, meta\_data=None, default\_columns=None, default\_error\_columns=None)  
*Construct object from input data.*
- def `getIterator` (self)  
*Iterator access to data.*
- def `getLength` (self)  
*Get number of data frames.*
- def `updateData` (self, label, index, column\_names, new\_data)  
*Update wrapped data.*
- def `addColumn` (self, label, column\_names, new\_data)  
*Add new column to data.*
- def `getDefaultColumns` (self)  
*Get the default columns of data.*
- def `getDefaultErrorColumns` (self)  
*Get the default error columns of data.*
- def `removeFrames` (self, label\_list)  
*Remove Data Frames from wrapper.*
- def `updateFrames` (self, label\_list, frame\_list)  
*Update data frames.*
- def `update` (self, obj)  
*Updated wrapped data.*
- def `get` (self)  
*Retrieve stored data.*
- def `getResults` (self)  
*Retrieve accumulated results, if any.*
- def `addResult` (self, rkey, rres)  
*Add a result to the data wrapper.*
- def `reset` (self)  
*Reset data back to original state.*
- def `info` (self, key=None)  
*Get information about data wrapper.*
- def `__len__` (self)  
*Get length of wrapped data.*

## Public Attributes

- [default\\_columns](#)
- [default\\_error\\_columns](#)
- [data](#)
- [results](#)
- [constants](#)
- [run\\_id](#)
- [meta\\_data](#)

### 6.33.1 Detailed Description

Data wrapper for table data using an ordered dictionary.

### 6.33.2 Constructor & Destructor Documentation

#### 6.33.2.1 `__init__()`

```
def skdaccess.framework.data_class.TableWrapper.__init__ (
    self,
    obj_wrap,
    run_id = -1,
    meta_data = None,
    default_columns = None,
    default_error_columns = None )
```

Construct object from input data.

#### Parameters

<i>obj_wrap</i>	Data to be wrapped
<i>run_id</i>	ID of the run
<i>meta_data</i>	Metadata to store with data
<i>default_columns</i>	Default columns for pipeline items
<i>default_error_columns</i>	Default error columns for pipeline items

### 6.33.3 Member Function Documentation

### 6.33.3.1 `__len__()`

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self ) [inherited]
```

Get length of wrapped data.

#### Returns

length of wrapped data

### 6.33.3.2 `addColumn()`

```
def skdaccess.framework.data_class.TableWrapper.addColumn (
    self,
    label,
    column_names,
    new_data )
```

Add new column to data.

#### Parameters

<i>label</i>	Data label
<i>column_names</i>	Names of columns to update
<i>new_data</i>	New data to add

### 6.33.3.3 `addResult()`

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres ) [inherited]
```

Add a result to the data wrapper.

#### Parameters

<i>rkey</i>	Result key
<i>rres</i>	Result



#### 6.33.3.4 get()

```
def skdaccess.framework.data_class.DataWrapperBase.get (
    self ) [inherited]
```

Retrieve stored data.

##### Returns

Stored data

#### 6.33.3.5 getDefaultColumns()

```
def skdaccess.framework.data_class.TableWrapper.getDefaultColumns (
    self )
```

Get the default columns of data.

##### Returns

List of default columns

#### 6.33.3.6 getDefaultErrorColumns()

```
def skdaccess.framework.data_class.TableWrapper.getDefaultErrorColumns (
    self )
```

Get the default error columns of data.

##### Returns

List of default error columns

#### 6.33.3.7 getIterator()

```
def skdaccess.framework.data_class.TableWrapper.getIterator (
    self )
```

Iterator access to data.

##### Returns

iterator to (label, data frame) from Dictionary

#### 6.33.3.8 `getLength()`

```
def skdaccess.framework.data_class.TableWrapper.getLength (
    self )
```

Get number of data frames.

##### Returns

Number of data frames

#### 6.33.3.9 `getResults()`

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self ) [inherited]
```

Retrieve accumulated results, if any.

##### Returns

store results

#### 6.33.3.10 `info()`

```
def skdaccess.framework.data_class.DataWrapperBase.info (
    self,
    key = None ) [inherited]
```

Get information about data wrapper.

##### Returns

The stored metadata

#### 6.33.3.11 `removeFrames()`

```
def skdaccess.framework.data_class.TableWrapper.removeFrames (
    self,
    label_list )
```

Remove Data Frames from wrapper.

## Parameters

<i>label_list</i>	List of labels to remove
-------------------	--------------------------

## 6.33.3.12 reset()

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self ) [inherited]
```

Reset data back to original state.

## 6.33.3.13 update()

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj ) [inherited]
```

Updated wrapped data.

## Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

## 6.33.3.14 updateData()

```
def skdaccess.framework.data_class.TableWrapper.updateData (
    self,
    label,
    index,
    column_names,
    new_data )
```

Update wrapped data.

## Parameters

<i>label</i>	Data label
<i>index</i>	Index of data to update
<i>column_names</i>	Names of columns to update
<i>new_data</i>	Data to replace the old data

#### 6.33.3.15 updateFrames()

```
def skdaccess.framework.data_class.TableWrapper.updateFrames (
    self,
    label_list,
    frame_list )
```

Update data frames.

##### Parameters

<i>label_list</i>	List of labels to update
<i>frame_list</i>	List of updated frames

### 6.33.4 Member Data Documentation

#### 6.33.4.1 constants

```
skdaccess.framework.data_class.DataWrapperBase.constants [inherited]
```

#### 6.33.4.2 data

```
skdaccess.framework.data_class.DataWrapperBase.data [inherited]
```

#### 6.33.4.3 default\_columns

```
skdaccess.framework.data_class.TableWrapper.default_columns
```

#### 6.33.4.4 default\_error\_columns

```
skdaccess.framework.data_class.TableWrapper.default_error_columns
```

#### 6.33.4.5 meta\_data

`skdaccess.framework.data_class.DataWrapperBase.meta_data` [inherited]

#### 6.33.4.6 results

`skdaccess.framework.data_class.DataWrapperBase.results` [inherited]

#### 6.33.4.7 run\_id

`skdaccess.framework.data_class.DataWrapperBase.run_id` [inherited]


The documentation for this class was generated from the following file:

- [framework/data\\_class.py](#)

## 6.34 skdaccess.framework.data\_class.XArrayWrapper Class Reference

Wrapper for xarrays.

Inheritance diagram for `skdaccess.framework.data_class.XArrayWrapper`:



## Public Member Functions

- def `__init__` (self, obj\_wrap, index\_list, run\_id=-1)
- def `getIterator` (self)  
*Get an iterator that iterates over the index.*
- def `info` (self, key=None)  
*Get information about xarray data wrapper.*
- def `update` (self, obj)  
*Updated wrapped data.*
- def `get` (self)  
*Retrieve stored data.*
- def `getResults` (self)  
*Retrieve accumulated results, if any.*
- def `addResult` (self, rkey, rres)  
*Add a result to the data wrapper.*
- def `reset` (self)  
*Reset data back to original state.*
- def `__len__` (self)  
*Get length of wrapped data.*

## Public Attributes

- `index_list`
- `data`
- `results`
- `constants`
- `run_id`
- `meta_data`

### 6.34.1 Detailed Description

Wrapper for xarrays.

### 6.34.2 Constructor & Destructor Documentation

#### 6.34.2.1 `__init__()`

```
def skdaccess.framework.data_class.XArrayWrapper.__init__ (
    self,
    obj_wrap,
    index_list,
    run_id = -1 )
```

### 6.34.3 Member Function Documentation

#### 6.34.3.1 `__len__()`

```
def skdaccess.framework.data_class.DataWrapperBase.__len__ (
    self ) [inherited]
```

Get length of wrapped data.

##### Returns

length of wrapped data

#### 6.34.3.2 `addResult()`

```
def skdaccess.framework.data_class.DataWrapperBase.addResult (
    self,
    rkey,
    rres ) [inherited]
```

Add a result to the data wrapper.

##### Parameters

<i>rkey</i>	Result key
<i>rres</i>	Result

#### 6.34.3.3 `get()`

```
def skdaccess.framework.data_class.DataWrapperBase.get (
    self ) [inherited]
```

Retrieve stored data.

##### Returns

Stored data

#### 6.34.3.4 `getIterator()`

```
def skdaccess.framework.data_class.XArrayWrapper.getIterator (
    self )
```

Get an iterator that iterates over the index.

##### Returns

iterator to data

#### 6.34.3.5 `getResults()`

```
def skdaccess.framework.data_class.DataWrapperBase.getResults (
    self ) [inherited]
```

Retrieve accumulated results, if any.

##### Returns

store results

#### 6.34.3.6 `info()`

```
def skdaccess.framework.data_class.XArrayWrapper.info (
    self,
    key = None )
```

Get information about xarray data wrapper.

##### Returns

The stored metadata

#### 6.34.3.7 `reset()`

```
def skdaccess.framework.data_class.DataWrapperBase.reset (
    self ) [inherited]
```

Reset data back to original state.

#### 6.34.3.8 `update()`

```
def skdaccess.framework.data_class.DataWrapperBase.update (
    self,
    obj ) [inherited]
```

Updated wrapped data.



#### Parameters

<i>obj</i>	New data for wrapper
------------	----------------------

### 6.34.4 Member Data Documentation

#### 6.34.4.1 constants

`skdaccess.framework.data_class.DataWrapperBase.constants` [inherited]

#### 6.34.4.2 data

`skdaccess.framework.data_class.DataWrapperBase.data` [inherited]

#### 6.34.4.3 index\_list

`skdaccess.framework.data_class.XArrayWrapper.index_list`

#### 6.34.4.4 meta\_data

`skdaccess.framework.data_class.DataWrapperBase.meta_data` [inherited]

#### 6.34.4.5 results

`skdaccess.framework.data_class.DataWrapperBase.results` [inherited]

#### 6.34.4.6 run\_id

`skdaccess.framework.data_class.DataWrapperBase.run_id` [inherited]

The documentation for this class was generated from the following file:

- framework/[data\\_class.py](#)



## Chapter 7

# File Documentation

### 7.1 astro/kepler/data\_fetcher.py File Reference

#### Classes

- class [skdaccess.astro.kepler.DataFetcher](#)  
*Data Fetcher for Kepler light curve data.*

#### Namespaces

- [skdaccess.astro.kepler.data\\_fetcher](#)

### 7.2 geo/gldas/data\_fetcher.py File Reference

#### Classes

- class [skdaccess.geo.gldas.DataFetcher](#)  
*Data Fetcher for GLDAS data.*

#### Namespaces

- [skdaccess.geo.gldas.data\\_fetcher](#)

### 7.3 geo/grace/data\_fetcher.py File Reference

#### Classes

- class [skdaccess.geo.grace.DataFetcher](#)  
*Data Fetcher for GRACE data.*

## Namespaces

- [skdaccess.geo.grace.data\\_fetcher](#)

## 7.4 geo/groundwater/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.groundwater.DataFetcher](#)  
*Generates Data Wrappers of groundwater measurements taken in the US.*

## Namespaces

- [skdaccess.geo.groundwater.data\\_fetcher](#)

## 7.5 geo/modis/cache/cloud\_mask/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.cache.cloud\\_mask.DataFetcher](#)  
*Data Fetcher for MODIS Cloud Mask.*

## Namespaces

- [skdaccess.geo.modis.cache.cloud\\_mask.data\\_fetcher](#)

## 7.6 geo/modis/cache/cloud\_opacity/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.cache.cloud\\_opacity.DataFetcher](#)  
*Data Fetcher for MODIS Cloud Opacity.*

## Namespaces

- [skdaccess.geo.modis.cache.cloud\\_opacity.data\\_fetcher](#)

## 7.7 geo/modis/cache/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.cache.DataFetcher](#)  
*Data Fetcher for MODIS data.*

### Namespaces

- [skdaccess.geo.modis.cache.data\\_fetcher](#)

## 7.8 geo/modis/cache/reflectance/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.cache.reflectance.DataFetcher](#)  
*Data fetcher for the modis surface reflectance product ('09', 1 km resolution)*

### Namespaces

- [skdaccess.geo.modis.cache.reflectance.data\\_fetcher](#)

## 7.9 geo/modis/stream/cloud\_mask/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.stream.cloud\\_mask.DataFetcher](#)  
*Data Fetcher for MODIS Cloud Mask.*

### Namespaces

- [skdaccess.geo.modis.stream.cloud\\_mask.data\\_fetcher](#)

## 7.10 geo/modis/stream/cloud\_opacity/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.stream.cloud\\_opacity.DataFetcher](#)  
*Data Fetcher for MODIS Cloud Opacity.*

## Namespaces

- [skdaccess.geo.modis.stream.cloud\\_opacity.data\\_fetcher](#)

## 7.11 geo/modis/stream/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.stream.DataFetcher](#)  
*Data Fetcher for MODIS data.*

## Namespaces

- [skdaccess.geo.modis.stream.data\\_fetcher](#)

## 7.12 geo/modis/stream/reflectance/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.modis.stream.reflectance.DataFetcher](#)  
*Data fetcher for the modis surface reflectance product ('09', 1 km resolution)*

## Namespaces

- [skdaccess.geo.modis.stream.reflectance.data\\_fetcher](#)

## 7.13 geo/pbo/data\_fetcher.py File Reference

### Classes

- class [skdaccess.geo.pbo.DataFetcher](#)  
*Data fetcher for PBO GPS data.*

## Namespaces

- [skdaccess.geo.pbo.data\\_fetcher](#)

## 7.14 bin/skdaccess.py File Reference

### Namespaces

- [skdaccess.bin.skdaccess](#)

### Functions

- def [skdaccess.bin.skdaccess.skdaccess\\_script\(\)](#)  
*This function defines a script for downloading data.*

## 7.15 framework/data\_class.py File Reference

### Classes

- class [skdaccess.framework.data\\_class.DataFetcherBase](#)  
*Base class for all data fetchers.*
- class [skdaccess.framework.data\\_class.DataFetcherLocal](#)  
*Data fetcher base class for use when storing data locally.*
- class [skdaccess.framework.data\\_class.DataFetcherStorage](#)  
*Data fetcher base class for use when entire data set is downloaded.*
- class [skdaccess.framework.data\\_class.DataFetcherStream](#)  
*Data fetcher base class for downloading data into memory.*
- class [skdaccess.framework.data\\_class.DataFetcherCache](#)  
*Data fetcher base class for downloading data and caching results on hard disk.*
- class [skdaccess.framework.data\\_class.DataWrapperBase](#)  
*Base class for wrapping data for use in DiscoveryPipeline.*
- class [skdaccess.framework.data\\_class.SeriesWrapper](#)  
*Data wrapper for series data using a data panel.*
- class [skdaccess.framework.data\\_class.SeriesDictionaryWrapper](#)  
*Data wrapper for series data using a dictionary of data frames.*
- class [skdaccess.framework.data\\_class.TableWrapper](#)  
*Data wrapper for table data using an ordered dictionary.*
- class [skdaccess.framework.data\\_class.ImageWrapper](#)  
*Wrapper for image data.*
- class [skdaccess.framework.data\\_class.XArrayWrapper](#)  
*Wrapper for xarrays.*

### Namespaces

- [skdaccess.framework.data\\_class](#)

## 7.16 framework/param\_class.py File Reference

### Classes

- class [skdaccess.framework.param\\_class.AutoParam](#)  
*Defines a tunable parameter class inherited by specific subclasses.*
- class [skdaccess.framework.param\\_class.AutoParamMinMax](#)  
*A tunable parameter with min and max ranges, perturbs to a random value in range.*
- class [skdaccess.framework.param\\_class.AutoParamList](#)  
*A tunable parameter with a specified list of choices that can be randomly selected via perturb.*
- class [skdaccess.framework.param\\_class.AutoParamListCycle](#)  
*Cycles through a list of paramters.*
- class [skdaccess.framework.param\\_class.AutoList](#)  
*Specifies a list for returning selections of lists, as opposed to a single element.*
- class [skdaccess.framework.param\\_class.AutoListSubset](#)  
*An [AutoList](#) perturber that creates random subsets of a list.*
- class [skdaccess.framework.param\\_class.AutoListPermute](#)  
*A perturber that permutes a list.*
- class [skdaccess.framework.param\\_class.AutoListRemove](#)  
*Removes a different single element from the initial list at each perturb call.*
- class [skdaccess.framework.param\\_class.AutoListCycle](#)  
*An Autolist that cycles through different lists.*

### Namespaces

- [skdaccess.framework.param\\_class](#)

## 7.17 utilities/grace\_util.py File Reference

### Namespaces

- [skdaccess.utilities.grace\\_util](#)

### Functions

- def [skdaccess.utilities.grace\\_util.averageDates](#) (dates, round\_nearest\_day=False)  
*Compute the average of a pandas series of timestamps.*
- def [skdaccess.utilities.grace\\_util.dateMismatch](#) (dates, days=10)  
*Check if dates are not within a certain number of days of each other.*
- def [skdaccess.utilities.grace\\_util.computeEWD](#) (grace\_data, scale\_factor, round\_nearest\_day=False)  
*Compute scale corrected equivalent water depth.*
- def [skdaccess.utilities.grace\\_util.readTellusData](#) (filename, lat\_lon\_list, lat\_name, lon\_name, data\_name, data\_label=None, time\_name=None, lat\_bounds\_name=None, lon\_bounds\_name=None, uncertainty\_name=None, lat\_bounds=None, lon\_bounds=None)  
*This function reads in netcdf data provided by GRACE Tellus.*
- def [skdaccess.utilities.grace\\_util.getStartEndDate](#) (in\_data)



## 7.18 utilities/gw\_util.py File Reference

### Namespaces

- [skdaccess.utilities.gw\\_util](#)

### Functions

- def [skdaccess.utilities.gw\\_util.combine\\_water\\_heights](#) (in\_data)  
*Combine median and average water heights.*

## 7.19 utilities/kepler\_util.py File Reference

### Namespaces

- [skdaccess.utilities.kepler\\_util](#)

### Functions

- def [skdaccess.utilities.kepler\\_util.normalize](#) (in\_data, column='PDCSAP\_FLUX', group\_column='QUARTER')  
*This function normalizes PDCSAP\_FLUX data by quarter by dividing the flux by the median for the quarter.*

## 7.20 utilities/modis\_util.py File Reference

### Classes

- class [skdaccess.utilities.modis\\_util.LatLon](#)  
*Calculates Lat/Lon position from y,x pixel coordinate.*

### Namespaces

- [skdaccess.utilities.modis\\_util](#)

## Functions

- def [skdaccess.utilities.modis\\_util.getImageType](#) (in\_data)  
*Determine what type of modis data is being processed.*
- def [skdaccess.utilities.modis\\_util.calibrateModis](#) (data, metadata)  
*This function calibrates input modis data.*
- def [skdaccess.utilities.modis\\_util.rescale](#) (in\_array, max\_val=0.9, min\_val=-0.01)  
*This function rescales an image to fall between 0 and 1.*
- def [skdaccess.utilities.modis\\_util.checkBit](#) (data, bit)  
*Get the bit value from a bit flag.*
- def [skdaccess.utilities.modis\\_util.createGrid](#) (data, y\_start, y\_end, x\_start, x\_end, y\_grid, x\_grid, dtype, grid\_fill=np.nan)  
*Subsets image data into a smaller image.*
- def [skdaccess.utilities.modis\\_util.getFileIDs](#) (modis\_identifier, start\_date, end\_date, lat, lon, daynightboth)  
*Retrieve file IDs for images matching search parameters.*
- def [skdaccess.utilities.modis\\_util.getFileURLs](#) (file\_ids)  
*Retrieve the ftp location for a list of file IDs.*
- def [skdaccess.utilities.modis\\_util.getModisData](#) (dataset, variable\_name)  
*Loads modis data.*
- def [skdaccess.utilities.modis\\_util.readMODISData](#) (modis\_list, variables, grid, grid\_fill, use\_long\_name, platform, product\_id)  
*Retrieve a list of modis data.*

## 7.21 utilities/pbo\_util.py File Reference

### Namespaces

- [skdaccess.utilities.pbo\\_util](#)

### Functions

- def [skdaccess.utilities.pbo\\_util.getStationCoords](#) (pbo\_info, station\_list)  
*Get the station coordinates for a list of stations.*
- def [skdaccess.utilities.pbo\\_util.getLatLonRange](#) (pbo\_info, station\_list)  
*Retrive the range of latitude and longitude occupied by a set of stations.*
- def [skdaccess.utilities.pbo\\_util.getROIstations](#) (geo\_point, radiusParam, data, header)  
*This function returns the 4ID station codes for the stations in a region.*
- def [skdaccess.utilities.pbo\\_util.stab\\_sys](#) (data\_iterator, metadata, stab\_min\_NE=.0005, stab\_min\_U=.005, sigsc=2, errProp=1)  
*Stabilize GPS data to a region.*
- def [skdaccess.utilities.pbo\\_util.propagateErrors](#) (R, sc, stationCovs)  
*Propagate GPS errors.*
- def [skdaccess.utilities.pbo\\_util.nostab\\_sys](#) (allH, allD, timerng, indx=1, mdyratio=.7, use\_progress\_bar=True, index\_date\_only=False)  
*Do not apply stabilization and simply returns stations after checking for sufficient amount of data.*
- def [skdaccess.utilities.pbo\\_util.removeAntennaOffset](#) (antenna\_offsets, data, window\_start=pd.to\_timedelta('4<D'), window\_end=pd.to\_timedelta('4D'), min\_diff=0.005, debug=False)  
*Remove offsets caused by changes in antennas.*

# Index

## `__call__`

`skdaccess::framework::param_class::AutoList`, [34](#)  
`skdaccess::framework::param_class::AutoListCycle`,  
[39](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Permute`, [43](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Remove`, [47](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Subset`, [51](#)  
`skdaccess::framework::param_class::AutoParam`, [56](#)  
`skdaccess::framework::param_class::AutoParamList`,  
[58](#)  
`skdaccess::framework::param_class::AutoParam`↔  
  `ListCycle`, [61](#)  
`skdaccess::framework::param_class::AutoParam`↔  
  `MinMax`, [64](#)  
`skdaccess::utilities::modis_util::LatLon`, [156](#)

## `__getitem__`

`skdaccess::framework::param_class::AutoList`, [34](#)  
`skdaccess::framework::param_class::AutoListCycle`,  
[39](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Permute`, [43](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Remove`, [47](#)  
`skdaccess::framework::param_class::AutoList`↔  
  `Subset`, [51](#)

## `__init__`

`skdaccess::astro::kepler::data_fetcher::DataFetcher`,  
[117](#)  
`skdaccess::framework::data_class::DataFetcher`↔  
  `Base`, [123](#)  
`skdaccess::framework::data_class::DataWrapper`↔  
  `Base`, [147](#)  
`skdaccess::framework::data_class::SeriesWrapper`,  
[165](#)  
`skdaccess::framework::data_class::TableWrapper`,  
[171](#)  
`skdaccess::framework::data_class::XArrayWrapper`,  
[178](#)  
`skdaccess::framework::param_class::AutoList`, [34](#)  
`skdaccess::framework::param_class::AutoListCycle`,  
[38](#)  
`skdaccess::framework::param_class::AutoList`↔

`Remove`, [47](#)

`skdaccess::framework::param_class::AutoParam`, [55](#)  
`skdaccess::framework::param_class::AutoParamList`,  
[58](#)  
`skdaccess::framework::param_class::AutoParam`↔  
  `ListCycle`, [61](#)  
`skdaccess::framework::param_class::AutoParam`↔  
  `MinMax`, [63](#)  
`skdaccess::geo::gldas::data_fetcher::DataFetcher`,  
[87](#)  
`skdaccess::geo::grace::data_fetcher::DataFetcher`,  
[93](#)  
`skdaccess::geo::groundwater::data_fetcher::Data`↔  
  `Fetcher`, [100](#)  
`skdaccess::geo::modis::cache::cloud_mask::data`↔  
  `fetcher::DataFetcher`, [106](#)  
`skdaccess::geo::modis::cache::cloud_opacity`↔  
  `::data_fetcher::DataFetcher`, [107](#)  
`skdaccess::geo::modis::cache::data_fetcher::Data`↔  
  `Fetcher`, [69](#)  
`skdaccess::geo::modis::cache::reflectance::data`↔  
  `fetcher::DataFetcher`, [115](#)  
`skdaccess::geo::modis::stream::cloud_mask::data`↔  
  `_fetcher::DataFetcher`, [98](#)  
`skdaccess::geo::modis::stream::cloud_opacity`↔  
  `::data_fetcher::DataFetcher`, [67](#)  
`skdaccess::geo::modis::stream::data_fetcher::`↔  
  `DataFetcher`, [109](#)  
`skdaccess::geo::modis::stream::reflectance::data`↔  
  `fetcher::DataFetcher`, [76](#)  
`skdaccess::geo::pbo::data_fetcher::DataFetcher`, [79](#)  
`skdaccess::utilities::modis_util::LatLon`, [156](#)

## `__len__`

`skdaccess::framework::data_class::DataWrapper`↔  
  `Base`, [147](#)  
`skdaccess::framework::data_class::ImageWrapper`,  
[151](#)  
`skdaccess::framework::data_class::SeriesDictionary`↔  
  `Wrapper`, [160](#)  
`skdaccess::framework::data_class::SeriesWrapper`,  
[166](#)  
`skdaccess::framework::data_class::TableWrapper`,  
[171](#)  
`skdaccess::framework::data_class::XArrayWrapper`,  
[179](#)

- skdaccess::framework::param\_class::AutoList, [35](#)
- skdaccess::framework::param\_class::AutoListCycle, [39](#)
- skdaccess::framework::param\_class::AutoList↔
  - Permute, [43](#)
- skdaccess::framework::param\_class::AutoList↔
  - Remove, [48](#)
- skdaccess::framework::param\_class::AutoList↔
  - Subset, [52](#)
- \_\_setitem\_\_
  - skdaccess::framework::param\_class::AutoList, [35](#)
  - skdaccess::framework::param\_class::AutoListCycle, [40](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Permute, [44](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Remove, [48](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Subset, [52](#)
- \_\_str\_\_
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, [117](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Base, [124](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Cache, [128](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Local, [134](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Storage, [138](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Stream, [143](#)
  - skdaccess::framework::param\_class::AutoList, [35](#)
  - skdaccess::framework::param\_class::AutoListCycle, [40](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Permute, [44](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Remove, [48](#)
  - skdaccess::framework::param\_class::AutoList↔
    - Subset, [52](#)
  - skdaccess::framework::param\_class::AutoParam, [56](#)
  - skdaccess::framework::param\_class::AutoParamList, [58](#)
  - skdaccess::framework::param\_class::AutoParam↔
    - ListCycle, [61](#)
  - skdaccess::framework::param\_class::AutoParam↔
    - MinMax, [64](#)
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, [87](#)
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, [93](#)
  - skdaccess::geo::groundwater::data\_fetcher::Data↔
    - Fetcher, [101](#)
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔
    - Fetcher, [70](#)
  - skdaccess::geo::modis::stream::data\_fetcher::↔
    - DataFetcher, [109](#)
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, [79](#)
- addColumn
  - skdaccess::framework::data\_class::TableWrapper, [172](#)
- addResult
  - skdaccess::framework::data\_class::DataWrapper↔
    - Base, [147](#)
  - skdaccess::framework::data\_class::ImageWrapper, [152](#)
  - skdaccess::framework::data\_class::SeriesDictionary↔
    - Wrapper, [160](#)
  - skdaccess::framework::data\_class::SeriesWrapper, [166](#)
  - skdaccess::framework::data\_class::TableWrapper, [172](#)
  - skdaccess::framework::data\_class::XArrayWrapper, [179](#)
- alat
  - skdaccess::utilities::modis\_util::LatLon, [158](#)
- alon
  - skdaccess::utilities::modis\_util::LatLon, [158](#)
- antenna\_info
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, [84](#)
- ap\_paramList
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, [122](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Base, [127](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Cache, [132](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Local, [137](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Storage, [141](#)
  - skdaccess::framework::data\_class::DataFetcher↔
    - Stream, [145](#)
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, [91](#)
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, [97](#)
  - skdaccess::geo::groundwater::data\_fetcher::Data↔
    - Fetcher, [104](#)
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔
    - Fetcher, [74](#)
  - skdaccess::geo::modis::stream::data\_fetcher::↔
    - DataFetcher, [112](#)
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, [84](#)
- astro/kepler/data\_fetcher.py, [183](#)
- averageDates

- skdaccess::utilities::grace\_util, 16
- bin/skdaccess.py, 187
- cacheData
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 117, 118
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 129
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 70
- calibrateModis
  - skdaccess::utilities::modis\_util, 21
- checkBit
  - skdaccess::utilities::modis\_util, 22
- combine\_water\_heights
  - skdaccess::utilities::gw\_util, 20
- computeEWD
  - skdaccess::utilities::grace\_util, 18
- constants
  - skdaccess::framework::data\_class::DataWrapper↔Base, 149
  - skdaccess::framework::data\_class::ImageWrapper, 154
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 163
  - skdaccess::framework::data\_class::SeriesWrapper, 168
  - skdaccess::framework::data\_class::TableWrapper, 176
  - skdaccess::framework::data\_class::XArrayWrapper, 181
- createGrid
  - skdaccess::utilities::modis\_util, 22
- current\_index
  - skdaccess::framework::param\_class::AutoParam↔ListCycle, 62
- cutoff
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 104
- data
  - skdaccess::framework::data\_class::DataWrapper↔Base, 149
  - skdaccess::framework::data\_class::ImageWrapper, 154
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 163
  - skdaccess::framework::data\_class::SeriesWrapper, 168
  - skdaccess::framework::data\_class::TableWrapper, 176
  - skdaccess::framework::data\_class::XArrayWrapper, 181
- data\_names
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 163
- dateMismatch
  - skdaccess::utilities::grace\_util, 18
- daynightboth
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 74
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 112
- decimals
  - skdaccess::framework::param\_class::AutoParam↔MinMax, 65
- default\_columns
  - skdaccess::framework::data\_class::TableWrapper, 176
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 84
- default\_error\_columns
  - skdaccess::framework::data\_class::TableWrapper, 176
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 84
- deleteData
  - skdaccess::framework::data\_class::ImageWrapper, 152
- downloadFullDataset
  - skdaccess::framework::data\_class::DataFetcher↔Storage, 138
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 88
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 94
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 101
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 80
- downloadKeplerData
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 118
- end\_date
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 91
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 97
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 104
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 74
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 112
- error\_names
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 163

- skdaccess::framework::data\_class::SeriesWrapper, 169
- find\_data
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 71
- framework/data\_class.py, 187
- framework/param\_class.py, 188
- geo/gldas/data\_fetcher.py, 183
- geo/grace/data\_fetcher.py, 183
- geo/groundwater/data\_fetcher.py, 184
- geo/modis/cache/cloud\_mask/data\_fetcher.py, 184
- geo/modis/cache/cloud\_opacity/data\_fetcher.py, 184
- geo/modis/cache/data\_fetcher.py, 185
- geo/modis/cache/reflectance/data\_fetcher.py, 185
- geo/modis/stream/cloud\_mask/data\_fetcher.py, 185
- geo/modis/stream/cloud\_opacity/data\_fetcher.py, 185
- geo/modis/stream/data\_fetcher.py, 186
- geo/modis/stream/reflectance/data\_fetcher.py, 186
- geo/pbo/data\_fetcher.py, 186
- get
  - skdaccess::framework::data\_class::DataWrapper↔Base, 148
  - skdaccess::framework::data\_class::ImageWrapper, 152
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 161
  - skdaccess::framework::data\_class::SeriesWrapper, 166
  - skdaccess::framework::data\_class::TableWrapper, 172
  - skdaccess::framework::data\_class::XArrayWrapper, 179
- getAllOptions
  - skdaccess::framework::param\_class::AutoList, 36
  - skdaccess::framework::param\_class::AutoListCycle, 40
  - skdaccess::framework::param\_class::AutoList↔Permute, 44
  - skdaccess::framework::param\_class::AutoList↔Remove, 49
  - skdaccess::framework::param\_class::AutoList↔Subset, 53
- getAntennaLogs
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 80
- getConfig
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 119
  - skdaccess::framework::data\_class::DataFetcher↔Base, 124
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 129
  - skdaccess::framework::data\_class::DataFetcher↔Local, 134
  - skdaccess::framework::data\_class::DataFetcher↔Storage, 139
  - skdaccess::framework::data\_class::DataFetcher↔Stream, 143
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 88
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 94
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 101
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 71
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 110
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 80
- getDataLocation
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 119
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 129
  - skdaccess::framework::data\_class::DataFetcher↔Local, 134
  - skdaccess::framework::data\_class::DataFetcher↔Storage, 139
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 88
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 94
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 101
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 71
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 81
- getDefaultColumns
  - skdaccess::framework::data\_class::TableWrapper, 173
- getDefaultErrorColumns
  - skdaccess::framework::data\_class::TableWrapper, 173
- getFileIDs
  - skdaccess::utilities::modis\_util, 23
- getFileURLs
  - skdaccess::utilities::modis\_util, 23
- getHDFSStorage
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 119
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 130
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 72
- getImageType
  - skdaccess::utilities::modis\_util, 24
- getIndices
  - skdaccess::framework::data\_class::SeriesDictionary↔

- Wrapper, 161
- skdaccess::framework::data\_class::SeriesWrapper, 166
- getInfo
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 81
- getIterator
  - skdaccess::framework::data\_class::DataWrapper↔ Base, 148
  - skdaccess::framework::data\_class::ImageWrapper, 153
  - skdaccess::framework::data\_class::SeriesDictionary↔ Wrapper, 161
  - skdaccess::framework::data\_class::SeriesWrapper, 167
  - skdaccess::framework::data\_class::TableWrapper, 173
  - skdaccess::framework::data\_class::XArrayWrapper, 179
- getLatLonRange
  - skdaccess::utilities::pbo\_util, 26
- getLength
  - skdaccess::framework::data\_class::SeriesDictionary↔ Wrapper, 161
  - skdaccess::framework::data\_class::SeriesWrapper, 167
  - skdaccess::framework::data\_class::TableWrapper, 173
- getMetadata
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 119
  - skdaccess::framework::data\_class::DataFetcher↔ Base, 124
  - skdaccess::framework::data\_class::DataFetcher↔ Cache, 130
  - skdaccess::framework::data\_class::DataFetcher↔ Local, 134
  - skdaccess::framework::data\_class::DataFetcher↔ Storage, 139
  - skdaccess::framework::data\_class::DataFetcher↔ Stream, 143
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 89
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 95
  - skdaccess::geo::groundwater::data\_fetcher::Data↔ Fetcher, 102
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔ Fetcher, 72
  - skdaccess::geo::modis::stream::data\_fetcher::↔ DataFetcher, 110
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 81
- getModisData
  - skdaccess::utilities::modis\_util, 24
- getROlstations
  - skdaccess::utilities::pbo\_util, 27
- getResults
  - skdaccess::framework::data\_class::DataWrapper↔ Base, 148
  - skdaccess::framework::data\_class::ImageWrapper, 153
  - skdaccess::framework::data\_class::SeriesDictionary↔ Wrapper, 162
  - skdaccess::framework::data\_class::SeriesWrapper, 167
  - skdaccess::framework::data\_class::TableWrapper, 174
  - skdaccess::framework::data\_class::XArrayWrapper, 180
- getStartDate
  - skdaccess::utilities::grace\_util, 19
- getStationCoords
  - skdaccess::utilities::pbo\_util, 27
- getStationMetadata
  - skdaccess::geo::groundwater::data\_fetcher::Data↔ Fetcher, 102
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 82
- grid
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔ Fetcher, 74
  - skdaccess::geo::modis::stream::data\_fetcher::↔ DataFetcher, 113
- grid\_fill
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔ Fetcher, 75
  - skdaccess::geo::modis::stream::data\_fetcher::↔ DataFetcher, 113
- index
  - skdaccess::framework::param\_class::AutoListCycle, 41
- index\_date\_only
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 85
- index\_list
  - skdaccess::framework::data\_class::XArrayWrapper, 181
- info
  - skdaccess::framework::data\_class::DataWrapper↔ Base, 148
  - skdaccess::framework::data\_class::ImageWrapper, 153
  - skdaccess::framework::data\_class::SeriesDictionary↔ Wrapper, 162
  - skdaccess::framework::data\_class::SeriesWrapper, 167
  - skdaccess::framework::data\_class::TableWrapper, 174
  - skdaccess::framework::data\_class::XArrayWrapper, 180

- lat\_data
  - skdaccess::utilities::modis\_util::LatLon, 158
- list\_val\_list
  - skdaccess::framework::param\_class::AutoListCycle, 41
- lon\_data
  - skdaccess::utilities::modis\_util::LatLon, 158
- meta\_data
  - skdaccess::framework::data\_class::DataWrapper↔Base, 150
  - skdaccess::framework::data\_class::ImageWrapper, 155
  - skdaccess::framework::data\_class::SeriesDictionary↔Wrapper, 163
  - skdaccess::framework::data\_class::SeriesWrapper, 169
  - skdaccess::framework::data\_class::TableWrapper, 176
  - skdaccess::framework::data\_class::XArrayWrapper, 181
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 85
- modis\_id
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 75
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 113
- modis\_identifier
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 75
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 113
- modis\_platform
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 75
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 113
- multirun\_enabled
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 120
  - skdaccess::framework::data\_class::DataFetcher↔Base, 124
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 130
  - skdaccess::framework::data\_class::DataFetcher↔Local, 135
  - skdaccess::framework::data\_class::DataFetcher↔Storage, 140
  - skdaccess::framework::data\_class::DataFetcher↔Stream, 143
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 89
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 95
- skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 102
- skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 72
- skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 110
- skdaccess::geo::pbo::data\_fetcher::DataFetcher, 82
- n
  - skdaccess::framework::param\_class::AutoList↔Remove, 50
  - skdaccess::framework::param\_class::AutoParam↔MinMax, 65
- n\_max
  - skdaccess::framework::param\_class::AutoParam↔MinMax, 65
- normalize
  - skdaccess::utilities::kepler\_util, 20
- nostab\_sys
  - skdaccess::utilities::pbo\_util, 28
- output
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 120
  - skdaccess::framework::data\_class::DataFetcher↔Base, 125
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 130
  - skdaccess::framework::data\_class::DataFetcher↔Local, 135
  - skdaccess::framework::data\_class::DataFetcher↔Storage, 140
  - skdaccess::framework::data\_class::DataFetcher↔Stream, 143
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 89
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 95
  - skdaccess::geo::groundwater::data\_fetcher::Data↔Fetcher, 103
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔Fetcher, 72
  - skdaccess::geo::modis::stream::data\_fetcher::↔DataFetcher, 110
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 82
- perturb
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, 120
  - skdaccess::framework::data\_class::DataFetcher↔Base, 125
  - skdaccess::framework::data\_class::DataFetcher↔Cache, 131
  - skdaccess::framework::data\_class::DataFetcher↔Local, 135



- skdaccess::framework::data\_class::DataFetcher↔  
Storage, 140
- skdaccess::framework::data\_class::DataFetcher↔  
Stream, 144
- skdaccess::framework::param\_class::AutoList, 36
- skdaccess::framework::param\_class::AutoListCycle,  
40
- skdaccess::framework::param\_class::AutoList↔  
Permute, 45
- skdaccess::framework::param\_class::AutoList↔  
Remove, 49
- skdaccess::framework::param\_class::AutoList↔  
Subset, 53
- skdaccess::framework::param\_class::AutoParam, 56
- skdaccess::framework::param\_class::AutoParamList,  
59
- skdaccess::framework::param\_class::AutoParam↔  
ListCycle, 61
- skdaccess::framework::param\_class::AutoParam↔  
MinMax, 64
- skdaccess::geo::gldas::data\_fetcher::DataFetcher,  
89
- skdaccess::geo::grace::data\_fetcher::DataFetcher,  
95
- skdaccess::geo::groundwater::data\_fetcher::Data↔  
Fetcher, 103
- skdaccess::geo::modis::cache::data\_fetcher::Data↔  
Fetcher, 73
- skdaccess::geo::modis::stream::data\_fetcher::↔  
DataFetcher, 111
- skdaccess::geo::pbo::data\_fetcher::DataFetcher, 82
- propagateErrors  
skdaccess::utilities::pbo\_util, 28
- quarter\_list  
skdaccess::astro::kepler::data\_fetcher::DataFetcher,  
122
- readMODISData  
skdaccess::utilities::modis\_util, 25
- readTellusData  
skdaccess::utilities::grace\_util, 19
- removeAntennaOffset  
skdaccess::utilities::pbo\_util, 30
- removeFrames  
skdaccess::framework::data\_class::TableWrapper,  
174
- resample  
skdaccess::geo::gldas::data\_fetcher::DataFetcher,  
91
- rescale  
skdaccess::utilities::modis\_util, 25
- reset  
skdaccess::astro::kepler::data\_fetcher::DataFetcher,  
120
- skdaccess::framework::data\_class::DataFetcher↔  
Base, 125
- skdaccess::framework::data\_class::DataFetcher↔  
Cache, 131
- skdaccess::framework::data\_class::DataFetcher↔  
Local, 135
- skdaccess::framework::data\_class::DataFetcher↔  
Storage, 140
- skdaccess::framework::data\_class::DataFetcher↔  
Stream, 144
- skdaccess::framework::data\_class::DataWrapper↔  
Base, 149
- skdaccess::framework::data\_class::ImageWrapper,  
153
- skdaccess::framework::data\_class::SeriesDictionary↔  
Wrapper, 162
- skdaccess::framework::data\_class::SeriesWrapper,  
168
- skdaccess::framework::data\_class::TableWrapper,  
175
- skdaccess::framework::data\_class::XArrayWrapper,  
180
- skdaccess::framework::param\_class::AutoList, 36
- skdaccess::framework::param\_class::AutoListCycle,  
41
- skdaccess::framework::param\_class::AutoList↔  
Permute, 45
- skdaccess::framework::param\_class::AutoList↔  
Remove, 49
- skdaccess::framework::param\_class::AutoList↔  
Subset, 53
- skdaccess::framework::param\_class::AutoParam, 56
- skdaccess::framework::param\_class::AutoParamList,  
59
- skdaccess::framework::param\_class::AutoParam↔  
ListCycle, 62
- skdaccess::framework::param\_class::AutoParam↔  
MinMax, 65
- skdaccess::geo::gldas::data\_fetcher::DataFetcher,  
90
- skdaccess::geo::grace::data\_fetcher::DataFetcher,  
96
- skdaccess::geo::groundwater::data\_fetcher::Data↔  
Fetcher, 103
- skdaccess::geo::modis::cache::data\_fetcher::Data↔  
Fetcher, 73
- skdaccess::geo::modis::stream::data\_fetcher::↔  
DataFetcher, 111
- skdaccess::geo::pbo::data\_fetcher::DataFetcher, 83
- results  
skdaccess::framework::data\_class::DataWrapper↔  
Base, 150
- skdaccess::framework::data\_class::ImageWrapper,  
155

- skdaccess::framework::data\_class::SeriesDictionary↔  
Wrapper, 163
- skdaccess::framework::data\_class::SeriesWrapper,  
169
- skdaccess::framework::data\_class::TableWrapper,  
177
- skdaccess::framework::data\_class::XArrayWrapper,  
181
- retrieveOnlineData
  - skdaccess::framework::data\_class::DataFetcher↔  
Stream, 144
  - skdaccess::geo::modis::stream::data\_fetcher::↔  
DataFetcher, 111
- run\_id
  - skdaccess::framework::data\_class::DataWrapper↔  
Base, 150
  - skdaccess::framework::data\_class::ImageWrapper,  
155
  - skdaccess::framework::data\_class::SeriesDictionary↔  
Wrapper, 164
  - skdaccess::framework::data\_class::SeriesWrapper,  
169
  - skdaccess::framework::data\_class::TableWrapper,  
177
  - skdaccess::framework::data\_class::XArrayWrapper,  
181
- setDataLocation
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher,  
121
  - skdaccess::framework::data\_class::DataFetcher↔  
Cache, 131
  - skdaccess::framework::data\_class::DataFetcher↔  
Local, 136
  - skdaccess::framework::data\_class::DataFetcher↔  
Storage, 140
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher,  
90
  - skdaccess::geo::grace::data\_fetcher::DataFetcher,  
96
  - skdaccess::geo::groundwater::data\_fetcher::Data↔  
Fetcher, 103
  - skdaccess::geo::modis::cache::data\_fetcher::Data↔  
Fetcher, 73
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 83
- setStationList
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, 83
- skdaccess, 9
- skdaccess.astro, 9
- skdaccess.astro.kepler, 9
- skdaccess.astro.kepler.data\_fetcher, 9
- skdaccess.astro.kepler.DataFetcher, 115
- skdaccess.bin, 10
- skdaccess.bin.skdaccess, 10
- skdaccess.framework, 10
- skdaccess.framework.data\_class, 11
- skdaccess.framework.data\_class.DataFetcherBase, 122
- skdaccess.framework.data\_class.DataFetcherCache, 127
- skdaccess.framework.data\_class.DataFetcherLocal, 133
- skdaccess.framework.data\_class.DataFetcherStorage,  
137
- skdaccess.framework.data\_class.DataFetcherStream,  
142
- skdaccess.framework.data\_class.DataWrapperBase, 146
- skdaccess.framework.data\_class.ImageWrapper, 150
- skdaccess.framework.data\_class.SeriesDictionary↔  
Wrapper, 159
- skdaccess.framework.data\_class.SeriesWrapper, 164
- skdaccess.framework.data\_class.TableWrapper, 170
- skdaccess.framework.data\_class.XArrayWrapper, 177
- skdaccess.framework.param\_class, 11
- skdaccess.framework.param\_class.AutoList, 33
- skdaccess.framework.param\_class.AutoListCycle, 37
- skdaccess.framework.param\_class.AutoListPermute, 42
- skdaccess.framework.param\_class.AutoListRemove, 46
- skdaccess.framework.param\_class.AutoListSubset, 50
- skdaccess.framework.param\_class.AutoParam, 54
- skdaccess.framework.param\_class.AutoParamList, 57
- skdaccess.framework.param\_class.AutoParamListCycle,  
60
- skdaccess.framework.param\_class.AutoParamMinMax,  
63
- skdaccess.geo, 12
- skdaccess.geo.gldas, 12
- skdaccess.geo.gldas.data\_fetcher, 12
- skdaccess.geo.gldas.DataFetcher, 86
- skdaccess.geo.grace, 12
- skdaccess.geo.grace.data\_fetcher, 12
- skdaccess.geo.grace.DataFetcher, 92
- skdaccess.geo.groundwater, 12
- skdaccess.geo.groundwater.data\_fetcher, 13
- skdaccess.geo.groundwater.DataFetcher, 99
- skdaccess.geo.modis, 13
- skdaccess.geo.modis.cache, 13
- skdaccess.geo.modis.cache.cloud\_mask, 13
- skdaccess.geo.modis.cache.cloud\_mask.data\_fetcher, 13
- skdaccess.geo.modis.cache.cloud\_mask.DataFetcher,  
105
- skdaccess.geo.modis.cache.cloud\_opacity, 13
- skdaccess.geo.modis.cache.cloud\_opacity.data\_fetcher,  
14
- skdaccess.geo.modis.cache.cloud\_opacity.DataFetcher,  
106
- skdaccess.geo.modis.cache.data\_fetcher, 14
- skdaccess.geo.modis.cache.DataFetcher, 67
- skdaccess.geo.modis.cache.reflectance, 14
- skdaccess.geo.modis.cache.reflectance.data\_fetcher, 14
- skdaccess.geo.modis.cache.reflectance.DataFetcher, 114

- skdaccess.geo.modis.stream, 14
- skdaccess.geo.modis.stream.cloud\_mask, 14
- skdaccess.geo.modis.stream.cloud\_mask.data\_fetcher, 15
- skdaccess.geo.modis.stream.cloud\_mask.DataFetcher, 98
- skdaccess.geo.modis.stream.cloud\_opacity, 15
- skdaccess.geo.modis.stream.cloud\_opacity.data\_fetcher, 15
- skdaccess.geo.modis.stream.cloud\_opacity.DataFetcher, 66
- skdaccess.geo.modis.stream.data\_fetcher, 15
- skdaccess.geo.modis.stream.DataFetcher, 107
- skdaccess.geo.modis.stream.reflectance, 15
- skdaccess.geo.modis.stream.reflectance.data\_fetcher, 15
- skdaccess.geo.modis.stream.reflectance.DataFetcher, 76
- skdaccess.geo.pbo, 16
- skdaccess.geo.pbo.data\_fetcher, 16
- skdaccess.geo.pbo.DataFetcher, 77
- skdaccess.utilities, 16
- skdaccess.utilities.grace\_util, 16
- skdaccess.utilities.gw\_util, 20
- skdaccess.utilities.kepler\_util, 20
- skdaccess.utilities.modis\_util, 21
- skdaccess.utilities.modis\_util.LatLon, 155
- skdaccess.utilities.pbo\_util, 26
- skdaccess::astro::kepler::data\_fetcher::DataFetcher
  - \_\_init\_\_, 117
  - \_\_str\_\_, 117
  - ap\_paramList, 122
  - cacheData, 117, 118
  - downloadKeplerData, 118
  - getConfig, 119
  - getDataLocation, 119
  - getHDFStorage, 119
  - getMetadata, 119
  - multirun\_enabled, 120
  - output, 120
  - perturb, 120
  - quarter\_list, 122
  - reset, 120
  - setDataLocation, 121
  - verbose, 122
  - verbose\_print, 121
  - writeConfig, 121
- skdaccess::bin::skdaccess
  - skdaccess\_script, 10
- skdaccess::framework::data\_class::DataFetcherBase
  - \_\_init\_\_, 123
  - \_\_str\_\_, 124
  - ap\_paramList, 127
  - getConfig, 124
  - getMetadata, 124
  - multirun\_enabled, 124
  - output, 125
  - perturb, 125
  - reset, 125
  - verbose, 127
  - verbose\_print, 125
  - writeConfig, 126
- skdaccess::framework::data\_class::DataFetcherCache
  - \_\_str\_\_, 128
  - ap\_paramList, 132
  - cacheData, 129
  - getConfig, 129
  - getDataLocation, 129
  - getHDFStorage, 130
  - getMetadata, 130
  - multirun\_enabled, 130
  - output, 130
  - perturb, 131
  - reset, 131
  - setDataLocation, 131
  - verbose, 132
  - verbose\_print, 132
  - writeConfig, 132
- skdaccess::framework::data\_class::DataFetcherLocal
  - \_\_str\_\_, 134
  - ap\_paramList, 137
  - getConfig, 134
  - getDataLocation, 134
  - getMetadata, 134
  - multirun\_enabled, 135
  - output, 135
  - perturb, 135
  - reset, 135
  - setDataLocation, 136
  - verbose, 137
  - verbose\_print, 136
  - writeConfig, 136
- skdaccess::framework::data\_class::DataFetcherStorage
  - \_\_str\_\_, 138
  - ap\_paramList, 141
  - downloadFullDataset, 138
  - getConfig, 139
  - getDataLocation, 139
  - getMetadata, 139
  - multirun\_enabled, 140
  - output, 140
  - perturb, 140
  - reset, 140
  - setDataLocation, 140
  - verbose, 141
  - verbose\_print, 141
  - writeConfig, 141
- skdaccess::framework::data\_class::DataFetcherStream
  - \_\_str\_\_, 143
  - ap\_paramList, 145

- getConfig, 143
- getMetadata, 143
- multirun\_enabled, 143
- output, 143
- perturb, 144
- reset, 144
- retrieveOnlineData, 144
- verbose, 145
- verbose\_print, 145
- writeConfig, 145
- skdaccess::framework::data\_class::DataWrapperBase
  - \_\_init\_\_, 147
  - \_\_len\_\_, 147
  - addResult, 147
  - constants, 149
  - data, 149
  - get, 148
  - getIterator, 148
  - getResults, 148
  - info, 148
  - meta\_data, 150
  - reset, 149
  - results, 150
  - run\_id, 150
  - update, 149
- skdaccess::framework::data\_class::ImageWrapper
  - \_\_len\_\_, 151
  - addResult, 152
  - constants, 154
  - data, 154
  - deleteData, 152
  - get, 152
  - getIterator, 153
  - getResults, 153
  - info, 153
  - meta\_data, 155
  - reset, 153
  - results, 155
  - run\_id, 155
  - update, 154
  - updateData, 154
- skdaccess::framework::data\_class::SeriesDictionary↔
  - Wrapper
  - \_\_len\_\_, 160
  - addResult, 160
  - constants, 163
  - data, 163
  - data\_names, 163
  - error\_names, 163
  - get, 161
  - getIndices, 161
  - getIterator, 161
  - getLength, 161
  - getResults, 162
  - info, 162
  - meta\_data, 163
  - reset, 162
  - results, 163
  - run\_id, 164
  - update, 162
- skdaccess::framework::data\_class::SeriesWrapper
  - \_\_init\_\_, 165
  - \_\_len\_\_, 166
  - addResult, 166
  - constants, 168
  - data, 168
  - data\_names, 169
  - error\_names, 169
  - get, 166
  - getIndices, 166
  - getIterator, 167
  - getLength, 167
  - getResults, 167
  - info, 167
  - meta\_data, 169
  - reset, 168
  - results, 169
  - run\_id, 169
  - update, 168
- skdaccess::framework::data\_class::TableWrapper
  - \_\_init\_\_, 171
  - \_\_len\_\_, 171
  - addColumn, 172
  - addResult, 172
  - constants, 176
  - data, 176
  - default\_columns, 176
  - default\_error\_columns, 176
  - get, 172
  - getDefaultColumns, 173
  - getDefaultErrorColumns, 173
  - getIterator, 173
  - getLength, 173
  - getResults, 174
  - info, 174
  - meta\_data, 176
  - removeFrames, 174
  - reset, 175
  - results, 177
  - run\_id, 177
  - update, 175
  - updateData, 175
  - updateFrames, 176
- skdaccess::framework::data\_class::XArrayWrapper
  - \_\_init\_\_, 178
  - \_\_len\_\_, 179
  - addResult, 179
  - constants, 181

- data, 181
- get, 179
- getIterator, 179
- getResults, 180
- index\_list, 181
- info, 180
- meta\_data, 181
- reset, 180
- results, 181
- run\_id, 181
- update, 180
- skdaccess::framework::param\_class::AutoList
  - \_\_call\_\_, 34
  - \_\_getitem\_\_, 34
  - \_\_init\_\_, 34
  - \_\_len\_\_, 35
  - \_\_setitem\_\_, 35
  - \_\_str\_\_, 35
  - getAllOptions, 36
  - perturb, 36
  - reset, 36
  - val, 36
  - val\_init, 37
  - val\_list, 37
- skdaccess::framework::param\_class::AutoListCycle
  - \_\_call\_\_, 39
  - \_\_getitem\_\_, 39
  - \_\_init\_\_, 38
  - \_\_len\_\_, 39
  - \_\_setitem\_\_, 40
  - \_\_str\_\_, 40
  - getAllOptions, 40
  - index, 41
  - list\_val\_list, 41
  - perturb, 40
  - reset, 41
  - val, 41
  - val\_init, 41
  - val\_list, 42
- skdaccess::framework::param\_class::AutoListPermute
  - \_\_call\_\_, 43
  - \_\_getitem\_\_, 43
  - \_\_len\_\_, 43
  - \_\_setitem\_\_, 44
  - \_\_str\_\_, 44
  - getAllOptions, 44
  - perturb, 45
  - reset, 45
  - val, 45
  - val\_init, 45
  - val\_list, 46
- skdaccess::framework::param\_class::AutoListRemove
  - \_\_call\_\_, 47
  - \_\_getitem\_\_, 47
  - \_\_init\_\_, 47
  - \_\_len\_\_, 48
  - \_\_setitem\_\_, 48
  - \_\_str\_\_, 48
  - getAllOptions, 49
  - n, 50
  - perturb, 49
  - reset, 49
  - val, 49
  - val\_init, 50
  - val\_list, 50
- skdaccess::framework::param\_class::AutoListSubset
  - \_\_call\_\_, 51
  - \_\_getitem\_\_, 51
  - \_\_len\_\_, 52
  - \_\_setitem\_\_, 52
  - \_\_str\_\_, 52
  - getAllOptions, 53
  - perturb, 53
  - reset, 53
  - val, 53
  - val\_init, 54
  - val\_list, 54
- skdaccess::framework::param\_class::AutoParam
  - \_\_call\_\_, 56
  - \_\_init\_\_, 55
  - \_\_str\_\_, 56
  - perturb, 56
  - reset, 56
  - val, 57
  - val\_init, 57
- skdaccess::framework::param\_class::AutoParamList
  - \_\_call\_\_, 58
  - \_\_init\_\_, 58
  - \_\_str\_\_, 58
  - perturb, 59
  - reset, 59
  - val, 59
  - val\_init, 59
  - val\_list, 59
- skdaccess::framework::param\_class::AutoParamListCycle
  - \_\_call\_\_, 61
  - \_\_init\_\_, 61
  - \_\_str\_\_, 61
  - current\_index, 62
  - perturb, 61
  - reset, 62
  - val, 62
  - val\_init, 62
  - val\_list, 62
- skdaccess::framework::param\_class::AutoParamMinMax
  - \_\_call\_\_, 64
  - \_\_init\_\_, 63
  - \_\_str\_\_, 64

- decimals, 65
- n, 65
- n\_max, 65
- perturb, 64
- reset, 65
- val, 65
- val\_init, 65
- val\_max, 66
- val\_min, 66
- skdaccess::geo::gldas::data\_fetcher::DataFetcher
  - \_\_init\_\_, 87
  - \_\_str\_\_, 87
  - ap\_paramList, 91
  - downloadFullDataset, 88
  - end\_date, 91
  - getConfig, 88
  - getDataLocation, 88
  - getMetadata, 89
  - multirun\_enabled, 89
  - output, 89
  - perturb, 89
  - resample, 91
  - reset, 90
  - setDataLocation, 90
  - start\_date, 91
  - verbose, 91
  - verbose\_print, 90
  - writeConfig, 90
- skdaccess::geo::grace::data\_fetcher::DataFetcher
  - \_\_init\_\_, 93
  - \_\_str\_\_, 93
  - ap\_paramList, 97
  - downloadFullDataset, 94
  - end\_date, 97
  - getConfig, 94
  - getDataLocation, 94
  - getMetadata, 95
  - multirun\_enabled, 95
  - output, 95
  - perturb, 95
  - reset, 96
  - setDataLocation, 96
  - start\_date, 97
  - verbose, 97
  - verbose\_print, 96
  - writeConfig, 96
- skdaccess::geo::groundwater::data\_fetcher::DataFetcher
  - \_\_init\_\_, 100
  - \_\_str\_\_, 101
  - ap\_paramList, 104
  - cutoff, 104
  - downloadFullDataset, 101
  - end\_date, 104
  - getConfig, 101
  - getDataLocation, 101
  - getMetadata, 102
  - getStationMetadata, 102
  - multirun\_enabled, 102
  - output, 103
  - perturb, 103
  - reset, 103
  - setDataLocation, 103
  - start\_date, 105
  - verbose, 105
  - verbose\_print, 104
  - writeConfig, 104
- skdaccess::geo::modis::cache::cloud\_mask::data\_fetcher::DataFetcher
  - \_\_init\_\_, 106
- skdaccess::geo::modis::cache::cloud\_opacity::data\_fetcher::DataFetcher
  - \_\_init\_\_, 107
- skdaccess::geo::modis::cache::data\_fetcher::DataFetcher
  - \_\_init\_\_, 69
  - \_\_str\_\_, 70
  - ap\_paramList, 74
  - cacheData, 70
  - daynightboth, 74
  - end\_date, 74
  - find\_data, 71
  - getConfig, 71
  - getDataLocation, 71
  - getHDFStorage, 72
  - getMetadata, 72
  - grid, 74
  - grid\_fill, 75
  - modis\_id, 75
  - modis\_identifier, 75
  - modis\_platform, 75
  - multirun\_enabled, 72
  - output, 72
  - perturb, 73
  - reset, 73
  - setDataLocation, 73
  - start\_date, 75
  - use\_long\_name, 75
  - variable\_list, 75
  - verbose, 76
  - verbose\_print, 74
  - writeConfig, 74
- skdaccess::geo::modis::cache::reflectance::data\_fetcher::DataFetcher
  - \_\_init\_\_, 115
- skdaccess::geo::modis::stream::cloud\_mask::data\_fetcher::DataFetcher
  - \_\_init\_\_, 98
- skdaccess::geo::modis::stream::cloud\_opacity::data\_fetcher::DataFetcher
  - \_\_init\_\_, 98

- \_\_init\_\_, 67
- skdaccess::geo::modis::stream::data\_fetcher::DataFetcher
  - \_\_init\_\_, 109
  - \_\_str\_\_, 109
  - ap\_paramList, 112
  - daynightboth, 112
  - end\_date, 112
  - getConfig, 110
  - getMetadata, 110
  - grid, 113
  - grid\_fill, 113
  - modis\_id, 113
  - modis\_identifier, 113
  - modis\_platform, 113
  - multirun\_enabled, 110
  - output, 110
  - perturb, 111
  - reset, 111
  - retrieveOnlineData, 111
  - start\_date, 113
  - use\_long\_name, 113
  - variable\_list, 114
  - verbose, 114
  - verbose\_print, 112
  - writeConfig, 112
- skdaccess::geo::modis::stream::reflectance::data\_fetcher::DataFetcher
  - \_\_init\_\_, 76
- skdaccess::geo::pbo::data\_fetcher::DataFetcher
  - \_\_init\_\_, 79
  - \_\_str\_\_, 79
  - antenna\_info, 84
  - ap\_paramList, 84
  - default\_columns, 84
  - default\_error\_columns, 84
  - downloadFullDataset, 80
  - getAntennaLogs, 80
  - getConfig, 80
  - getDataLocation, 81
  - getInfo, 81
  - getMetadata, 81
  - getStationMetadata, 82
  - index\_date\_only, 85
  - meta\_data, 85
  - multirun\_enabled, 82
  - output, 82
  - perturb, 82
  - reset, 83
  - setDataLocation, 83
  - setStationList, 83
  - station\_list, 85
  - use\_progress\_bar, 85
  - verbose, 85
  - verbose\_print, 84
  - writeConfig, 84
- skdaccess::utilities::grace\_util
  - averageDates, 16
  - computeEWD, 18
  - dateMismatch, 18
  - getStartEndDate, 19
  - readTellusData, 19
- skdaccess::utilities::gw\_util
  - combine\_water\_heights, 20
- skdaccess::utilities::kepler\_util
  - normalize, 20
- skdaccess::utilities::modis\_util
  - calibrateModis, 21
  - checkBit, 22
  - createGrid, 22
  - getFileIDs, 23
  - getFileURLs, 23
  - getImageType, 24
  - getModisData, 24
  - readMODISData, 25
  - rescale, 25
- skdaccess::utilities::modis\_util::LatLon
  - \_\_call\_\_, 156
  - \_\_init\_\_, 156
  - alat, 158
  - alon, 158
  - lat\_data, 158
  - lon\_data, 158
  - x\_offset, 158
  - y\_offset, 158
- skdaccess::utilities::pbo\_util
  - getLatLonRange, 26
  - getROIstations, 27
  - getStationCoords, 27
  - nostab\_sys, 28
  - propagateErrors, 28
  - removeAntennaOffset, 30
  - stab\_sys, 30
- skdaccess\_script
  - skdaccess::bin::skdaccess, 10
- stab\_sys
  - skdaccess::utilities::pbo\_util, 30
- start\_date
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, 91
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, 97
  - skdaccess::geo::groundwater::data\_fetcher::DataFetcher, 105
  - skdaccess::geo::modis::cache::data\_fetcher::DataFetcher, 75
  - skdaccess::geo::modis::stream::data\_fetcher::DataFetcher, 113

station\_list  
 skdaccess::geo::pbo::data\_fetcher::DataFetcher, 85

update  
 skdaccess::framework::data\_class::DataWrapper↔  
 Base, 149  
 skdaccess::framework::data\_class::ImageWrapper,  
 154  
 skdaccess::framework::data\_class::SeriesDictionary↔  
 Wrapper, 162  
 skdaccess::framework::data\_class::SeriesWrapper,  
 168  
 skdaccess::framework::data\_class::TableWrapper,  
 175  
 skdaccess::framework::data\_class::XArrayWrapper,  
 180

updateData  
 skdaccess::framework::data\_class::ImageWrapper,  
 154  
 skdaccess::framework::data\_class::TableWrapper,  
 175

updateFrames  
 skdaccess::framework::data\_class::TableWrapper,  
 176

use\_long\_name  
 skdaccess::geo::modis::cache::data\_fetcher::Data↔  
 Fetcher, 75  
 skdaccess::geo::modis::stream::data\_fetcher::↔  
 DataFetcher, 113

use\_progress\_bar  
 skdaccess::geo::pbo::data\_fetcher::DataFetcher, 85

utilities/grace\_util.py, 188  
 utilities/gw\_util.py, 189  
 utilities/kepler\_util.py, 189  
 utilities/modis\_util.py, 189  
 utilities/pbo\_util.py, 190

val  
 skdaccess::framework::param\_class::AutoList, 36  
 skdaccess::framework::param\_class::AutoListCycle,  
 41  
 skdaccess::framework::param\_class::AutoList↔  
 Permute, 45  
 skdaccess::framework::param\_class::AutoList↔  
 Remove, 49  
 skdaccess::framework::param\_class::AutoList↔  
 Subset, 53  
 skdaccess::framework::param\_class::AutoParam, 57  
 skdaccess::framework::param\_class::AutoParamList,  
 59  
 skdaccess::framework::param\_class::AutoParam↔  
 ListCycle, 62  
 skdaccess::framework::param\_class::AutoParam↔  
 MinMax, 65

val\_init  
 skdaccess::framework::param\_class::AutoList, 37  
 skdaccess::framework::param\_class::AutoListCycle,  
 41  
 skdaccess::framework::param\_class::AutoList↔  
 Permute, 45  
 skdaccess::framework::param\_class::AutoList↔  
 Remove, 50  
 skdaccess::framework::param\_class::AutoList↔  
 Subset, 54  
 skdaccess::framework::param\_class::AutoParam, 57  
 skdaccess::framework::param\_class::AutoParamList,  
 59  
 skdaccess::framework::param\_class::AutoParam↔  
 ListCycle, 62  
 skdaccess::framework::param\_class::AutoParam↔  
 MinMax, 65

val\_list  
 skdaccess::framework::param\_class::AutoList, 37  
 skdaccess::framework::param\_class::AutoListCycle,  
 42  
 skdaccess::framework::param\_class::AutoList↔  
 Permute, 46  
 skdaccess::framework::param\_class::AutoList↔  
 Remove, 50  
 skdaccess::framework::param\_class::AutoList↔  
 Subset, 54  
 skdaccess::framework::param\_class::AutoParamList,  
 59  
 skdaccess::framework::param\_class::AutoParam↔  
 ListCycle, 62

val\_max  
 skdaccess::framework::param\_class::AutoParam↔  
 MinMax, 66

val\_min  
 skdaccess::framework::param\_class::AutoParam↔  
 MinMax, 66

variable\_list  
 skdaccess::geo::modis::cache::data\_fetcher::Data↔  
 Fetcher, 75  
 skdaccess::geo::modis::stream::data\_fetcher::↔  
 DataFetcher, 114

verbose  
 skdaccess::astro::kepler::data\_fetcher::DataFetcher,  
 122  
 skdaccess::framework::data\_class::DataFetcher↔  
 Base, 127  
 skdaccess::framework::data\_class::DataFetcher↔  
 Cache, 132  
 skdaccess::framework::data\_class::DataFetcher↔  
 Local, 137  
 skdaccess::framework::data\_class::DataFetcher↔  
 Storage, 141  
 skdaccess::framework::data\_class::DataFetcher↔  
 Stream, 145



- skdaccess::geo::gldas::data\_fetcher::DataFetcher, [91](#)
- skdaccess::geo::grace::data\_fetcher::DataFetcher, [97](#)
- skdaccess::geo::groundwater::data\_fetcher::DataFetcher, [105](#)
- skdaccess::geo::modis::cache::data\_fetcher::DataFetcher, [76](#)
- skdaccess::geo::modis::stream::data\_fetcher::DataFetcher, [114](#)
- skdaccess::geo::pbo::data\_fetcher::DataFetcher, [85](#)
- verbose\_print
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, [121](#)
  - skdaccess::framework::data\_class::DataFetcherBase, [125](#)
  - skdaccess::framework::data\_class::DataFetcherCache, [132](#)
  - skdaccess::framework::data\_class::DataFetcherLocal, [136](#)
  - skdaccess::framework::data\_class::DataFetcherStorage, [141](#)
  - skdaccess::framework::data\_class::DataFetcherStream, [145](#)
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, [90](#)
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, [96](#)
  - skdaccess::geo::groundwater::data\_fetcher::DataFetcher, [104](#)
  - skdaccess::geo::modis::cache::data\_fetcher::DataFetcher, [74](#)
  - skdaccess::geo::modis::stream::data\_fetcher::DataFetcher, [112](#)
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, [84](#)
- writeConfig
  - skdaccess::astro::kepler::data\_fetcher::DataFetcher, [121](#)
  - skdaccess::framework::data\_class::DataFetcherBase, [126](#)
  - skdaccess::framework::data\_class::DataFetcherCache, [132](#)
  - skdaccess::framework::data\_class::DataFetcherLocal, [136](#)
  - skdaccess::framework::data\_class::DataFetcherStorage, [141](#)
  - skdaccess::framework::data\_class::DataFetcherStream, [145](#)
  - skdaccess::geo::gldas::data\_fetcher::DataFetcher, [90](#)
  - skdaccess::geo::grace::data\_fetcher::DataFetcher, [96](#)
  - skdaccess::geo::groundwater::data\_fetcher::DataFetcher, [104](#)
  - skdaccess::geo::modis::cache::data\_fetcher::DataFetcher, [74](#)
  - skdaccess::geo::modis::stream::data\_fetcher::DataFetcher, [112](#)
  - skdaccess::geo::pbo::data\_fetcher::DataFetcher, [84](#)
- x\_offset
  - skdaccess::utilities::modis\_util::LatLon, [158](#)
- y\_offset
  - skdaccess::utilities::modis\_util::LatLon, [158](#)