
auxi User Manual

Release 0.3.5rc2

Ex Mente Technologies (Pty) Ltd.

Mar 13, 2017

CONTENTS

1	Introduction	1
2	Getting Started	3
2.1	auxi Installation	3
2.2	Importing auxi Components	3
2.3	Getting Help	4
3	Structure	5
3.1	Tools	5
3.2	Modelling Frameworks	10
4	auxi Reference	49
4.1	auxi package	49
5	Indices and tables	99
	Python Module Index	101
	Index	103

**CHAPTER
ONE**

INTRODUCTION

auxi is a toolkit to help metallurgical process engineers with their day-to-day tasks. Many of the calculations that we do require things like molar masses, conversion of one compound to another using stoichiometry, heat transfer calculations, mass balances, energy balances, etc. It is usually quite time consuming to get started with these calculations in a tool like Excel. auxi aims to save you time by making many of these calculations available from within python.

We hope that auxi will help you spend less time focusing on searching for formulas and data, and setting up calculations, and more on thinking about the problems that you need to solve with these calculations. Enjoy!

For video tutorials on using auxi visit [auxi youtube](#) .

CHAPTER
TWO

GETTING STARTED

auxi Installation

auxi runs on both Linux and Windows.

Prerequisite

NumPy is required to run the auxi.modelling.materials packages. You can follow the instructions at <http://www.scipy.org/install.html> on how to install NumPy.

Installation

To install auxi:

```
* On Linux: sudo pip install auxi  
* On Windows: pip install auxi
```

To uninstall auxi:

```
* On Linux: sudo pip uninstall auxi  
* On Windows: pip uninstall auxi
```

Importing auxi Components

If you want to use auxi in one of your python modules, you need to import its components in the same way that you do for any other python package. For example, to use the stoichiometry tool, you will have to do the following:

```
from auxi.tools.chemistry import stoichiometry
```

The same method is used for all modules, functions and classes in auxi. Here are a few more import examples:

```
from auxi.tools.chemistry.stoichiometry import molar_mass
from auxi.tools.chemistry.stoichiometry import molar_mass as mm
from auxi.tools.chemistry.stoichiometry import convert_compound
from auxi.tools.chemistry.stoichiometry import convert_compound as cc

from auxi.tools.chemistry import thermochemistry
from auxi.tools.chemistry.thermochemistry import Compound
```

Getting Help

You can use Python's standard help function on any of auxi's components. For example:

```
import auxi
help(auxi)

from auxi.tools.chemistry import stoichiometry

help(stoichiometry)
help(stoichiometry.molar_mass)
help(stoichiometry.convert_compound)
```

All the help information that you are able to access in this way are also available through auxi's HTML documentation that is included in the auxi Python package distribution.

CHAPTER THREE

STRUCTURE

auxi is a Python package, and it is currently divided into two main sub-packages, namely tools and modelling. The tools package provides help with simple tasks like calculating molar masses, enthalpies of heat capacities. The modelling package helps you to do more sophisticated calculations, and to build process models.

Tools

This package currently only contains a single set of tools, namely for chemistry calculations.

Chemistry Tools

The auxi.tools.chemistry package contains modules, functions and classes for doing chemical calculations. Specifically, the package contains a module called “stoichiometry” for doing stoichiometry calculations, and another called “thermochemistry” for doing thermochemical calculations.

Chemical Calculations

The auxi.tools.chemistry sub-package provides you with modules, classes and functions to do chemical calculations. The calculations are divided into the categories of stoichiometry and thermochemistry.

Thermochemical Calculations

Preparing Thermochemical Data

The auxi.tools.chemistry.thermochemistry module provides a number of useful functions for doing thermochemical calculations that would otherwise have been quite cumbersome to do. To make these calculations possible, some thermochemical data is needed. The `auxi` distribution package currently contains data for around 80 compounds. This may, however, not be sufficient for your process calculations. FactSage data can be converted into

auxi thermochemical data using the `convert_fact_file_to_auxi_thermo_file()` function.

To prepare your own compound data files with FactSage, follow these steps:

- Open FactSage.
- Click on the “View Data” button.
- Select the “Compound” option, NOT “Solution”.
- Select the database that you want to use. “FactPS” should be OK.
- Type the formula of the compound you need in the box at the bottom.
- Click OK.
- Click on the “Cp(T)” tab.
- Select “File” from the menu and then “Save As ...”.
- Select the folder where you want to store all your thermochemical data files.
- The filename must have a specific format. Taking “Ar” as an example, use “Compound_Ar.txt” for the file name.
- Click “Save”.

You will have to repeat this procedure for all the compounds that you need to include in your calculations.

To convert the factsage file to an auxi thermochemical file use the following code:

```
from auxi.tools.chemistry import thermochemistry as thermo
thermo.convert_fact_file_to_auxi_thermo_file("path/to/factsage_file"
                                          ↵", "path/to/new_auxi_thermo_file")
```

Loading Thermochemical Data

If you are going to use the default set of data provided with `auxi`, you do not need to do anything. The entire data set will be available by default. You can obtain a list of all the compounds and their phases by using the following code:

```
from auxi.tools.chemistry import thermochemistry as thermo
thermo.list_compounds()
```

Here are the first few lines of the result:

```
Compounds currently loaded in the thermochemistry module:
Ag ['G', 'L', 'S']
Ag2O ['S']
Al ['G', 'L', 'S']
Al2O3 ['G', 'L', 'S1', 'S2', 'S3', 'S4']
```

```
A14C3 ['S1']
C ['G', 'S1', 'S2']
C2H2 ['G']
CH4 ['Aq', 'G']
CO ['G']
CO2 ['G']
...
```

The result lists all the compounds with the phases for which data are available. Taking the compound SiO₂ as an example, data are available for eight solid phases (S1 to S8), for the liquid phase and for the gas phase.

If you have decided to create your own data folder, you can force *auxi* to use the data in that folder. Here is the code for this:

```
from auxi.tools.chemistry import thermochemistry as thermo

thermo.load_data('/home/someuser/thermodata')
thermo.list_compounds()
```

This example data folder only contains a small selection of files:

```
Compounds currently loaded in the thermo module:
Ag ['G', 'L', 'S']
CaO ['G', 'L', 'S']
Cr2O3 ['L', 'S']
Cu ['G', 'L', 'S']
CuO ['G', 'S']
```

Calculating Heat Capacity

The `Cp()` function in the `auxi.tools.chemistry.thermochemistry` module can be used to calculate the heat capacity at constant pressure for a compound. This can be done as follows:

```
from auxi.tools.chemistry import thermochemistry as thermo

Cp_H2O = thermo.Cp("H2O[L]", 70.0)
print("The Cp of 1 kg of water at 70 °C is", Cp_H2O, "kWh/K.")

Cp_H2O = thermo.Cp("H2O[G]", 70.0)
print("The Cp of 1 kg of water vapour at 70 °C is", Cp_H2O, "kWh/K.

m_ZrO2 = 2.34
Cp_ZrO2 = thermo.Cp("ZrO2[S1]", 893.5, m_ZrO2)
print("The Cp of 2.34 kg of ZrO2[S1] at 893.5 °C is", Cp_ZrO2, "kWh/
K.")
```

Here are the results:

```
The Cp of 1 kg of water at 70 °C is 0.0011634065724223574 kWh/K.  
The Cp of 1 kg of water vapour at 70 °C is 0.0005217114220395267 ↵kWh/K.  
The Cp of 2.34 kg of ZrO2[S1] at 70 °C is 0.0004084615851157184 kWh/ ↵K.
```

The first parameter to the function must specify both the compound's formula and phase. If the phase is not specified it is impossible to calculate a result. The heat capacity of water is clearly significantly different from that of water vapour.

The last parameter of the `Cp()` is mass and it is optional. If no value is specified, it is taken to be 1 kg. This was the case for the first two calculations above. A mass of 2.34 kg was specified in the last `Cp` calculation.

Calculating Enthalpy

The `H()` function in thermochemistry is used to calculate the enthalpy of a compound. This can be done as follows:

```
from auxi.tools.chemistry import thermochemistry as thermo

H_H2O = thermo.H("H2O[L]", 70.0)
print("The enthalpy of 1 kg of water at 70 °C is", H_H2O, "kWh.")

H_H2O = thermo.H("H2O[G]", 70.0)
print("The enthalpy of 1 kg of water vapour at 70 °C is", H_H2O,
      "kWh.")

m_ZrO2 = 2.34
H_ZrO2 = thermo.H("ZrO2[S1]", 893.5, m_ZrO2)
print("The enthalpy of 2.34 kg of ZrO2[S1] at 893.5 °C is", H_ZrO2,
      "kWh.")
```

Here are the results:

```
The enthalpy of 1 kg of water at 70 °C is -4.35495670039936 kWh.  
The enthalpy of 1 kg of water vapour at 70 °C is -3.  
    ↵7054553712406264 kWh.  
The enthalpy of 2.34 kg of ZrO2[S1] at 893.5 °C is -5.  
    ↵463105585819936 kWh.
```

The parameters to the `H()` function works the same as that of the `Cp()` function. Both formula and phase are required in the first parameter, the second is temperature in °C and the third is mass, which is optional with a default value of 1 kg.

Calculating Entropy

The `S()` function in `thermochemistry` is used to calculate the entropy of a compound. This can be done as follows:

```
from auxi.tools.chemistry import thermo

S_H2O = thermo.S("H2O[L]", 70.0)
print("The entropy of 1 kg of water at 70 °C is", S_H2O, "kWh/K.")

S_H2O = thermo.S("H2O[G]", 70.0)
print("The entropy of 1 kg of water vapour at 70 °C is", S_H2O,
      "kWh/K.")

m_ZrO2 = 2.34
S_ZrO2 = thermo.S("ZrO2[S1]", 893.5, m_ZrO2)
print("The entropy of 2.34 kg of ZrO2[S1] at 893.5 °C is", S_ZrO2,
      "kWh/K.")
```

Here are the results:

```
The entropy of 1 kg of water at 70 °C is 0.0012418035680941087 kWh/
      ←K.
The entropy of 1 kg of water vapour at 70 °C is 0.
      ←0029829908763826032 kWh/K.
The entropy of 2.34 kg of ZrO2[S1] at 893.5 °C is 0.
      ←000762164298048799 kWh/K.
```

The parameters to the `S()` function works the same as that of the `Cp()` function. Both formula and phase are required in the first parameter, the second is temperature in °C and the third is mass, which is optional with a default value of 1 kg.

Calculating Gibbs Free Energy

The `G()` function in `thermochemistry` is used to calculate the Gibbs free energy of a compound. This can be done as follows:

```
from auxi.tools.chemistry import thermo

G_H2O = thermo.G("H2O[L]", 70.0)
print("The Gibbs free energy of 1 kg of water at 70 °C is", G_H2O,
      "kWh.")

G_H2O = thermo.G("H2O[G]", 70.0)
print("The Gibbs free energy of 1 kg of water vapour at 70 °C is", ←
      G_H2O,
      "kWh.")

m_ZrO2 = 2.34
```

```
G_ZrO2 = thermo.G("ZrO2[S1]", 893.5, m_ZrO2)
print("The Gibbs free energy of 2.34 kg of ZrO2[S1] at 893.5 °C is",
    ↪ G_ZrO2,
    "kWh.")
```

Here are the results:

```
The Gibbs free energy of 1 kg of water at 70 °C is
-4.781081594790853 kWh.
The Gibbs free energy of 1 kg of water vapour at 70 °C is
-4.729068690471317 kWh.
The Gibbs free energy of 2.34 kg of ZrO2[S1] at 893.5 °C is
-6.352284564138569 kWh.
```

The parameters to the `G()` function works the same as that of the `Cp()` function. Both formula and phase are required in the first parameter, the second is temperature in °C and the third is mass, which is optional with a default value of 1 kg.

Material Physical Properties Tools

The `auxi.tools.transportphenomena` package provides tools to calculate material physical properties.

Transport Phenomena Tools

The `auxi.tools.transportphenomena` package provides tools to do calculations related to heat transfer, mass transfer, and fluid flow.

Heat transfer Calculations

The `auxi.tools.transportphenomena` sub-package provides tools to do calculations related to heat transfer.

Modelling Frameworks

This package contains modules, functions and classes for developing different types of computational models.

Process Modelling

The `auxi.modelling.process` package contains modules, functions and classes for performing process modelling. Specifically, the package contains a module called “materials” for modelling materials.

Material Modelling

The auxi.modelling.process sub-package provides you with modules, classes and functions to model process. The process modelling package contains material models.

Material Modelling

The auxi.modelling.process.materials package contains modules, functions and classes that help perform material-related calculations and build process models. Specifically, the package contains a module called “chemistry” for a material and material package that can perform chemistry calculations, another called “psd” for a particulate material and material package that can do size distribution as well as a material and material package that can, in addition, perform slurry calculations, and another called “thermochemistry” that contains a material consisting of multiple chemical compounds, having the ability to do thermochemical calculations.

Material Models

The auxi.modelling.process.materials sub-package provides you with modules, classes and functions to do material modelling. The material models are divided into chemical, psd and thermochemistry.

Concepts

Motivation

The material, material assay and material package concepts used in *auxi.modelling.process.materials* may initially seem somewhat foreign to new users. These concepts were developed to assist process engineers when doing metallurgical calculations, and while developing process models. It aims to reduce the complexity and time involved in performing these important but sometimes tedious tasks. Once these concepts have been mastered, they become incredibly powerful in the hands of a metallurgical process engineer.

Materials, Material Assays and Material Packages

auxi.modelling.process.materials includes a number of different representations of materials, material assays and material packages, each of which is contained in a separate Python module. The different modules cater for different situations as follows:

- auxi.modelling.process.materials.psd describes materials using particle size distributions. It can be used for processes in which particle size is the most important material property, such as a comminution circuit.
- auxi.modelling.process.materials.slurry adds water to psd. It can describe the solid and liquid portion of a particulate process such as a comminution circuit.

- auxi.modelling.process.materials.chem can be used for doing mass balances in chemically reactive processes such as leaching, precipitation, direct reduction and smelting. Its material class describes a material using its chemical composition. This module cannot perform any energy balance calculations.
- auxi.modelling.process.materials.thermo adds thermochemistry to chem. It can be used to do mass and energy balances in chemically reactive system such as smelting furnaces, direct reduction kilns, etc.

The auxi.modelling.process.materials.thermo module will be used to illustrate the concepts here.

Material

A Material class is used to represent a “type of material”. Examples are ilmenite, iron ore, coal, ferrochrome alloy, etc. These terms are fairly abstract and generic, since they don’t refer to something specific. The thermo module’s Material class uses a list of specific phases of chemical compounds to describe a “type of material”. Here are some examples:

=====		=====	
Material		Material	
=====		=====	
Name	Ilmenite	Name	Coal
Compound		Compound	
Al2O3 [S1]		C [S1]	
CaO [S]		H2 [G]	
Cr2O3 [S]		O2 [G]	
Fe2O3 [S1]		N2 [G]	
Fe3O4 [S1]		S [S1]	
FeO [S]		Al2O3 [S1]	
K2O [S]		CaO [S]	
MgO [S]		Fe2O3 [S1]	
MnO [S]		MgO [S]	
Na2O [S1]		SiO2 [S1]	
P4O10 [S]		=====	
SiO2 [S1]			
TiO2 [S1]			
V2O5 [S]			
=====			

With the Ilmenite material we are specifying that, in our model or calculation, ilmenites will consist of the 14 compounds included in the first list. In the case of Coal, different coals will consist of the 10 compounds listed in the second list.

Material Assay

When we need to develop a model or do some calculations, it is not sufficient to simply know that a “type of material”, such as ilmenite or coal, can consist of a specified list of compound phases. We need to know what the composition of a “specific material” is. With this composition we will be able to get started on some calculations. This is where material assays come in. In the next example, assays were added to the two materials defined above:

=====						
Material			=====			
=====						
Name	Ilmenite					
=====						
Composition Details (mass fractions)						
Compound	IlmeniteA	IlmeniteB	IlmeniteC			
=====						
Al ₂ O ₃ [S1]	1.16000000e-02	1.55000000e-02	9.41000000e-03			
CaO [S]	2.20000000e-04	1.00000000e-05	1.70000000e-04			
Cr ₂ O ₃ [S]	8.00000000e-05	2.20000000e-04	1.10000000e-04			
Fe ₂ O ₃ [S1]	2.02000000e-01	4.73000000e-01	4.96740000e-01			
Fe ₃ O ₄ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00			
FeO [S]	2.79000000e-01	1.91000000e-01	0.00000000e+00			
K ₂ O [S]	4.00000000e-05	1.00000000e-05	5.00000000e-05			
MgO [S]	1.04000000e-02	5.80000000e-03	1.09000000e-02			
MnO [S]	5.40000000e-03	4.80000000e-03	5.25000000e-03			
Na ₂ O [S1]	7.00000000e-05	5.00000000e-05	3.10000000e-04			
P ₄ O ₁₀ [S]	1.00000000e-05	3.20000000e-04	1.50000000e-04			
SiO ₂ [S1]	8.50000000e-03	4.90000000e-03	1.74400000e-02			
TiO ₂ [S1]	4.77000000e-01	2.94000000e-01	4.59490000e-01			
V ₂ O ₅ [S]	3.60000000e-03	8.00000000e-03	0.00000000e+00			
=====						
=====						
Name	Coal					
=====						
Composition Details (mass fractions)						
Compound	ReductantA	ReductantB				
=====						
C [S1]	8.40973866e-01	1.00000000e+00				
H ₂ [G]	1.37955186e-02	0.00000000e+00				
O ₂ [G]	4.94339606e-02	0.00000000e+00				
N ₂ [G]	6.09802120e-03	0.00000000e+00				
S [S1]	2.04933390e-03	0.00000000e+00				
Al ₂ O ₃ [S1]	1.20884160e-03	0.00000000e+00				
CaO [S]	2.94179980e-03	0.00000000e+00				
Fe ₂ O ₃ [S1]	7.85955656e-02	0.00000000e+00				
MgO [S]	1.41179360e-03	0.00000000e+00				

SiO ₂ [S1]	3.49129950e-03	0.00000000e+00
=====		

Our Ilmenite material now has three assays associated with it, and they are named IlmeniteA, IlmeniteB and IlmeniteC. Ilmenite therefore refers to a “type of material”, and IlmeniteA, IlmeniteB and IlmeniteC refer to “specific materials”.

Two assays were added to our Coal material. The first, ReductantA, refers to a coal with 84 % carbon and roughly 8.5 % ash. Reductant B is pure graphite.

Material Packages

Using `auxi.modelling.process` we can now create a certain quantity of a “specific material” that is identified by a material and material assay. When we do this with the `thermo` Material class, we also have to specify pressure and temperature. The result of creating 1000 kg of IlmeniteB at 1 atm pressure and 500 °C temperature is the following:

=====	MaterialPackage	=====
=====		
Material	Ilmenite	
Mass	1.00000000e+03 kg	
Amount	9.81797715e+00 kmol	
Pressure	1.00000000e+00 atm	
Temperature	5.00000000e+02 °C	
Enthalpy	-1.87069549e+03 kWh	
=====	Compound Details:	=====
Formula	Mass	Mass Fraction Mole Fraction
=====	=====	=====
Al ₂ O ₃ [S1]	1.55371337e+01	1.55371337e-02 1.55207829e-02
CaO [S]	1.00239573e-02	1.00239573e-05 1.82066196e-05
Cr ₂ O ₃ [S]	2.20527060e-01	2.20527060e-04 1.47782739e-04
Fe ₂ O ₃ [S1]	4.74133178e+02	4.74133178e-01 3.02416515e-01
Fe ₃ O ₄ [S1]	0.00000000e+00	0.00000000e+00 0.00000000e+00
FeO [S]	1.91457584e+02	1.91457584e-01 2.71429867e-01
K ₂ O [S]	1.00239573e-02	1.00239573e-05 1.08388880e-05
MgO [S]	5.81389521e+00	5.81389521e-03 1.46923993e-02
MnO [S]	4.81149948e+00	4.81149948e-03 6.90848565e-03
Na ₂ O [S1]	5.01197863e-02	5.01197863e-05 8.23650657e-05
P ₄ O ₁₀ [S]	3.20766632e-01	3.20766632e-04 1.15084949e-04
SiO ₂ [S1]	4.91173906e+00	4.91173906e-03 8.32630400e-03
TiO ₂ [S1]	2.94704343e+02	2.94704343e-01 3.75840583e-01
V ₂ O ₅ [S]	8.01916581e+00	8.01916581e-03 4.49078466e-03
=====	=====	=====

In the above result some of the useful work that `auxi.modelling.process.materials` does behind the scenes is already evident. The amount in kmol and the enthalpy in kWh of the material package was calculated, as were the masses and mole fractions of the compounds.

You will notice that the mass fractions in the material package is slightly different from those in the IlmeniteB material assay. This is because the assay was automatically normalised to add up to 1.0. You can switch off normalisation if that is more appropriate.

Summary

The `auxi.modelling.process.materials` concepts described above can be summarised as follows:

- A material provides a list of properties that describes a “type of material”.
- A material assay describes a “specific material” by providing values for the listed properties.
- A material package describes a “specific quantity of material” belonging to a certain “type of material”.

You may be wondering what the use of all this is. Why go through all the effort of defining materials, material assays and material packages? The next section demonstrates the power of these concepts.

Material Package Calculations

The use of materials and material packages are demonstrated here through the use of code snippets and the results produced by that code. We will be using ilmenite in the example. Firstly, let us import the `:py:class:`auxi.modelling.process.materials.thermo.Material`` class, create a material object and print it out:

```
from auxi.modelling.process.materials.thermo import Material

ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
print(ilmenite)
```

The material looks as follows:

=====			
Material			
=====			
Name	Ilmenite		

Composition Details (mass fractions)			
Compound	IlmeniteA	IlmeniteB	IlmeniteC

Al2O3[S1]	1.16000000e-02	1.55000000e-02	9.41000000e-03
CaO[S]	2.20000000e-04	1.00000000e-05	1.70000000e-04
Cr2O3[S]	8.00000000e-05	2.20000000e-04	1.10000000e-04
Fe2O3[S1]	2.02000000e-01	4.73000000e-01	4.96740000e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	2.79000000e-01	1.91000000e-01	0.00000000e+00
K2O[S]	4.00000000e-05	1.00000000e-05	5.00000000e-05

MgO [S]	1.04000000e-02	5.80000000e-03	1.09000000e-02
MnO [S]	5.40000000e-03	4.80000000e-03	5.25000000e-03
Na ₂ O [S1]	7.00000000e-05	5.00000000e-05	3.10000000e-04
P ₄ O ₁₀ [S]	1.00000000e-05	3.20000000e-04	1.50000000e-04
SiO ₂ [S1]	8.50000000e-03	4.90000000e-03	1.74400000e-02
TiO ₂ [S1]	4.77000000e-01	2.94000000e-01	4.59490000e-01
V ₂ O ₅ [S]	3.60000000e-03	8.00000000e-03	0.00000000e+00
<hr/>			

Creating, Adding and Extracting

Next we can use the material object (called ilmenite) to create a material package using each of the ilmenite assays:

```
ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.  
                                     ↵0)  
print(ilma_package)  
ilmb_package = ilmenite.create_package("IlmeniteB", 500.0, 1.0, 750.  
                                     ↵0)  
print(ilmb_package)  
ilmc_package = ilmenite.create_package("IlmeniteC", 250.0, 1.0,  
                                     ↵1200.0)  
print(ilmc_package)
```

Different masses were created from each assay (300 kg of IlmeniteA, 500.0 kg of IlmeniteB and 250.0 kg of IlmeniteC). All three packages were assigned a pressure of 1 atm, which is of no consequence. The packages were assigned temperatures of 25, 750 and 1200 °C respectively. In three short lines of code, `auxi.modelling.process.materials` did the following for us:

- Normalise the specified assay so that the mass fractions add up to 1.0. (We can choose not to do this.)
- Calculate the mass of each compound by multiplying the component mass fraction by the total package mass.
- Calculate the mass fraction of each compound.
- Calculate the mole fraction of each compound.
- Calculate the total amount (in kmol) of components in the package.
- Calculate the total enthalpy of the package by calculating the enthalpy of each compound and adding it together.

The result is as follows:

```
=====  
MaterialPackage  
=====  
Material           Ilmenite
```

Mass	3.00000000e+02	kg	
Amount	3.52817004e+00	kmol	
Pressure	1.00000000e+00	atm	
Temperature	2.50000000e+01	°C	
Enthalpy	-6.87812118e+02	kWh	
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
<hr/>			
Al2O3[S1]	3.48725349e+00	1.16241783e-02	9.69390473e-03
CaO[S]	6.61375661e-02	2.20458554e-04	3.34280337e-04
Cr2O3[S]	2.40500241e-02	8.01667468e-05	4.48486990e-05
Fe2O3[S1]	6.07263107e+01	2.02421036e-01	1.07784066e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	8.38744589e+01	2.79581530e-01	3.30892788e-01
K2O[S]	1.20250120e-02	4.00833734e-05	3.61829148e-05
MgO[S]	3.12650313e+00	1.04216771e-02	2.19865404e-02
MnO[S]	1.62337662e+00	5.41125541e-03	6.48625791e-03
Na2O[S1]	2.10437710e-02	7.01459035e-05	9.62343053e-05
P4O10[S]	3.00625301e-03	1.00208434e-05	3.00142421e-06
SiO2[S1]	2.55531506e+00	8.51771685e-03	1.20540764e-02
TiO2[S1]	1.43398268e+02	4.77994228e-01	5.08901291e-01
V2O5[S]	1.08225108e+00	3.60750361e-03	1.68652807e-03
<hr/>			
<hr/>			
MaterialPackage			
<hr/>			
Material	Ilmenite		
Mass	5.00000000e+02	kg	
Amount	4.90898858e+00	kmol	
Pressure	1.00000000e+00	atm	
Temperature	7.50000000e+02	°C	
Enthalpy	-9.05451326e+02	kWh	
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
<hr/>			
Al2O3[S1]	7.76856687e+00	1.55371337e-02	1.55207829e-02
CaO[S]	5.01197863e-03	1.00239573e-05	1.82066196e-05
Cr2O3[S]	1.10263530e-01	2.20527060e-04	1.47782739e-04
Fe2O3[S1]	2.37066589e+02	4.74133178e-01	3.02416515e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	9.57287918e+01	1.91457584e-01	2.71429867e-01
K2O[S]	5.01197863e-03	1.00239573e-05	1.08388880e-05
MgO[S]	2.90694760e+00	5.81389521e-03	1.46923993e-02
MnO[S]	2.40574974e+00	4.81149948e-03	6.90848565e-03
Na2O[S1]	2.50598931e-02	5.01197863e-05	8.23650657e-05
P4O10[S]	1.60383316e-01	3.20766632e-04	1.15084949e-04
SiO2[S1]	2.45586953e+00	4.91173906e-03	8.32630400e-03

```

TiO2[S1]           1.47352172e+02  2.94704343e-01  3.75840583e-01
V2O5[S]            4.00958290e+00  8.01916581e-03   4.49078466e-03
=====
=====
MaterialPackage
=====
Material          Ilmenite
Mass              2.50000000e+02 kg
Amount            2.40014670e+00 kmol
Pressure          1.00000000e+00 atm
Temperature       1.20000000e+03 °C
Enthalpy          -5.25247309e+02 kWh
-----
Compound Details
Formula          Mass      Mass Fraction    Mole Fraction
-----
Al2O3[S1]         2.35245295e+00  9.40981180e-03  9.61275553e-03
CaO[S]            4.24991500e-02   1.69996600e-04  3.15758164e-04
Cr2O3[S]          2.74994500e-02   1.09997800e-04  7.53824179e-05
Fe2O3[S1]         1.24182516e+02   4.96730065e-01  3.24003606e-01
Fe3O4[S1]         0.00000000e+00   0.00000000e+00  0.00000000e+00
FeO[S]             0.00000000e+00   0.00000000e+00  0.00000000e+00
K2O[S]             1.24997500e-02   4.99990000e-05  5.52880254e-05
MgO[S]             2.72494550e+00   1.08997820e-02  2.81687499e-02
MnO[S]             1.31247375e+00   5.24989500e-03  7.70863128e-03
Na2O[S1]           7.74984500e-02   3.09993800e-04  5.20968045e-04
P4O10[S]           3.74992500e-02   1.49997000e-04  5.50346434e-05
SiO2[S1]           4.35991280e+00   1.74396512e-02  3.02328445e-02
TiO2[S1]           1.14870203e+02   4.59480810e-01  5.99250982e-01
V2O5[S]            0.00000000e+00   0.00000000e+00  0.00000000e+00
=====
```

We can now add these three packages of ilmenite together:

```

total_package = ilma_package + ilmb_package + ilmc_package
print(total_package)

```

In one line of code we did the following:

- Calculate the total mass of each component by adding up the component masses from the three original packages.
- Calculate the mass fraction of each compound.
- Calculate the mole fraction of each compound.
- Calculate the total amount (in kmol) of compounds in the package.
- Calculate the total enthalpy of the package by adding up the enthalpies from the three original packages.
- Calculate the temperature of the new package.

This new package (total_package) looks like this:

```
=====
MaterialPackage
=====
Material           Ilmenite
Mass              1.05000000e+03 kg
Amount            1.08373053e+01 kmol
Pressure          1.00000000e+00 atm
Temperature       6.61513374e+02 °C
Enthalpy          -2.11851075e+03 kWh
-----
Compound Details
Formula          Mass      Mass Fraction   Mole Fraction
-----
Al2O3[S1]        1.36082733e+01 1.29602603e-02 1.23153413e-02
CaO[S]           1.13648695e-01 1.08236852e-04 1.87005885e-04
Cr2O3[S]         1.61813004e-01 1.54107623e-04 9.82371950e-05
Fe2O3[S1]        4.21975416e+02 4.01881349e-01 2.43833300e-01
Fe3O4[S1]        0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]           1.79603251e+02 1.71050715e-01 2.30674699e-01
K2O[S]           2.95367407e-02 2.81302292e-05 2.89340215e-05
MgO[S]           8.75839623e+00 8.34132975e-03 2.00516825e-02
MnO[S]           5.34160012e+00 5.08723821e-03 6.94823498e-03
Na2O[S1]         1.23602114e-01 1.17716299e-04 1.84018059e-04
P4O10[S]         2.00888819e-01 1.91322685e-04 6.52958859e-05
SiO2[S1]         9.37109739e+00 8.92485465e-03 1.43915687e-02
TiO2[S1]         4.05620643e+02 3.86305374e-01 4.68638424e-01
V2O5[S]          5.09183399e+00 4.84936570e-03 2.58325918e-03
=====
```

We can easily extract a part of a material package into a new one. Let us remove 30 kg from the new package and store it in a new package:

```
dust_package = total_package.extract(30.0)
print(dust_package)
print(total_package)
```

By using one line of code we subtracted 30 kg of material from the original package and created a new one containing the subtracted 30 kg. All the other properties (e.g component masses, total amount and enthalpy) of the two packages were also recalculated. The extracted 30 kg package looks like this:

```
=====
MaterialPackage
=====
Material           Ilmenite
Mass              3.00000000e+01 kg
Amount            3.09637295e-01 kmol
Pressure          1.00000000e+00 atm
Temperature       6.61513374e+02 °C
=====
```

Enthalpy	-6.05288787e+01	kWh	
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
Al2O3[S1]	3.88807809e-01	1.29602603e-02	1.23153413e-02
CaO[S]	3.24710557e-03	1.08236852e-04	1.87005885e-04
Cr2O3[S]	4.62322868e-03	1.54107623e-04	9.82371950e-05
Fe2O3[S1]	1.20564405e+01	4.01881349e-01	2.43833300e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	5.13152145e+00	1.71050715e-01	2.30674699e-01
K2O[S]	8.43906876e-04	2.81302292e-05	2.89340215e-05
MgO[S]	2.50239892e-01	8.34132975e-03	2.00516825e-02
MnO[S]	1.52617146e-01	5.08723821e-03	6.94823498e-03
Na2O[S1]	3.53148898e-03	1.17716299e-04	1.84018059e-04
P4O10[S]	5.73968055e-03	1.91322685e-04	6.52958859e-05
SiO2[S1]	2.67745640e-01	8.92485465e-03	1.43915687e-02
TiO2[S1]	1.15891612e+01	3.86305374e-01	4.68638424e-01
V2O5[S]	1.45480971e-01	4.84936570e-03	2.58325918e-03
<hr/>			

The original package, which now contains 30 kg less, now looks like this:

Material	Ilmenite		
Mass	1.02000000e+03 kg		
Amount	1.05276680e+01 kmol		
Pressure	1.00000000e+00 atm		
Temperature	6.61513374e+02 °C		
Enthalpy	-2.05798187e+03 kWh		
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
Al2O3[S1]	1.32194655e+01	1.29602603e-02	1.23153413e-02
CaO[S]	1.10401589e-01	1.08236852e-04	1.87005885e-04
Cr2O3[S]	1.57189775e-01	1.54107623e-04	9.82371950e-05
Fe2O3[S1]	4.09918976e+02	4.01881349e-01	2.43833300e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	1.74471729e+02	1.71050715e-01	2.30674699e-01
K2O[S]	2.86928338e-02	2.81302292e-05	2.89340215e-05
MgO[S]	8.50815634e+00	8.34132975e-03	2.00516825e-02
MnO[S]	5.18898297e+00	5.08723821e-03	6.94823498e-03
Na2O[S1]	1.20070625e-01	1.17716299e-04	1.84018059e-04
P4O10[S]	1.95149139e-01	1.91322685e-04	6.52958859e-05
SiO2[S1]	9.10335175e+00	8.92485465e-03	1.43915687e-02
TiO2[S1]	3.94031481e+02	3.86305374e-01	4.68638424e-01
V2O5[S]	4.94635301e+00	4.84936570e-03	2.58325918e-03

Summary

All the other capabilities of the `auxi.modelling.process.materials.thermomaterial.Material` class are not demonstrated here, since the purpose of this section is simply to introduce you to the material, material assay and material package concepts in `auxi.modelling.process.materials`. For full details on how to use the different Material and MaterialPackage classes and objects, refer to the following section:

- `section_chemistry_material_calculations`
- `section_psd_material_calculations`
- `section_psd_slurry_material_calculations`
- *thermochemistry material Calculations*

The final point to make is that the classes in `auxi.modelling.process.materials` can assist you in performing large numbers of metallurgical calculations with very few lines of code. The purpose of this is to focus you on the process concepts rather than entangle you in the detail of tens or hundreds of stoichiometry and thermochemical calculations. This should keep your code clean and your mind clear, getting the job done well in a short space of time.

thermochemistry material Calculations

The purpose of this section is to explain a number of concepts and demonstrate the use of the Material and MaterialPackage classes in the `auxi.modelling.process.materials.thermo` module.

Material Description Files

You need to create one or more material description files (MDFs) before you can create a material object in Python. Material description data are stored in simple text files with ".txt" extensions. The most simple format of such a file is the "mix.txt" file shown here:

```
Compound
Al2O3 [S1]
C [S1]
CaO [S]
Cr2O3 [S]
Fe2O3 [S1]
Fe3O4 [S1]
FeO [S]
H2 [G]
K2O [S]
MgO [S]
```

```
MnO[S]  
Na2O[S1]  
N2[G]  
O2[G]  
P4O10[S]  
S[S1]  
SiO2[S1]  
TiO2[S1]  
V2O5[S]
```

The file contains a header row, which in this case only contains the word “Compound”. All subsequent rows contain chemical compound phases. For example, the second line contains the S1 phase of Al₂O₃. When you consult FactSage, you will see that S1 refers to the gamma phase. The third line contains the graphite phase of carbon, and so forth. The purpose of this file is to tell *auxi* that materials based on this MDF will contain these compound phases, and nothing else.

Material description files can also contain material assays. The content of the “ilmenite.txt” MDF is shown here:

Compound	IlmeniteA	IlmeniteB	IlmeniteC
Al ₂ O ₃ [S1]	0.01160	0.01550	0.00941
CaO[S]	0.00022	0.00001	0.00017
Cr ₂ O ₃ [S]	0.00008	0.00022	0.00011
Fe ₂ O ₃ [S1]	0.20200	0.47300	0.49674
Fe ₃ O ₄ [S1]	0.00000	0.00000	0.00000
FeO[S]	0.27900	0.19100	0.00000
K ₂ O[S]	0.00004	0.00001	0.00005
MgO[S]	0.01040	0.00580	0.01090
MnO[S]	0.00540	0.00480	0.00525
Na ₂ O[S1]	0.00007	0.00005	0.00031
P ₄ O ₁₀ [S]	0.00001	0.00032	0.00015
SiO ₂ [S1]	0.00850	0.00490	0.01744
TiO ₂ [S1]	0.47700	0.29400	0.45949
V ₂ O ₅ [S]	0.00360	0.00800	0.00000

The first row still contains the word “Compound” as header for the list of compound phases. The subsequent words in the first row are assay names. **An assay name may not contain space or tab characters.** If it does, it will be interpreted as more than one name.

The first column of the file has the same meaning as the single column in the “mix.txt” file. It is a list of chemical compound phases that are allowed in materials based on this MDF. All subsequent columns contain assay information. Generally the numbers are mass fractions of the different component phases for the respective material assays. If you will be normalising your assays, the numbers can be masses, percentages or mass fractions, since they will be converted to mass fractions by normalisation.

There is more twist in the MDF tale. You can add your own custom material properties to the file. The “ilmenite.txt” file was modified to include prices for the different ilmenites:

Compound	IlmeniteA	IlmeniteB	IlmeniteC
Al ₂ O ₃ [S1]	0.01160	0.01550	0.00941
CaO[S]	0.00022	0.00001	0.00017
Cr ₂ O ₃ [S]	0.00008	0.00022	0.00011
Fe ₂ O ₃ [S1]	0.20200	0.47300	0.49674
Fe ₃ O ₄ [S1]	0.00000	0.00000	0.00000
FeO[S]	0.27900	0.19100	0.00000
K ₂ O[S]	0.00004	0.00001	0.00005
MgO[S]	0.01040	0.00580	0.01090
MnO[S]	0.00540	0.00480	0.00525
Na ₂ O[S1]	0.00007	0.00005	0.00031
P ₄ O ₁₀ [S]	0.00001	0.00032	0.00015
SiO ₂ [S1]	0.00850	0.00490	0.01744
TiO ₂ [S1]	0.47700	0.29400	0.45949
V ₂ O ₅ [S]	0.00360	0.00800	0.00000
#			
Price[USD/ton]	47.5000	32.2300	45.1400

The name of the property in this case is “Price” and its units are “USD/ton”. **There may be no spaces in the string containing the property name and units.** In this case the string is “Price[USD/ton]”, which serves the purpose of describing the custom property clearly.

Be careful not to leave empty lines at the end of your material description file. It tends to cause problems.

Materials

Now that we have created a few material description files, we can create material objects in Python.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 print(ilmenite)
5
6 reductant = Material("Reductant", "./materials/reductant.txt")
7 print(reductant)
8
9 mix = Material("Mix", "./materials/mix.txt")
10 print(mix)

```

The Material class is imported on line 1. On line 3 a Material object is created, specifying the name of the object as the first parameter, and the location and name of the material description file as the second parameter. Two more Material objects are created on lines 6 and 9. The materials are printed out after creation, with the following result:

```
=====
Material
=====
```

Name	Ilmenite		
<hr/>			
Composition Details (mass fractions)	IlmeniteA	IlmeniteB	IlmeniteC
<hr/>			
Al ₂ O ₃ [S1]	1.1600000e-02	1.5500000e-02	9.4100000e-03
CaO [S]	2.2000000e-04	1.0000000e-05	1.7000000e-04
Cr ₂ O ₃ [S]	8.0000000e-05	2.2000000e-04	1.1000000e-04
Fe ₂ O ₃ [S1]	2.0200000e-01	4.7300000e-01	4.9674000e-01
Fe ₃ O ₄ [S1]	0.0000000e+00	0.0000000e+00	0.0000000e+00
FeO [S]	2.7900000e-01	1.9100000e-01	0.0000000e+00
K ₂ O [S]	4.0000000e-05	1.0000000e-05	5.0000000e-05
MgO [S]	1.0400000e-02	5.8000000e-03	1.0900000e-02
MnO [S]	5.4000000e-03	4.8000000e-03	5.2500000e-03
Na ₂ O [S1]	7.0000000e-05	5.0000000e-05	3.1000000e-04
P ₄ O ₁₀ [S]	1.0000000e-05	3.2000000e-04	1.5000000e-04
SiO ₂ [S1]	8.5000000e-03	4.9000000e-03	1.7440000e-02
TiO ₂ [S1]	4.7700000e-01	2.9400000e-01	4.5949000e-01
V ₂ O ₅ [S]	3.6000000e-03	8.0000000e-03	0.0000000e+00
<hr/>			
Custom Properties:			
<hr/>			
Price [USD/ton]	4.7500000e+01	3.2230000e+01	4.5140000e+01
<hr/>			
<hr/>			
Material			
<hr/>			
Name	Reductant		
<hr/>			
Composition Details (mass fractions)	ReductantA	ReductantB	
<hr/>			
C [S1]	8.40973866e-01	1.0000000e+00	
H ₂ [G]	1.37955186e-02	0.0000000e+00	
O ₂ [G]	4.94339606e-02	0.0000000e+00	
N ₂ [G]	6.09802120e-03	0.0000000e+00	
S [S1]	2.04933390e-03	0.0000000e+00	
Al ₂ O ₃ [S1]	1.20884160e-03	0.0000000e+00	
CaO [S]	2.94179980e-03	0.0000000e+00	
Fe ₂ O ₃ [S1]	7.85955656e-02	0.0000000e+00	
MgO [S]	1.41179360e-03	0.0000000e+00	
SiO ₂ [S1]	3.49129950e-03	0.0000000e+00	
<hr/>			
<hr/>			
Material			
<hr/>			
Name	Mix		
<hr/>			

```
Compound
-----
Al2O3[S1]
C[S1]
CaO[S]
Cr2O3[S]
Fe2O3[S1]
Fe3O4[S1]
FeO[S]
H2[G]
K2O[S]
MgO[S]
MnO[S]
Na2O[S1]
N2[G]
O2[G]
P4O10[S]
S[S1]
SiO2[S1]
TiO2[S1]
V2O5[S]
=====
```

The material objects are now ready to create material packages.

Material Packages

Creating Empty Packages

The simplest way to create material packages is to create empty ones.

```
1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 empty_ilmenite_package = ilmenite.create_package()
8 print(empty_ilmenite_package)
9
10 empty_reductant_package = reductant.create_package()
11 print(empty_reductant_package)
12
13 empty_mix_package = mix.create_package()
14 print(empty_mix_package)
```

The empty packages are created by calling the “create_package” method of the Material objects without passing any parameters.

```
=====
MaterialPackage
=====

Material           Ilmenite
Mass              0.00000000e+00 kg
Amount            0.00000000e+00 kmol
Pressure          1.00000000e+00 atm
Temperature       2.50000000e+01 °C
Enthalpy          0.00000000e+00 kWh
-----

Compound Details
-----
```

Formula	Mass	Mass Fraction	Mole Fraction
Al ₂ O ₃ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
CaO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Cr ₂ O ₃ [S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe ₂ O ₃ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe ₃ O ₄ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
K ₂ O[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
MgO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
MnO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Na ₂ O[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
P ₄ O ₁₀ [S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
SiO ₂ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
TiO ₂ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
V ₂ O ₅ [S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Formula	Mass	Mass Fraction	Mole Fraction
Material	Reductant		
Mass	0.00000000e+00 kg		
Amount	0.00000000e+00 kmol		
Pressure	1.00000000e+00 atm		
Temperature	2.50000000e+01 °C		
Enthalpy	0.00000000e+00 kWh		
Formula	Mass	Mass Fraction	Mole Fraction
C[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
H ₂ [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
O ₂ [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
N ₂ [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
S[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Al ₂ O ₃ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
CaO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe ₂ O ₃ [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00

```

MgO[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
SiO2[S1]        0.00000000e+00  0.00000000e+00  0.00000000e+00
=====
=====
MaterialPackage
=====
Material      Mix
Mass           0.00000000e+00 kg
Amount         0.00000000e+00 kmol
Pressure       1.00000000e+00 atm
Temperature    2.50000000e+01 °C
Enthalpy       0.00000000e+00 kWh
-----
Compound Details
Formula        Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]      0.00000000e+00  0.00000000e+00  0.00000000e+00
C[S1]          0.00000000e+00  0.00000000e+00  0.00000000e+00
CaO[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
Cr2O3[S]        0.00000000e+00  0.00000000e+00  0.00000000e+00
Fe2O3[S1]      0.00000000e+00  0.00000000e+00  0.00000000e+00
Fe3O4[S1]      0.00000000e+00  0.00000000e+00  0.00000000e+00
FeO[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
H2[G]           0.00000000e+00  0.00000000e+00  0.00000000e+00
K2O[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
MgO[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
MnO[S]          0.00000000e+00  0.00000000e+00  0.00000000e+00
Na2O[S1]        0.00000000e+00  0.00000000e+00  0.00000000e+00
N2[G]           0.00000000e+00  0.00000000e+00  0.00000000e+00
O2[G]           0.00000000e+00  0.00000000e+00  0.00000000e+00
P4O10[S]        0.00000000e+00  0.00000000e+00  0.00000000e+00
S[S1]           0.00000000e+00  0.00000000e+00  0.00000000e+00
SiO2[S1]        0.00000000e+00  0.00000000e+00  0.00000000e+00
TiO2[S1]        0.00000000e+00  0.00000000e+00  0.00000000e+00
V2O5[S]         0.00000000e+00  0.00000000e+00  0.00000000e+00
=====

```

Creating Filled Packages

It is just as easy to create packages that contain some mass. Let's do that with ilmenite.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
                                          ↵0)

```

```
8 print(ilma_package)
```

The parameters to the “create_package” method are:

1. material assay name, “IlmeniteA”
2. mass, 300 kg
3. pressure, 1 atm
4. temperature, 25 °C

We therefore created 300 kg based on the composition specified by the IlmeniteA assay, at 1 atm pressure and 25 °C temperature. The resulting package is shown here.

```
=====
MaterialPackage
=====
Material           Ilmenite
Mass              3.0000000e+02 kg
Amount            3.52817004e+00 kmol
Pressure          1.0000000e+00 atm
Temperature       2.5000000e+01 °C
Enthalpy          -6.87812118e+02 kWh
-----
Compound Details
Formula          Mass      Mass Fraction   Mole Fraction
-----
Al2O3[S1]        3.48725349e+00 1.16241783e-02 9.69390473e-03
CaO[S]           6.61375661e-02 2.20458554e-04 3.34280337e-04
Cr2O3[S]         2.40500241e-02 8.01667468e-05 4.48486990e-05
Fe2O3[S1]        6.07263107e+01 2.02421036e-01 1.07784066e-01
Fe3O4[S1]        0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]            8.38744589e+01 2.79581530e-01 3.30892788e-01
K2O[S]            1.20250120e-02 4.00833734e-05 3.61829148e-05
MgO[S]            3.12650313e+00 1.04216771e-02 2.19865404e-02
MnO[S]            1.62337662e+00 5.41125541e-03 6.48625791e-03
Na2O[S1]          2.10437710e-02 7.01459035e-05 9.62343053e-05
P4O10[S]          3.00625301e-03 1.00208434e-05 3.00142421e-06
SiO2[S1]          2.55531506e+00 8.51771685e-03 1.20540764e-02
TiO2[S1]          1.43398268e+02 4.77994228e-01 5.08901291e-01
V2O5[S]           1.08225108e+00 3.60750361e-03 1.68652807e-03
=====
```

Adding Material to a Package - Another Package

Now we create another ilmenite package with a different composition, mass and temperature, and add it to the first:

```
1 from auxi.modelling.process.materials.thermo import Material
2
```

```

3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8   ↵0)
9 ilmb_package = ilmenite.create_package("IlmeniteB", 500.0, 1.0, 750.
10  ↵0)
11
12 ilma_package += ilmb_package
13 print(ilma_package)
14 print(ilmb_package)

```

This changes the original “ilma_package”, but the second “ilmb_package” remains the same. This is quite a powerful action, since one line of code does all of the following:

- Calculate the total mass of each component by adding up the component masses from the two packages.
- Calculate the mass fraction of each compound.
- Calculate the mole fraction of each compound.
- Calculate the total amount (in kmol) of compounds in the package.
- Calculate the total enthalpy by adding up the enthalpies of the two original packages.
- Calculate the temperature of the new package.

The resulting two packages are shown below:

=====				
MaterialPackage				
=====				
Material	Ilmenite			
Mass	8.0000000e+02	kg		
Amount	8.43715862e+00	kmol		
Pressure	1.0000000e+00	atm		
Temperature	4.88474167e+02	°C		
Enthalpy	-1.59326344e+03	kWh		

Compound Details				

Formula	Mass	Mass Fraction	Mole Fraction	

Al2O3[S1]	1.12558204e+01	1.40697755e-02	1.30841549e-02	
CaO[S]	7.11495448e-02	8.89369310e-05	1.50379294e-04	
Cr2O3[S]	1.34313554e-01	1.67891942e-04	1.04738770e-04	
Fe2O3[S1]	2.97792900e+02	3.72241125e-01	2.21026985e-01	
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00	
FeO[S]	1.79603251e+02	2.24504063e-01	2.96295501e-01	
K2O[S]	1.70369907e-02	2.12962383e-05	2.14370100e-05	
MgO[S]	6.03345073e+00	7.54181341e-03	1.77425932e-02	
MnO[S]	4.02912637e+00	5.03640796e-03	6.73192250e-03	

Na2O[S1]	4.61036642e-02	5.76295802e-05	8.81647712e-05
P4O10[S]	1.63389569e-01	2.04236961e-04	6.82149359e-05
SiO2[S1]	5.01118458e+00	6.26398073e-03	9.88514810e-03
TiO2[S1]	2.90750440e+02	3.63438050e-01	4.31482633e-01
V2O5[S]	5.09183399e+00	6.36479248e-03	3.31812755e-03
<hr/>			
<hr/>			
MaterialPackage			
<hr/>			
Material	Ilmenite		
Mass	5.00000000e+02	kg	
Amount	4.90898858e+00	kmol	
Pressure	1.00000000e+00	atm	
Temperature	7.50000000e+02	°C	
Enthalpy	-9.05451326e+02	kWh	
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
<hr/>			
Al2O3[S1]	7.76856687e+00	1.55371337e-02	1.55207829e-02
CaO[S]	5.01197863e-03	1.00239573e-05	1.82066196e-05
Cr2O3[S]	1.10263530e-01	2.20527060e-04	1.47782739e-04
Fe2O3[S1]	2.37066589e+02	4.74133178e-01	3.02416515e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	9.57287918e+01	1.91457584e-01	2.71429867e-01
K2O[S]	5.01197863e-03	1.00239573e-05	1.08388880e-05
MgO[S]	2.90694760e+00	5.81389521e-03	1.46923993e-02
MnO[S]	2.40574974e+00	4.81149948e-03	6.90848565e-03
Na2O[S1]	2.50598931e-02	5.01197863e-05	8.23650657e-05
P4O10[S]	1.60383316e-01	3.20766632e-04	1.15084949e-04
SiO2[S1]	2.45586953e+00	4.91173906e-03	8.32630400e-03
TiO2[S1]	1.47352172e+02	2.94704343e-01	3.75840583e-01
V2O5[S]	4.00958290e+00	8.01916581e-03	4.49078466e-03
<hr/>			

Adding Material to a Package - A Compound Mass

Sometimes you need to add material to a package, one compound at a time.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8 ↵0)

```

```

9 ilma_package += ("TiO2[S1]", 150.0)
10 print(ilma_package)

```

This adds 150 kg of TiO₂[S1] to ilma_package. The temperature of the added material is assumed to be the same as that of the original package, which means that ilma_package's temperature does not change. Here is the result:

```

=====
MaterialPackage
=====
Material           Ilmenite
Mass               4.5000000e+02 kg
Amount             5.40632064e+00 kmol
Pressure           1.0000000e+00 atm
Temperature        2.5000000e+01 °C
Enthalpy           -1.18069622e+03 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          3.48725349e+00 7.74945219e-03 6.32625154e-03
CaO[S]              6.61375661e-02 1.46972369e-04 2.18151669e-04
Cr2O3[S]            2.40500241e-02 5.34444979e-05 2.92683040e-05
Fe2O3[S1]           6.07263107e+01 1.34947357e-01 7.03399852e-02
Fe3O4[S1]           0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]               8.38744589e+01 1.86387686e-01 2.15940951e-01
K2O[S]              1.20250120e-02 2.67222489e-05 2.36130050e-05
MgO[S]              3.12650313e+00 6.94778473e-03 1.43484374e-02
MnO[S]              1.62337662e+00 3.60750361e-03 4.23293814e-03
Na2O[S1]             2.10437710e-02 4.67639357e-05 6.28026001e-05
P4O10[S]             3.00625301e-03 6.68056224e-06 1.95873232e-06
SiO2[S1]             2.55531506e+00 5.67847790e-03 7.86650184e-03
TiO2[S1]             2.93398268e+02 6.51996152e-01 6.79508511e-01
V2O5[S]              1.08225108e+00 2.40500241e-03 1.10062984e-03
=====
```

Adding Material to a Package - A Compound Mass with Specified Temperature

We can also add a certain mass of a specified compound at a temperature different from the original package.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
  ↵0)

```

```

8
9 ilma_package += ("TiO2[S1]", 150.0, 1000.0)
10 print(ilma_package)

```

This action calculates a new total mass, component masses, mass fractions and mole fractions, as well as a new enthalpy and temperature.

```

=====
MaterialPackage
=====
Material           Ilmenite
Mass               4.5000000e+02 kg
Amount             5.40632064e+00 kmol
Pressure           1.0000000e+00 atm
Temperature        3.84927151e+02 °C
Enthalpy           -1.14449836e+03 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          3.48725349e+00 7.74945219e-03 6.32625154e-03
CaO[S]              6.61375661e-02 1.46972369e-04 2.18151669e-04
Cr2O3[S]            2.40500241e-02 5.34444979e-05 2.92683040e-05
Fe2O3[S1]           6.07263107e+01 1.34947357e-01 7.03399852e-02
Fe3O4[S1]            0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]               8.38744589e+01 1.86387686e-01 2.15940951e-01
K2O[S]               1.20250120e-02 2.67222489e-05 2.36130050e-05
MgO[S]               3.12650313e+00 6.94778473e-03 1.43484374e-02
MnO[S]               1.62337662e+00 3.60750361e-03 4.23293814e-03
Na2O[S1]              2.10437710e-02 4.67639357e-05 6.28026001e-05
P4O10[S]              3.00625301e-03 6.68056224e-06 1.95873232e-06
SiO2[S1]              2.55531506e+00 5.67847790e-03 7.86650184e-03
TiO2[S1]              2.93398268e+02 6.51996152e-01 6.79508511e-01
V2O5[S]               1.08225108e+00 2.40500241e-03 1.10062984e-03
=====
```

Adding Packages of Different Materials Together

We very often need to add packages from different materials together. For example, ilmenite and reductant can be added together so that reduction reactions can be modelled.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
    ↴0)

```

```

8 reda_package = reductant.create_package("ReductantA", 35.0, 1.0, 25.
9   ↵0)
10 new_package = ilma_package + reda_package
11 print(new_package)

```

This, however, does not work. See the last two lines of the error message below.

```

Traceback (most recent call last):
File "test.py", line 10, in <module>
    new_package = ilma_package + reda_package
File "thermochemistry.material.py", line 430, in __add__
    self.material.name + ".")
Exception: Packages of 'Reductant' cannot be added to packages of
↪'Ilmenite'.
    The compound 'C[S1]' was not found in 'Ilmenite'.

```

Let's try it by swapping the two material packages around.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8   ↵0)
9 reda_package = reductant.create_package("ReductantA", 35.0, 1.0, 25.
10  ↵0)
11 new_package = reda_package + ilma_package
12 print(new_package)

```

```

Traceback (most recent call last):
File "test.py", line 10, in <module>
    new_package = reda_package + ilma_package
File "thermochemistry.material.py", line 430, in __add__
    self.material.name + ".")
Exception: Packages of 'Ilmenite' cannot be added to packages of
↪'Reductant'.
    The compound 'Cr2O3[S]' was not found in 'Reductant'.

```

Still no luck. These packages cannot be added together because their materials are not compatible. We need to use an intermediate material package from a compatible material that will allow us to add ilmenite and reductant together. This is the purpose of the “mix” material that we created early on.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")

```

```

4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↵0)
9 reda_package = reductant.create_package("ReductantA", 35.0, 1.0, 25.
10    ↵0)
11 new_package = mix.create_package()
12 new_package += ilma_package
13 new_package += reda_package
14 print(new_package)

```

Success at last! The mix material package is able to receive all the compound masses from both the ilmenite and reductant packages.

```

=====
MaterialPackage
=====
Material          Mix
Mass              3.35000000e+02 kg
Amount            6.30500835e+00 kmol
Pressure          1.00000000e+00 atm
Temperature       2.50000000e+01 °C
Enthalpy          -6.92925041e+02 kWh
-----
Compound Details
Formula           Mass      Mass Fraction   Mole Fraction
-----
Al2O3[S1]         3.52956294e+00 1.05360088e-02 5.49034965e-03
C[S1]              2.94340853e+01 8.78629412e-02 3.88683906e-01
CaO[S]             1.69100559e-01 5.04777788e-04 4.78268203e-04
Cr2O3[S]           2.40500241e-02 7.17911166e-05 2.50965308e-05
Fe2O3[S1]          6.34771555e+01 1.89484046e-01 6.30462073e-02
Fe3O4[S1]          0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]              8.38744589e+01 2.50371519e-01 1.85161693e-01
H2[G]               4.82843151e-01 1.44132284e-03 3.79888138e-02
K2O[S]              1.20250120e-02 3.58955583e-05 2.02473128e-05
MgO[S]              3.17591590e+00 9.48034598e-03 1.24977222e-02
MnO[S]              1.62337662e+00 4.84590037e-03 3.62959406e-03
Na2O[S1]             2.10437710e-02 6.28172270e-05 5.38509982e-05
N2[G]               2.13430742e-01 6.37106693e-04 1.20838199e-03
O2[G]               1.73018862e+00 5.16474215e-03 8.57578913e-03
P4O10[S]             3.00625301e-03 8.97388957e-06 1.67954337e-06
S[S1]                7.17266865e-02 2.14109512e-04 3.54772799e-04
SiO2[S1]             2.67751054e+00 7.99256877e-03 7.06780432e-03
TiO2[S1]             1.43398268e+02 4.28054533e-01 2.84772072e-01
V2O5[S]              1.08225108e+00 3.23060025e-03 9.43750984e-04
=====
```

Adding Material Together - Package + Package

In the above three sections we demonstrated how material can be added to an existing package. Here we will add material together to create a new package.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↵0)
9 ilmb_package = ilmenite.create_package("IlmeniteB", 500.0, 1.0, 750.
10    ↵0)
11 new_package = ilma_package + ilmb_package
12 print(new_package)

```

This action performs all the calculations to create a new package with properties based on the two original packages. Specifically note that the temperature was automatically calculated.

```

=====
MaterialPackage
=====
Material           Ilmenite
Mass               8.0000000e+02 kg
Amount             8.43715862e+00 kmol
Pressure           1.0000000e+00 atm
Temperature        4.88474167e+02 °C
Enthalpy           -1.59326344e+03 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          1.12558204e+01  1.40697755e-02  1.30841549e-02
CaO[S]              7.11495448e-02  8.89369310e-05  1.50379294e-04
Cr2O3[S]            1.34313554e-01  1.67891942e-04  1.04738770e-04
Fe2O3[S1]           2.97792900e+02  3.72241125e-01  2.21026985e-01
Fe3O4[S1]            0.00000000e+00  0.00000000e+00  0.00000000e+00
FeO[S]               1.79603251e+02  2.24504063e-01  2.96295501e-01
K2O[S]              1.70369907e-02  2.12962383e-05  2.14370100e-05
MgO[S]              6.03345073e+00  7.54181341e-03  1.77425932e-02
MnO[S]              4.02912637e+00  5.03640796e-03  6.73192250e-03
Na2O[S1]             4.61036642e-02  5.76295802e-05  8.81647712e-05
P4O10[S]             1.63389569e-01  2.04236961e-04  6.82149359e-05
SiO2[S1]             5.01118458e+00  6.26398073e-03  9.88514810e-03
TiO2[S1]             2.90750440e+02  3.63438050e-01  4.31482633e-01
V2O5[S]              5.09183399e+00  6.36479248e-03  3.31812755e-03
=====
```

Adding Material Together - Package + Compound Mass

Now we add a package and specific mass of a compound together to produce a new package.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↵0)
9 new_package = ilma_package + ("TiO2[S1]", 150.0)
10 print(new_package)

```

The added compound mass is assumed to be at the same temperature as the original package. This results in the new package having the same temperature as the original package.

```

=====
MaterialPackage
=====
Material           Ilmenite
Mass               4.5000000e+02 kg
Amount             5.40632064e+00 kmol
Pressure           1.0000000e+00 atm
Temperature        2.5000000e+01 °C
Enthalpy           -1.18069622e+03 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          3.48725349e+00 7.74945219e-03 6.32625154e-03
CaO[S]              6.61375661e-02 1.46972369e-04 2.18151669e-04
Cr2O3[S]            2.40500241e-02 5.34444979e-05 2.92683040e-05
Fe2O3[S1]           6.07263107e+01 1.34947357e-01 7.03399852e-02
Fe3O4[S1]           0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]              8.38744589e+01 1.86387686e-01 2.15940951e-01
K2O[S]              1.20250120e-02 2.67222489e-05 2.36130050e-05
MgO[S]              3.12650313e+00 6.94778473e-03 1.43484374e-02
MnO[S]              1.62337662e+00 3.60750361e-03 4.23293814e-03
Na2O[S1]             2.10437710e-02 4.67639357e-05 6.28026001e-05
P4O10[S]             3.00625301e-03 6.68056224e-06 1.95873232e-06
SiO2[S1]             2.55531506e+00 5.67847790e-03 7.86650184e-03
TiO2[S1]             2.93398268e+02 6.51996152e-01 6.79508511e-01
V2O5[S]              1.08225108e+00 2.40500241e-03 1.10062984e-03
=====
```

Adding Material Together - Package + Compound Mass at Specified Temperature

Now we add the same compound mass as in the previous section, but at a different temperature.

```

1 from auxi.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↵0)
9 new_package = ilma_package + ("TiO2[S1]", 150.0, 1000.0)
10 print(new_package)

```

The new package now has a different temperature, which is calculated based on the enthalpy of the original package and the enthalpy of the added compound mass.

```

=====
MaterialPackage
=====
Material           Ilmenite
Mass               4.50000000e+02 kg
Amount             5.40632064e+00 kmol
Pressure           1.00000000e+00 atm
Temperature        3.84927151e+02 °C
Enthalpy           -1.14449836e+03 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          3.48725349e+00 7.74945219e-03 6.32625154e-03
CaO[S]              6.61375661e-02 1.46972369e-04 2.18151669e-04
Cr2O3[S]            2.40500241e-02 5.34444979e-05 2.92683040e-05
Fe2O3[S1]           6.07263107e+01 1.34947357e-01 7.03399852e-02
Fe3O4[S1]            0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]              8.38744589e+01 1.86387686e-01 2.15940951e-01
K2O[S]              1.20250120e-02 2.67222489e-05 2.36130050e-05
MgO[S]              3.12650313e+00 6.94778473e-03 1.43484374e-02
MnO[S]              1.62337662e+00 3.60750361e-03 4.23293814e-03
Na2O[S1]             2.10437710e-02 4.67639357e-05 6.28026001e-05
P4O10[S]             3.00625301e-03 6.68056224e-06 1.95873232e-06
SiO2[S1]             2.55531506e+00 5.67847790e-03 7.86650184e-03
TiO2[S1]             2.93398268e+02 6.51996152e-01 6.79508511e-01
V2O5[S]              1.08225108e+00 2.40500241e-03 1.10062984e-03
=====
```

Extract Material from a Package - Mass

When we need to create a new package by extracting material from an existing material, we use the “extract” method. First of all we can simply specify the total mass to be extracted.

```

1  from auxi.modelling.process.materials.thermo import Material
2
3  ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4  reductant = Material("Reductant", "./materials/reductant.txt")
5  mix = Material("Mix", "./materials/mix.txt")
6
7  ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8      ↵0)
9
10 new_package = ilma_package.extract(75.0)
11 print(ilma_package)
12 print(new_package)
```

This removes 75 kg from the original package, and produces a new package of 75 kg. The new package has the same composition, temperature and pressure as the original one.

```
=====
MaterialPackage
=====
Material           Ilmenite
Mass               2.2500000e+02 kg
Amount             2.64612753e+00 kmol
Pressure           1.0000000e+00 atm
Temperature        2.5000000e+01 °C
Enthalpy           -5.15859089e+02 kWh
-----
Compound Details
Formula            Mass          Mass Fraction   Mole Fraction
-----
Al2O3[S1]          2.61544012e+00 1.16241783e-02 9.69390473e-03
CaO[S]              4.96031746e-02 2.20458554e-04 3.34280337e-04
Cr2O3[S]            1.80375180e-02 8.01667468e-05 4.48486990e-05
Fe2O3[S1]           4.55447330e+01 2.02421036e-01 1.07784066e-01
Fe3O4[S1]           0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]              6.29058442e+01 2.79581530e-01 3.30892788e-01
K2O[S]              9.01875902e-03 4.00833734e-05 3.61829148e-05
MgO[S]              2.34487734e+00 1.04216771e-02 2.19865404e-02
MnO[S]              1.21753247e+00 5.41125541e-03 6.48625791e-03
Na2O[S1]             1.57828283e-02 7.01459035e-05 9.62343053e-05
P4O10[S]             2.25468975e-03 1.00208434e-05 3.00142421e-06
SiO2[S1]             1.91648629e+00 8.51771685e-03 1.20540764e-02
TiO2[S1]             1.07548701e+02 4.77994228e-01 5.08901291e-01
V2O5[S]              8.11688312e-01 3.60750361e-03 1.68652807e-03
=====
```

```

MaterialPackage
=====
Material           Ilmenite
Mass              7.5000000e+01 kg
Amount            8.82042511e-01 kmol
Pressure          1.0000000e+00 atm
Temperature       2.5000000e+01 °C
Enthalpy          -1.71953030e+02 kWh
-----
Compound Details
Formula          Mass      Mass Fraction   Mole Fraction
-----
Al2O3[S1]        8.71813372e-01 1.16241783e-02 9.69390473e-03
CaO[S]           1.65343915e-02 2.20458554e-04 3.34280337e-04
Cr2O3[S]         6.01250601e-03 8.01667468e-05 4.48486990e-05
Fe2O3[S1]        1.51815777e+01 2.02421036e-01 1.07784066e-01
Fe3O4[S1]        0.00000000e+00 0.00000000e+00 0.00000000e+00
FeO[S]            2.09686147e+01 2.79581530e-01 3.30892788e-01
K2O[S]            3.00625301e-03 4.00833734e-05 3.61829148e-05
MgO[S]            7.81625782e-01 1.04216771e-02 2.19865404e-02
MnO[S]            4.05844156e-01 5.41125541e-03 6.48625791e-03
Na2O[S1]          5.26094276e-03 7.01459035e-05 9.62343053e-05
P4O10[S]          7.51563252e-04 1.00208434e-05 3.00142421e-06
SiO2[S1]          6.38828764e-01 8.51771685e-03 1.20540764e-02
TiO2[S1]          3.58495671e+01 4.77994228e-01 5.08901291e-01
V2O5[S]           2.70562771e-01 3.60750361e-03 1.68652807e-03
=====
```

Extract Material from a Package - Compound

We can also extract all the mass of a single compound from an existing package into a new one.

```

1  from auxi.modelling.process.materials.thermo import Material
2
3  ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4  reductant = Material("Reductant", "./materials/reductant.txt")
5  mix = Material("Mix", "./materials/mix.txt")
6
7  ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8      ↵0)
9
10 new_package = ilma_package.extract("TiO2[S1]")
11 print(ilma_package)
12 print(new_package)
```

This modifies the original package's composition and enthalpy, and creates a new package of the same temperature consisting purely of the specified compound.

```
=====
MaterialPackage
=====

Material           Ilmenite
Mass              1.56601732e+02 kg
Amount             1.73267975e+00 kmol
Pressure            1.00000000e+00 atm
Temperature         2.50000000e+01 °C
Enthalpy            -2.16620609e+02 kWh
-----

Compound Details
-----
```

Formula	Mass	Mass Fraction	Mole Fraction
Al2O3[S1]	3.48725349e+00	2.22682946e-02	1.97392185e-02
CaO[S]	6.61375661e-02	4.22329724e-04	6.80678509e-04
Cr2O3[S]	2.40500241e-02	1.53574445e-04	9.13231864e-05
Fe2O3[S1]	6.07263107e+01	3.87775474e-01	2.19475361e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	8.38744589e+01	5.35590878e-01	6.73780610e-01
K2O[S]	1.20250120e-02	7.67872226e-05	7.36774791e-05
MgO[S]	3.12650313e+00	1.99646779e-02	4.47701043e-02
MnO[S]	1.62337662e+00	1.03662751e-02	1.32076460e-02
Na2O[S1]	2.10437710e-02	1.34377640e-04	1.95957154e-04
P4O10[S]	3.00625301e-03	1.91968057e-05	6.11165160e-06
SiO2[S1]	2.55531506e+00	1.63172848e-02	2.45451193e-02
TiO2[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
V2O5[S]	1.08225108e+00	6.91085003e-03	3.43419366e-03

=====

=====

Formula	Mass	Mass Fraction	Mole Fraction
Al2O3[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
CaO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Cr2O3[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe2O3[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
K2O[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
MgO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00

=====

MnO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Na2O[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
P4O10[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
SiO2[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
TiO2[S1]	1.43398268e+02	1.00000000e+00	1.00000000e+00
V2O5[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
<hr/>			

Extract Material from a Package - Compound Mass

We may not want to extract all the mass of a specific compound. In this case we can specify the mass to extract.

```

1  from auxi.modelling.process.materials.thermo import Material
2
3  ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4  reductant = Material("Reductant", "./materials/reductant.txt")
5  mix = Material("Mix", "./materials/mix.txt")
6
7  ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8      ↘0)
9
10 new_package = ilma_package.extract(("TiO2[S1]", 110.0))
11 print(ilma_package)
12 print(new_package)

```

The existing package is modified appropriately and a new package containing only the specified mass of the required compound is produced.

<hr/>			
MaterialPackage			
<hr/>			
Material	Ilmenite		
Mass	1.9000000e+02 kg		
Amount	2.15085961e+00 kmol		
Pressure	1.0000000e+00 atm		
Temperature	2.5000000e+01 °C		
Enthalpy	-3.26363778e+02 kWh		
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
<hr/>			
Al2O3[S1]	3.48725349e+00	1.83539657e-02	1.59014304e-02
CaO[S]	6.61375661e-02	3.48092453e-04	5.48337915e-04
Cr2O3[S]	2.40500241e-02	1.26579074e-04	7.35677195e-05
Fe2O3[S1]	6.07263107e+01	3.19612162e-01	1.76803968e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	8.38744589e+01	4.41444520e-01	5.42781136e-01
K2O[S]	1.20250120e-02	6.32895370e-05	5.93527704e-05

MgO[S]	3.12650313e+00	1.64552796e-02	3.60656982e-02
MnO[S]	1.62337662e+00	8.54408749e-03	1.06397557e-02
Na2O[S1]	2.10437710e-02	1.10756690e-04	1.57858278e-04
P4O10[S]	3.00625301e-03	1.58223842e-05	4.92339666e-06
SiO2[S1]	2.55531506e+00	1.34490266e-02	1.97729462e-02
TiO2[S1]	3.33982684e+01	1.75780360e-01	1.94424522e-01
V2O5[S]	1.08225108e+00	5.69605833e-03	2.76650220e-03
<hr/>			
<hr/>			
MaterialPackage			
<hr/>			
Material	Ilmenite		
Mass	1.1000000e+02 kg		
Amount	1.37731044e+00 kmol		
Pressure	1.0000000e+00 atm		
Temperature	2.5000000e+01 °C		
Enthalpy	-3.61448340e+02 kWh		
<hr/>			
Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction
<hr/>			
Al2O3[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
CaO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Cr2O3[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe2O3[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
K2O[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
MgO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
MnO[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Na2O[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
P4O10[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
SiO2[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
TiO2[S1]	1.1000000e+02	1.0000000e+00	1.0000000e+00
V2O5[S]	0.00000000e+00	0.00000000e+00	0.00000000e+00
<hr/>			

Extract Material from a Package - Material

We may need to extract all the compounds that appear in a specific material into a new package.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
   ↵0)

```

```

8
9 new_package = ilma_package.extract(reductant)
10 print(ilma_package)
11 print(new_package)

```

The existing package loses all the masses of components that appear in the specified material. The new package contains these masses and have the same temperature and pressure as the original material.

```

=====
MaterialPackage
=====

Material           Ilmenite
Mass              2.30038480e+02 kg
Amount            2.99240730e+00 kmol
Pressure          1.00000000e+00 atm
Temperature       2.50000000e+01 °C
Enthalpy          -5.62518853e+02 kWh
-----

Compound Details
-----

| Formula   | Mass           | Mass Fraction  | Mole Fraction  |
|-----------|----------------|----------------|----------------|
| Al2O3[S1] | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| CaO[S]    | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| Cr2O3[S]  | 2.40500241e-02 | 1.04547831e-04 | 5.28784420e-05 |
| Fe2O3[S1] | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| Fe3O4[S1] | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| FeO[S]    | 8.38744589e+01 | 3.64610559e-01 | 3.90136068e-01 |
| K2O[S]    | 1.20250120e-02 | 5.22739153e-05 | 4.26611298e-05 |
| MgO[S]    | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| MnO[S]    | 1.62337662e+00 | 7.05697857e-03 | 7.64756215e-03 |
| Na2O[S1]  | 2.10437710e-02 | 9.14793518e-05 | 1.13464164e-04 |
| P4O10[S]  | 3.00625301e-03 | 1.30684788e-05 | 3.53880134e-06 |
| SiO2[S1]  | 0.00000000e+00 | 0.00000000e+00 | 0.00000000e+00 |
| TiO2[S1]  | 1.43398268e+02 | 6.23366440e-01 | 6.00015342e-01 |
| V2O5[S]   | 1.08225108e+00 | 4.70465238e-03 | 1.98848527e-03 |


=====

MaterialPackage
=====

Material           Reductant
Mass              6.99615200e+01 kg
Amount            5.35762740e-01 kmol
Pressure          1.00000000e+00 atm
Temperature       2.50000000e+01 °C
Enthalpy          -1.25293265e+02 kWh
-----

Compound Details
-----

| Formula | Mass | Mass Fraction | Mole Fraction |
|---------|------|---------------|---------------|
|---------|------|---------------|---------------|


```

C [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
H2 [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
O2 [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
N2 [G]	0.00000000e+00	0.00000000e+00	0.00000000e+00
S [S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
Al2O3 [S1]	3.48725349e+00	4.98453077e-02	6.38374820e-02
Cao [S]	6.61375661e-02	9.45342042e-04	2.20134358e-03
Fe2O3 [S1]	6.07263107e+01	8.67995875e-01	7.09792759e-01
MgO [S]	3.12650313e+00	4.46888965e-02	1.44788444e-01
SiO2 [S1]	2.55531506e+00	3.65245789e-02	7.93799718e-02

Multiplying a Package by a Scalar

It may sometimes be useful to multiply a package by a scalar.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↪0)
9 ilma_package *= 2.0
10 print(ilma_package)

```

This doubles the package mass and enthalpy. Temperature, pressure and composition remain the same, since these are intensive properties.

=====			
MaterialPackage			
=====			
Material	Ilmenite		
Mass	6.0000000e+02 kg		
Amount	7.05634009e+00 kmol		
Pressure	1.0000000e+00 atm		
Temperature	2.5000000e+01 °C		
Enthalpy	-1.37562424e+03 kWh		

Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction

Al2O3 [S1]	6.97450697e+00	1.16241783e-02	9.69390473e-03
Cao [S]	1.32275132e-01	2.20458554e-04	3.34280337e-04
Cr2O3 [S]	4.81000481e-02	8.01667468e-05	4.48486990e-05
Fe2O3 [S1]	1.21452621e+02	2.02421036e-01	1.07784066e-01

Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	1.67748918e+02	2.79581530e-01	3.30892788e-01
K2O[S]	2.40500241e-02	4.00833734e-05	3.61829148e-05
MgO[S]	6.25300625e+00	1.04216771e-02	2.19865404e-02
MnO[S]	3.24675325e+00	5.41125541e-03	6.48625791e-03
Na2O[S1]	4.20875421e-02	7.01459035e-05	9.62343053e-05
P4O10[S]	6.01250601e-03	1.00208434e-05	3.00142421e-06
SiO2[S1]	5.11063011e+00	8.51771685e-03	1.20540764e-02
TiO2[S1]	2.86796537e+02	4.77994228e-01	5.08901291e-01
V2O5[S]	2.16450216e+00	3.60750361e-03	1.68652807e-03
<hr/>			

Setting Package Temperature

Using the “T” property of a `MaterialPackage` object, it is easy to set the temperature of a package to a new value.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8   ↵0)
9
10 ilma_package.T = 1000.0
11 print(ilma_package)

```

This results in the temperature to be updated, as well as the package’s enthalpy.

<hr/>			
MaterialPackage			
<hr/>			
Material	Ilmenite		
Mass	3.00000000e+02 kg		
Amount	3.52817004e+00 kmol		
Pressure	1.00000000e+00 atm		
Temperature	1.00000000e+03 °C		
Enthalpy	-6.18986580e+02 kWh		
<hr/>			
Compound Details			
<hr/>			
Formula	Mass	Mass Fraction	Mole Fraction
Al2O3[S1]	3.48725349e+00	1.16241783e-02	9.69390473e-03
CaO[S]	6.61375661e-02	2.20458554e-04	3.34280337e-04
Cr2O3[S]	2.40500241e-02	8.01667468e-05	4.48486990e-05
Fe2O3[S1]	6.07263107e+01	2.02421036e-01	1.07784066e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00

FeO[S]	8.38744589e+01	2.79581530e-01	3.30892788e-01
K2O[S]	1.20250120e-02	4.00833734e-05	3.61829148e-05
MgO[S]	3.12650313e+00	1.04216771e-02	2.19865404e-02
MnO[S]	1.62337662e+00	5.41125541e-03	6.48625791e-03
Na2O[S1]	2.10437710e-02	7.01459035e-05	9.62343053e-05
P4O10[S]	3.00625301e-03	1.00208434e-05	3.00142421e-06
SiO2[S1]	2.55531506e+00	8.51771685e-03	1.20540764e-02
TiO2[S1]	1.43398268e+02	4.77994228e-01	5.08901291e-01
V2O5[S]	1.08225108e+00	3.60750361e-03	1.68652807e-03
<hr/>			

Setting Package Enthalpy

We can use the “H” property of a `MaterialPackage` object to add or subtract enthalpy, or to set it to a new value. This is very useful when building an energy balance.

```

1 from auxi.modelling.process.materials.thermo import Material
2
3 ilmenite = Material("Ilmenite", "./materials/ilmenite.txt")
4 reductant = Material("Reductant", "./materials/reductant.txt")
5 mix = Material("Mix", "./materials/mix.txt")
6
7 ilma_package = ilmenite.create_package("IlmeniteA", 300.0, 1.0, 25.
8     ↵0)
9 ilma_package.H = ilma_package.H + 1.0
10 print(ilma_package)

```

This updates the package’s enthalpy and automatically re-calculates its temperature.

=====			
MaterialPackage			
=====			
Material	Ilmenite		
Mass	3.0000000e+02 kg		
Amount	3.52817004e+00 kmol		
Pressure	1.0000000e+00 atm		
Temperature	4.22166385e+01 °C		
Enthalpy	-6.86812118e+02 kWh		

Compound Details			
Formula	Mass	Mass Fraction	Mole Fraction

Al2O3[S1]	3.48725349e+00	1.16241783e-02	9.69390473e-03
CaO[S]	6.61375661e-02	2.20458554e-04	3.34280337e-04
Cr2O3[S]	2.40500241e-02	8.01667468e-05	4.48486990e-05
Fe2O3[S1]	6.07263107e+01	2.02421036e-01	1.07784066e-01
Fe3O4[S1]	0.00000000e+00	0.00000000e+00	0.00000000e+00
FeO[S]	8.38744589e+01	2.79581530e-01	3.30892788e-01

K2O [S]	1.20250120e-02	4.00833734e-05	3.61829148e-05
MgO [S]	3.12650313e+00	1.04216771e-02	2.19865404e-02
MnO [S]	1.62337662e+00	5.41125541e-03	6.48625791e-03
Na2O [S1]	2.10437710e-02	7.01459035e-05	9.62343053e-05
P4O10 [S]	3.00625301e-03	1.00208434e-05	3.00142421e-06
SiO2 [S1]	2.55531506e+00	8.51771685e-03	1.20540764e-02
TiO2 [S1]	1.43398268e+02	4.77994228e-01	5.08901291e-01
V2O5 [S]	1.08225108e+00	3.60750361e-03	1.68652807e-03
<hr/>			

Business Modelling

The purpose of this section is to explain a number of concepts and demonstrate the use of the Entity, Component, Activity classes in the auxi.modelling.business module.

Basic Activity

A basic activity periodically create a transaction between two specified accounts.

To create an basic activity, import the ‘BasicActivity’ and the create a ‘BasicActivity’

```
from auxi.modelling.business.basic import BasicActivity

basic_activity = BasicActivity("NameA",
                               description="DescriptionA",
                               dt_account="Bank\Default",
                               cr_account="Sales\Default",
                               amount=5000,
                               start=datetime(2016, 2, 1),
                               end=datetime(2017, 2, 1),
                               interval=3)
```

CHAPTER
FOUR

AUXI REFERENCE

auxi package

Subpackages

[auxi.core package](#)

Submodules

[auxi.core.bibliography module](#)

[auxi.core.bibliography_test module](#)

[auxi.core.helpers module](#)

This module contains helper functions to ease various tasks.

`auxi.core.helpers.get_date(date)`

Get the date from a value that could be a date object or a string.

Parameters `date` – The date object or string.

Returns The date object.

`auxi.core.helpers.get_path_relative_to_module(module_file_path,
relative_target_path)`

Calculate a path relative to the specified module file.

Parameters `module_file_path` – The file path to the module.

[auxi.core.helpers_test module](#)

This module contains code used to test core helpers classes.

```
class auxi.core.helpers_test.HelpersUnitTester (methodName='runTest')  
    Bases: unittest.case.TestCase
```

The unit tester for the helpers functions being tested.

```
test_get_date()  
test_get_path_relative_to_module()
```

auxi.core.objects module

```
class auxi.core.objects.NamedObject (name, description=None)  
    Bases: auxi.core.objects.Object
```

Base class for all auxi classes requiring a name and description.

Parameters

- **name** – the object’s name
- **description** – the object’s description

```
class auxi.core.objects.Object  
    Bases: object
```

Base class for all auxi classes.

```
static read(path)  
write(path)
```

auxi.core.objects_test module

This module contains code used to test core object classes.

```
class auxi.core.objects_test.NamedObjectUnitTester (methodName='runTest')  
    Bases: unittest.case.TestCase
```

The unit tester for the class being tested.

```
setUp()  
tearDown()  
test__str__()  
    Test whether the __str__ method successfully generates a json string representation  
    of the object.  
test_constructor()  
    Test whether the constructor successfully initialises the object.
```

```
class auxi.core.objects_test.ObjectUnitTester (methodName='runTest')  
    Bases: unittest.case.TestCase
```

The unit tester for the class being tested.

```
setUp()
tearDown()
test__str__()
Test whether the __str__ method successfully generates a json string representation
of the object.
```

auxi.core.reporting module

This module provides classes to create reports.

```
class auxi.core.reporting.Report (data_source, output_path=None)
Bases: auxi.core.objects.Object
```

Base class for all auxi reports.

```
render (format=<ReportFormat.printout: (1,)>)
Render the report in the specified format
```

Parameters **format** – The format. The default format is to print the report to the console.

Returns If the format was set to ‘string’ then a string representation of the report is returned.

```
class auxi.core.reporting.ReportFormat
Bases: enum.Enum
```

Represents the format the report should be outputted as.

```
csv = <ReportFormat.csv: (4,>
latex = <ReportFormat.latex: (2,>
matplotlib = <ReportFormat.matplotlib: (6,>
png = <ReportFormat.png: 7>
printout = <ReportFormat.printout: (1,>
string = <ReportFormat.string: (5,>
txt = <ReportFormat.txt: (3,>
```

auxi.core.reporting_test module

This module contains code used to test core reporting classes.

```
class auxi.core.reporting_test.ReportingUnitTester (methodName='runTest')
Bases: unittest.case.TestCase
```

The unit tester for the class being tested.

```
setUp()
```

tearDown()

test_render_with_file()

Test whether a value is returned when a report is rendered in a string format. And whether any of the other formats throw an error.

test_render_without_file()

Test whether a value is returned when a report is rendered in a string format. And whether any of the other formats throw an error.

auxi.core.time module

This module provides classes to manage time.

```
class auxi.core.time.Clock(name,                                     description=None,
                           start_datetime=datetime.datetime(1, 1, 1, 0, 0),
                           timestep_period_duration=<TimePeriod.month:
                           7>, timestep_period_count=1)
```

Bases: *auxi.core.objects.NamedObject*

Represents a clock that provides functions to manage a ticking clock based on a time period as well as retrieve the current tick's date since the start date.

get_datetime()

Get the clock's current datetime.

Returns The datetime.

get_datetime_at_period_ix(ix)

Get the datetime at a given period.

Parameters **period** – The index of the period.

Returns The datetime.

reset()

Resets the clock's timestep index to '0'.

tick()

Increment the clock's timestep index.

```
class auxi.core.time.TimePeriod
```

Bases: enum.Enum

Represents a period in time.

day = <TimePeriod.day: 5>

hour = <TimePeriod.hour: 4>

millisecond = <TimePeriod.millisecond: 1>

minute = <TimePeriod.minute: 3>

month = <TimePeriod.month: 7>

second = <TimePeriod.second: 2>

```
week = <TimePeriod.week: 6>
year = <TimePeriod.year: 8>
```

auxi.core.time_test module

This module provides testing code for the auxi.core.time module.

```
class auxi.core.time_test.ClockUnitTester(methodName='runTest')
    Bases: unittest.case.TestCase
```

Tester for the auxi.core.time.Clock class.

```
setUp()
test_constructor()
test_get_datetime()
test_get_datetime_at_period_ix()
test_reset()
test_tick()
```

Module contents

This package contains foundational infrastructure classes and functions that are used throughout the rest of auxi.

auxi.modelling package

Subpackages

auxi.modelling.business package

Submodules

auxi.modelling.business.basic module

This module provides class and functions for basic business activities.

```
class auxi.modelling.business.basic.BasicActivity(name,
                                                 dt_account,
                                                 cr_account,
                                                 amount=0,
                                                 start=datetime.datetime(1,
                                                       1, 1, 0, 0),
                                                 end=datetime.datetime(9999,
                                                       12, 31, 23, 59,
                                                       59, 999999),
                                                 interval=1,
                                                 descrip-
                                                 tion=None)
```

Bases: auxi.modelling.business.structure.Activity

An activity class that provides the most basic activity functionality: periodically create a transaction between two specified accounts.

Parameters

- **name** – The name.
- **dt_account** – The debit account.
- **cr_account** – The credit account.
- **amount** – The amount of an activity.
- **start** – The datetime the activity should be started.
- **end** – The datetime the activity should be run until.
- **interval** – The interval of the activity.
- **description** – The description.

get_referenced_accounts()

Retrieve the general ledger accounts referenced in this instance.

Returns The referenced accounts.

run(clock, generalLedger)

Execute the activity at the current clock cycle.

Parameters

- **clock** – The clock containing the current execution time and period information.
- **generalLedger** – The general ledger into which to create the transactions.

```
class auxi.modelling.business.basic.BasicLoanActivity(name,
                                                       bank_account,
                                                       loan_account,
                                                       inter-
                                                       est_account,
                                                       amount=0,
                                                       inter-
                                                       est_rate=0.0,
                                                       start=datetime.datetime(1,
                                                       1, 1, 0,
                                                       0), dura-
                                                       tion=60,
                                                       inter-
                                                       val=1,
                                                       descrip-
                                                       tion=None)
```

Bases: auxi.modelling.business.structure.Activity

An activity class that provides the most basic activity functionality for a loan: Creates a loan transaction and periodically create transactions to consider the interest and to pay the interest.

Parameters

- **name** – The name.
- **description** – The description.
- **bank_account** – The asset account that is increased.
- **loan_account** – The liability account that is decreased.
- **interest_account** – The expense account the interest is added to.
- **amount** – The loan amount. The default amount is 0
- **interest_rate** – The interest rate as a fraction of the whole (e.g. 0.15 = 15%). The default value is 0.0
- **start** – The datetime the activity should be started.
- **duration** – The duration of the loan in months.
- **interval** – The interval of the activity.

amount

get_referenced_accounts()

Retrieve the general ledger accounts referenced in this instance.

Returns The referenced accounts.

interest_rate

prepare_to_run(clock, period_count)

Prepare the activity for execution.

Parameters

- **clock** – The clock containing the execution start time and execution period information.
- **period_count** – The total amount of periods this activity will be requested to be run for.

run (clock, generalLedger)

Execute the activity at the current clock cycle.

Parameters

- **clock** – The clock containing the current execution time and period information.
- **generalLedger** – The general ledger into which to create the transactions.

auxi.modelling.business.basic_test module

This module provides testing code for the auxi.modelling.business.basic module.

class auxi.modelling.business.basic_test.BasicActivityUnitTester (methodName=
Bases: unittest.case.TestCase

Tester for the auxi.modelling.business.basic.BasicActivity class.

setUp ()

test_meet_execution_criteria ()

Test that the activity only meets the execution criteria when it's amount is greater than 0.

test_constructor ()

test_get_referenced_accounts ()

Test that the activity run method get_referenced_accounts accounts matches the debit and credit accounts self.object was initialised with.

test_run ()

Test that the activity run method creates a transaction with an amount of 5000.

class auxi.modelling.business.basic_test.BasicLoanActivityUnitTester (methodName=
Bases: unittest.case.TestCase

Tester for the auxi.modelling.business.basic.BasicLoanActivity class.

setUp ()

test_meet_execution_criteria ()

Test that the activity only meets the execution criteria when it's amount is greater than 0 and its duration is greater than 0.

test_constructor ()

test_get_referenced_accounts()

Test that the activity run method get_referenced_accounts accounts matches the debit and credit accounts self.object was initialised with.

test_run_first_month()

Test that the activity run method creates a transaction with an amount of 180000 on the first month. No other transactions

test_run_last_month()

Test that the activity run method creates settled the loan on the loans' last month and that the transactions

test_run_third_month()

Test that the activity run method accrued the interest correctly.

auxi.modelling.business.models module

This module provides classes to work with business models.

```
class auxi.modelling.business.models.TimeBasedModel(name,  
                                                    descrip-  
                                                    tion=None,  
                                                    start_datetime=datetime.datetime(  
                                                    3, 13, 18,  
                                                    28, 22,  
                                                    712721), pe-  
                                                    riod_duration=<TimePeriod.year:  
                                                    8>, pe-  
                                                    riod_count=1)
```

Bases: *auxi.core.objects.NamedObject*

Represents an time based model class. An instance of this class is by default configured to run only once, thus functioning as a steady state model. The instance's time based parameters must be configured for it to function as a time based model.

Parameters

- **name** – The name.
- **description** – The description.
- **start_datetime** – The start datetime of the model.
- **period_duration** – The duration of the model's time period. e.g. month, day etc.
- **period_count** – The number of periods to execute the model for.

create_entity(name, gl_structure, description=None)

Create an entity and add it to the model.

Parameters

- **name** – The entity name.

- **gl_structure** – The entity's general ledger structure.
- **description** – The entity description.

Returns The created entity.

name

prepare_to_run()

Prepare the model for execution.

remove_entity(name)

Remove an entity from the model.

Parameters **name** – The name of the entity to remove.

run()

Execute the model.

auxi.modelling.business.models_test module

This module provides testing code for the classes in the auxi.modelling.business.models module.

class auxi.modelling.business.models_test.**TimeBasedModelUnitTester**(methodName)

Bases: unittest.case.TestCase

Tester for the auxi.modelling.business.models.TimeBasedModel class.

setUp()

test_constructor()

test_create_entity()

test_prepare_to_run()

Test that the model's entities prepare_to_run is called when the model's prepare_to_run is called.

test_remove_entity()

test_run()

Test that the model's entities run is called when the model's run is called. Also test that the model was run for the expected time period.

test_set_name()

Test whether the name changes when it is set, that the model's path is updated and that the model's children's paths are updated correctly.

auxi.modelling.business.structure module

This module provides an classes used to create a business structure.

```
class auxi.modelling.business.structure.Activity (name,  

                                                 start=datetime.datetime(1,  

                                                 1, 1, 0, 0),  

                                                 end=datetime.datetime(9999,  

                                                 12, 31, 23, 59,  

                                                 59, 999999),  

                                                 interval=1, de-  

                                                 scription=None)
```

Bases: *auxi.core.objects.NamedObject*

Represents an activity base class. An activity will typically represent a transaction activity in a business.

Parameters

- **name** – The name.
- **description** – The description.
- **start** – The datetime the activity should be started.
- **end** – The datetime the activity should be run until.
- **interval** – The interval of the activity.

get_referenced_accounts()

Retrieve the general ledger accounts referenced in this instance.

Returns The referenced accounts.

name

prepare_to_run (*clock*, *period_count*)

Prepare the activity for execution.

Parameters

- **clock** – The clock containing the execution start time and execution period information.
- **period_count** – The total amount of periods this activity will be requested to be run for.

set_parent_path (*value*)

Set the parent path and the path from the new parent path.

Parameters **value** – The path to the object's parent

```
class auxi.modelling.business.structure.Component (name, gl,  

                                                 descrip-  

                                                 tion=None)
```

Bases: *auxi.core.objects.NamedObject*

Represents an component class. A component class that represents a component of an entity. A component has business activities

Parameters

- **name** – The name.

- **description** – The description.

add_activity (*activity*)

Add an activity to the component.

Parameters **activity** – The activity.

create_component (*name*, *description=None*)

Create a sub component in the business component.

Parameters

- **name** – The new component's name.
- **description** – The new component's description.

Returns The created component.

get_activity (*name*)

Retrieve an activity given its name.

Parameters **name** – The name of the activity.

Returns The activity.

get_component (*name*)

Retrieve a child component given its name.

Parameters **name** – The name of the component.

Returns The component.

name

prepare_to_run (*clock*, *period_count*)

Prepare the component for execution.

Parameters

- **clock** – The clock containing the execution start time and execution period information.
- **period_count** – The total amount of periods this activity will be requested to be run for.

remove_component (*name*)

Remove a sub component from the component.

Parameters **name** – The name of the component to remove.

run (*clock*, *generalLedger*)

Execute the component at the current clock cycle.

Parameters

- **clock** – The clock containing the current execution time and period information.
- **generalLedger** – The general ledger into which to create the transactions.

set_parent_path(*value*)

Set the parent path and the path from the new parent path.

Parameters **value** – The path to the object’s parent.

class auxi.modelling.business.structure.**Entity**(*name*, *gl_structure*,
description=None)

Bases: *auxi.core.objects.NamedObject*

Represents an entity class. An entity consists of business components e.g. Sales department. It executes its components and performs financial year end transactions.

Parameters

- **name** – The name.
- **gl_structure** – The general ledger structure the entity’s general ledger will be initialized with.
- **description** – The description.
- **period_count** – The number of periods the entity should be run for.

create_component(*name*, *description=None*)

Create a component in the business entity.

Parameters

- **name** – The component’s name.
- **description** – The component’s description.

Returns The created component.

name**prepare_to_run**(*clock*, *period_count*)

Prepare the entity for execution.

Parameters

- **clock** – The clock containing the execution start time and execution period information.
- **period_count** – The total amount of periods this activity will be requested to be run for.

remove_component(*name*)

Remove a component from the entity.

Parameters **name** – The name of the component to remove.

run(*clock*)

Execute the entity at the current clock cycle.

Parameters **clock** – The clock containing the current execution time and period information.

set_parent_path (value)

Set the parent path and the path from the new parent path.

Parameters value – The path to the object’s parent

auxi.modelling.business.structure_test module

This module provides testing code for the auxi.modelling.business.activity module.

@author: Ex Mente Technologies (Pty) Ltd

class auxi.modelling.business.structure_test.ActivityUnitTester (methodName='r'

Bases: unittest.case.TestCase

Tester for the auxi.modelling.business.structure.Activity class.

setUp ()

test_meet_execution_criteria ()

test_constructor ()

test_get_path ()

test_get_referenced_accounts ()

test_prepare_to_run ()

test_set_name ()

Test whether the name changes when it is set and that the activity’s path is updated correctly.

test_set_parent_path ()

class auxi.modelling.business.structure_test.ComponentUnitTester (methodName='r'

Bases: unittest.case.TestCase

Tester for the auxi.modelling.business.structure.Component class.

setUp ()

test_add_activity_invalid_account_name ()

test_add_activity_valid_account_name ()

test_constructor ()

test_create_component ()

test_get_activity_exists ()

test_get_activity_not_exists ()

test_get_component_exists ()

test_get_component_not_exists ()

test_prepare_to_run ()

Test that the component run’s its activities’ prepare_to_run methods.

```
test_remove_component()
test_run()
    Test that the component runs its activities.

test_set_name()
    Test whether the name changes when it is set, that the component's name changes
    and that the component's children's paths are updated correctly.

test_set_parent_path()

class auxi.modelling.business.structure_test.EntityUnitTester(methodName='run')
Bases: unittest.case.TestCase

Tester for the auxi.modelling.entity.component class.

setUp()
test_perform_year_end_gross_profit()
    Test that the year end gross profit account is closed correctly.

test_perform_year_end_gross_profit_and_income_summary()
    Test that the year end gross profit and income summary accounts are summed up
    correctly.

test_perform_year_end_income_summary()
    Test that the year end income summary account is closed correctly.

test_perform_year_end_income_tax()
test_perform_year_end_procedure()
    Test that all the year end accounts has been closed of correctly.

test_perform_year_end_retained_earnings()
    Test that the year end retained earnings account is closed correctly.

test_constructor()
test_create_component()
test_getitem_exists()
test_getitem_not_exists()
test_prepare_to_run()
    Test that the entity run's its component' prepare_to_run methods.

test_remove_component()
test_run()
    Test that the entity runs its components.

test_set_name()
    Test whether the name changes when it is set, that the entity's name changes and
    that the component's children's paths are updated correctly.

test_set_parent_path()
```

Module contents

auxi.modelling.business Package

The purpose of this package is to provide common classes and functions for the auxi.modelling.business namespace

auxi.modelling.financial package

Submodules

auxi.modelling.financial.des module

This module provides classes representing the accounting double entry system.

`auxi.modelling.financial.des.AT`

alias of `AccountType`

`class auxi.modelling.financial.des.AccountType`

Bases: `enum.Enum`

Represents the type of general ledger account.

`asset = <AccountType.asset: 1>`

`equity = <AccountType.equity: 2>`

`expense = <AccountType.expense: 3>`

`liability = <AccountType.liability: 4>`

`revenue = <AccountType.revenue: 5>`

`class auxi.modelling.financial.des.GeneralLedger(name, structure, description=None)`

Bases: `auxi.core.objects.NamedObject`

Represents the account structure of a general ledger.

Parameters

- `name` – The name.
- `structure` – The general ledger structure.
- `description` – The description.

`balance_sheet(end=datetime.datetime(9999, 12, 31, 23, 59, 59, 999999), format=<ReportFormat.printout: (1,)>, output_path=None)`

Generate a transaction list report.

Parameters

- `end` – The end date to generate the report for.

- **format** – The format of the report.
- **output_path** – The path to the file the report is written to. If None, then the report is not written to a file.

Returns The generated report.

```
create_transaction(name, description=None, tx_date=datetime.date(1,
    1, 1), dt_account=None, cr_account=None,
    source=None, amount=0.0)
```

Create a transaction in the general ledger.

Parameters

- **name** – The transaction’s name.
- **description** – The transaction’s description.
- **tx_date** – The date of the transaction.
- **cr_account** – The transaction’s credit account’s name.
- **dt_account** – The transaction’s debit account’s name.
- **source** – The name of source the transaction originated from.
- **amount** – The transaction amount.

Returns The created transaction.

```
income_statement(start=datetime.datetime(1, 1, 1, 0, 0),
    end=datetime.datetime(9999, 12, 31, 23, 59, 59,
    999999), format=<ReportFormat.printout: (1, )>,
    component_path='', output_path=None)
```

Generate a transaction list report.

Parameters

- **start** – The start date to generate the report for.
- **end** – The end date to generate the report for.
- **format** – The format of the report.
- **component_path** – The path of the component to filter the report’s transactions by.
- **output_path** – The path to the file the report is written to. If None, then the report is not written to a file.

Returns The generated report.

```
transaction_list(start=datetime.datetime(1, 1, 1, 0, 0),
    end=datetime.datetime(9999, 12, 31, 23, 59, 59,
    999999), format=<ReportFormat.printout: (1, )>,
    component_path='', output_path=None)
```

Generate a transaction list report.

Parameters

- **start** – The start date to generate the report for.
- **end** – The end date to generate the report for.
- **format** – The format of the report.
- **component_path** – The path of the component to filter the report's transactions by.
- **output_path** – The path to the file the report is written to. If None, then the report is not written to a file.

Returns The generated report.

```
class auxi.modelling.financial.des.GeneralLedgerAccount(name,
    de-
    scrip-
    tion=None,
    num-
    ber=None,
    ac-
    count_type=<AccountType.r
    5>)
```

Bases: *auxi.core.objects.NamedObject*

Represents an account of a general ledger.

Parameters

- **name** – The name.
- **description** – The description.
- **number** – The number.
- **account_type** – The type of account.

create_account (*name*, *number=None*, *description=None*)

Create a sub account in the account.

Parameters

- **name** – The account name.
- **description** – The account description.
- **number** – The account number.

Returns The created account.

get_child_account (*account_name*)

Retrieves a child account. This could be a descendant nested at any level.

Parameters **account_name** – The name of the account to retrieve.

Returns The child account, if found, else None.

name

remove_account (*name*)

Remove an account from the account's sub accounts.

Parameters **name** – The name of the account to remove.

set_parent_path (*value*)

Set the parent path and the path from the new parent path.

Parameters **value** – The path to the object's parent

class auxi.modelling.financial.des.**GeneralLedgerStructure** (*name*,
de-
scrip-
tion=None)

Bases: *auxi.core.objects.NamedObject*

The account structure of a general ledger.

Parameters

- **name** – The name.
- **description** – The description.

get_account (*account_name*)

Retrieves an account from the general ledger structure given the account name.

Parameters **account_name** – The account name.

Returns The requested account, if found, else None.

get_account_descendants (*account*)

Retrieves an account's descendants from the general ledger structure given the account name.

Parameters **account_name** – The account name.

Returns The descendants of the account.

report (*format=<ReportFormat.printout: (1,)>*, *output_path=None*)

Returns a report of this class.

Parameters

- **format** – The format of the report.
- **output_path** – The path to the file the report is written to. If None, then the report is not written to a file.

Returns The descendants of the account.

validate_account_names (*names*)

Validates whether the accounts in a list of account names exists.

Parameters **names** – The names of the accounts.

Returns The descendants of the account.

```
class auxi.modelling.financial.des.Transaction(name,      description=None,
                                                tx_date=datetime.date(1,
                                                1,           1),
                                                dt_account=None,
                                                cr_account=None,
                                                source=None,
                                                amount=0.0,
                                                is_closing_dt_account=False,
                                                is_closing_cr_account=False)
```

Bases: *auxi.core.objects.NamedObject*

Represents a financial transaction between two general ledger accounts.

Parameters

- **name** – The name.
- **description** – The description.
- **tx_date** – The transaction's date.
- **dt_account** – The account to debit.
- **cr_account** – The account to credit.
- **source** – The source that created the transaction.
- **amount** – The transaction's amount.
- **is_closing_dt_account** – Specifies whether this is a closing debit account.
- **is_closing_cr_account** – Specifies whether this is a closing credit account.

```
class auxi.modelling.financial.des.TransactionTemplate(name,
                                                       dt_account,
                                                       cr_account,
                                                       description=None)
```

Bases: *auxi.core.objects.NamedObject*

Represents a template for how a transaction is to be created.

Parameters

- **name** – The name of the transaction.
- **description** – The description of the transaction.
- **dt_account** – The account to debit.
- **cr_account** – The account to credit.

auxi.modelling.financial.des_test module

This module provides testing code for the auxi.modelling.financial.des module.

class auxi.modelling.financial.des_test.GeneralLedgerAccountUnitTester (*methodName='r'*)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.financial.des.GeneralLedgerAccount class.

```
setUp()  
test_constructor()  
test_create_account()  
test_get_child_account()  
test_remove_account()  
test_set_parent_path()
```

class auxi.modelling.financial.des_test.GeneralLedgerStructureUnitTester (*methodName='r'*)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.financial.des.generalledgerstructure class.

```
setUp()  
test_constructor()  
Test the the variables has been initialised and that the default accounts has been  
created.  
  
test_get_account()  
test_get_account_descendants()  
test_report()  
test_validate_account_name_invalid()  
test_validate_account_name_valid()
```

class auxi.modelling.financial.des_test.GeneralLedgerUnitTester (*methodName='r'*)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.financial.des.GeneralLedger class.

```
setUp()  
test_constructor()  
test_create_transaction()
```

class auxi.modelling.financial.des_test.TransactionTemplateUnitTester (*methodName='r'*)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.financial.des.TransactionTemplate class.

```
setUp()  
test_constructor()
```

```
class auxi.modelling.financial.des_test.TransactionUnitTester (methodName='run')
Bases: unittest.case.TestCase

Tester for the auxi.modelling.financial.des.Transaction class.

setUp()
test_constructor()
```

auxi.modelling.financial.reporting module

This module provides classes to manage currencies.

```
class auxi.modelling.financial.reporting.BalanceSheet (data_source,
                                                       end=datetime.date(9999,
                                                       12, 31),
                                                       out-
                                                       put_path=None)
```

Bases: auxi.modelling.financial.reporting.Report

Report a balance sheet of a general ledger.

Parameters

- **data_source** – The object to report on.
- **end** – The end date to generate the report for.
- **output_path** – The path to write the report file to.

```
class auxi.modelling.financial.reporting.GeneralLedgerStructure (data_source,
                                                               out-
                                                               put_path=None)
```

Bases: auxi.modelling.financial.reporting.Report

Report on a general ledger structure.

Parameters

- **data_source** – The object to report on.
- **output_path** – The path to write the report file to.

```
class auxi.modelling.financial.reporting.IncomeStatement (data_source,
                                                          start=datetime.date(1,
                                                          1, 1),
                                                          end=datetime.date(9999,
                                                          12,
                                                          31),
                                                          com-
                                                          po-
                                                          nent_path='',
                                                          out-
                                                          put_path=None)
```

Bases: auxi.modelling.financial.reporting.Report

Report an income statement of a general ledger.

Parameters

- **data_source** – The object to report on.
- **end** – The start date to generate the report for.
- **end** – The end date to generate the report for.
- **component_path** – The path of the component to filter the report's transactions by.
- **output_path** – The path to write the report file to.

```
class auxi.modelling.financial.reporting.Report(data_source, output_path=None)
```

Bases: *auxi.core.reporting.Report*

Base class for reports.

Parameters

- **data_source** – The object to report on.
- **output_path** – The path to write the report file to.

```
class auxi.modelling.financial.reporting.ReportType
```

Bases: enum.Enum

Represents a report type, e.g. balance sheet or income statement.

balance_sheet = <ReportType.balance_sheet: (1,>

cash_flow = <ReportType.cash_flow: 4>

income_statement = <ReportType.income_statement: (2,>

transaction_list = <ReportType.transaction_list: (3,>

```
class auxi.modelling.financial.reporting.TransactionList(data_source, start=datetime.date(1, 1, 1), end=datetime.date(9999, 12, 31), component_path='', output_path=None)
```

Bases: *auxi.modelling.financial.reporting.Report*

Report on a list of transactions.

Parameters

- **data_source** – The object to report on.

- **end** – The start date to generate the report for.
- **end** – The end date to generate the report for.
- **component_path** – The path of the component to filter the report's transactions by.
- **output_path** – The path to write the report file to.

auxi.modelling.financial.reporting_test module

This module provides testing code for the auxi.modelling.financial.des module.

```
class auxi.modelling.financial.reporting_test.GeneralLedgerStructureUnitTests
    Bases: unittest.case.TestCase

    Tester for the auxi.modelling.financial.reporting.GeneralLedgerStructure class.

    setUp()
    test_generate_table_()

class auxi.modelling.financial.reporting_test.TransactionListUnitTester(meth...
    Bases: unittest.case.TestCase

    Tester for the auxi.modelling.financial.reporting.TransactionList class.

    setUp()
    test_generate_table_()
```

Module contents

auxi.modelling.financial Package

The purpose of this package is to provide common classes and functions for the the auxi.modelling.financial namespace

auxi.modelling.process package

Subpackages

auxi.modelling.process.materials package

Submodules

auxi.modelling.process.materials.chem module

This module provides classes to work with materials and material packages that are described with chemical compositions.

```
class auxi.modelling.process.materials.chem.Material (name,  

                                                    file_path,  

                                                    descrip-  

                                                    tion=None)
```

Bases: *auxi.core.objects.NamedObject*

A material consisting of multiple chemical compounds.

Parameters

- **name** – The material’s name.
- **file_path** – The path of the material definition file.
- **description** – the material’s description

The format of the text file is as follows:

- The lines are space separated. The values in a line are separated by one or more spaces.
- The first line is a heading line.
- All subsequent lines contain a compound formula, followed by mass fractions.
- The first column lists the compounds in the material.
- All subsequent columns describe assays of the material.

The following is an example of a material text file:

Compound	IlmeniteA	IlmeniteB	IlmeniteC
Al2O3	0.01160	0.01550	0.00941
CaO	0.00022	0.00001	0.00017
Cr2O3	0.00008	0.00022	0.00011
Fe2O3	0.20200	0.47300	0.49674
Fe3O4	0.00000	0.00000	0.00000
FeO	0.27900	0.19100	0.00000
K2O	0.00004	0.00001	0.00005
MgO	0.01040	0.00580	0.01090
MnO	0.00540	0.00480	0.00525
Na2O	0.00007	0.00005	0.00031
P4O10	0.00001	0.00032	0.00015
SiO2	0.00850	0.00490	0.01744
TiO2	0.47700	0.29400	0.45949
V2O5	0.00360	0.00800	0.00000

add_assay (*name*, *assay*)

Add an assay to the material.

Parameters

- **name** – The name of the new assay.
- **assay** – A list containing the compound mass fractions for the assay. The sequence of the assay’s elements must correspond to the sequence of the material’s compounds.

create_empty_assay()

Create an empty array to store an assay. The array's length will be equal to the number of compounds in the material.

Returns A floating point array.

create_package (*assay=None, mass=0.0, normalise=True*)

Create a MaterialPackage based on the specified parameters.

Parameters

- **assay** – The name of the assay based on which the package must be created.
- **mass** – [kg] The mass of the package.
- **normalise** – Indicates whether the assay must be normalised before creating the package.

Returns The created MaterialPackage.

get_assay_total (*name*)

Calculate the total of the specified assay.

Parameters **name** – The name of the assay.

Returns The total mass fraction of the specified assay.

get_compound_index (*compound*)

Determine the index of the specified compound.

Parameters **compound** – The formula and phase of the specified compound, e.g. ‘Fe2O3[S1]’.

Returns The index of the specified compound.

class auxi.modelling.process.materials.chem.**MaterialPackage** (*material, compound_masses*)

Bases: *auxi.core.objects.Object*

A package of a material consisting of multiple chemical compounds.

Parameters

- **material** – A reference to the Material to which self belongs.
- **compound_masses** – [kg] The masses of the compounds in the package.

add_to (*other*)

Add another chem material package to this material package.

Parameters **other** – The other material package.

clear()

Set all the compound masses in the package to zero.

clone()

Create a complete copy of self.

Returns A MaterialPackage that is identical to self.

extract (*other*)

Extract ‘other’ from self, modifying self and returning the extracted material as a new package.

Parameters other – Can be one of the following:

- float: A mass equal to other is extracted from self. Self is reduced by other and the extracted package is returned as a new package.
- tuple (compound, mass): The other tuple specifies the mass of a compound to be extracted. It is extracted from self and the extracted mass is returned as a new package.
- string: The ‘other’ string specifies the compound to be extracted. All of the mass of that compound will be removed from self and a new package created with it.

Returns A new material package containing the material that was extracted from self.

get_assay()

Determine the assay of self.

Returns [mass fractions] An array containing the assay of self.

get_compound_mass (*compound*)

Get the mass of the specified compound in the package.

Parameters compound – The formula of the compound, e.g. Fe₂O₃.

Returns [kg]

get_compound_mass_fraction (*compound*)

Get the mass fraction of the specified compound in self.

Parameters compound – The formula and phase of the compound, e.g. Fe₂O₃.

Returns []

get_element_mass (*element*)

Determine the masses of elements in the package.

Returns [kg] An array of element masses. The sequence of the elements in the result corresponds with the sequence of elements in the element list of the material.

get_element_mass_dictionary()

Determine the masses of elements in the package and return as a dictionary.

Returns [kg] A dictionary of element symbols and masses.

get_element_masses()

Get the masses of elements in the package.

Returns [kg] An array of element masses. The sequence of the elements in the result corresponds with the sequence of elements in the element list of the material.

get_mass()

Get the mass of the package.

Returns [kg]

auxi.modelling.process.materials.chem_test module

This module provides testing code for classes in the chem module.

class auxi.modelling.process.materials.chem_test.ChemMaterialPackageUnitTests

Bases: unittest.case.TestCase

Tester for the auxi.modelling.process.materials.chemistry.material.Material class.

add_incompatible_packages()

setUp()

test_add_operator_1()

other = MaterialPackage

Test whether the add operator calculates the resulting package correctly. Results were checked against FactSage results. They are not exactly the same, since the magnetic and other non-cp contributions are omitted by the thermo module.

test_add_operator_2()

Tests the scenario when a ‘mix’ is created and two packages ‘mixed’ into the mix package.

test_add_operator_3()

other = tuple (compound, mass) Test whether the add operator calculates the resulting package correctly. Results were checked against FactSage results. They are not exactly the same, since the magnetic and other non-cp contributions are omitted by the thermo module.

test_clone()

test_constructor()

test_extract_1()

test_get_assay()

test_get_compound_mass()

test_get_element_masses()

test_get_mass()

test_multiply_operator()

```
test_subtract_operator_2()
test_subtract_operator_3()

class auxi.modelling.process.materials.chem_test.ChemMaterialUnitTester(meth)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.process.materials.chem.Material class.

assertAlmostEqual(first, second, places=14, msg=None, delta=None)

setUp()
test_add_assay()
test_constructor()
test_create_empty_assay()
test_create_package()
test_get_assay_total()
test_get_compound_index()
```

auxi.modelling.process.materials.core module

auxi.modelling.process.materials.core_test module

auxi.modelling.process.materials.psd module

This module provides psd material and material package classes that can do size distribution calculations.

```
class auxi.modelling.process.materials.psd.Material(name,
                                                     file_path,
                                                     descrip-
                                                     tion=None)
Bases: auxi.core.objects.NamedObject
```

Represents a particulate material consisting of multiple particle size classes.

Parameters

- **name** – The material’s name.
- **file_path** – The path of the material definition file.
- **description** – the material’s description

The format of the text file is as follows:

- The lines are space separated. The values in a line are separated by one or more spaces.
- The first line is a heading line.

- All subsequent lines contain a particle size, followed by mass fractions.
- Particle sizes are indicated in [meter].
- The first column lists the particle sizes in the material. Each class must be interpreted as “mass fraction retained”. In other words if the size class is indicated as 307.2E-3, it means that it is the class of material retained on a 307.2mm screen, and can also be thought of as +307.2mm material. The first size class represents the largest particles. The final size class should be zero, as it represents all material that passed through the smallest aperture screen.
- All subsequent columns describe assays of the material.

The following is an example of a material text file:

Compound	FeedA	MillCharge
307.2E-3	0.20	0.02
108.6E-3	0.18	0.06
38.4E-3	0.17	0.04
13.6E-3	0.07	0.03
4.8E-3	0.13	0.03
1.7E-3	0.07	0.04
600.0E-6	0.06	0.18
210.0E-6	0.02	0.50
75.0E-6	0.10	0.10
0.0E0	0.00	0.00

add_assay (*name, assay*)

Add an assay to the material.

Parameters

- **name** – The name of the new assay.
- **assay** – A numpy array containing the size class mass fractions for the assay. The sequence of the assay’s elements must correspond to the sequence of the material’s size classes.

create_empty_assay ()

Create an empty array to store an assay. The array’s length will be equal to the number of size classes in the material.

Returns A floating point array.

create_package (*assay=None, mass=0.0, normalise=True*)

Create a MaterialPackage based on the specified parameters.

Parameters

- **assay** – The name of the assay based on which the package must be created.
- **mass** – [kg] The mass of the package.
- **normalise** – Indicates whether the assay must be normalised before creating the package.

Returns The created MaterialPackage.

get_assay_total(*name*)

Calculate the total of the specified assay.

Parameters **name** – The name of the assay.

Returns The total mass fraction of the specified assay.

get_size_class_index(*size_class*)

Determine the index of the specified size class.

Parameters **size_class** – The formula and phase of the specified size class, e.g. ‘Fe2O3[S1]’.

Returns The index of the specified size class.

class auxi.modelling.process.materials.psd.**MaterialPackage**(*material*,
size_class_masses)

Bases: *auxi.core.objects.Object*

A package of a material consisting of multiple particle size classes.

Properties defined here:

Parameters

- **material** – A reference to the Material to which self belongs.
- **size_class_masses** – [kg] [kg] The masses of the size classes in the package.

add_to(*other*)

Add another psd material package to this material package.

Parameters **other** – The other material package.

clear()

Set all the size class masses in the package to zero.

clone()

Create a complete copy of self.

Returns A MaterialPackage that is identical to self.

extract(*other*)

Extract ‘other’ from self, modifying self and returning the extracted material as a new package.

Parameters **other** – Can be one of the following:

- float: A mass equal to other is extracted from self. Self is reduced by other and the extracted package is returned as a new package.
- tuple (size class, mass): The other tuple specifies the mass of a size class to be extracted. It is extracted from self and the extracted mass is returned as a new package.

- string: The ‘other’ string specifies the size class to be extracted. All of the mass of that size class will be removed from self and a new package created with it.

Returns A new material package containing the material that was extracted from self.

get_assay()

Determine the assay of self.

Returns [mass fractions] An array containing the assay of self.

get_mass()

Determine the mass of self.

returns: [kg] The mass of self.

get_size_class_mass(size_class)

Determine the mass of the specified size class in self.

Parameters **size_class** – The formula and phase of the size class,
e.g. ‘Fe2O3[S1]’

Returns [kg] The mass of the size class in self.

get_size_class_mass_fraction(size_class)

Determine the mass fraction of the specified size class in self.

Parameters **size_class** – The formula and phase of the size class,
e.g. ‘Fe2O3[S1]’

Returns The mass fraction of the size class in self.

auxi.modelling.process.materials.psd_test module

This module provides testing code for the psdmaterial module.

@author: Ex Mente Technologies (Pty) Ltd

class auxi.modelling.process.materials.psd_test.**PsdMaterialPackageUnitTest**

Bases: unittest.case.TestCase

Tester for the auxi.modelling.process.materials.psd.material.MaterialPackage class.

setUp()

test_add_operator_1()

other = MaterialPackage Test whether the add operator calculates the resulting package correctly.

test_add_operator_3()

other = tuple (size_class, mass) Test whether the add operator calculates the resulting package correctly. Results were checked against FactSage results. They are not exactly the same, since the magnetic and other non-cp contributions are omitted by the thermo module.

```
test_clone()
test_constructor()
test_extract_1()
test_get_assay()
test_get_mass()
test_get_size_class_mass()
test_multiply_operator()
test_subtract_operator_2()
test_subtract_operator_3()
```

class auxi.modelling.process.materials.psd_test.**PsdMaterialUnitTester**(method)
Bases: unittest.case.TestCase

Tester for the auxi.modelling.process.materials.psd.Material class.

```
setUp()
test_add_assay()
test_constructor()
test_create_empty_assay()
test_create_package()
test_get_assay_total()
test_get_size_class_index()
```

auxi.modelling.process.materials.slurry module

This module provides material and material package classes that can do size distribution and slurry calculations.

class auxi.modelling.process.materials.slurry.**Material**(name,
 file_path,
 descrip-
 tion=None)

Bases: *auxi.core.objects.NamedObject*

Represents a particulate material consisting of multiple particle size classes.

Parameters

- **name** – The material’s name.
- **file_path** – The path of the material definition file.
- **description** – the material’s description

The format of the text file is as follows:

- The lines are space separated. The values in a line are separated by one or more spaces.
- The first line is a heading line.
- The second line contains the density of the solid material.
- The third line contains the water fraction of the slurry (wet basis).
- All subsequent lines contain a particle size, followed by mass fractions (dry basis).
- Particle sizes are indicated in [meter].
- The first column lists the particle sizes in the material. Each class must be interpreted as “mass fraction retained”. In other words if the size class is indicated as 307.2E-3, it means that it is the class of material retained on a 307.2mm screen, and can also be thought of as +307.2mm material. The first size class represents the largest particles. The final size class should be zero, as it represents all material that passed through the smallest aperture screen.
- All subsequent columns describe assays of the material.

The following is an example of a material text file:

SizeClass	DryFeedA	DryMillCharge	WetFeedA	
↪ WetMillCharge	Water			
solid_density	3.00	3.00	3.00	3.00
↪ 1.0.				
H2O	0.00	0.00	0.80	0.60
↪ 1.00				
307.2E-3	0.20	0.02	0.20	0.02
↪ 0.00				
108.6E-3	0.18	0.06	0.18	0.06
↪ 0.00				
38.4E-3	0.17	0.04	0.17	0.04
↪ 0.00				
13.6E-3	0.07	0.03	0.07	0.03
↪ 0.00				
4.8E-3	0.13	0.03	0.13	0.03
↪ 0.00				
1.7E-3	0.07	0.04	0.07	0.04
↪ 0.00				
600.0E-6	0.06	0.18	0.06	0.18
↪ 0.00				
210.0E-6	0.02	0.50	0.02	0.50
↪ 0.00				
75.0E-6	0.10	0.09	0.10	0.09
↪ 0.00				
0.0E0	0.00	0.00	0.00	0.00
↪ 0.00				

add_assay (*name, solid_density, H2O_fraction, assay*)

Add an assay to the material.

Parameters

- **name** – The name of the new assay.
- **assay** – A numpy array containing the size class mass fractions for the assay. The sequence of the assay’s elements must correspond to the sequence of the material’s size classes.

`create_empty_assay()`

Create an empty array to store an assay. The array’s length will be equal to the number of size classes in the material.

Returns A floating point array.

`create_package(assay=None, mass=0.0, normalise=True)`

Create a MaterialPackage based on the specified parameters.

Parameters

- **assay** – The name of the assay based on which the package must be created.
- **mass** – [kg] The mass of the package.
- **normalise** – Indicates whether the assay must be normalised before creating the package.

Returns The created MaterialPackage.

`get_assay_total(name)`

Calculate the total of the specified assay.

Parameters **name** – The name of the assay.

Returns The total mass fraction of the specified assay.

`get_size_class_index(size_class)`

Determine the index of the specified size class.

Parameters **size_class** – The formula and phase of the specified size class, e.g. ‘Fe2O3[S1]’.

Returns The index of the specified size class.

```
class auxi.modelling.process.materials.slurry.MaterialPackage(material,
                                                               solid_density,
                                                               H2O_mass,
                                                               size_class_masses)
```

Bases: `auxi.core.objects.Object`

A package of a slurry material consisting of multiple particle size classes.

Parameters

- **material** – A reference to the Material to which self belongs.
- **size_class_masses** – [kg] [kg] The masses of the size classes in the package.

clear()

Set all the size class masses and H2O_mass in the package to zero and the solid_density to 1.0

clone()

Create a complete copy of self.

Returns A MaterialPackage that is identical to self.

extract (other)

Extract ‘other’ from self, modifying self and returning the extracted material as a new package.

Parameters other – Can be one of the following:

- float: A mass equal to other is extracted from self. Self is reduced by other and the extracted package is returned as a new package.
- tuple (size class, mass): The other tuple specifies the mass of a size class to be extracted. It is extracted from self and the extracted mass is returned as a new package.
- string: The ‘other’ string specifies the size class to be extracted. All of the mass of that size class will be removed from self and a new package created with it.

Returns A new material package containing the material that was extracted from self.

get_assay()

Determine the assay of self.

Returns [mass fractions] An array containing the assay of self.

get_density()

Determine the density of self.

get_mass()

Determine the mass of self.

Returns [kg] The mass of self.

get_mass_fraction_solids()

Determine the mass fraction of the solids of self.

get_size_class_mass (size_class)

Determine the mass of the specified size class in self.

Parameters size_class – The formula and phase of the size class, e.g. ‘Fe2O3[S1]’

Returns [kg] The mass of the size class in self.

get_size_class_mass_fraction (size_class)

Determine the mass fraction of the specified size class in self.

Parameters `size_class` – The formula and phase of the size class,
e.g. Fe2O3[S1]

Returns The mass fraction of the size class in self.

`get_solid_mass()`

Determine the solid mass of self.

Returns [kg] The solid mass of self.

`get_volume()`

Determine the volume of self.

`get_volume_fraction_solids()`

Determine the volume fraction of the solids of self.

auxi.modelling.process.materials.slurry_test module

This module provides testing code for the psdslurrymaterial module.

@author: Ex Mente Technologies (Pty) Ltd

class auxi.modelling.process.materials.slurry_test.`SlurryMaterialPackageUnit`
Bases: unittest.case.TestCase

`setUp()`

`test__str__()`

`test_add_operator_1()`

other = MaterialPackage Test whether the add operator calculates the resulting package correctly.

`test_add_operator_3()`

other = tuple (size_class, mass) Test whether the add operator calculates the resulting package correctly. Results were checked against FactSage results. They are not exactly the same, since the magnetic and other non-cp contributions are omitted by the thermo module.

`test_clone()`

`test_constructor()`

`test_extract_1()`

`test_get_assay()`

`test_get_mass()`

`test_get_size_class_mass()`

`test_multiply_operator()`

`test_subtract_operator_2()`

`test_subtract_operator_3()`

```
class auxi.modelling.process.materials.slurry_test.SlurryMaterialUnitTester
    Bases: unittest.case.TestCase

    Tester for the auxi.modelling.process.materials.slurry.Material class.

    setUp()
    test_add_assay()
    test_constructor()
    test_create_empty_assay()
    test_create_package()
    test_get_assay_total()
    test_get_size_class_index()
```

auxi.modelling.process.materials.thermo module

auxi.modelling.process.materials.thermo_test module

Module contents

This package provides classes and functions for working with different types of materials and material packages.

Module contents

The purpose of this package is to provide common classes and functions for the the auxi.modelling.process namespace

Module contents

The purpose of this package is to provide common classes and functions for the auxi.modelling namespace

auxi.tools package

Subpackages

auxi.tools.chemistry package

Submodules

auxi.tools.chemistry.stoichiometry module

This module provides a number of functions for doing stoichiometry calculations.

```
class auxi.tools.chemistry.stoichiometry.Compound(group, dotted-
                                                 group=None,
                                                 phase=None)
```

Bases: `object`

Represents a full compound formula

Parameters

- **group** – iterable of Group/Element
- **dottedgroup** – A Group if there is a .H₂O part, None otherwise
- **phase** – The phase if there is a [phase] part, None otherwise

```
count()
```

```
molar_mass()
```

```
class auxi.tools.chemistry.stoichiometry.CompoundVisitor
```

Bases: `parsimonious.nodes.NodeVisitor`

Visitor which takes parsed tree to useful groups.

For parallels, check the grammar.

```
generic_visit(node, other)
visit_compound(_, compound)
visit_dottedgroup(_, dottedgroup)
visit_element(node, _)
visit_group(_, group)
visit_number(node, _)
visit_phase(node, _)
visit_subscriptedelement(_, subscriptedelement)
visit_subscriptedgroup(_, subscriptedgroup)
```

```
class auxi.tools.chemistry.stoichiometry.Element(period, group,
                                                 atomic_number,
                                                 symbol,      mo-
                                                 lar_mass)
```

Bases: `auxi.core.objects.Object`

An element in the periodic table.

Parameters

- **period** – Period to which the element belongs.
- **group** – Group to which the element belongs.

- **atomic_number** – Number of protons in the element’s nucleus.
- **symbol** – Element’s symbol.
- **molar_mass** – [kg/kmol] Element’s standard atomic mass.

count()

class auxi.tools.chemistry.stoichiometry.Group(*group*, *multiplier=1*,
dotted=False)

Bases: [object](#)

Represent a part of a compound formula

Parameters

- **group** – iterable of Group/Element parts
- **multiplier** – multiplier in subscript or prefix of group
- **dotted** – True of the group is like ‘.2H₂O’

count()

auxi.tools.chemistry.stoichiometry.amount(*compound*, *mass*)

Calculate the number of moles in the specified mass of a chemical compound.

Parameters

- **compound** – Formula and phase of a compound, e.g. ‘Fe₂O₃[S1]’. The phase may be omitted.
- **mass** – [kg]

Returns

Amount. [kmol]

auxi.tools.chemistry.stoichiometry.amount_fractions(*masses*)

Calculate the mole fractions from the specified compound masses.

Parameters **masses** – [kg] dictionary, e.g. {‘SiO₂’: 3.0, ‘FeO’: 1.5}

Returns [mole fractions] dictionary

auxi.tools.chemistry.stoichiometry.amounts(*masses*)

Calculate the amounts from the specified compound masses.

Parameters **masses** – [kg] dictionary, e.g. {‘SiO₂’: 3.0, ‘FeO’: 1.5}

Returns [kmol] dictionary

auxi.tools.chemistry.stoichiometry.convert_compound(*mass*,
source,
target,
element)

Convert the specified mass of the source compound to the target using element as basis.

Parameters

- **mass** – Mass of from_compound. [kg]

- **source** – Formula and phase of the original compound, e.g. ‘Fe₂O₃[S1]’.
- **target** – Formula and phase of the target compound, e.g. ‘Fe[S1]’.
- **element** – Element to use as basis for the conversion, e.g. ‘Fe’ or ‘O’.

Returns Mass of target. [kg]

```
auxi.tools.chemistry.stoichiometry.count_with_multiplier(groups,
mul-
ti-
plier)
```

Update group counts with multiplier

This is for handling atom counts on groups like (OH)₂

Parameters

- **groups** – iterable of Group/Element
- **multiplier** – the number to multiply by

```
auxi.tools.chemistry.stoichiometry.element_mass_fraction(compound,
el-
e-
ment)
```

Determine the mass fraction of an element in a chemical compound.

Parameters

- **compound** – Formula of the chemical compound, ‘FeCr₂O₄’.
- **element** – Element, e.g. ‘Cr’.

Returns Element mass fraction.

```
auxi.tools.chemistry.stoichiometry.element_mass_fractions(compound,
el-
e-
ments)
```

Determine the mass fractions of a list of elements in a chemical compound.

Parameters

- **compound** – Formula and phase of a chemical compound, e.g. ‘Fe₂O₃[S1]’.
- **elements** – List of elements, [‘Si’, ‘O’, ‘Fe’].

Returns Mass fractions.

```
auxi.tools.chemistry.stoichiometry.elements(compounds)
```

Determine the set of elements present in a list of chemical compounds.

The list of elements is sorted alphabetically.

Parameters **compounds** – List of compound formulas and phases, e.g. [‘Fe2O3[S1]’, ‘Al2O3[S1]’].

Returns List of elements.

`auxi.tools.chemistry.stoichiometry.mass (compound, amount)`

Calculate the mass of the specified amount of a chemical compound.

Parameters

- **compound** – Formula and phase of a compound, e.g. ‘Fe2O3[S1]’. The phase may be omitted.
- **amount** – [kmol]

Returns Mass. [kg]

`auxi.tools.chemistry.stoichiometry.mass_fractions (amounts)`

Calculate the mole fractions from the specified compound masses.

Parameters **masses** – [kg] dictionary, e.g. {‘SiO2’: 3.0, ‘FeO’: 1.5}

Returns [mass fractions] dictionary

`auxi.tools.chemistry.stoichiometry.masses (amounts)`

Calculate the masses from the specified compound amounts.

Parameters **masses** – [kmol] dictionary, e.g. {‘SiO2’: 3.0, ‘FeO’: 1.5}

Returns [kg] dictionary

`auxi.tools.chemistry.stoichiometry.molar_mass (compound=’’)`

Determine the molar mass of a chemical compound.

The molar mass is usually the mass of one mole of the substance, but here it is the mass of 1000 moles, since the mass unit used in auxi is kg.

Parameters **compound** – Formula of a chemical compound, e.g. ‘Fe2O3’.

Returns Molar mass. [kg/kmol]

`auxi.tools.chemistry.stoichiometry.parse_compound`

`auxi.tools.chemistry.stoichiometry.stoichiometry_coefficient (compound, el-
e-
ment)`

Determine the stoichiometry coefficient of an element in a chemical compound.

Parameters

- **compound** – Formula of a chemical compound, e.g. ‘SiO2’.
- **element** – Element, e.g. ‘Si’.

Returns Stoichiometry coefficient.

```
auxi.tools.chemistry.stoichiometry.stoichiometry_coefficients(compound,
el-
e-
ments)
```

Determine the stoichiometry coefficients of the specified elements in the specified chemical compound.

Parameters

- **compound** – Formula of a chemical compound, e.g. ‘SiO₂’.
- **elements** – List of elements, e.g. [‘Si’, ‘O’, ‘C’].

Returns List of stoichiometry coefficients.

auxi.tools.chemistry.stoichiometry_test module

This module contains all the code used to test the testee module.

```
class auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester(methodName)
Bases: unittest.case.TestCase
```

The function tester for the stoichiometry module.

```
assertAlmostEqual(first, second, places=14, msg=None, delta=None)
```

```
test_amount()
```

Test whether the amount of a compound is calculated correctly.

```
test_amount_fractions()
```

Test whether compound amount fractions are calculated correctly.

```
test_amounts()
```

Test whether compound amounts are calculated correctly.

```
test_convert_compound()
```

Test whether compound conversions are calculated correctly.

```
test_element_mass_fraction()
```

Test whether an element mass fraction is calculated correctly.

```
test_element_mass_fractions()
```

Test whether a list of element mass fraction is calculated correctly.

```
test_elements()
```

Test whether the set of elements in a list of compounds is calculated correctly.

```
test_invalid_characters()
```

Test whether an exception is raised when a compound formula contains an invalid character.

```
test_mass()
```

Test whether the mass of a compound is calculated correctly.

```
test_mass_fractions()
```

Test whether compound mass fractions are calculated correctly.

test_masses()

Test whether compound masses are calculated correctly.

test_molar_mass()

Test whether the molar mass of a compound is calculated correctly.

test_phase()

Test whether the phase of a compound is parsed correctly

test_stoichiometry_coefficient()

Test whether the stoichiometry coefficient of a specified element in a compound is calculated correctly.

test_stoichiometry_coefficients()

Test whether the stoichiometry coefficients of a specified list of elements in a compound is calculated correctly.

auxi.tools.chemistry.thermochemistry module

auxi.tools.chemistry.thermochemistry_test module

Module contents

This package provides chemistry-related tools to make various tasks quick, easy and accurate.

auxi.tools.materialphysicalproperties package

Submodules

auxi.tools.materialphysicalproperties.core module

auxi.tools.materialphysicalproperties.core_test module

auxi.tools.materialphysicalproperties.gases module

auxi.tools.materialphysicalproperties.idealgas module

auxi.tools.materialphysicalproperties.idealgas_test module

auxi.tools.materialphysicalproperties.liquids module

auxi.tools.materialphysicalproperties.polynomial module

auxi.tools.materialphysicalproperties.polynomial_test module

auxi.tools.materialphysicalproperties.slags module

Module contents

This package provides tools to calculate material physical properties.

auxi.tools.transportphenomena package

Submodules

auxi.tools.transportphenomena.dimensionlessquantities module

This module provides functions to calculate dimensionless quantities used when doing transport phenomena calculations.

```
auxi.tools.transportphenomena.dimensionlessquantities.Gr(L:  
          float,  
          Ts:  
          float,  
          Tf:  
          float,  
          beta:  
          float,  
          nu:  
          float,  
          g:  
          float)
```

Calculate the Grashof number.

Parameters

- **L** – [m] heat transfer surface characteristic length.
- **Ts** – [K] heat transfer surface temperature.
- **Tf** – [K] bulk fluid temperature.
- **beta** – [1/K] fluid coefficient of thermal expansion.
- **nu** – [m²/s] fluid kinematic viscosity.

Returns float

$$\text{Gr} = \frac{g\beta(Ts - Tinf)L^3}{\nu^2}$$

Characteristic dimensions:

- vertical plate: vertical length
- pipe: diameter
- bluff body: diameter

```
auxi.tools.transportphenomena.dimensionlessquantities.Nu (L:  
          float,  
          h:  
          float,  
          k:  
          float)  
          →  
          float
```

Calculate the Nusselt number.

Parameters

- **L** – [m] heat transfer surface characteristic length.
- **h** – [W/K/m²] convective heat transfer coefficient.
- **k** – [W/K/m] fluid thermal conductivity.

Returns float

```
auxi.tools.transportphenomena.dimensionlessquantities.Pr (nu:  
          float,  
          al-  
          pha:  
          float)  
          →  
          float
```

Calculate the Prandtl number.

Parameters

- **nu** – [m²/s] fluid kinematic viscosity / momentum diffusivity.
- **alpha** – [m²/s] fluid thermal diffusivity.

Returns float

```
auxi.tools.transportphenomena.dimensionlessquantities.Ra (L:  
          float,  
          Ts:  
          float,  
          Tf:  
          float,  
          al-  
          pha:  
          float,  
          beta:  
          float,  
          nu:  
          float)  
          →  
          float
```

Calculate the Grashof number.

Parameters

- **L** – [m] heat transfer surface characteristic length.
- **Ts** – [K] heat transfer surface temperature.
- **Tf** – [K] bulk fluid temperature.
- **alpha** – [m²/s] fluid thermal diffusivity.
- **beta** – [1/K] fluid coefficient of thermal expansion.
- **nu** – [m²/s] fluid kinematic viscosity.

Returns float

$$\text{Ra} = \text{Gr} * \text{Pr}$$

Characteristic dimensions:

- vertical plate: vertical length
- pipe: diameter
- bluff body: diameter

```
auxi.tools.transportphenomena.dimensionlessquantities.Re(L:  
float,  
v:  
float,  
nu:  
float)  
→  
float
```

Calculate the Reynolds number.

Parameters

- **L** – [m] surface characteristic length.
- **v** – [m/s] fluid velocity relative to the object.
- **nu** – [m²/s] fluid kinematic viscosity.

Returns float

```
auxi.tools.transportphenomena.dimensionlessquantities.Sh(L:  
float,  
h:  
float,  
D:  
float)  
→  
float
```

Calculate the Sherwood number.

Parameters

- **L** – [m] mass transfer surface characteristic length.
- **h** – [m/s] mass transfer coefficient.

- **D** – [m²/s] fluid mass diffusivity.

Returns float

Module contents

This package provides tools to do calculations related to heat transfer, mass transfer, and fluid flow.

Submodules

auxi.tools.physicalconstants module

This module provides a set of physical constants that are used frequently.

`auxi.tools.physicalconstants.F = 96485.3365`

[C·mol⁻¹] Faraday constant

`auxi.tools.physicalconstants.G = 6.67408e-11`

[m³kg⁻¹s⁻²] Newtonian constant of gravitation

`auxi.tools.physicalconstants.N_A = 6.02214129e+23`

[mol⁻¹] Avogadro's number

`auxi.tools.physicalconstants.R = 8.3144621`

[J·K⁻¹·mol⁻¹] gas constant

`auxi.tools.physicalconstants.c = 299792458`

[m·s⁻¹] speed of light in vacuum

`auxi.tools.physicalconstants.g = 9.80665`

[m·s⁻²] standard acceleration of gravity

`auxi.tools.physicalconstants.h = 6.62607004e-34`

[J·s] Planck constant

`auxi.tools.physicalconstants.h_bar = 1.0545718e-34`

[J·s] reduced Planck constant ($\hbar/(2\pi)$)

`auxi.tools.physicalconstants.k_B = 1.3806488e-23`

[J·K⁻¹] Boltzmann constant

`auxi.tools.physicalconstants.m_u = 1.660538921e-27`

[kg] atomic mass constant

Module contents

This package provides tools to make common tasks quick, easy and accurate.

Submodules

auxi.tests module

Module contents

A toolkit to help metallurgical process engineers to rapidly do day-to-day calculations.

auxi is a toolkit to help metallurgical process engineers with their day-to-day tasks. Many of the calculations that we do require things like molar masses, conversion of one compound to another using stoichiometry, heat transfer calculations, mass balances, energy balances, etc. It is usually quite time consuming to get started with these calculations in a tool like Excel. auxi aims to save you time by making many of these calculations available from within python.

We hope that auxi will help you spend less time focusing on searching for formulas and data, and setting up calculations, and more on thinking about the problems that you need to solve with these calculations. Enjoy!

If you need more information about how to use auxi, please refer the documentation at <https://auxi.readthedocs.org/en/latest/>.

**CHAPTER
FIVE**

INDICES AND TABLES

- genindex
- modindex
- search

PYTHON MODULE INDEX

a

auxi, 97
auxi.core, 53
auxi.core.helpers, 49
auxi.core.helpers_test, 49
auxi.core.objects, 50
auxi.core.objects_test, 50
auxi.core.reporting, 51
auxi.core.reporting_test, 51
auxi.core.time, 52
auxi.core.time_test, 53
auxi.modelling, 86
auxi.modelling.business, 64
auxi.modelling.business.basic_test,
 56
auxi.modelling.business.models_test,
 58
auxi.modelling.business.structure_test,
 62
auxi.modelling.financial, 72
auxi.modelling.financial.des_test,
 69
auxi.modelling.financial.reporting_test,
 72
auxi.modelling.process, 86
auxi.modelling.process.materials,
 86
auxi.modelling.process.materials.chem_test,
 76
auxi.modelling.process.materials.psd_test,
 80
auxi.modelling.process.materials.slurry_test,
 85
auxi.tools, 96
auxi.tools.chemistry, 92
auxi.tools.chemistry.stoichiometry_test,
 91
auxi.tools.materialphysicalproperties,

INDEX

A

AccountType (class in auxi.modelling.financial.des), 64

Activity (class in auxi.modelling.business.structure), 58

ActivityUnitTester (class in auxi.modelling.business.structure_test), 62

add_activity() (auxi.modelling.business.structure.Component method), 60

add_assay() (auxi.modelling.process.materials.chem.Material method), 73

add_assay() (auxi.modelling.process.materials.psd.Material method), 78

add_assay() (auxi.modelling.process.materials.slurry.Material method), 82

add_incompatible_packages() (auxi.modelling.process.materials.chem.Material method), 76

add_to() (auxi.modelling.process.materials.chem.Material method), 74

add_to() (auxi.modelling.process.materials.psd.Material method), 79

amount (auxi.modelling.business.basic.BasicLoanActivity attribute), 55

amount() (in module auxi.tools.chemistry.stoichiometry), 88

amount_fractions() (in module auxi.tools.chemistry.stoichiometry), 88

amounts() (in module auxi.tools.chemistry.stoichiometry), 88

assertAlmostEqual() (auxi.modelling.process.materials.chem.ChemMaterialUnitTester method), 77

assertAlmostEqual() (auxi.tools.chemistry.stoichiometry_test.StoichFunction method), 91

asset (auxi.modelling.financial.des.AccountType attribute), 64

AT (in module auxi.modelling.financial.des), 64

auxi (module), 97

auxi.core (module), 53

auxi.core_helpers (module), 49

auxi.core_helpers_test (module), 49

auxi.core_objects (module), 50

auxi.core_objects_test (module), 50

auxi.core_reporting (module), 51

auxi.core_reporting_test (module), 51

auxi.core_time (module), 52

auxi.core_time_test (module), 53

auxi.modelling (module), 86

auxi.modelling_business (module), 64

auxi.modelling_business.basic (module), 53

auxi.modelling_business.basic_test (module), 56

auxi.modelling_business.models (module), 57

auxi.modelling_business.models_test (module), 58

auxi.modelling.business.structure (module), 58

auxi.modelling.business.structure_test (module), 62

auxi.modelling.financial (module), 72

auxi.modelling.financial.des (module), 64

auxi.modelling.financial.des_test (module), 69

auxi.modelling.financial.reporting (module), 70

auxi.modelling.financial.reporting_test (module), 72

auxi.modelling.process (module), 86

auxi.modelling.process.materials (module),		C	
86		c (in module auxi.tools.physicalconstants),	96
auxi.modelling.process.materials.chem (module),	72	cash_flow (auxi.modelling.financial.reporting.ReportType attribute),	71
auxi.modelling.process.materials.chem_test (module),	76	ChemMaterialPackageUnitTester (class in auxi.modelling.process.materials.chem_test),	76
auxi.modelling.process.materials.psd (module),	77	ChemMaterialUnitTester (class in auxi.modelling.process.materials.chem_test),	77
auxi.modelling.process.materials.psd_test (module),	80	clear() (auxi.modelling.process.materials.chem.MaterialPacka method),	74
auxi.modelling.process.materials.slurry (module),	81	clear() (auxi.modelling.process.materials.psd.MaterialPackag method),	79
auxi.modelling.process.materials.slurry_test (module),	85	clear() (auxi.modelling.process.materials.slurry.MaterialPack method),	83
auxi.tools (module),	96	Clock (class in auxi.core.time),	52
auxi.tools.chemistry (module),	92	ClockUnitTester (class in auxi.core.time_test),	53
auxi.tools.chemistry.stoichiometry (module),	87	clone() (auxi.modelling.process.materials.chem.MaterialPack method),	74
auxi.tools.chemistry.stoichiometry_test (module),	91	clone() (auxi.modelling.process.materials.psd.MaterialPackag method),	79
auxi.tools.materialphysicalproperties (module),	93	clone() (auxi.modelling.process.materials.slurry.MaterialPack method),	84
auxi.tools.physicalconstants (module),	96	Component (class in auxi.modelling.business.structure),	
auxi.tools.transportphenomena (module),	96	59	
auxi.tools.transportphenomena.dimensionlessquantities (module),	93	ComponentUnitTest (class in auxi.modelling.business.structure_test),	62
		Compound (class in auxi.tools.chemistry.stoichiometry),	
		87	
		CompoundVisitor (class in auxi.tools.chemistry.stoichiometry),	
		87	
		convert_compound() (in module auxi.tools.chemistry.stoichiometry),	
		88	
		count() (auxi.tools.chemistry.stoichiometry.Compound method),	87
		count() (auxi.tools.chemistry.stoichiometry.Element method),	88
		count() (auxi.tools.chemistry.stoichiometry.Group method),	88
		count_with_multiplier() (in module auxi.tools.chemistry.stoichiometry),	

		auxi.tools.chemistry.stoichiometry),
create_account()		89
	(auxi.modelling.financial.des.GeneralLedgerAccountUnit method),	66
create_component()		89
	(auxi.modelling.business.structure.ComponentEntity method),	60
create_component()		61
	(auxi.modelling.business.structure.EntityUnitTester method),	61
create_empty_assay()		63
	(auxi.modelling.process.materials.chemicalMaterial method),	73
create_empty_assay()		64
	(auxi.modelling.financial.des.AccountType attribute),	64
create_empty_assay()		64
	(auxi.modelling.financial.des.AccountType attribute),	64
create_empty_assay()		64
	extract() (auxi.modelling.process.materials.chem.MaterialPack method),	75
create_entity()		75
	extract() (auxi.modelling.process.materials.slurry.MaterialPack method),	79
create_package()		79
	F	
create_package()		96
	(auxi.modelling.process.materials.chem.MaterialF method),	74
create_package()		96
	(auxi.modelling.process.materials.psd.MaterialF method),	78
create_package()		96
	GeneralLedger (class in auxi.tools.physicalconstants),	96
create_transaction()		96
	GeneralLedger (class in auxi.modelling.financial.des),	64
csv	(auxi.core.reporting.ReportFormat attribute),	51
	G	
Element	(class in auxi.tools.chemistry.stoichiometry),	87
element_mass_fraction()	(in module auxi.tools.chemistry.stoichiometry),	89
element_mass_fractions()	(in module auxi.tools.chemistry.stoichiometry),	89
	GeneralLedgerAccount (class in auxi.modelling.financial.des),	64
	GeneralLedgerAccountUnitTester (class in auxi.modelling.financial.des_test),	69
	GeneralLedgerStructure (class in auxi.modelling.financial.des),	67
	GeneralLedgerStructure (class in auxi.modelling.financial.reporting),	70
	GeneralLedgerStructureUnitTester (class in auxi.modelling.financial.des_test),	69
	GeneralLedgerStructureUnitTester (class in auxi.modelling.financial.reporting_test),	72
	GeneralLedgerUnitTester (class in auxi.modelling.financial.des_test),	69
	generic_visit()	
	(auxi.tools.chemistry.stoichiometry.CompoundVisitor method),	87

method), 85	mass_fractions() (in module auxi.tools.chemistry.stoichiometry),
get_volume_fraction_solids() (auxi.modelling.process.materials.slurry.MaterialPackage method), 85	masses() (in module auxi.tools.chemistry.stoichiometry),
Gr() (in module auxi.tools.transportphenomena.dimensionlessquantities), 93	Material (class in auxi.modelling.process.materials.chem), 72
Group (class in auxi.tools.chemistry.stoichiometry), 88	Material (class in auxi.modelling.process.materials.psd), 77
H	Material (class in auxi.modelling.process.materials.slurry), 81
h (in module auxi.tools.physicalconstants), 96	MaterialPackage (class in auxi.modelling.process.materials.chem), 74
h_bar (in module auxi.tools.physicalconstants), 96	MaterialPackage (class in auxi.modelling.process.materials.psd), 79
HelpersUnitTester (class in auxi.core.helpers_test), 49	MaterialPackage (class in auxi.modelling.process.materials.slurry), 83
hour (auxi.core.time.TimePeriod attribute), 52	matplotlib (auxi.core.reporting.ReportFormat attribute), 51
I	millisecond (auxi.core.time.TimePeriod attribute), 52
income_statement (auxi.modelling.financial.reporting.ReportType attribute), 71	minute (auxi.core.time.TimePeriod attribute), 52
income_statement()	month (auxi.core.time.TimePeriod attribute), 52
IncomeStatement (class in auxi.modelling.financial.reporting), 70	N
k_B (in module auxi.tools.physicalconstants), 96	N_A (in module auxi.tools.physicalconstants), 96
L	name (auxi.modelling.business.models.TimeBasedModel attribute), 58
latex (auxi.core.reporting.ReportFormat attribute), 51	name (auxi.modelling.business.structure.Activity attribute), 59
liability (auxi.modelling.financial.des.AccountType attribute), 64	name (auxi.modelling.business.structure.Component attribute), 60
M	name (auxi.modelling.business.structure.Entity
m_u (in module auxi.tools.physicalconstants), 96	
mass() (in module auxi.tools.chemistry.stoichiometry), 90	

attribute), 61
name (auxi.modelling.financial.des.GeneralLedgerAccount attribute), 66
NamedObject (class in auxi.core.objects), 50
NamedObjectUnitTester (class in auxi.core.objects_test), 50
Nu() (in module auxi.tools.transportphenomena.dimensionlessquantities), 93

R

Re() (in module auxi.tools.transportphenomena.dimensionlessquantities), 94
Ra() (in module auxi.tools.transportphenomena.dimensionlessquantities), 95
read() (auxi.core.objects.Object static method), 50
remove_account() (auxi.modelling.financial.des.GeneralLedgerAccount method), 66
remove_component() (auxi.modelling.business.structure.Component method), 60
remove_component() (auxi.modelling.business.structure.Entity method), 61
remove_entity() (auxi.modelling.business.models.TimeBasedModel method), 58
render() (auxi.core.reporting.Report method), 51
Report (class in auxi.core.reporting), 51
ReportActivity (class in auxi.modelling.financial.reporting), 71
ReportFormat (class in auxi.core.reporting), 51
ReportingUnitTest (class in auxi.core.reporting_test), 51
ReportType (class in auxi.modelling.financial.reporting), 71
reset() (auxi.core.time.Clock method), 52
revenue (auxi.modelling.financial.des.AccountType attribute), 64
run() (auxi.modelling.business.basic.BasicActivity method), 54
run() (auxi.modelling.business.basic.BasicLoanActivity method), 56
run() (auxi.modelling.business.models.TimeBasedModel method), 58
run() (auxi.modelling.business.structure.Component method), 60

O

Object (class in auxi.core.objects), 50
ObjectUnitTester (class in auxi.core.objects_test), 50

P

parse_compound (in module auxi.tools.chemistry.stoichiometry), 90
png (auxi.core.reporting.ReportFormat attribute), 51
Pr() (in module auxi.tools.transportphenomena.dimensionlessquantities), 94
prepare_to_run() (auxi.modelling.business.basic.BasicLoanActivity method), 55
prepare_to_run() (auxi.modelling.business.models.TimeBasedModel method), 58
prepare_to_run() (auxi.modelling.business.structure.Activity method), 59
prepare_to_run() (auxi.modelling.business.structure.Component method), 60
prepare_to_run() (auxi.modelling.business.structure.Entity method), 61
printout (auxi.core.reporting.ReportFormat attribute), 51
PsdMaterialPackageUnitTester (class in auxi.modelling.process.materials.psd_test), 80
PsdMaterialUnitTester (class in auxi.modelling.process.materials.psd_test), 81

test__generate_table_()	(auxi.modelling.process.materials.slurry_test.SlurryM (auxi.modelling.financial.reporting_test.GeneralMethodUnitTester method), 72	test_add_operator_1()
test__generate_table_()	(auxi.modelling.process.materials.chem_test.ChemM (auxi.modelling.financial.reporting_test.TransactionMethodUnitTester method), 72	test_add_operator_1()
test_meet_execution_criteria()	(auxi.modelling.process.materials.psd_test.PsdMater (auxi.modelling.business.basic_test.BasicActivityMethodUnitTester method), 56	test_add_operator_1()
test_meet_execution_criteria()	(auxi.modelling.process.materials.slurry_test.SlurryM (auxi.modelling.business.basic_test.BasicLoanActivityMethodUnitTester method), 56	test_add_operator_2()
test_meet_execution_criteria()	(auxi.modelling.process.materials.chem_test.ChemM (auxi.modelling.business.structure_test.ActivityMethodUnitTester method), 62	test_add_operator_3()
test_perform_year_end_gross_profit()	(auxi.modelling.process.materials.chem_test.ChemM (auxi.modelling.business.structure_test.EntityUnitTester, 76 method), 63	test_add_operator_3()
test_perform_year_end_gross_profit_and_income_summary()	(auxi.modelling.process.materials.psd_test.PsdMater (auxi.modelling.business.structure_test.EntityUnitTester, 80 method), 63	test_add_operator_3()
test_perform_year_end_income_summary()	(auxi.modelling.process.materials.slurry_test.SlurryM (auxi.modelling.business.structure_test.EntityUnitTester, 85 method), 63	test_amount() (auxi.tools.chemistry.stoichiometry_test.Stoich method), 91
test_perform_year_end_income_tax()	(auxi.modelling.business.structure_test.EntityUnitTester method), 63	EntityUnitTesterfractions() (auxi.tools.chemistry.stoichiometry_test.StoichFunct method), 91
test_perform_year_end_procedure()	(auxi.modelling.business.structure_test.EntityUnitTester method), 63	EntityUnitTestermethod), 91
test_perform_year_end_retained_earnings()	(auxi.modelling.business.structure_test.EntityUnitTester method), 63	EntityUnitTestermethod), 91
test_str__()	(auxi.core.objects_test.NamedObjectUnitTester (auxi.modelling.process.materials.chem_test.Che method), 50	method), 76
test_add_activity_invalid_account_name()	test_clone() (auxi.modelling.process.materials.slurry_test.Slu (auxi.modelling.business.structure_test.ComponentUnitTester method), 62	test_constructor()
test_add_activity_valid_account_name()	(auxi.core.objects_test.NamedObjectUnitTester (auxi.modelling.business.structure_test.ComponentUnitTester method), 62	test_constructor()
test_add_assay()	(auxi.core.time_test.ClockUnitTester (auxi.modelling.process.materials.chem_test.ChemMaterialUnitTester method), 77	test_constructor()
test_add_assay()	(auxi.modelling.business.basic_test.BasicActivityUnitTester (auxi.modelling.process.materials.psd_test.PsdMaterialUnitTester method), 81	test_constructor()
test_add_assay()	(auxi.modelling.business.basic_test.BasicLoanActivi	

method), 56
 test_constructor()
 (auxi.modelling.business.models_test.TimeBaseUnitTesting)
 method), 58
 test_constructor()
 (auxi.modelling.business.structure_test.ActivityUnitTesting)
 method), 62
 test_constructor()
 (auxi.modelling.business.structure_test.ComponentUnitTesting)
 method), 62
 test_constructor()
 (auxi.modelling.business.structure_test.EntityUnitTesting)
 method), 62
 test_constructor()
 (auxi.modelling.business.structure_test.EntityUnitTesting)
 method), 63
 test_constructor()
 (auxi.modelling.financial.des_test.GeneralLedgerUnitTesting)
 method), 69
 test_constructor()
 (auxi.modelling.financial.des_test.GeneralLedgerUnitTesting)
 method), 69
 test_constructor()
 (auxi.modelling.financial.des_test.GeneralLedgerUnitTesting)
 method), 69
 test_constructor()
 (auxi.modelling.financial.des_test.GeneralLedgerUnitTesting)
 method), 69
 test_constructor()
 (auxi.modelling.financial.des_test.TransactionUnitTesting)
 method), 69
 test_constructor()
 (auxi.modelling.financial.des_test.TransactionUnitTesting)
 method), 70
 test_constructor()
 (auxi.modelling.process.materials.chem_test.ChemMaterialPackagingUnitTesting)
 method), 76
 test_constructor()
 (auxi.modelling.process.materials.chem_test.ChemMaterialPackagingUnitTesting)
 method), 77
 test_constructor()
 (auxi.modelling.process.materials.chem_test.ChemMaterialPackagingUnitTesting)
 method), 77
 test_constructor()
 (auxi.modelling.process.materials.psd_test.PsdMaterialPackagingUnitTesting)
 method), 81
 test_constructor()
 (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTesting)
 method), 76

method), 81
test_extract_1()
 (auxi.modelling.process.materials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 85
test_get_account()
 (auxi.modelling.financial.des_test.GeneralLedgerStructureUnitTesterClockUnitTester
 method), 69
test_get_account_descendants()
 (auxi.modelling.financial.des_test.GeneralLedgerStructureUnitTesterClockUnitTester
 method), 69
test_get_activity_exists()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.chem_test.ChemMaterialHelpersUnitTester
 method), 62
test_get_activity_not_exists()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.chem_test.ChemMaterialHelpersUnitTester
 method), 62
test_get_assay()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestMaterials.psd_test.PsdMaterialHelpersUnitTester
 method), 76
test_get_assay()
 (auxi.modelling.process.materials.psd_test.PsdMaterialHelpersUnitTestMaterials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 81
test_get_assay()
 (auxi.modelling.process.materials.slurry_test.SlurryMaterialHelpersUnitTestActivityUnitTest
 method), 85
test_get_assay_total()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestHelpersUnitTester
 method), 77
test_get_assay_total()
 (auxi.modelling.process.materials.psd_test.PsdMaterialHelpersUnitTestBusiness.basic_test.BasicActivityUnitTest
 method), 81
test_get_assay_total()
 (auxi.modelling.process.materials.slurry_test.SlurryMaterialHelpersUnitTestBusiness.basic_test.BasicLoanActivityUnitTest
 method), 86
test_get_child_account()
 (auxi.modelling.financial.des_test.GeneralLedgerActivityUnitTestBusiness.structure_test.ActivityUnitTest
 method), 69
test_get_component_exists()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.psd_test.PsdMaterialHelpersUnitTester
 method), 62
test_get_component_not_exists()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 62
test_get_compound_index()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestMaterials.psd_test.PsdMaterialHelpersUnitTester
 method), 77
test_get_compound_mass()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestMaterials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 81
method), 76
test_get_date()
 (auxi.MaterialHelpersUnitTester
 method), 50
test_get_datetime()
 (auxi.StructureUnitTesterClockUnitTester
 method), 53
test_get_datetime_at_period_ix()
 (auxi.StructureUnitTesterClockUnitTester
 method), 53
test_get_element_masses()
 (auxi.unknowning
 method), 76
test_get_mass()
 (auxi.ChemMaterialHelpersUnitTestMaterials.psd_test.PsdMaterialHelpersUnitTester
 method), 81
test_get_mass()
 (auxi.ChemMaterialHelpersUnitTestMaterials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 85
test_get_path()
 (auxi.modelling.materials.slurry_test.SlurryMaterialHelpersUnitTestActivityUnitTest
 method), 62
test_get_path_relative_to_module()
 (auxi.modelling.materials.chem_test.ChemMaterialHelpersUnitTestHelpersUnitTester
 method), 50
test_get_referenced_accounts()
 (auxi.modelling.materials.psd_test.PsdMaterialHelpersUnitTestBusiness.basic_test.BasicActivityUnitTest
 method), 56
test_get_referenced_accounts()
 (auxi.modelling.materials.slurry_test.SlurryMaterialHelpersUnitTestBusiness.basic_test.BasicLoanActivityUnitTest
 method), 56
test_get_referenced_accounts()
 (auxi.modelling.financial.des_test.GeneralLedgerActivityUnitTestBusiness.structure_test.ActivityUnitTest
 method), 62
test_get_size_class_index()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.psd_test.PsdMaterialHelpersUnitTester
 method), 81
test_get_size_class_index()
 (auxi.modelling.business.structure_test.ComponentUnitTesting.process.materials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 86
test_get_size_class_mass()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestMaterials.psd_test.PsdMaterialHelpersUnitTester
 method), 81
test_get_size_class_mass()
 (auxi.modelling.process.materials.chem_test.ChemMaterialHelpersUnitTestMaterials.slurry_test.SlurryMaterialHelpersUnitTester
 method), 81

method), 85
 test_getitem_exists()
 (auxi.modelling.business.structure_test.EntityUnitTester)
 method), 63
 test_getitem_not_exists()
 (auxi.modelling.business.structure_test.EntityUnitTester)
 method), 63
 test_invalid_characters()
 (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 91
 test_mass() (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 91
 test_mass_fractions()
 (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 91
 test_masses() (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 91
 test_molar_mass()
 (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 92
 test_multiply_operator()
 (auxi.modelling.process.materials.chemtest.ChemMaterialPackageUnitTester)
 method), 76
 test_multiply_operator()
 (auxi.modelling.process.materials.psd_test.PsdMaterialPackageUnitTester)
 method), 81
 test_multiply_operator()
 (auxi.modelling.process.materials.slurry_test.SlurryMaterialPackageUnitTester)
 method), 85
 test_phase() (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTester)
 method), 92
 test_prepare_to_run()
 (auxi.modelling.business.models_test.TimeBasedModelUnitTester)
 method), 58
 test_prepare_to_run()
 (auxi.modelling.business.structure_test.ActivityUnitTester)
 method), 62
 test_prepare_to_run()
 (auxi.modelling.business.structure_test.ComponentUnitTester)
 method), 62
 test_prepare_to_run()
 (auxi.modelling.business.structure_test.EntityUnitTester)
 method), 63
 test_remove_account()
 (auxi.modelling.financial.des_test.GeneralLedgerAccountingUnitTester)
 method), 69
 test_remove_component()
 (auxi.modelling.business.structure_test.ComponentUnitTester)

method), 62	58
test_set_parent_path() (auxi.modelling.business.structure_test.TransactionUnitTester (method), 63 in auxi.modelling.financial.des), 67	TimePeriod (class in auxi.core.time), 52 transactionUnitTester (modelling.financial.reporting.ReportType attribute), 71
test_set_parent_path() (auxi.modelling.business.structure_test.EntityUnitTester (method), 63 in auxi.modelling.financial.reporting.GeneralLedger), 65	transaction_list (transactionList), 71
test_set_parent_path() (auxi.modelling.financial.des_test.GeneralLedger), 69 in auxi.modelling.financial.GeneralLedger (method), 65	AxiomModelUnitTester (AxiomModelUnitTester), 69
test_stoichiometry_coefficient() (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTesting.financial.reporting), (method), 92	TransactionList (class in auxi.tools.chemistry.stoichiometry_test.StoichFunctionTesting.financial.reporting_test), 71
test_stoichiometry_coefficients() (auxi.tools.chemistry.stoichiometry_test.StoichFunctionTesting.financial.reporting_test), (method), 92	TransactionListUnitTester (class in auxi.tools.chemistry.stoichiometry_test.StoichFunctionTesting.financial.reporting_test), 72
test_subtract_operator_2() (auxi.modelling.process.materials.chem_test.ChemMaterialPackageUnitTester), 68 (method), 77	TransactionTemplate (class in auxi.modelling.financial.des_test), 69 TransactionTemplateUnitTester (class in auxi.modelling.financial.des_test), 69
test_subtract_operator_2() (auxi.modelling.process.materials.psd_test.PsdMaterialPackageUnitTester), 68 (method), 81	TransactionTemplateUnitTester (class in auxi.modelling.financial.des_test), 69
test_subtract_operator_2() (auxi.modelling.process.materials.slurry_test.SlurryMaterialPackageUnitTester (method), 85	txt (auxi.core.reporting.ReportFormat at auxi.modelling.process.materials.slurry_test.SlurryMaterialPackageUnitTester method), 85
test_subtract_operator_3() (auxi.modelling.process.materials.chem_test.ChemMaterialPackageUnitTester (method), 77	V
test_subtract_operator_3() (auxi.modelling.process.materials.psd_test.PsdMaterialPackageUnitTester (method), 81	validate_account_name() (auxi.modelling.financial.des.GeneralLedgerStructureUnitTester (method), 67
test_subtract_operator_3() (auxi.modelling.process.materials.slurry_test.SlurryMaterialPackageUnitTester (method), 85	visit_element() (auxi.tools.chemistry.stoichiometry.CompoundVisitor (method), 87
test_tick() (auxi.core.time_test.ClockUnitTester (method), 53	visit_group() (auxi.tools.chemistry.stoichiometry.CompoundVisitor (method), 87
test_validate_account_name_invalid() (auxi.modelling.financial.des_test.GeneralLedgerStructureUnitTester (method), 69	visit_phase() (auxi.tools.chemistry.stoichiometry.CompoundVisitor (method), 87
test_validate_account_name_valid() (auxi.modelling.financial.des_test.GeneralLedgerStructureUnitTester (method), 69	visit_subscriptedelement() (auxi.tools.chemistry.stoichiometry.CompoundVisitor (method), 87
tick() (auxi.core.time.Clock method), 52	
TimeBasedModel (class auxi.modelling.business.models), 57	
TimeBasedModelUnitTester (class auxi.modelling.business.models_test),	

visit_subscriptedgroup()
(auxi.tools.chemistry.stoichiometry.CompoundVisitor
method), [87](#)

W

week (auxi.core.time.TimePeriod attribute),
[52](#)
write() (auxi.core.objects.Object method), [50](#)

Y

year (auxi.core.time.TimePeriod attribute), [53](#)