




Features

- Memory safety analysis
- Overflow detection
- Termination analysis using Büchi automata
- Nontermination analysis using geometric nontermination arguments
- LTL software model checking
- Bitprecise analysis
- IEEE 754 floating point analysis
- Error witnesses
- Correctness witnesses
- Error localization

Techniques


- On-demand trace-based decomposition
- Interprocedural analysis via nested word automata
- Theory-independent interpolation
- Refinement selection
- Configurable block encodings
- Multi SMT solver support
- Synthesis of ranking functions
- Efficient complementation of semi-deterministic Büchi automata
- (Nested word) automata minimization

ULTIMATE program analysis framework




Automata-theoretic proof of program correctness


Program \mathcal{P} is correct because each error trace is infeasible, i.e. the inclusion $\mathcal{P} \subseteq \mathcal{A}_1 \cup \mathcal{A}_2$ holds.



Program / automaton \mathcal{P} whose language is the set of error traces.

 \subseteq


Automaton \mathcal{A}_1
whose language is a
set of infeasible traces.

 \cup


Automaton \mathcal{A}_2
whose language is a
set of infeasible traces.

- Alphabet: set of program statements
 $\Sigma = \{ p \neq 0, n < 0, n \geq 0, p == 0, n == 0, n != 0, p := 0, n-- \}$

- The language of \mathcal{P} is the set of error traces.

- In the first iteration, we analyze feasibility of the error trace $\pi_1 = p \neq 0, n \geq 0, p == 0$. π_1 is infeasible. Via interpolation, we obtain the following Hoare triples.

$\{true\}$	$p \neq 0$	$\{p \neq 0\}$
$\{p \neq 0\}$	$n \geq 0$	$\{p \neq 0\}$
$\{p \neq 0\}$	$p == 0$	$\{false\}$

We construct the automaton \mathcal{A}_1 such that its language is the set of all traces whose infeasibility can be shown using the predicates $\{true\}$, $\{p \neq 0\}$, and $\{false\}$.

- Analogously, in the second iteration the automaton \mathcal{A}_2 is constructed.

- We check the inclusion $\mathcal{P} \subseteq \mathcal{A}_1 \cup \mathcal{A}_2$ and conclude that each error trace is infeasible and hence \mathcal{P} is correct.

Definition Given an automaton $\mathcal{A} = (Q, \delta, q_{init}, Q_{final})$ over the alphabet of program statements, we call a mapping that assigns to each state $q \in Q$ a predicate φ_q a *Floyd-Hoare annotation for automaton \mathcal{A}* if the following implications hold.


$$\begin{aligned}
 (q, \mathfrak{s}, q') \in \delta &\implies \{\varphi_q\} \mathfrak{s} \{\varphi_{q'}\} \text{ is a valid Hoare triple} \\
 q = q_{init} &\implies \varphi_q = true \\
 q \in Q_{final} &\implies \varphi_q = false
 \end{aligned}$$

Theorem If an automaton \mathcal{A} has a Floyd-Hoare annotation, then \mathcal{A} recognizes a set of infeasible traces.

Interpolation with unsatisfiable cores


Level 1: “interpolation” via

- strongest post




Level 2: interpolation via

- strongest post
- live variable analysis



Level 3: interpolation via

- strongest post
- live variable analysis
- unsatisfiable cores



Algorithm (for level 3)

- Input: infeasible trace $\mathfrak{s}_1, \dots, \mathfrak{s}_n$ and unsatisfiable core $UC \subseteq \{\mathfrak{s}_1, \dots, \mathfrak{s}_n\}$.
- Replace each statement that does not occur in UC by a skip statement or a havoc statement.
 - assume statement $\psi \rightsquigarrow skip$
 - assignment statement $x := t \rightsquigarrow havoc\ x$
- Compute sequence of predicates $\varphi_0, \dots, \varphi_n$ iteratively using the strongest post predicate transformer sp .

$$\begin{aligned}
 \varphi_0 &:= true \\
 \varphi_{i+1} &:= sp(\varphi_i, \mathfrak{s}_{i+1})
 \end{aligned}$$

- Eliminate each variable from predicate φ_i that is not live at position i of the trace.
- Output: sequence of predicates $\varphi_0, \dots, \varphi_n$ which is a sequence of interpolants for the infeasible trace $\mathfrak{s}_1, \dots, \mathfrak{s}_n$.