

Article information

Article title

Materials Science Optimization Benchmark Dataset for Multi-Objective, Multi-Fidelity Optimization of Hard-Sphere Packing Simulations

Authors

Sterling G. Baird^{1*}, Ramsey Issa¹, Taylor D. Sparks¹

Affiliations

1. Materials Science & Engineering, 122 S. Central Campus Drive, #304 Salt Lake City, Utah 84112-0056

Corresponding author's email address and Twitter handle

sterling.baird@utah.edu

@SterlingBaird1

Keywords

adaptive design, physics-based, Lubachevsky–Stillinger, force-biased algorithms, particle packing, packing generation, transfer learning, size distribution

Abstract

In scientific disciplines, benchmarks play a vital role in driving progress forward. For a benchmark to be effective, it must closely resemble real-world tasks. If the level of difficulty or relevance is inadequate, it can impede progress in the field. Moreover, benchmarks should have low computational overhead to ensure accessibility and repeatability. The objective is to achieve a kind of "Turing test" by creating a surrogate model that is practically indistinguishable from the ground truth observation, at least within the dataset's explored boundaries. This objective necessitates a large quantity of data. This study encompasses numerous features that are characteristic of chemistry and materials science optimization tasks that are relevant to industry. These features include high levels of noise, multiple fidelities, multiple objectives, linear constraints, non-linear correlations, and failure regions. We performed 494498 random hard-sphere packing simulations representing 206 CPU days' worth of computational overhead. Simulations required nine input parameters with linear constraints and two discrete fidelities each with continuous fidelity parameters. The results were logged in a free-tier shared MongoDB Atlas database, producing two core tabular datasets: a failure probability dataset and a regression dataset. The failure probability dataset maps unique input parameter sets to the estimated probabilities that the simulation will fail. The regression dataset maps input parameter sets (including repeats) to particle packing fractions and computational runtimes for each of the two steps. These two datasets were used to create a surrogate model as close as possible to running the actual simulations by incorporating simulation failure and heteroskedastic noise. In

the regression dataset, percentile ranks were calculated for each group of identical parameter sets to account for heteroskedastic noise, thereby ensuring reliable and accurate results. This differs from the conventional approach that imposes a-priori assumptions, such as Gaussian noise, by specifying mean and standard deviation. This technique can be extended to other benchmark datasets to bridge the gap between optimization benchmarks with low computational overhead and the complex optimization scenarios encountered in the real world.

Specifications table

| | |
|---------------------------------------|--|
| Subject | Computational materials science |
| Specific subject area | Physics-based geometric packing |
| Type of data | Table Figure |
| How the data were acquired | Data was acquired by running compiled C software hosted at https://github.com/VasiliBaranov/packing-generation in a two-step process orchestrated using Python in https://github.com/sparks-baird/matsci-opt-benchmarks/blob/main/scripts/particle_packing/packing_generation_submitit.py . The Python code was utilized as a driver for the compiled packing generation executable and executed using the resources provided by the University of Utah's Center for High-performance Computing (CHPC). The submission of jobs to the SLURM scheduler was facilitated through https://github.com/facebookincubator/submitit , and the MongoDB Data API was utilized to record results in JSON format. For a snapshot of the code utilized in matsci-opt-benchmarks, please refer to https://github.com/sparks-baird/matsci-opt-benchmarks/tree/v0.2.2 (https://zenodo.org/record/7697264#.ZAJ06nbMleM). |
| Data format | Raw Analyzed Filtered |
| Description of data collection | A total of 65536 parameter combinations were randomly sampled using quasi-random Sobol sampling, varying seven irreducible parameters in addition to the number of particles and initial scaling factor. A constrained search space was employed through the Ax Platform with repeats. Out of these simulations, 494498 were successfully completed, requiring 206 CPU days to run. Failed |

| | |
|-----------------------------|--|
| | simulations were recorded as NaN values with ratio of successful to total simulations tracked on a per parameter set basis (sobol_probability_filter.csv). Repeat simulations were grouped and ranked by percentile using the “dense” method with pct=True in pandas.core.groupby.GroupBy.rank (sobol_regression.csv) ¹ . Surrogate models were fitted for failure probability, packing fraction, and computational runtime for each of two particle packing algorithms, totaling six surrogate models. |
| Data source location | University of Utah, Salt Lake City UT USA |
| Data accessibility | Repository name: Zenodo Data identification number: 7696165 Direct URL to data: https://dx.doi.org/10.5281/zenodo.7696165 |

Value of the data

- Valuable for adaptive design benchmarking
- Benefits optimization researchers and practitioners in the physical sciences
- Provides insight into packing behavior in powder-bed additive manufacturing, can be integrated with experimental data
- Provides an example for future datasets

Objective

Optimization tasks that are relevant to industry in the fields of materials science and chemistry are typically hierarchical, noisy, multi-fidelity^{2,3}, multi-objective^{4,5}, high-dimensional^{6,7}, non-linearly correlated, and involve mixed numerical and categorical variables subject to linear⁸ and non-linear constraints. Existing benchmark datasets^{9–14} have limitations as they ignore or simplify the impact of noise and the occurrence of failure with certain parameter combinations. By integrating simulation failure and heteroskedastic noise, we aim to achieve a "Turing test" scenario where the surrogate model is practically indistinguishable from the ground truth simulation. This strategy bridges the gap between low-cost surrogate functions based on benchmark datasets and the high-cost evaluation of objective functions in real-world scenarios.

Data description

The failure probability dataset (sobol_probability_filter.csv) contains unique input parameter sets (nine variables) and the estimated probabilities that the simulation will fail at each of the two steps (force-biased algorithm and Lubachevsky–Stillinger).

The regression dataset (sobol_regression.csv) contains input parameters (including repeats) spanning nine variables and corresponding particle packing fractions as well as computational runtimes for each of the two steps (force-biased algorithm and Lubachevsky–Stillinger).

There are six regression models (surrogate_models.pkl) trained on all data meant for production use. These six models can be used together to create the benchmark function.

There are five cross-validation sets of six regression models (cross_validation_models_0.pkl, cross_validation_models_1.pkl, cross_validation_models_2.pkl, cross_validation_models_3.pkl, cross_validation_models_4.pkl).

The model metadata (model_metadata.json) contains the raw mean absolute error scores, the raw predictions, and the true values for each of the cross-validation folds.

Figure 1 contains a histogram for the number of successful repeats for each parameter combination.

Figure 2 contains the probability of a simulation failing for each of the two algorithms.

Figure 3 contains the histograms of observed particle packing fractions for each of the two algorithms.




Figure 1. Histogram of number of parameter groups vs. number of successful repeats within a given group.




Figure 2. Histogram of normalized simulation counts vs. the probability of a simulation failing for a given parameter set. On average, the force-biased algorithm or fba (blue) is more likely to succeed than the Lubachevsky–Stillinger or ls (red) algorithm.




Figure 3. Histogram of number of simulations vs. packing fraction for the force-biased algorithm or fba (blue) and Lubachevsky–Stillinger or ls algorithm (red). On average, the ls algorithm tends to have higher packing fractions with a more Gaussian-like distribution than fba.

Experimental design, materials and methods

In this study, 494498 hard-sphere packing simulations were conducted using a two-step process of a force-biased algorithm^{15,16} followed by the Lubachevsky–Stillinger algorithm^{17–19}. The simulations were performed using mixtures of three different particle types, each characterized by two log-normal distribution parameters and three composition parameters. Two parameters (scale and shape) describe each of the three distributions, and three additional composition parameters describe the fractional share (e.g., in terms of volume) of each of the particle types. Additionally, the number of particles and an initial scaling factor were allowed to vary. With a greater number of particles, denser and more realistic packs can be generated at the expense of computational cost (i.e., the fidelity parameter). The initial scaling factor affects the computational stability of the simulation; with an adequate scaling factor, the simulation is more likely to be completed successfully. The quasi-random Sobol sampling technique was employed to generate parameter combinations, enabling a more uniform sampling of the allowable parameter space. Although it may serve other purposes, this dataset was primarily designed as a multi-fidelity benchmark dataset for constrained adaptive design experiments. To realistically capture the noise in this dataset, simulations were run multiple times for each quasi-random parameter combination. To increase throughput and reduce latency, simulation parameters (including repeats) were shuffled and divided into batches, which were then dispatched to a high-performance computing environment for asynchronous evaluation. The

results were recorded in a free-tier MongoDB Atlas database and then consolidated and prepared as datasets suitable for machine learning applications. For further implementation details, see https://github.com/sparks-baird/matsci-opt-benchmarks/tree/v0.2.2/scripts/particle_packing and https://github.com/sparks-baird/matsci-opt-benchmarks/tree/v0.2.2/notebooks/particle_packing. Instructions for model usage are available at <https://matsci-opt-benchmarks.readthedocs.io/>.

Ethics statements

There are no statements to declare.

CRediT author statement

Sterling G. Baird: Project administration, Conceptualization, Methodology, Software, Validation, Formal analysis, Investigation, Data Curation, Writing - Original Draft, Writing - Review & Editing, Visualization. **Ramsey Issa:** Methodology, Software, Validation, Formal Analysis, Writing - Review & Editing. **Taylor D. Sparks:** Supervision, Funding acquisition

Acknowledgments

Funding: This work was supported by the National Science Foundation Division of Materials Research [Grant no. DMR-1651668].

We acknowledge Vasili Baranov and Robin De Schepper for help with the packing-generation codebase. We acknowledge Ramsey Issa and Hasan M. Sayeed for reviewing the manuscript and providing valuable feedback. We acknowledge Jason R. Hall for discussion of particle packing simulations in the context of industry processes. We acknowledge the University of Utah's Center for High Performance Computing (CHPC) for providing computational resources. We acknowledge OpenAI for providing free usage of their research tool, ChatGPT, which was used during the review and editing process.

Declaration of interests

☒ The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

☐ The authors declare the following financial interests/personal relationships which may be considered as potential competing interests:

References

- (1) Baird, S. G. Materials Science Optimization Benchmark Dataset for Multi-Fidelity Hard-Sphere Packing Simulations, 2023. <https://doi.org/10.5281/zenodo.7513019>.

- (2) Ghoreishi, S. F.; Molkeri, A.; Arróyave, R.; Allaire, D.; Srivastava, A. Efficient Use of Multiple Information Sources in Material Design. *Acta Materialia* **2019**, *180*, 260–271. <https://doi.org/10.1016/j.actamat.2019.09.009>.
- (3) Kandasamy, K.; Vysyaraju, K. R.; Neiswanger, W.; Paria, B.; Collins, C. R.; Schneider, J.; Poczos, B.; Xing, E. P. Tuning Hyperparameters without Grad Students: Scalable and Robust Bayesian Optimisation with Dragonfly. *arXiv:1903.06694 [cs, stat]* **2020**.
- (4) Hanaoka, K. Comparison of Conceptually Different Multi-Objective Bayesian Optimization Methods for Material Design Problems. *Materials Today Communications* **2022**, 103440. <https://doi.org/10.1016/j.mtcomm.2022.103440>.
- (5) Häse, F.; Roch, L. M.; Aspuru-Guzik, A. Chimera: Enabling Hierarchy Based Multi-Objective Optimization for Self-Driving Laboratories. *Chem. Sci.* **2018**, *9* (39), 7642–7655. <https://doi.org/10.1039/C8SC02239A>.
- (6) Baird, S. G.; Liu, M.; Sparks, T. D. High-Dimensional Bayesian Optimization of 23 Hyperparameters over 100 Iterations for an Attention-Based Network to Predict Materials Property: A Case Study on CrabNet Using Ax Platform and SAASBO. *Computational Materials Science* **2022**, *211*, 111505. <https://doi.org/10.1016/j.commatsci.2022.111505>.
- (7) Eriksson, D.; Jankowiak, M. High-Dimensional Bayesian Optimization with Sparse Axis-Aligned Subspaces. *arXiv:2103.00349 [cs, stat]* **2021**.
- (8) Baird, S.; Hall, J. R.; Sparks, T. D. The Most Compact Search Space Is Not Always the Most Efficient: A Case Study on Maximizing Solid Rocket Fuel Packing Fraction via Constrained Bayesian Optimization. *ChemRxiv* September 6, 2022. <https://doi.org/10.26434/chemrxiv-2022-nz2w8-v2>.
- (9) Dunn, A.; Wang, Q.; Ganose, A.; Dopp, D.; Jain, A. Benchmarking Materials Property Prediction Methods: The Matbench Test Set and Automatminer Reference Algorithm. *npj Comput Mater* **2020**, *6* (1), 138. <https://doi.org/10.1038/s41524-020-00406-3>.
- (10) De Breuck, P.-P.; Evans, M. L.; Rignanese, G.-M. Robust Model Benchmarking and Bias-Imbalance in Data-Driven Materials Science: A Case Study on MODNet. *J. Phys.: Condens. Matter* **2021**, *33* (40), 404002. <https://doi.org/10.1088/1361-648X/ac1280>.
- (11) Wang, A.; Liang, H.; McDannald, A.; Takeuchi, I.; Kusne, A. G. Benchmarking Active Learning Strategies for Materials Optimization and Discovery. *arXiv* April 12, 2022. <http://arxiv.org/abs/2204.05838> (accessed 2022-07-04).
- (12) Liang, Q.; Gongora, A. E.; Ren, Z.; Tiihonen, A.; Liu, Z.; Sun, S.; Deneault, J. R.; Bash, D.; Mekki-Berrada, F.; Khan, S. A.; Hippalgaonkar, K.; Maruyama, B.; Brown, K. A.; Fisher III, J.; Buonassisi, T. Benchmarking the Performance of Bayesian Optimization across Multiple Experimental Materials Science Domains. *npj Comput Mater* **2021**, *7* (1), 188. <https://doi.org/10.1038/s41524-021-00656-9>.
- (13) Henderson, A. N.; Kauwe, S. K.; Sparks, T. D. Benchmark Datasets Incorporating Diverse Tasks, Sample Sizes, Material Systems, and Data Heterogeneity for Materials Informatics. *Data in Brief* **2021**, *37*, 107262. <https://doi.org/10.1016/j.dib.2021.107262>.
- (14) Häse, F.; Aldeghi, M.; Hickman, R. J.; Roch, L. M.; Christensen, M.; Liles, E.; Hein, J. E.; Aspuru-Guzik, A. Olympus: A Benchmarking Framework for Noisy Optimization and Experiment Planning. *Mach. Learn.: Sci. Technol.* **2021**, *2* (3), 035021. <https://doi.org/10.1088/2632-2153/abedc8>.
- (15) Mościński, J.; Bargieł, M.; Rycerz, Z. A.; Jacobs, P. W. M. The Force-Biased Algorithm for the Irregular Close Packing of Equal Hard Spheres. *Molecular Simulation* **1989**, *3* (4), 201–212. <https://doi.org/10.1080/08927028908031373>.
- (16) Bezrukov, A.; Bargieł, M.; Stoyan, D. Statistical Analysis of Simulated Random Packings of Spheres. *Particle & Particle Systems Characterization* **2002**, *19* (2), 111–118. [https://doi.org/10.1002/1521-4117\(200205\)19:2<111::AID-PPSC111>3.0.CO;2-M](https://doi.org/10.1002/1521-4117(200205)19:2<111::AID-PPSC111>3.0.CO;2-M).

- (17) Skoge, M.; Donev, A.; Stillinger, F. H.; Torquato, S. Packing Hyperspheres in High-Dimensional Euclidean Spaces. *Phys. Rev. E* **2006**, *74* (4), 041127. <https://doi.org/10.1103/PhysRevE.74.041127>.
- (18) Lubachevsky, B. D. How to Simulate Billiards and Similar Systems. *Journal of Computational Physics* **1991**, *94* (2), 255–283. [https://doi.org/10.1016/0021-9991\(91\)90222-7](https://doi.org/10.1016/0021-9991(91)90222-7).
- (19) Lubachevsky, B. D.; Stillinger, F. H. Geometric Properties of Random Disk Packings. *Journal of Statistical Physics* **1990**, *60* (5), 561–583. <https://doi.org/10.1007/BF01025983>.